AIR QUALITY, ENERGY, GREENHOUSE GAS EMISSIONS AND HEALTH RISK ASSESSMENT IMPACT ANALYSIS

SLOVER / ALDER AVENUE INDUSTRIAL PROJECT BLOOMINGTON

Lead Agency:

County of San Bernardino

385 N Arrowhead Ave 1st floor San Bernardino, CA 92415

Prepared by:

Vista Environmental

1021 Didrickson Way Laguna Beach, CA 92651 949 510 5355 Greg Tonkovich, AICP

Project No. 21060

October 4, 2022

TABLE OF CONTENTS

1.0	Introduction	1
	1.1 Purpose of Analysis and Study Objectives	1
	1.2 Site Locations and Study Area	1
	1.3 Proposed Project Description	2
	1.4 Executive Summary	2
	1.5 Project Design Features Incorporated into the Proposed Project	3
	1.6 Mitigation Measures for the Proposed Project	3
2.0	Air Pollutants	7
	2.1 Criteria Pollutants and Ozone Precursors	7
	2.2 Other Pollutants of Concern	9
3.0	Greenhouse Gases	12
	3.1 Greenhouse Gases	12
	3.2 Global Warming Potential	14
	3.3 Greenhouse Gas Emissions Inventory	15
4.0	Air Quality Management	16
	4.1 Federal – United States Environmental Protection Agency	16
	4.2 State – California Air Resources Board	19
	4.3 Regional – Southern California	20
	4.4 Local – County of San Bernardino	23
5.0	Energy Conservation Management	25
5.0	Energy Conservation Management	
5.0	-	25
5.06.0	5.1 State	25 27
	5.1 State	25 27
	5.1 State	25 27 29
	5.1 State	2527292929
	5.1 State	
	5.1 State	
	5.1 State	
6.0	5.1 State	
6.0	5.1 State 5.2 Local – County of San Bernardino Global Climate Change Management 6.1 International 6.2 Federal – United States Environmental Protection Agency 6.3 State 6.4 Regional – Southern California 6.5 Local – County of San Bernardino Atmospheric Setting.	
6.0	5.1 State	
6.0	5.1 State	
6.0	5.1 State	
7.0	5.1 State	
7.0	5.1 State 5.2 Local – County of San Bernardino	

TABLE OF CONTENTS CONTINUED

5454545656
54 56
56
56
57
57
58
58
58
60
66
72
73
77
78
79
80
•

APPENDICES

Appendix A – CalEEMod Model Daily Printouts

Appendix B – EMFAC2017 Model Printouts

Appendix C – AERMOD Model Years 2023 – 2025 Operational PM10 Printouts

Appendix D – AERMOD Model Years 2026 – 2040 Operational PM10 Printouts

Appendix E – AERMOD Model Years 2041 – 2052 Operational PM10 Printouts

Appendix F – CalEEMod Model Annual Printouts

LIST OF FIGURES

Figure 1 – Project Local Study Area	5
, ,	
Figure 2 – Proposed Site Plan	6
Figure 3 – AFRMOD Model Sources and Receptor Placement	53

LIST OF TABLES

Table A – Diesel Emission Pollutants that Cause Acute and Chronic Health Impacts	10
Table B – Global Warming Potentials, Atmospheric Lifetimes and Abundances of GHGs	14
Table C – State and Federal Criteria Pollutant Standards	16
Table D – South Coast Air Basin Attainment Status	17
Table E – Applicable County of San Bernardino General Plan Energy-Related Policies	28
Table F – Monthly Climate Data	38
Table G – Local Area Air Quality Monitoring Summary	39
Table H – CalEEMod Land Use Parameters	41
Table I – Inventory of Vehicle Trips During Operation of Proposed Project	44
Table J – Fleet Mix During Operation of Proposed Project	44
Table K – Off-Road Equipment and Fuel Consumption from Construction of the Proposed Project	46
Table L $-$ On-Road Vehicle Trips and Fuel Consumption from Construction of the Proposed Project	47
Table M – EMFAC2017 Diesel Truck Running PM10 Emission Rates	50
Table N – EMFAC2017 Diesel Truck Idling PM10 Emission Rates	50
Table O – AERMOD Model Operational DPM Truck Travel Emissions Sources	51
Table P – AERMOD Model Operational DPM Truck Idling Emissions Sources	52
Table Q – SCAQMD Regional Criteria Pollutant Emission Thresholds of Significance	54
Table R – Construction Equipment Modeled in CalEEMod and Acres Disturbed per Day	55
Table S – SCAQMD Local Air Quality Thresholds of Significance	56
Table T – Construction-Related Regional Criteria Pollutant Emissions	61
Table U – Construction-Related Local Criteria Pollutant Emissions	62
Table V – Operational Regional Criteria Pollutant Emissions	63
Table W – Operations-Related Local Criteria Pollutant Emissions	66
Table X – Cancer Risk Calculation Parameters	69
Table Y – Project Operational DPM Emissions Cancer Risks at Nearby Sensitive Receptors	70
Table Z – Proposed Project Compliance with Applicable General Plan Energy Policies	77
Table AA – Project Related Greenhouse Gas Annual Emissions	78

ACRONYMS AND ABBREVIATIONS

AB Assembly Bill

AQMP Air Quality Management Plan

BACT Best Available Control Technology

BSFC Brake Specific Fuel Consumption

CAAQS California Ambient Air Quality Standards

CalEEMod California Emissions Estimator Model

CalEPA California Environmental Protection Agency

CAPCOA California Air Pollution Control Officers Association

CARB California Air Resources Board
CEC California Energy Commission

CEQA California Environmental Quality Act

CFCs chlorofluorocarbons Cf_4 tetrafluoromethane C_2F_6 hexafluoroethane

CH₄ Methane

CO Carbon monoxide
CO₂ Carbon dioxide

CO₂e Carbon dioxide equivalent County County of San Bernardino DPM Diesel particulate matter

EPA Environmental Protection Agency

FTIP Federal Transportation Improvement Program

GHG Greenhouse gas

GWP Global warming potential
HAP Hazardous Air Pollutants

HFCs Hydrofluorocarbons

IPCC International Panel on Climate Change

kWhr kilowatt-hour

LCFS Low Carbon Fuel Standard

LST Localized Significant Thresholds

MATES Multiple Air Toxics Exposure Study

MMTCO₂e Million metric tons of carbon dioxide equivalent

MPO Metropolitan Planning Organization

MWh Megawatt-hour

NAAQS National Ambient Air Quality Standards

NO_x Nitrogen oxides NO₂ Nitrogen dioxide

OPR Office of Planning and Research

Pfc Perfluorocarbons
PM Particle matter

PM10 Particles that are less than 10 micrometers in diameter
PM2.5 Particles that are less than 2.5 micrometers in diameter

PPM Parts per million
PPB Parts per billion
PPT Parts per trillion

RTIP Regional Transportation Improvement Plan

RTP/SCS Regional Transportation Plan/Sustainable Communities Strategy

SB Senate Bill

SCAQMD South Coast Air Quality Management District

SCAG Southern California Association of Governments

SF₆ Sulfur Hexafluoride

SIP State Implementation Plan

SO_x Sulfur oxides

TAC Toxic air contaminants

UNFCCC United Nations' Framework Convention on Climate Change

VOC Volatile organic compounds

1.0 INTRODUCTION

1.1 Purpose of Analysis and Study Objectives

This Air Quality, Energy, Greenhouse Gas (GHG) Emissions and Health Risk Assessment (HRA) Impact Analysis has been completed to determine the air quality, energy, GHG emissions and HRA impacts associated with the proposed Slover / Alder Avenue Industrial project (proposed project). The following is provided in this report:

- A description of the proposed project;
- A description of the atmospheric setting;
- A description of the criteria pollutants and GHGs;
- A description of the air quality regulatory framework;
- A description of the energy conservation regulatory framework;
- A description of the GHG emissions regulatory framework;
- A description of the air quality, energy, and GHG emissions thresholds including the California Environmental Quality Act (CEQA) significance thresholds;
- An analysis of the conformity of the proposed project with the South Coast Air Quality Management District (SCAQMD) Air Quality Management Plan (AQMP);
- An analysis of the short-term construction related and long-term operational air quality, energy, and GHG emissions impacts;
- An analysis of the cancer and non-cancer risks (acute and chronic) from operational TAC emissions; and
- An analysis of the conformity of the proposed project with all applicable energy and GHG emissions reduction plans and policies.

1.2 Site Locations and Study Area

The project site is located in Bloomington, which is an unincorporated area of the County of San Bernardino (County). The 13.23-acre project site currently contains two single-family residences on the northwest and southwest corner of the project site, three commercial/industrial buildings, a construction storage site, and trailer parking lot. Multiple shipping containers and other storage units are located on the northeast portion of the project site. The project site is bounded by Slover Avenue and a combination of industrial and residential uses to the north, industrial uses to the east, a combination of residential and industrial uses to the south, and Alder Avenue and a combination of residential and industrial uses to the west. The project local study area is shown in Figure 1.

Sensitive Receptors in Project Vicinity

The nearest sensitive receptors to the project site are the single-family homes that are located adjacent to the south side of the project site, where the residential structures are located as close as 30 feet south of the project site. The nearest school is Bloomington High School, which is located as near as 330 feet south of the project site.

1.3 Proposed Project Description

The proposed project consists of demolition of the existing buildings onsite and construction of an approximately 259,481 square foot high-cube warehouse building, inclusive of 4,000 square feet of office space. The Project also includes the construction of parking, landscaping, signage, and utility improvements to serve the site. A total of 40 dock-high doors are proposed. The dock doors would be placed along the northern boundary of the warehouse. The parking lot would include 131 passenger vehicle stalls and 85 trailer stalls to the north and to the east of the proposed building. Vehicle access to the project site would be provided by two driveways on Slover Avenue and one driveway on Alder Avenue. The proposed site plan is shown in Figure 2.

1.4 Executive Summary

Standard Air Quality, Energy, and GHG Regulatory Conditions

The proposed project will be required to comply with the following regulatory conditions from the SCAQMD and State of California (State).

South Coast Air Quality Management District Rules

The following lists the SCAQMD rules that are applicable, but not limited to the proposed project.

- Rule 402 Nuisance Controls the emissions of odors and other air contaminants;
- Rule 403 Fugitive Dust Controls the emissions of fugitive dust;
- Rules 1108 and 1108.1 Cutback and Emulsified Asphalt Controls the VOC content in asphalt;
- Rule 1113 Architectural Coatings Controls the VOC content in paints and solvents; and
- Rule 1143 Paint Thinners Controls the VOC content in paint thinners.
- Rule 1403 Asbestos Removal Regulates asbestos emissions from demolition activities.

State of California Rules

The following lists the State of California Code of Regulations (CCR) air quality emission rules that are applicable, but not limited to the proposed project.

- CCR Title 13, Article 4.8, Chapter 9, Section 2449 In use Off-Road Diesel Vehicles;
- CCR Title 13, Section 2025 On-Road Diesel Truck Fleets;
- CCR Title 24 Part 6 California Building Energy Standards; and
- CCR Title 24 Part 11 California Green Building Standards.

Summary of Analysis Results

The following is a summary of the proposed project's impacts with regard to the State CEQA Guidelines air quality, energy, and GHG emissions checklist questions.

Conflict with or obstruct implementation of the applicable air quality plan?

Less than significant impact.

Result in a cumulatively considerable net increase of any criteria pollutant for which the project region is non-attainment under an applicable Federal or State ambient air quality standard?

Less than significant impact.

Expose sensitive receptors to substantial pollutant concentrations?

Less than significant impact.

Result in other emissions (such as those leading to odors) adversely affecting a substantial number of people?

Less than significant impact.

Result in potentially significant environmental impact due to wasteful, inefficient, or unnecessary consumption of energy resources, during project construction or operation;

Less than significant impact.

Conflict with or obstruct a state or local plan for renewable energy;

Less than significant impact.

Generate GHG emissions, either directly or indirectly, that may have a significant impact on the environment?

Less than significant impact.

Conflict with any applicable plan, policy or regulation of an agency adopted for the purpose of reducing the emissions of GHGs?

Less than significant impact.

1.5 Project Design Features Incorporated into the Proposed Project

This analysis was based on implementation of the following project design features that the project applicant has committed to implementing. According to *Forklift Market Analysis*, 2016-2027, prepared by Grand View Research, 2019, currently two-thirds of all new forklifts sold are electric-powered and by 2027 three-quarter of all new forklifts will be electric-powered. As such Project Design Feature 1 is based on current market trends, as it would not be cost-effective to install the diesel tanks onsite for the limited duration of use of diesel-powered equipment onsite.


Project Design Feature 1:

All off-road equipment (non-street legal), such as forklifts and street sweepers, used onsite for warehouse operations shall be powered by alternative fuels, electrical batteries or other alternative/non-diesel fuels (e.g., propane or compressed natural gas (CNG)) that do not emit diesel particulate matter, and that are low or zero emission.

1.6 Mitigation Measures for the Proposed Project


This analysis found that implementation of the State and SCAQMD air quality, energy, and GHG emissions reductions regulations detailed in Section 1.4 above, through implementation of the Project Design Features detailed in Section 1.5 above would limit criteria pollutants, toxic air contaminants, odors, and

GHG emissions from the proposed project to le- required for the proposed project with respect to	ss than significant levels. o air quality, energy, and Gl	No mitigation measures are HG emissions.



Imagery @2021 Google, Imagery @2021 County of San Bernardino, Maxar Technologies, U.S. Geological Survey, USDA Farm Service Agency, Map data @2021

SOURCE: Google Maps.





2.0 AIR POLLUTANTS

Air pollutants are generally classified as either criteria pollutants or non-criteria pollutants. Federal ambient air quality standards have been established for criteria pollutants, whereas no ambient standards have been established for non-criteria pollutants. For some criteria pollutants, separate standards have been set for different periods. Most standards have been set to protect public health. For some pollutants, standards have been based on other values (such as protection of crops, protection of materials, or avoidance of nuisance conditions). A summary of federal and state ambient air quality standards is provided in the Regulatory Framework section.

2.1 Criteria Pollutants and Ozone Precursors

The criteria pollutants consist of: ozone, nitrogen oxides (NOx), CO, sulfur oxides (SOx), lead, and particulate matter (PM). The ozone precursors consist of NO_x and VOC. These pollutants can harm your health and the environment, and cause property damage. The Environmental Protection Agency (EPA) calls these pollutants "criteria" air pollutants because it regulates them by developing human health-based and/or environmentally-based criteria for setting permissible levels. The following provides descriptions of each of the criteria pollutants and ozone precursors.

Nitrogen Oxides

NOx is the generic term for a group of highly reactive gases which contain nitrogen and oxygen. While most NOx are colorless and odorless, concentrations of nitrogen dioxide (NO_2) can often be seen as a reddish-brown layer over many urban areas. NOx form when fuel is burned at high temperatures, as in a combustion process. The primary manmade sources of NO_x are motor vehicles, electric utilities, and other industrial, commercial, and residential sources that burn fuel. NOx reacts with other pollutants to form, ground-level ozone, nitrate particles, acid aerosols, as well as NO_2 , which cause respiratory problems. NO_x and the pollutants formed from NO_x can be transported over long distances, following the patterns of prevailing winds. Therefore, controlling NOx is often most effective if done from a regional perspective, rather than focusing on the nearest sources.

Ozone

Ozone is not usually emitted directly into the air, instead it is created by a chemical reaction between NOx and VOC in the presence of sunlight. Motor vehicle exhaust, industrial emissions, gasoline vapors, chemical solvents as well as natural sources emit NOx and VOC that help form ozone. Ground-level ozone is the primary constituent of smog. Sunlight and hot weather cause ground-level ozone to form with the greatest concentrations usually occurring downwind from urban areas. Ozone is subsequently considered a regional pollutant. Ground-level ozone is a respiratory irritant and an oxidant that increases susceptibility to respiratory infections and can cause substantial damage to vegetation and other materials. Because NOx and VOC are ozone precursors, the health effects associated with ozone are also indirect health effects associated with significant levels of NOx and VOC emissions.

Carbon Monoxide

Carbon monoxide (CO) is a colorless, odorless gas that is formed when carbon in fuel is not burned completely. It is a component of motor vehicle exhaust, which contributes approximately 56 percent of all CO emissions nationwide. In cities, 85 to 95 percent of all CO emissions may come from motor vehicle exhaust. Other sources of CO emissions include industrial processes (such as metals processing and chemical manufacturing), residential wood burning, and natural sources such as forest fires. Woodstoves,

gas stoves, cigarette smoke, and unvented gas and kerosene space heaters are indoor sources of CO. The highest levels of CO in the outside air typically occur during the colder months of the year when inversion conditions are more frequent. The air pollution becomes trapped near the ground beneath a layer of warm air. CO is described as having only a local influence because it dissipates quickly. Since CO concentrations are strongly associated with motor vehicle emissions, high CO concentrations generally occur in the immediate vicinity of roadways with high traffic volumes and traffic congestion, active parking lots, and in automobile tunnels. Areas adjacent to heavily traveled and congested intersections are particularly susceptible to high CO concentrations.

CO is a public health concern because it combines readily with hemoglobin and thus reduces the amount of oxygen transported in the bloodstream. The health threat from lower levels of CO is most serious for those who suffer from heart disease such as angina, clogged arteries, or congestive heart failure. For a person with heart disease, a single exposure to CO at low levels may cause chest pain and reduce that person's ability to exercise; repeated exposures may contribute to other cardiovascular effects. High levels of CO can affect even healthy people. People who breathe high levels of CO can develop vision problems, reduced ability to work or learn, reduced manual dexterity, and difficulty performing complex tasks. At extremely high levels, CO is poisonous and can cause death.

Sulfur Oxides

SOx gases are formed when fuel containing sulfur, such as coal and oil is burned, as well as from the refining of gasoline. SOx dissolves easily in water vapor to form acid and interacts with other gases and particles in the air to form sulfates and other products that can be harmful to people and the environment.

Lead

Lead is a metal found naturally in the environment as well as manufactured products. The major sources of lead emissions have historically been motor vehicles and industrial sources. Due to the phase out of leaded gasoline, metal processing is now the primary source of lead emissions to the air. High levels of lead in the air are typically only found near lead smelters, waste incinerators, utilities, and lead-acid battery manufacturers. Exposure of fetuses, infants and children to low levels of lead can adversely affect the development and function of the central nervous system, leading to learning disorders, distractibility, inability to follow simple commands, and lower intelligence quotient. In adults, increased lead levels are associated with increased blood pressure.

Particulate Matter

PM is the term for a mixture of solid particles and liquid droplets found in the air. PM is made up of a number of components including acids (such as nitrates and sulfates), organic chemicals, metals, and soil or dust particles. The size of particles is directly linked to their potential for causing health problems. Particles that are less than 10 micrometers in diameter (PM10) that are also known as *Respirable Particulate Matter* are the particles that generally pass through the throat and nose and enter the lungs. Once inhaled, these particles can affect the heart and lungs and cause serious health effects. Particles that are less than 2.5 micrometers in diameter (PM2.5) that are also known as *Fine Particulate Matter* have been designated as a subset of PM10 due to their increased negative health impacts and its ability to remain suspended in the air longer and travel further.

Volatile Organic Compounds

Hydrocarbons are organic gases that are formed from hydrogen and carbon and sometimes other elements. Hydrocarbons that contribute to formation of ozone are referred to and regulated as VOCs (also

referred to as reactive organic gases). Combustion engine exhaust, oil refineries, and fossil-fueled power plants are the sources of hydrocarbons. Other sources of hydrocarbons include evaporation from petroleum fuels, solvents, dry cleaning solutions, and paint.

VOC is not classified as a criteria pollutant, since VOCs by themselves are not a known source of adverse health effects. The primary health effects of VOCs result from the formation of ozone and its related health effects. High levels of VOCs in the atmosphere can interfere with oxygen intake by reducing the amount of available oxygen through displacement. Carcinogenic forms of hydrocarbons, such as benzene, are considered TACs. There are no separate health standards for VOCs as a group.

2.2 Other Pollutants of Concern

Toxic Air Contaminants

In addition to the above-listed criteria pollutants, TACs are another group of pollutants of concern. TACs is a term that is defined under the California Clean Air Act and consists of the same substances that are defined as Hazardous Air Pollutants (HAPs) in the Federal Clean Air Act. There are over 700 hundred different types of TACs with varying degrees of toxicity. Sources of TACs include industrial processes such as petroleum refining and chrome plating operations, commercial operations such as gasoline stations and dry cleaners, and motor vehicle exhaust. Cars and trucks release at least 40 different toxic air contaminants. The most important of these TACs, in terms of health risk, are diesel particulates, benzene, formaldehyde, 1,3-butadiene, and acetaldehyde. Public exposure to TACs can result from emissions from normal operations as well as from accidental releases. Health effects of TACs include cancer, birth defects, neurological damage, and death.

TACs are less pervasive in the urban atmosphere than criteria air pollutants, however they are linked to short-term (acute) or long-term (chronic or carcinogenic) adverse human health effects. There are hundreds of different types of TACs with varying degrees of toxicity. Sources of TACs include industrial processes, commercial operations (e.g., gasoline stations and dry cleaners), and motor vehicle exhaust.

According to *The California Almanac of Emissions and Air Quality 2013 Edition*, the majority of the estimated health risk from TACs can be attributed to relatively few compounds, the most important of which is DPM. DPM is a subset of PM2.5 because the size of diesel particles are typically 2.5 microns and smaller. The identification of DPM as a TAC in 1998 led the California Air Resources Board (CARB) to adopt the Risk Reduction Plan to Reduce Particulate Matter Emissions from Diesel-fueled Engines and Vehicles in September 2000. The plan's goals are a 75-percent reduction in DPM by 2010 and an 85-percent reduction by 2020 from the 2000 baseline. Diesel engines emit a complex mixture of air pollutants, composed of gaseous and solid material. The visible emissions in diesel exhaust are known as particulate matter or PM, which includes carbon particles or "soot." Diesel exhaust also contains a variety of harmful gases and over 40 other cancer-causing substances. California's identification of DPM as a toxic air contaminant was based on its potential to cause cancer, premature deaths, and other health problems. Exposure to DPM is a health hazard, particularly to children whose lungs are still developing and the elderly who may have other serious health problems. Overall, diesel engine emissions are responsible for the majority of California's potential airborne cancer risk from combustion sources.

The various pollutants within DPM that also cause acute and chronic health impacts are detailed below in Table A. Table A was developed through crosschecking all diesel emissions pollutants provided in San

Diego Air Pollutant Control District's (SDAPCD) Diesel Fired Engines Emissions Factor Table to the list of acute and chronic reference exposure levels provided at: http://oehha.ca.gov/air/allrels.html.

According to the California Office of Environmental Health and Hazards Assessment (OEHHA), no acute risk had been found to be directly created from DPM, so there is no acute AREL assigned to DPM. However, as detailed in Table A, other TAC emissions associated with diesel exhaust do have an acute REL assigned to them. In order to account for the acute risk from all TAC emissions associated with diesel emissions, a hypothetical acute REL was calculated for DPM through multiplying each TAC with an acute REL to its diesel weight fraction and then adding together the results, which resulted in a hypothetical acute AREL of 2,189 for diesel emissions.

Table A - Diesel Emission Pollutants that Cause Acute and Chronic Health Impacts

	TAC Potency Factors (μg/m³)¹		Percent of DPM		
TAC	Acute REL ²	Chronic REL	Emission Rate ³	Target Organ Systems	
1,3-Butadiene	660	140	0.51%	Development	
Acetaldehyde	470	140	1.84%	Eyes, respiratory system (sensory irritation)	
Acrolein	2.5	0.35	0.08%	Eyes, respiratory system	
Arsenic	0.2	0.015	0.004%	Reproductive/developmental, cardiovascular system, nervous system	
Benzene	27	3	0.44%	Hematologic system, immune system, reproductive/developmental	
Cadmium		0.02	0.004%	kidney, respiratory system	
Chlorobenzene		1,000	0.0005%	Eyes, respiratory system	
Chromium (hexavalent)		0.2	0.001%	Respiratory system, hematologic system	
Copper	100		0.01%	Respiratory system	
Ethyl benzene		5	0.03%	Liver, kidney, developmental	
Formaldehyde	55	9	4.07%	Eyes, immune system, respiratory	
Hexane		200	0.06%	Nervous system	
Hydrogen Chloride	2,100	9	0.44%	Eyes, respiratory system	
Manganese		0.09	0.01%	Nervous system	
Mercury	0.6	0.03	0.005%	Reproductive/developmental	
Naphthalene		9	0.05%	Respiratory system	
Nickel	0.2	002	0.01%	Immune system, respiratory system	
Propylene		3000	1.10%	Respiratory System	
Selenium		20	0.01%	Liver, cardiovascular system, nervous system	
Toluene	37000	300	0.25%	Nervous system, eyes, respiratory system, reproductive/developmental	
Xylene	22000	700	0.10%	Eyes, nervous and respiratory systems	
DPM		5		Respiratory system	

Notes:

Sources: SDAPCD, 2011 and OEHHA, 2014.

¹ Potency factors obtained from: <u>http://www.oehha.ca.gov/risk/ChemicalDB/index.asp</u>

² REL = Reference Exposure Level

³ Percentage of DPM Emission Rate calculated by dividing the pollutant's pounds per 1,000 gallons rate by the PM2.5 pounds per 1,000 gallons rate provided by the SDAPCD

Asbestos

Asbestos is listed as a TAC by CARB and as a HAP by the EPA. Asbestos occurs naturally in mineral formations and crushing or breaking these rocks, through construction or other means, can release asbestiform fibers into the air. Asbestos emissions can result from the sale or use of asbestos-containing materials, road surfacing with such materials, grading activities, and surface mining. The risk of disease is dependent upon the intensity and duration of exposure. When inhaled, asbestos fibers may remain in the lungs and with time may be linked to such diseases as asbestosis, lung cancer, and mesothelioma. The nearest likely locations of naturally occurring asbestos, as identified in the *General Location Guide for Ultramafic Rocks in California*, prepared by the California Division of Mines and Geology, is located in Santa Barbara County. The nearest historic asbestos mine to the project site, as identified in the *Reported Historic Asbestos Mines*, *Historic Asbestos Prospects*, and Other Natural Occurrences of Asbestos in California, prepared by U.S. Geological Survey, is located at Asbestos Mountain, which is approximately 60 miles southeast of the project site in the San Jacinto Mountains. Due to the distance to the nearest natural occurrences of asbestos, the project site is not likely to contain asbestos.

In addition to naturally occurring asbestos, asbestos was used extensively in building construction from the early 1940s through the 1970s as highly-effective and inexpensive fire-retardant material and thermal and acoustic insulator. Asbestos is most commonly found as thermal insulation on pipes, but also may be found in certain types of floor and ceiling tiles. There are two types of asbestos: "friable" and "non-friable." Friable asbestos generally contains more than 1 percent asbestos by weight or area, and can be crumbled, pulverized, or reduced to powder by the pressure of an ordinary human hand, which releases fibers. Non friable asbestos generally contains more than 1 percent asbestos but cannot be pulverized under hand pressure and generally does not release asbestos fibers. Due to the age of the existing onsite buildings, the project site has a potential to contain asbestos, which is analyzed below in Section 10.4 of this Report.

3.0 GREENHOUSE GASES

3.1 Greenhouse Gases

Constituent gases of the Earth's atmosphere, called atmospheric GHGs, play a critical role in the Earth's radiation amount by trapping infrared radiation from the Earth's surface, which otherwise would have escaped to space. Prominent greenhouse gases contributing to this process include carbon dioxide (CO_2), methane (CH_4), ozone, water vapor, nitrous oxide (N_2O), and chlorofluorocarbons (CFC_5). This phenomenon, known as the Greenhouse Effect, is responsible for maintaining a habitable climate. Anthropogenic (caused or produced by humans) emissions of these greenhouse gases in excess of natural ambient concentrations are responsible for the enhancement of the Greenhouse Effect and have led to a trend of unnatural warming of the Earth's natural climate, known as global warming or climate change. Emissions of gases that induce global warming are attributable to human activities associated with industrial/manufacturing, agriculture, utilities, transportation, and residential land uses. Emissions of CO_2 and N_2O are byproducts of fossil fuel combustion. Methane, a potent greenhouse gas, results from offgassing associated with agricultural practices and landfills. Sinks of CO_2 , where CO_2 is stored outside of the atmosphere, include uptake by vegetation and dissolution into the ocean. The following provides a description of each of the greenhouse gases and their global warming potential.

Water Vapor

Water vapor is the most abundant, important, and variable GHG in the atmosphere. Water vapor is not considered a pollutant; in the atmosphere it maintains a climate necessary for life. Changes in its concentration are primarily considered a result of climate feedbacks related to the warming of the atmosphere rather than a direct result of industrialization. The feedback loop in which water is involved is critically important to projecting future climate change. As the temperature of the atmosphere rises, more water is evaporated from ground storage (rivers, oceans, reservoirs, soil). Because the air is warmer, the relative humidity can be higher (in essence, the air is able to "hold" more water when it is warmer), leading to more water vapor in the atmosphere. As a GHG, the higher concentration of water vapor is then able to absorb more thermal indirect energy radiated from the Earth, thus further warming the atmosphere. The warmer atmosphere can then hold more water vapor and so on and so on. This is referred to as a "positive feedback loop." The extent to which this positive feedback loop will continue is unknown as there is also dynamics that put the positive feedback loop in check. As an example, when water vapor increases in the atmosphere, more of it will eventually also condense into clouds, which are more able to reflect incoming solar radiation (thus allowing less energy to reach the Earth's surface and heat it up).

Carbon Dioxide

The natural production and absorption of CO_2 is achieved through the terrestrial biosphere and the ocean. However, humankind has altered the natural carbon cycle by burning coal, oil, natural gas, and wood. Since the industrial revolution began in the mid-1700s, each of these activities has increased in scale and distribution. CO_2 was the first GHG demonstrated to be increasing in atmospheric concentration with the first conclusive measurements being made in the last half of the 20^{th} century. Prior to the industrial revolution, concentrations were fairly stable at 280 parts per million (ppm). The International Panel on Climate Change (IPCC) indicates that concentrations were 379 ppm in 2005, an increase of more than 30 percent. Left unchecked, the IPCC projects that concentration of carbon dioxide in the atmosphere is projected to increase to a minimum of 540 ppm by 2100 as a direct result of anthropogenic sources. This

could result in an average global temperature rise of at least two degrees Celsius or 3.6 degrees Fahrenheit.

Methane

 CH_4 is an extremely effective absorber of radiation, although its atmospheric concentration is less than that of CO_2 . Its lifetime in the atmosphere is brief (10 to 12 years), compared to some other GHGs (such as CO_2 , N_2O , and CFCs). CH_4 has both natural and anthropogenic sources. It is released as part of the biological processes in low oxygen environments, such as in swamplands or in rice production (at the roots of the plants). Over the last 50 years, human activities such as growing rice, raising cattle, using natural gas, and mining coal have added to the atmospheric concentration of methane. Other anthropocentric sources include fossil-fuel combustion and biomass burning.

Nitrous Oxide

Concentrations of N_2O also began to rise at the beginning of the industrial revolution. In 1998, the global concentration of this GHG was documented at 314 parts per billion (ppb). N_2O is produced by microbial processes in soil and water, including those reactions which occur in fertilizer containing nitrogen. In addition to agricultural sources, some industrial processes (fossil fuel-fired power plants, nylon production, nitric acid production, and vehicle emissions) also contribute to its atmospheric load. N_2O is also commonly used as an aerosol spray propellant (i.e., in whipped cream bottles, in potato chip bags to keep chips fresh, and in rocket engines and race cars).

Chlorofluorocarbons

CFCs are gases formed synthetically by replacing all hydrogen atoms in methane or ethane with chlorine and/or fluorine atoms. CFCs are nontoxic, nonflammable, insoluble, and chemically unreactive in the troposphere (the level of air at the Earth's surface). CFCs have no natural source, but were first synthesized in 1928. They were used for refrigerants, aerosol propellants, and cleaning solvents. Due to the discovery that they are able to destroy stratospheric ozone, a global effort to halt their production was undertaken and in 1989 the European Community agreed to ban CFCs by 2000 and subsequent treaties banned CFCs worldwide by 2010. This effort was extremely successful, and the levels of the major CFCs are now remaining level or declining. However, their long atmospheric lifetimes mean that some of the CFCs will remain in the atmosphere for over 100 years.

Hydrofluorocarbons

Hydrofluorocarbons (HFCs) are synthetic man-made chemicals that are used as a substitute for CFCs. Out of all the GHGs, they are one of three groups with the highest global warming potential. The HFCs with the largest measured atmospheric abundances are (in order), HFC-23 (CHF $_3$), HFC-134a (CF $_3$ CH $_2$ F), and HFC-152a (CH $_3$ CHF $_2$). Prior to 1990, the only significant emissions were HFC-23. HFC-134a use is increasing due to its use as a refrigerant. Concentrations of HFC-23 and HFC-134a in the atmosphere are now about 10 parts per trillion (ppt) each. Concentrations of HFC-152a are about 1 ppt. HFCs are manmade for applications such as automobile air conditioners and refrigerants.

Perfluorocarbons

Perfluorocarbons (PFCs) have stable molecular structures and do not break down through the chemical processes in the lower atmosphere. High-energy ultraviolet rays about 60 kilometers above Earth's surface are able to destroy the compounds. Because of this, PFCs have very long lifetimes, between 10,000 and 50,000 years. Two common PFCs are tetrafluoromethane (C_{F_4}) and hexafluoroethane (C_{F_6}).

Concentrations of CF₄ in the atmosphere are over 70 ppt. The two main sources of PFCs are primary aluminum production and semiconductor manufacturing.

Sulfur Hexafluoride

Sulfur Hexafluoride (SF₆) is an inorganic, odorless, colorless, nontoxic, nonflammable gas. SF₆ has the highest global warming potential of any gas evaluated; 23,900 times that of CO₂. Concentrations in the 1990s were about 4 ppt. Sulfur hexafluoride is used for insulation in electric power transmission and distribution equipment, in the magnesium industry, in semiconductor manufacturing, and as a tracer gas for leak detection.

Aerosols

Aerosols are particles emitted into the air through burning biomass (plant material) and fossil fuels. Aerosols can warm the atmosphere by absorbing and emitting heat and can cool the atmosphere by reflecting light. Cloud formation can also be affected by aerosols. Sulfate aerosols are emitted when fuel containing sulfur is burned. Black carbon (or soot) is emitted during biomass burning due to the incomplete combustion of fossil fuels. Particulate matter regulation has been lowering aerosol concentrations in the United States; however, global concentrations are likely increasing.

3.2 Global Warming Potential

GHGs have varying global warming potential (GWP). The GWP is the potential of a gas or aerosol to trap heat in the atmosphere; it is the cumulative radiative forcing effects of a gas over a specified time horizon resulting from the emission of a unit mass of gas relative to the reference gas, CO_2 . The GHGs listed by the IPCC and the CEQA Guidelines are discussed in this section in order of abundance in the atmosphere. Water vapor, the most abundant GHG, is not included in this list because its natural concentrations and fluctuations far outweigh its anthropogenic (human-made) sources. To simplify reporting and analysis, GHGs are commonly defined in terms of their GWP. The IPCC defines the GWP of various GHG emissions on a normalized scale that recasts all GHG emissions in terms of CO_2 equivalent (CO_2 e). As such, the GWP of CO_2 is equal to 1. The GWP values used in this analysis are based on the 2007 IPCC Fourth Assessment Report, which are used in CARB's 2014 Scoping Plan Update and the CalEEMod Model Version 2020.4.0 and are detailed in Table B. The IPCC has updated the Global Warming Potentials of some gases in their Fifth Assessment Report, however the new values have not yet been incorporated into the CalEEMod model that has been utilized in this analysis.

Table B - Global Warming Potentials, Atmospheric Lifetimes and Abundances of GHGs

Gas	Atmospheric Lifetime (years)¹	Global Warming Potential (100 Year Horizon) ²	Atmospheric Abundance
Carbon Dioxide (CO ₂)	50-200	1	379 ppm
Methane (CH ₄)	9-15	25	1,774 ppb
Nitrous Oxide (N ₂ O)	114	298	319 ppb
HFC-23	270	14,800	18 ppt
HFC-134a	14	1,430	35 ppt
HFC-152a	1.4	124	3.9 ppt
PFC: Tetrafluoromethane (CF ₄)	50,000	7,390	74 ppt
PFC: Hexafluoroethane (C ₂ F ₆)	10,000	12,200	2.9 ppt
Sulfur Hexafluoride (SF ₆)	3,200	22,800	5.6 ppt

Notes:

Definitions: ppm = parts per million; ppb = parts per billion; ppt = parts per trillion

Source: IPCC 2007, EPA 2015

3.3 Greenhouse Gas Emissions Inventory

According to the Carbon Dioxide Information Analysis Center¹, 9,855 million metric tons (MMT) of CO₂e emissions were created globally in the year 2014. According to the Environmental Protection Agency (EPA), the breakdown of global GHG emissions by sector consists of: 25 percent from electricity and heat production; 21 percent from industry; 24 percent from agriculture, forestry and other land use activities; 14 percent from transportation; 6 percent from building energy use; and 10 percent from all other sources of energy use².

According to *Inventory of U.S. Greenhouse Gas Emissions and Sinks 1990-2019*, prepared by EPA, in 2019 total U.S. GHG emissions were 6,558 million metric tons (MMT) of CO₂e emissions. Total U.S. emissions have increased by 4 percent between 1990 and 2016 and GHG emissions decreased by 13 percent between 2005 and 2019. The recent decrease in GHG emissions was a result of multiple factors, including population, economic growth, energy markets, and technological changes the include energy efficiency and energy fuel choices. Between 2018 and 2019, GHG emissions decreased by almost 2 percent due to multiple factors, including a one percent decrease in total energy use.

According to California Greenhouse Gas Emissions for 2000 to 2019 Trends of Emissions and Other Indicators, prepared by CARB, July 28, 2021, the State of California created 418.2 million metric tons of carbon dioxide equivalent (MMTCO₂e) in 2019. The 2019 emissions were 7.2 MMTCO₂e lower than 2018 levels and almost 13 MMTCO₂e below the State adopted year 2020 GHG limit of 431 MMTCO₂e. The breakdown of California GHG emissions by sector consists of: 39.7 percent from transportation; 21.1 percent from industrial; 14.1 percent from electricity generation; 7.6 percent from agriculture; 10.5 percent from residential and commercial buildings; 4.9 percent from high global warming potential sources, and 2.1 percent from waste.

¹ Defined as the half-life of the gas.

 $^{^2}$ Compared to the same quantity of CO $_2$ emissions and is based on the Intergovernmental Panel On Climate Change (IPCC) 2007 standard, which is utilized in CalEEMod (Version 2020.4.0), that is used in this report (CalEEMod User Guide, May 2021).

¹ Obtained from: https://cdiac.ess-dive.lbl.gov/trends/emis/tre_glob_2014.html

² Obtained from: https://www.epa.gov/ghgemissions/global-greenhouse-gas-emissions-data

4.0 AIR QUALITY MANAGEMENT

The project site is located within the South Coast Air Basin (Air Basin). The air quality at the project site is addressed through the efforts of various international, federal, state, regional, and local government agencies. These agencies work jointly, as well as individually, to improve air quality through legislation, regulations, planning, policy-making, education, and a variety of programs. The agencies responsible for improving the air quality are discussed below.

4.1 Federal – United States Environmental Protection Agency

The Clean Air Act, first passed in 1963 with major amendments in 1970, 1977 and 1990, is the overarching legislation covering regulation of air pollution in the United States. The Clean Air Act has established the mandate for requiring regulation of both mobile and stationary sources of air pollution at the state and federal level. The EPA was created in 1970 in order to consolidate research, monitoring, standard-setting and enforcement authority into a single agency.

The EPA is responsible for setting and enforcing the National Ambient Air Quality Standards (NAAQS) for atmospheric pollutants. It regulates emission sources that are under the exclusive authority of the federal government, such as aircraft, ships, and certain locomotives. NAAQS pollutants were identified using medical evidence and are shown below in Table C.

Table C – State and Federal Criteria Pollutant Standards

Air	Concentration / Averaging Time		
Pollutant	California	Federal Primary	Adama Dalamana Effects
	Standards	Standards	Most Relevant Effects
Ozone	0.09 ppm / 1-hour 0.07 ppm / 8-hour	0.070 ppm, / 8-hour	(a) Pulmonary function decrements and localized lung edema in humans and animals; (b) Risk to public health implied by alterations in pulmonary morphology and host defense in animals; (c) Increased mortality risk; (d) Risk to public health implied by altered connective tissue metabolism and altered pulmonary morphology in animals after long-term exposures and pulmonary function decrements in chronically exposed humans; (e) Vegetation damage; and (f) Property damage.
Carbon Monoxide (CO)	20.0 ppm / 1-hour 9.0 ppm / 8-hour	35.0 ppm / 1-hour 9.0 ppm / 8-hour	(a) Aggravation of angina pectoris and other aspects of coronary heart disease; (b) Decreased exercise tolerance in persons with peripheral vascular disease and lung disease; (c) Impairment of central nervous system functions; and (d) Possible increased risk to fetuses.
Nitrogen Dioxide (NO ₂)	0.18 ppm / 1-hour 0.030 ppm / annual	100 ppb / 1-hour 0.053 ppm / annual	(a) Potential to aggravate chronic respiratory disease and respiratory symptoms in sensitive groups; (b) Risk to public health implied by pulmonary and extra-pulmonary biochemical and cellular changes and pulmonary structural changes; and (c) Contribution to atmospheric discoloration.
Sulfur Dioxide (SO ₂)	0.25 ppm / 1-hour 0.04 ppm / 24-hour	75 ppb / 1-hour 0.14 ppm/annual	(a) Bronchoconstriction accompanied by symptoms which may include wheezing, shortness of breath and chest tightness, during exercise or physical activity in persons with asthma.
Suspended Particulate	50 μg/m³ / 24-hour 20 μg/m³ / annual	150 μg/m³ / 24- hour	(a) Exacerbation of symptoms in sensitive patients with respiratory or cardiovascular disease; (b) Declines in

Air	Concentration / Averaging Time			
Pollutant	California Standards	Federal Primary Standards	Most Relevant Effects	
Matter (PM ₁₀)			pulmonary function growth in children; and (c) Increased risk of premature death from heart or lung diseases in elderly.	
Suspended Particulate Matter (PM _{2.5})	12 μg/m³ / annual	35 μg/m³ / 24-hour 12 μg/m³ / annual		
Sulfates	25 μg/m³ / 24-hour	No Federal Standards	(a) Decrease in ventilatory function; (b) Aggravation of asthmatic symptoms; (c) Aggravation of cardio-pulmonary disease; (d) Vegetation damage; (e) Degradation of visibility; and (f) Property damage.	
Lead	1.5 μg/m³ / 30-day	0.15 μg/m³ /3- month rolling	(a) Learning disabilities; and (b) Impairment of blood formation and nerve conduction.	
Visibility Reducing Particles	Extinction coefficient of 0.23 per kilometer - visibility of ten miles or more due to particles when relative humidity is less than 70 percent.	No Federal Standards	Visibility impairment on days when relative humidity is less than 70 percent.	

 $Source: \underline{http://www.arb.ca.gov/research/aaqs/aaqs2.pdf} \ .$

As part of its enforcement responsibilities, the EPA requires each state with federal nonattainment areas to prepare and submit a State Implementation Plan (SIP) that demonstrates the means to attain the national standards. The SIP must integrate federal, state, and local components and regulations to identify specific measures to reduce pollution, using a combination of performance standards and market-based programs within the timeframe identified in the SIP. The CARB defines attainment as the category given to an area with no violations in the past three years. As indicated below in Table D, the Air Basin has been designated by EPA for the national standards as a non-attainment area for ozone and PM2.5 and partial non-attainment for lead. Currently, the Air Basin is in attainment with the national ambient air quality standards for CO, PM10, SO₂, and NO₂.

Table D - South Coast Air Basin Attainment Status

Criteria Pollutant	Standard	Averaging Time	Designation ^{a)}	Attainment Date ^{b)}
1-Hour Ozone ^{c)}	NAAQS	NAAQS 1979 1-Hour (0.12 ppm) Nonattainment (Extreme)		2/6/2023 (revised deadline)
	CAAQS	1-Hour (0.09 ppm)	Nonattainment	N/A
0.11 O d)	NAAQS	1997 8-Hour (0.08 ppm)	Nonattainment (Extreme)	6/15/2024
8-Hour Ozone ^{d)}	NAAQS	2008 8-Hour (0.075 ppm)	Nonattainment (Extreme)	8/3/2038
	NAAQS	2015 8-Hour (0.070 ppm)	Pending – Expect Nonattainment (Extreme)	Pending (beyond 2032)
	CAAQS	8-Hour (0.070 ppm)	Nonattainment	Beyond 2032

Criteria Pollutant	Standard	Averaging Time	Designation ^{a)}	Attainment Dateb)
60	NAAQS	1-Hour (35 ppm) 8-Hour (9 ppm)	Attainment (Maintenance)	6/11/2007 (attained)
CO -	CAAQS	1-Hour (20 ppm) 8-Hour (9 ppm)	Attainment	6/11/2007 (attained)
	NAAQS	2010 1-Hour (0.10 ppm)	Unclassifiable/ Attainment	N/A (attained)
$NO_2^{e)}$	NAAQS	1971 Annual (0.053 ppm)	Attainment (Maintenance)	9/22/1998 (attained)
	CAAQS	1-Hour (0.18 ppm) Annual (0.030 ppm)	Attainment	
so fl	NAAQS	2010 1-Hour (75 ppb)	Designations Pending (expect Unclassifiable/ Attainment)	N/A (attained)
SO ₂ ·/	NAAAS	1971 24-Hour (0.14 ppm) 1971 Annual (0.03 ppm)	Unclassifiable/ Attainment	3/19/1979 (attained)
D1440	NAAQS	1987 24-hour (150 μg/m³)	Attainment (Maintenance) ^{g)}	7/26/2013 (attained)
PM10 -	CAAQS	24-hour (50 μg/m³) Annual (20 μg/m³)	Nonattainment	N/A
	NAAQS	2006 24-Hour (35 μg/m³)	Nonattainment (Serious)	12/31/2019
PM2.5 ^{h)}	NAAQS	1997 Annual (15.0 μg/m³)	Attainment (final determination pending)	8/24/2016 (attained 2013)
	NAAQS	2012 Annual (12.0 μg/m³)	Nonattainment (Moderate)	12/31/2025
	CAAQS	Annual (12.0 μg/m³)	Nonattainment	N/A
Lead ⁱ⁾	NAAQS	2008 3-Months Rolling (0.15 μg/m³)	Nonattainment (Partial) (Attainment determination requested)	12/31/2015

Source: SCAQMD, February 2016

Notes:

- a) U.S. EPA often only declares Nonattainment areas; everywhere else is listed as Unclassifiable/Attainment or Unclassifiable b) A design value below the NAAQS for data through the full year or smog season prior to the attainment date is typically required for attainment demonstration
- c) The 1979 1-hour ozone standard (0.12 ppm) was revoked, effective June 15, 2005; however, the Basin has not attained this standard and therefore has some continuing obligations with respect to the revoked standard
- d) The 2008 8-hour ozone NAAQS (0.075 ppm) was revised to 0.070 ppm. Effective 12/28/15 with classifications and implementation goals to be finalized by 10/1/17; the 1997 8-hour ozone NAAQS (0.08 ppm) was revoked in the 2008 ozone implementation rule, effective 4/6/15; there are continuing obligations under the revoked 1997 and revised 2008 ozone until they are attained.
- e) New NO₂ 1-hour standard, effective August 2, 2010; attainment designations January 20, 2012; annual NO₂ standard retained
- f) The 1971 annual and 24-hour SO₂ standards were revoked, effective August 23, 2010; however, these 1971 standards will remain in effect until one year after U.S. EPA promulgates area designations for the 2010 SO₂ 1-hour standard. Area designations are still pending, with Basin expected to be designated Unclassifiable /Attainment.
- g) Annual PM10 standard was revoked, effective December 18, 2006; 24-hour PM10 NAAQS deadline was 12/31/2006; SCAQMD request for attainment redesignation and PM10 maintenance plan was approved by U.S. EPA on June 26, 2013, effective July 26, 2013.
- h) The attainment deadline for the 2006 24-Hour PM2.5 NAAQS was 12/31/15 for the former "moderate" classification; EPA approved reclassification to "serious", effective 2/12/16 with an attainment deadline of 12/31/19; the 2012 (proposal year) annual PM2.5 NAAQS was revised on 1/15/13, effective 3/18/13, from 15 to 12 μ g/m³; new annual designations were final 1/15/15, effective 4/15/15; on July 25, 2016 EPA finalized a determination that the Basin attained the 1997 annual (15.0 μ g/m³) and 24-hour PM2.5 (65 μ g/m³) NAAQS, effective August 24, 2016
- i) Partial Nonattainment designation Los Angeles County portion of Basin only for near-source monitors. Expect to remain in attainment based on current monitoring data; attainment re-designation request pending.

In 2015, one or more stations in the Air Basin exceeded the most current federal standards on a total of 146 days (40 percent of the year), including: 8-hour ozone (113 days over 2015 ozone NAAQS), 24-hour PM2.5 (30 days, including near-road sites; 25 days for ambient sites only), PM10 (2 days), and NO₂ (1 day).

Despite substantial improvement in air quality over the past few decades, some air monitoring stations in the Air Basin still exceed the NAAQS for ozone more frequently than any other area in the United States. Seven of the top 10 stations in the nation most frequently exceeding the 2015 8-hour ozone NAAQS in 2015 were located within the Air Basin, including stations in San Bernardino, Riverside, and Los Angeles Counties (SCAQMD, 2016).

PM2.5 levels in the Air Basin have improved significantly in recent years. By 2013 and again in 2014 and 2015, there were no stations measuring PM2.5 in the Air Basin that violated the former 1997 annual PM2.5 NAAQS (15.0 μ g/m³) for the 3-year design value period. On July 25, 2016 the EPA finalized a determination that the Basin attained the 1997 annual (15.0 μ g/m³) and 24-hour PM2.5 (65 μ g/m³) NAAQS, effective August 24, 2016. Of the 17 federal PM2.5 monitors at ambient stations in the Air Basin for the 2013-2015 period, five stations had design values over the current 2012 annual PM2.5 NAAQS (12.0 μ g/m³), including: Mira Loma (Air Basin maximum at 14.1 μ g/m³), Rubidoux, Fontana, Ontario, Central Los Angeles, and Compton. For the 24-hour PM2.5 NAAQS (35.0 μ g/m³) there were 14 stations in the Air Basin in 2015 that had one or more daily exceedances of the standard, with a combined total of 25 days over that standard in the Air Basin. While it was previously anticipated that the Air Basin's 24-hour PM2.5 NAAQS would be attained by 2015, this did not occur based on the data for 2013 through 2015. The higher number of days exceeding the 24-hour PM2.5 NAAQS over what was expected is largely attributed to the severe drought conditions over this period that allowed for more stagnant conditions in the Air Basin with multi-day buildups of higher PM2.5 concentrations. This was caused by the lack of storm-related dispersion and rain-out of PM and its precursors (SCAQMD, 2016).

The Air Basin is currently in attainment for the federal standards for SO₂, CO, NO₂, and PM10 and the San Bernardino County portion of the Air Basin is currently in attainment for the federal standards for lead. While the concentration level of the 1-hour NO₂ federal standard (100 ppb) was exceeded in the Air Basin for one day in 2015 (Long Beach- Hudson Station), the NAAQS NO₂ design value has not been exceeded. Therefore, the Air Basin remains in attainment of the NO₂ NAAQS (SCAQMD, 2016).

4.2 State - California Air Resources Board

The CARB, which is a part of the California Environmental Protection Agency, is responsible for the coordination and administration of both federal and state air pollution control programs within California. In this capacity, the CARB conducts research, sets the California Ambient Air Quality Standards (CAAQS), compiles emission inventories, develops suggested control measures, provides oversight of local programs, and prepares the SIP. The CAAQS for criteria pollutants are shown above in Table C. In addition, the CARB establishes emission standards for motor vehicles sold in California, consumer products (e.g., hairspray, aerosol paints, and barbeque lighter fluid), and various types of commercial equipment. It also sets fuel specifications to further reduce vehicular emissions.

The Air Basin has been designated by the CARB as a non-attainment area for ozone, PM10 and PM2.5. Currently, the Air Basin is in attainment with the ambient air quality standards for CO, NO_2 , SO_2 , lead, and sulfates and is unclassified for visibility reducing particles and Hydrogen Sulfide.

The following lists the State of California Code of Regulations (CCR) air quality emission rules that are applicable, but not limited to all warehouse projects in the State.

Assembly Bill 2588

The Air Toxics "Hot Spots" Information and Assessment Act (Assembly Bill [AB] 2588, 1987, Connelly) was enacted in 1987 as a means to establish a formal air toxics emission inventory risk quantification program. AB 2588, as amended, establishes a process that requires stationary sources to report the type and quantities of certain substances their facilities routinely release in California. The data is ranked by high, intermediate, and low categories, which are determined by: the potency, toxicity, quantity, volume, and proximity of the facility to nearby receptors.

CARB Regulation for In-Use Off-Road Diesel Vehicles

On July 26, 2007, the CARB adopted California Code of Regulations Title 13, Article 4.8, Chapter 9, Section 2449 to reduce DPM and NOx emissions from in-use off-road heavy-duty diesel vehicles in California. Such vehicles are used in construction, mining, and industrial operations. The regulation limits idling to no more than five consecutive minutes, requires reporting and labeling, and requires disclosure of the regulation upon vehicle sale. Performance requirements of the rule are based on a fleet's average NOx emissions, which can be met by replacing older vehicles with newer, cleaner vehicles or by applying exhaust retrofits. The regulation was amended in 2010 to delay the original timeline of the performance requirement making the first compliance deadline January 1, 2014 for large fleets (over 5,000 horsepower), 2017 for medium fleets (2,501-5,000 horsepower), and 2019 for small fleets (2,500 horsepower or less). Currently, no commercial operation in California may add any equipment to their fleet that has a Tier 0 or Tier 1 engine. By January 1, 2018 medium and large fleets will be restricted from adding Tier 2 engines to their fleets and by January 2023, no commercial operation will be allowed to add Tier 2 engines to their fleets. It should be noted that commercial fleets may continue to use their existing Tier 0 and 1 equipment, if they can demonstrate that the average emissions from their entire fleet emissions meet the NOx emissions targets.

CARB Resolution 08-43 for On-Road Diesel Truck Fleets

On December 12, 2008 the CARB adopted Resolution 08-43, which limits NOx, PM10 and PM2.5 emissions from on-road diesel truck fleets that operate in California. On October 12, 2009 Executive Order R-09-010 was adopted that codified Resolution 08-43 into Section 2025, title 13 of the California Code of Regulations. This regulation requires that by the year 2023 all commercial diesel trucks that operate in California shall meet model year 2010 (Tier 4 Final) or latter emission standards. In the interim period, this regulation provides annual interim targets for fleet owners to meet. By January 1, 2014, 50 percent of a truck fleet is required to have installed Best Available Control Technology (BACT) for NOx emissions and 100 percent of a truck fleet installed BACT for PM10 emissions. This regulation also provides a few exemptions including a onetime per year 3-day pass for trucks registered outside of California. All onroad diesel trucks utilized during construction of the proposed project will be required to comply with Resolution 08-43.

4.3 Regional – Southern California

The SCAQMD is the agency principally responsible for comprehensive air pollution control in the South Coast Air Basin. To that end, as a regional agency, the SCAQMD works directly with the Southern California Association of Governments (SCAG), county transportation commissions, and local governments and cooperates actively with all federal and state agencies.

South Coast Air Quality Management District

SCAQMD develops rules and regulations, establishes permitting requirements for stationary sources, inspects emission sources, and enforces such measures through educational programs or fines, when necessary. SCAQMD is directly responsible for reducing emissions from stationary, mobile, and indirect sources. It has responded to this requirement by preparing a sequence of AQMPs. The *Final 2016 Air Quality Management Plan* (2016 AQMP) was adopted by the SCAQMD Board on March 3, 2016 and was adopted by CARB on March 23, 2017 for inclusion into the SIP. The 2016 AQMP was prepared in order to meet the following standards:

- 8-hour Ozone (75 ppb) by 2032
- Annual PM2.5 (12 μg/m3) by 2021-2025
- 8-hour Ozone (80 ppb) by 2024 (updated from the 2007 and 2012 AQMPs)
- 1-hour Ozone (120 ppb) by 2023 (updated from the 2012 AQMP)
- 24-hour PM2.5 (35 μg/m³) by 2019 (updated from the 2012 AQMP)

In addition to meeting the above standards, the 2016 AQMP also includes revisions to the attainment demonstrations for the 1997 8-hour ozone NAAQS and the 1979 1-hour ozone NAAQS. The prior 2012 AQMP was prepared in order to demonstrate attainment with the 24-hour PM2.5 standard by 2014 through adoption of all feasible measures. The prior 2007 AQMP demonstrated attainment with the 1997 8-hour ozone (80 ppb) standard by 2023, through implementation of future improvements in control techniques and technologies. These "black box" emissions reductions represent 65 percent of the remaining NOx emission reductions by 2023 in order to show attainment with the 1997 8-hour ozone NAAQS. Given the magnitude of these needed emissions reductions, additional NOx control measures have been provided in the 2012 AQMP even though the primary purpose was to show compliance with 24-hour PM2.5 emissions standards.

The 2016 AQMP provides a new approach that focuses on available, proven and cost effective alternatives to traditional strategies, while seeking to achieve multiple goals in partnership with other entities to promote reductions in GHG emissions and TAC emissions as well as efficiencies in energy use, transportation, and goods movement. The 2016 AQMP recognizes the critical importance of working with other agencies to develop funding and other incentives that encourage the accelerated transition of vehicles, buildings and industrial facilities to cleaner technologies in a manner that benefits not only air quality, but also local businesses and the regional economy.

Although SCAQMD is responsible for regional air quality planning efforts, it does not have the authority to directly regulate air quality issues associated with plans and new development projects throughout the Air Basin. Instead, this is controlled through local jurisdictions in accordance to CEQA. In order to assist local jurisdictions with air quality compliance issues the CEQA Air Quality Handbook (SCAQMD CEQA Handbook), prepared by SCAQMD, 1993, with the most current updates found at http://www.aqmd.gov/ceqa/hdbk.html, was developed in accordance with the projections and programs detailed in the AQMPs. The purpose of the SCAQMD CEQA Handbook is to assist Lead Agencies, as well as consultants, project proponents, and other interested parties in evaluating a proposed project's potential air quality impacts. Specifically, the SCAQMD CEQA Handbook explains the procedures that SCAQMD recommends be followed for the environmental review process required by CEQA. The SCAQMD CEQA Handbook provides direction on how to evaluate potential air quality impacts, how to determine whether these impacts are significant, and how to mitigate these impacts. The SCAQMD

intends that by providing this guidance, the air quality impacts of plans and development proposals will be analyzed accurately and consistently throughout the Air Basin, and adverse impacts will be minimized.

The following lists the SCAQMD rules that are applicable but not limited to warehouse projects in the Air Basin.

Rule 402 - Nuisance

Rule 402 prohibits a person from discharging from any source whatsoever such quantities of air contaminants or other material which causes injury, detriment, nuisance, or annoyance to any considerable number of persons or to the public, or which endanger the comfort, repose, health or safety of any such persons or the public, or which cause, or have a natural tendency to cause, injury or damage to business or property. Compliance with Rule 402 will reduce local air quality and odor impacts to nearby sensitive receptors.

Rule 403- Fugitive Dust

Rule 403 governs emissions of fugitive dust during construction activities and requires that no person shall cause or allow the emissions of fugitive dust such that dust remains visible in the atmosphere beyond the property line or the dust emission exceeds 20 percent opacity, if the dust is from the operation of a motorized vehicle. Compliance with this rule is achieved through application of standard Best Available Control Measures, which include but are not limited to the measures below. Compliance with these rules would reduce local air quality impacts to nearby sensitive receptors.

- Utilize either a pad of washed gravel 50 feet long, 100 feet of paved surface, a wheel shaker, or a
 wheel washing device to remove material from vehicle tires and undercarriages before leaving
 project site.
- Do not allow any track out of material to extend more than 25 feet onto a public roadway and remove all track out at the end of each workday.
- Water all exposed areas on active sites at least three times per day and pre-water all areas prior to clearing and soil moving activities.
- Apply nontoxic chemical stabilizers according to manufacturer specifications to all construction areas that will remain inactive for 10 days or longer.
- Pre-water all material to be exported prior to loading, and either cover all loads or maintain at least 2 feet of freeboard in accordance with the requirements of California Vehicle Code Section 23114.
- Replant all disturbed area as soon as practical.
- Suspend all grading activities when wind speeds (including wind gusts) exceed 25 miles per hour.
- Restrict traffic speeds on all unpaved roads to 15 miles per hour or less.

Rules 1108 and 1108.1 - Cutback and Emulsified Asphalt

Rules 1108 and 1108.1 govern the sale, use, and manufacturing of asphalt and limits the VOC content in asphalt. This rule regulates the VOC contents of asphalt used during construction as well as any on-going maintenance during operations. Therefore, all asphalt used during construction and operation of the proposed project must comply with SCAQMD Rules 1108 and 1108.1.

Rule 1113 - Architectural Coatings

Rule 1113 governs the sale, use, and manufacturing of architectural coatings and limits the VOC content in sealers, coatings, paints and solvents. This rule regulates the VOC contents of paints available during construction. Therefore, all paints and solvents used during construction and operation of the proposed project must comply with SCAQMD Rule 1113.

Rule 1143 – Paint Thinners

Rule 1143 governs the sale, use, and manufacturing of paint thinners and multi-purpose solvents that are used in thinning of coating materials, cleaning of coating application equipment, and other solvent cleaning operations. This rule regulates the VOC content of solvents used during construction. Solvents used during construction and operation of the proposed project must comply with SCAQMD Rule 1143.

Rule 1403 – Asbestos Removal

Rule 1403 governs asbestos emissions from demolition and renovation activities. The existing structures on the project site shall be surveyed for asbestos prior to demolition activities. If asbestos is found within the existing structures, the asbestos shall be removed through utilization of the removal procedures detailed in Rule 1403.

Southern California Association of Governments

The SCAG is the regional planning agency for Los Angeles, Orange, Ventura, Riverside, San Bernardino, and Imperial Counties and addresses regional issues relating to transportation, the economy, community development and the environment. SCAG is the federally designated Metropolitan Planning Organization (MPO) for the majority of the southern California region and is the largest MPO in the nation. With respect to air quality planning, SCAG has prepared the 2020-2045 Regional Transportation Plan/Sustainable Communities Strategy (Connect SoCal), adopted September 3, 2020and the 2019 Federal Transportation Improvement Program (2019 FTIP), adopted September 2018, which addresses regional development and growth forecasts. Although the Connect SoCal and 2019 FTIP are primarily planning documents for future transportation projects a key component of these plans are to integrate land use planning with transportation planning that promotes higher density infill development in close proximity to existing transit service. These plans form the basis for the land use and transportation components of the AQMP, which are utilized in the preparation of air quality forecasts and in the consistency analysis included in the AQMP. The Connect SoCal, 2019 FTIP, and AQMP are based on projections originating within the City and County General Plans.

4.4 Local – County of San Bernardino

Local jurisdictions, such as the County of San Bernardino, have the authority and responsibility to reduce air pollution through its police power and decision-making authority. Specifically, the County is responsible for the assessment and mitigation of air emissions resulting from its land use decisions. The County is also responsible for the implementation of transportation control measures as outlined in the AQMPs. Examples of such measures include bus turnouts, energy-efficient streetlights, and synchronized traffic signals. In accordance with CEQA requirements and the CEQA review process, the County assesses the air quality impacts of new development projects, requires mitigation of potentially significant air quality impacts by conditioning discretionary permits, and monitors and enforces implementation of such mitigation.

In accordance with the CEQA requirements, the County does not, however, have the expertise to develop plans, programs, procedures, and methodologies to ensure that air quality within the County and region will meet federal and state standards. Instead, the County relies on the expertise of the SCAQMD and utilizes the SCAQMD CEQA Handbook as the guidance document for the environmental review of plans and development proposals within its jurisdiction.

5.0 ENERGY CONSERVATION MANAGEMENT

The regulatory setting related to energy conservation is primarily addressed through State and County regulations, which are discussed below.

5.1 State

Energy conservation management in the State was initiated by the 1974 Warren-Alquist State Energy Resources Conservation and Development Act that created the California Energy Resource Conservation and Development Commission (currently named California Energy Commission [CEC]), which was originally tasked with certifying new electric generating plants based on the need for the plant and the suitability of the site of the plant. In 1976 the Warren-Alquist Act was expanded to include new restrictions on nuclear generating plants, that effectively resulted in a moratorium of any new nuclear generating plants in the State. The following details specific regulations adopted by the State in order to reduce the consumption of energy.

California Code of Regulations (CCR) Title 20

On November 3, 1976 the CEC adopted the *Regulations for Appliance Efficiency Standards Relating to Refrigerators, Refrigerator-Freezers and Freezers and Air Conditioners*, which were the first energy-efficiency standards for appliances. The appliance efficiency regulations have been updated several times by the Commission and the most current version is the *2016 Appliance Efficiency Regulations*, adopted January 2017 and now includes almost all types of appliances and lamps that use electricity, natural gas as well as plumbing fixtures. The authority for the CEC to control the energy-efficiency of appliances is detailed in California Code of Regulations (CCR), Title 20, Division 2, Chapter 4, Article 4, Sections 1601-1609.

California Code of Regulations (CCR) Title 24, Part 6

The CEC is also responsible for implementing the CCR Title 24, Part 6: California's Energy Efficiency Standards for Residential and Nonresidential Buildings (Title 24 Part 6) that were first established in 1978 in response to a legislative mandate to reduce California's energy consumption. In 2008 the State set an energy-use reduction goal of zero-net-energy use of all new homes by 2020 and the CEC was mandated to meet this goal through revisions to the Title 24, Part 6 regulations.

The Title 24 standards are updated on a three-year schedule and since 2008 the standards have been incrementally moving to the 2020 goal of the zero-net-energy use. On January 1, 2020 the 2019 standards went into effect, that have been designed so that the average new home built in California will now use zero-net-energy and that non-residential buildings will use about 30 percent less energy than the 2016 standards due mainly to lighting upgrades. The 2019 standards also encourage the use of battery storage and heat pump water heaters, require the more widespread use of LED lighting, as well as improve the building's thermal envelope through high performance attics, walls and windows. The 2019 standards also require improvements to ventilation systems by requiring highly efficient air filters to trap hazardous air particulates as well as improvements to kitchen ventilation systems.

California Code of Regulations (CCR) Title 24, Part 11

CCR Title 24, Part 11: California Green Building Standards (CalGreen) was developed in response to continued efforts to reduce GHG emissions associated with energy consumption. The CalGreen Building

Standards are also updated every three years and the current version is the 2019 California Green Building Standard Code that become effective on January 1, 2020.

The CALGreen Code contains requirements for construction site selection; storm water control during construction; construction waste reduction; indoor water use reduction; material selection; natural resource conservation; site irrigation conservation; and more. The code provides for design options allowing the designer to determine how best to achieve compliance for a given site or building condition. The code also requires building commissioning, which is a process for verifying that all building systems (e.g., heating and cooling equipment and lighting systems) are functioning at their maximum efficiency.

The CALGreen Code provides standards for bicycle parking, carpool/vanpool/electric vehicle spaces, light and glare reduction, grading and paving, energy efficient appliances, renewable energy, graywater systems, water efficient plumbing fixtures, recycling and recycled materials, pollutant controls (including moisture control and indoor air quality), acoustical controls, storm water management, building design, insulation, flooring, and framing, among others. Implementation of the CALGreen Code measures reduces energy consumption and vehicle trips and encourages the use of alternative-fuel vehicles, which reduces pollutant emissions.

Some of the notable changes in the 2019 CALGreen Code over the prior 2016 CALGreen Code include: an alignment of building code engineering requirements with the national standards that include anchorage requirements for solar panels, provides design requirements for buildings in tsunami zones, increases Minimum Efficiency Reporting Value (MERV) for air filters from 8 to 13, increased electric vehicle charging requirements in parking areas, and sets minimum requirements for use of shade trees.

Executive Order N-79-20

The California Governor issued Executive Order N-79-20 on September 23, 2020 that requires all new passenger cars and trucks and commercial drayage trucks sold in California to be zero-emissions by the year 2035 and all medium- heavy-duty vehicles (commercial trucks) sold in the state to be zero-emission by 2045 for all operations where feasible. Executive Order N-79-20 also requires all off-road vehicles and equipment to transition to 100 percent zero-emission equipment, where feasible by 2035.

Senate Bill 100

Senate Bill 100 (SB 100) was adopted September 2018 and requires that by December 1, 2045 that 100 percent of retail sales of electricity to be generated from renewable or zero-carbon emission sources of electricity. SB 100 supersedes the renewable energy requirements set by SB 350, SB 1078, SB 107, and SB X1-2. SB 100 codified the interim renewable energy thresholds from the prior Bills of: 33 percent by 2020, 40 percent by December 31, 2024, 45 percent by December 31, 2027, and 50 percent by December 31, 2030.

Executive Order B-48-18 and Assembly Bill 2127

The California Governor issued Executive Order B-48-18 on January 26, 2018 that orders all state entities to work with the private sector to put at least five million zero-emission vehicles on California roads by 2030 and to install 200 hydrogen fueling stations and 250,000 electric vehicle chargers by 2025. Currently there are approximately 350,000 electric vehicles operating in California, which represents approximately 1.5 percent of the 24 million vehicles total currently operating in California. Implementation of Executive Order B-48-18 would result in approximately 20 percent of all vehicles in California to be zero emission electric vehicles. Assembly Bill 2127 (AB 2127) was codified into statute on September 13, 2018 and

requires that the California Energy Commission working with the State Air Resources Board prepare biannual assessments of the statewide electric vehicle charging infrastructure needed to support the levels of zero emission vehicle adoption required for the State to meet its goals of putting at least 5 million zero-emission vehicles on California roads by 2030.

Assembly Bill 1109

California Assembly Bill 1109 (AB 1109) was adopted October 2007, also known as the Lighting Efficiency and Toxics Reduction Act, prohibits the manufacturing of lights after January 1, 2010 that contain levels of hazardous substances prohibited by the European Union pursuant to the RoHS Directive. AB 1109 also requires reductions in energy usage for lighting and is structured to reduce lighting electrical consumption by: (1) At least 50 percent reduction from 2007 levels for indoor residential lighting; and (2) At least 25 percent reduction from 2007 levels for indoor commercial and all outdoor lighting by 2018. AB 1109 would reduce GHG emissions through reducing the amount of electricity required to be generated by fossil fuels in California.

Assembly Bill 1493

California Assembly Bill 1493 (also known as the Pavley Bill, in reference to its author Fran Pavley) was enacted on July 22, 2002 and required CARB to develop and adopt regulations that reduce GHGs emitted by passenger vehicles and light duty trucks. In 2004, CARB approved the "Pavley I" regulations limiting the amount of GHGs that may be released from new passenger automobiles that are being phased in between model years 2009 through 2016. These regulations will reduce GHG emissions by 30 percent from 2002 levels by 2016. In June 2009, the EPA granted California the authority to implement GHG emission reduction standards for light duty vehicles, in September 2009, amendments to the Pavley I regulations were adopted by CARB and implementation of the "Pavley I" regulations started in 2009.

The second set of regulations "Pavley II" was developed in 2010, and is being phased in between model years 2017 through 2025 with the goal of reducing GHG emissions by 45 percent by the year 2020 as compared to the 2002 fleet. The Pavley II standards were developed by linking the GHG emissions and formerly separate toxic tailpipe emissions standards previously known as the "LEV III" (third stage of the Low Emission Vehicle standards) into a single regulatory framework. The new rules reduce emissions from gasoline-powered cars as well as promote zero-emissions auto technologies such as electricity and hydrogen, and through increasing the infrastructure for fueling hydrogen vehicles. In 2009, the U.S. EPA granted California the authority to implement the GHG standards for passenger cars, pickup trucks and sport utility vehicles and these GHG emissions standards are currently being implemented nationwide. However, EPA has performed a midterm evaluation of the longer-term standards for model years 2022-2025, and based on the findings of this midterm evaluation, the EPA proposed The Safer Affordable Fuel Efficient (SAFE) Vehicles Proposed Rule for Model Years 2021-2026 that amends the corporate average fuel economy (CAFE) and GHG emissions standards for light vehicles for model years 2021 through 2026. The EPA's proposed amendments do not include any extension of the legal waiver granted to California by the 1970 Clean Air Act and which has allowed the State to set tighter standards for vehicle pipe emissions than the EPA standards. On September 20, 2019, California filed suit over the EPA decision to revoke California's legal waiver that has been joined by 22 other states.

5.2 Local – County of San Bernardino

The applicable energy plan for the proposed project is the *County of San Bernardino General Plan Renewable Energy and Conservation Element*, Amended February, 2019. The applicable energy-related policies in the General Plan for the proposed project are shown in Table E.

Table E – Applicable County of San Bernardino General Plan Energy-Related Policies

Policy No.	General Plan Policy
1.4	Encourage residents and businesses to conserve energy.
2.1	Support solar energy generation, solar water heating, wind energy and bioenergy systems that are consistent with the orientation, siting and environmental compatibility policies of the General Plan.
2.2	Promote use of energy storage technologies that are appropriate for the character of the proposed location.
2.3	Encourage the use of feasible emerging and experimental renewable energy technologies that are compatible with County regulatory standards.
2.6	Encourage energy efficiency through appropriate renewable energy systems.
3.1	Prioritize, facilitate, and encourage onsite accessory RE generation to serve the unincorporated county, with a primary focus on rooftop and parking lot solar energy generation.

Source: County of San Bernardino, 2019.

6.0 GLOBAL CLIMATE CHANGE MANAGEMENT

The regulatory setting related to global climate change is addressed through the efforts of various international, federal, state, regional, and local government agencies. These agencies work jointly, as well as individually, to reduce GHG emissions through legislation, regulations, planning, policy-making, education, and a variety of programs. The agencies responsible for global climate change regulations are discussed below.

6.1 International

In 1988, the United Nations established the IPCC to evaluate the impacts of global climate change and to develop strategies that nations could implement to curtail global climate change. In 1992, the United States joined other countries around the world in signing the United Nations' Framework Convention on Climate Change (UNFCCC) agreement with the goal of controlling GHG emissions. The parties of the UNFCCC adopted the Kyoto Protocol, which set binding GHG reduction targets for 37 industrialized countries, the objective of reducing their collective GHG emissions by five percent below 1990 levels by 2012. The Kyoto Protocol has been ratified by 182 countries, but has not been ratified by the United States. It should be noted that Japan and Canada opted out of the Kyoto Protocol and the remaining developed countries that ratified the Kyoto Protocol have not met their Kyoto targets. The Kyoto Protocol expired in 2012 and the amendment for the second commitment period from 2013 to 2020 has not yet entered into legal force. The Parties to the Kyoto Protocol negotiated the Paris Agreement in December 2015, agreeing to set a goal of limiting global warming to less than 2 degrees Celsius compared with preindustrial levels. The Paris Agreement has been adopted by 195 nations with 147 ratifying it, including the United States by President Obama, who ratified it by Executive Order on September 3, 2016. On June 1, 2017, President Trump announced that the United States is withdrawing from the Paris Agreement and on January 21, 2021 President Biden signed an executive order rejoining the Paris Agreement.

Additionally, the Montreal Protocol was originally signed in 1987 and substantially amended in 1990 and 1992. The Montreal Protocol stipulates that the production and consumption of compounds that deplete ozone in the stratosphere—CFCs, halons, carbon tetrachloride, and methyl chloroform—were to be phased out, with the first three by the year 2000 and methyl chloroform by 2005.

6.2 Federal – United States Environmental Protection Agency

The United States Environmental Protection Agency (EPA) is responsible for implementing federal policy to address global climate change. The Federal government administers a wide array of public-private partnerships to reduce U.S. GHG intensity. These programs focus on energy efficiency, renewable energy, methane, and other non-CO₂ gases, agricultural practices and implementation of technologies to achieve GHG reductions. EPA implements several voluntary programs that substantially contribute to the reduction of GHG emissions.

In Massachusetts v. Environmental Protection Agency (Docket No. 05–1120), argued November 29, 2006 and decided April 2, 2007, the U.S. Supreme Court held that not only did the EPA have authority to regulate greenhouse gases, but the EPA's reasons for not regulating this area did not fit the statutory requirements. As such, the U.S. Supreme Court ruled that the EPA should be required to regulate CO2 and other greenhouse gases as pollutants under the federal Clean Air Act (CAA).

In response to the FY2008 Consolidations Appropriations Act (H.R. 2764; Public Law 110-161), EPA proposed a rule on March 10, 2009 that requires mandatory reporting of GHG emissions from large sources in the United States. On September 22, 2009, the Final Mandatory Reporting of GHG Rule was signed and published in the Federal Register on October 30, 2009. The rule became effective on December 29, 2009. This rule requires suppliers of fossil fuels or industrial GHGs, manufacturers of vehicles and engines, and facilities that emit 25,000 metric tons or more per year of GHG emissions to submit annual reports to EPA.

On December 7, 2009, the EPA Administrator signed two distinct findings under section 202(a) of the Clean Air Act. One is an endangerment finding that finds concentrations of the six GHGs in the atmosphere threaten the public health and welfare of current and future generations. The other is a cause or contribute finding, that finds emissions from new motor vehicles and new motor vehicle engines contribute to the GHG pollution which threatens public health and welfare. These actions did not impose any requirements on industry or other entities, however, since 2009 the EPA has been providing GHG emission standards for vehicles and other stationary sources of GHG emissions that are regulated by the EPA. On September 13, 2013 the EPA Administrator signed 40 CFR Part 60, that limits emissions from new sources to 1,100 pounds of CO₂ per mega-watt hour (MWh) for fossil fuel-fired utility boilers and 1,000 pounds of CO₂ per MWh for large natural gas-fired combustion units.

On August 3, 2015, the EPA announced the Clean Power Plan, emissions guidelines for U.S. states to follow in developing plans to reduce GHG emissions from existing fossil fuel-fired power plants (Federal Register Vol. 80, No. 205, October 23 2015). On October 11, 2017, the EPA issued a formal proposal to repeal the Clean Power Plan and on June 19, 2019 the EPA replaced the Clean Power Plan with the Affordable Clean Energy rule that is anticipated to lower power sector GHG emissions by 11 million tons by the year 2030.

On April 30, 2020, the EPA and the National Highway Safety Administration published the Final Rule for the Safer Affordable Fuel-Efficient (SAFE) Vehicles Rule for Model Years 2021-2026 Passenger Cars and Light Trucks (SAFE Vehicles Rule). Part One of the Rule revokes California's authority to set its own GHG emissions standards and zero-emission vehicle mandates in California, which results in one emission standard to be used nationally for all passenger cars and light trucks that is set by the EPA.

6.3 State

The CARB has the primary responsible for implementing state policy to address global climate change, however there are State regulations related to global climate change that affect a variety of State agencies. CARB, which is a part of the California Environmental Protection Agency, is responsible for the coordination and administration of both the federal and state air pollution control programs within California. In this capacity, the CARB conducts research, sets California Ambient Air Quality Standards (CAAQS), compiles emission inventories, develops suggested control measures, provides oversight of local programs, and prepares the SIP. In addition, the CARB establishes emission standards for motor vehicles sold in California, consumer products (e.g. hairspray, aerosol paints, and barbeque lighter fluid), and various types of commercial equipment. It also sets fuel specifications to further reduce vehicular emissions.

In 2008, CARB approved a Climate Change Scoping Plan that proposes a "comprehensive set of actions designed to reduce overall carbon GHG emissions in California, improve our environment, reduce our dependence on oil, diversify our energy sources, save energy, create new jobs, and enhance public health" (CARB 2008). The Climate Change Scoping Plan has a range of GHG reduction actions which include direct

regulations; alternative compliance mechanisms; monetary and non-monetary incentives; voluntary actions; market-based mechanisms such as a cap-and-trade system. In 2014, CARB approved the First Update to the Climate Change Scoping Plan (CARB, 2014) that identifies additional strategies moving beyond the 2020 targets to the year 2050. On December 14, 2017 CARB adopted the California's 2017 Climate Change Scoping Plan, November 2017 (CARB, 2017) that provides specific statewide policies and measures to achieve the 2030 GHG reduction target of 40 percent below 1990 levels by 2030 and the aspirational 2050 GHG reduction target of 80 percent below 1990 levels by 2050. In addition, the State has passed the following laws directing CARB to develop actions to reduce GHG emissions, which are listed below in chronological order, with the most current first.

Executive Order N-79-20

EO N-79-20 establish targets for when all new vehicles and equipment are zero-emission and is described in more detail above in Section 5.1 under Energy Conservation Management.

California Code of Regulations (CCR) Title 24, Part 6

The Title 24 Part 6 standards have been developed by the CEC primarily for energy conservation and is described in more detail above in Section 5.1 under Energy Conservation Management. It should be noted that implementation of the Title 24 Part 6 building standards would also reduce GHG emissions, since as detailed above in Section 3.3 Greenhouse Gas Emissions Inventory, energy use for residential and commercial buildings creates 9.7 percent of the GHG emissions in the State.

California Code of Regulations (CCR) Title 24, Part 11

The CalGreen Building standards have been developed by the CEC primarily for energy conservation and is described in more detail above in Section 5.1 under Energy Conservation Management. It should be noted that implementation of the CalGreen Building standards would also reduce GHG emissions, since as detailed above under Title 24, Part 6, energy usage from buildings creates 9.7 percent of GHG emissions in the State.

Senate Bill 100

SB 100 requires that by December 1, 2045 that 100 percent of retail sales of electricity to be generated from renewable or zero-carbon emission sources of electricity and is described in more detail above in Section 5.1 under Energy Conservation Management.

Executive Order B-48-18 and Assembly Bill 2127

Executive Order B-48-18 and AB 2127 provides measures to put at least five million zero-emission vehicles on California roads by 2030 and to install 200 hydrogen fueling stations and 250,000 electric vehicle chargers by 2025 and is described in more detail above in Section 5.1 under Energy Conservation Management.

Executive Order B-30-15, Senate Bill 32 and Assembly Bill 197

The California Governor issued Executive Order B-30-15 on April 29, 2015 that aims to reduce California's GHG emissions 40 percent below 1990 levels by 2030. This executive order aligns California's GHG reduction targets with those of other international governments, such as the European Union that set the same target for 2030 in October, 2014. This target will make it possible to reach the ultimate goal of reducing GHG emissions 80 percent under 1990 levels by 2050 that is based on scientifically established levels needed in the U.S.A to limit global warming below 2 degrees Celsius – the warming threshold at

which scientists say there will likely be major climate disruptions such as super droughts and rising sea levels. Assembly Bill 197 (AB 197) (September 8, 2016) and Senate Bill 32 (SB 32) (September 8, 2016) codified into statute the GHG emissions reduction targets of at least 40 percent below 1990 levels by 2030 as detailed in Executive Order B-30-15. AB 197 also requires additional GHG emissions reporting that is broken down to sub-county levels and requires CARB to consider the social costs of emissions impacting disadvantaged communities.

Executive Order B-29-15

The California Governor issued Executive Order B-29-15 on April 1, 2015 and directed the State Water Resources Control Board to impose restrictions to achieve a statewide 25% reduction in urban water usage and directed the Department of Water Resources to replace 50 million square feet of lawn with drought tolerant landscaping through an update to the State's Model Water Efficient Landscape Ordinance. The Ordinance also requires installation of more efficient irrigation systems, promotion of greywater usage and onsite stormwater capture, and limits the turf planted in new residential landscapes to 25 percent of the total area and restricts turf from being planted in median strips or in parkways unless the parkway is next to a parking strip and a flat surface is required to enter and exit vehicles. Executive Order B-29-15 would reduce GHG emissions associated with the energy used to transport and filter water.

Assembly Bill 341 and Senate Bills 939 and 1374

Senate Bill 939 (SB 939) requires that each jurisdiction in California to divert at least 50 percent of its waste away from landfills, whether through waste reduction, recycling or other means. Senate Bill 1374 (SB 1374) requires the California Integrated Waste Management Board to adopt a model ordinance by March 1, 2004 suitable for adoption by any local agency to require 50 to 75 percent diversion of construction and demolition of waste materials from landfills. Assembly Bill 341 (AB 341) was adopted in 2011 and builds upon the waste reduction measures of SB 939 and 1374, and set a new target of a 75 percent reduction in solid waste generated by the year 2020.

Senate Bill 375

Senate Bill 375 (SB 375) was adopted September 2008 in order to support the State's climate action goals to reduce GHG emissions from transportation sources through coordinated regional transportation planning efforts, regional GHG emission reduction targets, and land use and housing allocation. SB 375 requires CARB to set regional targets for GHG emissions reductions from passenger vehicle use. In 2010, CARB established targets for 2020 and 2035 for each Metropolitan Planning Organizations (MPO) within the State. It was up to each MPO to adopt a sustainable communities strategy (SCS) that will prescribe land use allocation in that MPOs Regional Transportation Plan (RTP) to meet CARB's 2020 and 2035 GHG emission reduction targets. These reduction targets are required to be updated every eight years and the most current targets are detailed at: https://ww2.arb.ca.gov/our-work/programs/sustainable-communities-program/regional-plan-targets, which provides GHG emissions reduction targets for SCAG of 8 percent by 2020 and 19 percent by 2035.

The Connect SoCal (SCAG, 2020) provides a 2035 GHG emission reduction target of 19 percent reduction over the 2005 per capita emissions levels. The Connect SoCal include new initiatives of land use, transportation and technology to meet the 2035 new 19 percent GHG emission reduction target for 2035. CARB is also charged with reviewing SCAG's RTP/SCS for consistency with its assigned targets.

City and County land use policies, including General Plans, are not required to be consistent with the RTP and associated SCS. However, new provisions of CEQA incentivize, through streamlining and other

provisions, qualified projects that are consistent with an approved SCS and categorized as "transit priority projects."

Assembly Bill 1109

AB 1109 requires reductions in energy usage for lighting and is described in more detail above in Section 5.1 under Energy Conservation Management.

Executive Order S-1-07

Executive Order S-1-07 was issued in 2007 and proclaims that the transportation sector is the main source of GHG emissions in the State, since it generates more than 40 percent of the State's GHG emissions. It establishes a goal to reduce the carbon intensity of transportation fuels sold in the State by at least ten percent by 2020. This Executive Order also directs CARB to determine whether this Low Carbon Fuel Standard (LCFS) could be adopted as a discrete early-action measure as part of the effort to meet the mandates in AB 32.

In 2009 CARB approved the proposed regulation to implement the LCFS. The standard was challenged in the courts, but has been in effect since 2011 and was re-approved by the CARB in 2015. The LCFS is anticipated to reduce GHG emissions by about 16 MMT per year by 2020. The LCFS is designed to provide a framework that uses market mechanisms to spur the steady introduction of lower carbon fuels. The framework establishes performance standards that fuel producers and importers must meet annually. Reformulated gasoline mixed with corn-derived ethanol and low-sulfur diesel fuel represent the baseline fuels. Lower carbon fuels may be ethanol, biodiesel, renewable diesel, or blends of these fuels with gasoline or diesel. Compressed natural gas and liquefied natural gas also may be low-carbon fuels. Hydrogen and electricity, when used in fuel cells or electric vehicles, are also considered as low-carbon fuels.

Senate Bill 97

Senate Bill 97 (SB 97) was adopted August 2007 and acknowledges that climate change is a prominent environmental issue that requires analysis under CEQA. SB 97 directed the Governor's Office of Planning and Research (OPR), which is part of the State Natural Resources Agency, to prepare, develop, and transmit to CARB guidelines for the feasible mitigation of GHG emissions or the effects of GHG emissions, as required by CEQA, by July 1, 2009. The Natural Resources Agency was required to certify and adopt those guidelines by January 1, 2010.

Pursuant to the requirements of SB 97 as stated above, on December 30, 2009 the Natural Resources Agency adopted amendments to the State CEQA guidelines that addresses GHG emissions. The CEQA Guidelines Amendments changed 14 sections of the CEQA Guidelines and incorporated GHG language throughout the Guidelines. However, no GHG emissions thresholds of significance were provided and no specific mitigation measures were identified. The GHG emission reduction amendments went into effect on March 18, 2010 and are summarized below:

- Climate Action Plans and other greenhouse gas reduction plans can be used to determine whether
 a project has significant impacts, based upon its compliance with the plan.
- Local governments are encouraged to quantify the GHG emissions of proposed projects, noting
 that they have the freedom to select the models and methodologies that best meet their needs
 and circumstances. The section also recommends consideration of several qualitative factors that
 may be used in the determination of significance, such as the extent to which the given project

complies with state, regional, or local GHG reduction plans and policies. OPR does not set or dictate specific thresholds of significance. Consistent with existing CEQA Guidelines, OPR encourages local governments to develop and publish their own thresholds of significance for GHG impacts assessment.

- When creating their own thresholds of significance, local governments may consider the thresholds of significance adopted or recommended by other public agencies, or recommended by experts.
- New amendments include guidelines for determining methods to mitigate the effects of GHG emissions in Appendix F of the CEQA Guidelines.
- OPR is clear to state that "to qualify as mitigation, specific measures from an existing plan must be identified and incorporated into the project; general compliance with a plan, by itself, is not mitigation."
- OPR's emphasizes the advantages of analyzing GHG impacts on an institutional, programmatic level. OPR therefore approves tiering of environmental analyses and highlights some benefits of such an approach.
- Environmental impact reports must specifically consider a project's energy use and energy efficiency potential.

Assembly Bill 32

In 2006, the California State Legislature adopted AB 32, the California Global Warming Solutions Act of 2006. AB 32 requires CARB, to adopt rules and regulations that would achieve GHG emissions equivalent to statewide levels in 1990 by 2020 through an enforceable statewide emission cap which will be phased in starting in 2012. Emission reductions shall include carbon sequestration projects that would remove carbon from the atmosphere and utilize best management practices that are technologically feasible and cost effective.

In 2007 CARB released the calculated Year 1990 GHG emissions of 431 MMTCO₂e. The 2020 target of 431 MMTCO₂e requires the reduction of 78 MMTCO₂e, or approximately 16 percent from the State's projected 2020 business as usual emissions of 509 MMTCO₂e (CARB, 2014). Under AB 32, CARB was required to adopt regulations by January 1, 2011 to achieve reductions in GHGs to meet the 1990 cap by 2020. Early measures CARB took to lower GHG emissions included requiring operators of the largest industrial facilities that emit 25,000 metric tons of CO_2 in a calendar year to submit verification of GHG emissions by December 1, 2010. The CARB Board also approved nine discrete early action measures that include regulations affecting landfills, motor vehicle fuels, refrigerants in cars, port operations and other sources, all of which became enforceable on or before January 1, 2010.

CARB's Scoping Plan that was adopted in 2009, proposes a variety of measures including: strengthening energy efficiency and building standards; targeted fees on water and energy use; a market-based capand-trade system; achieving a 33 percent renewable energy mix; and a fee regulation to fund the program. The 2014 update to the Scoping Plan identifies strategies moving beyond the 2020 targets to the year 2050.

The Cap-and-Trade Program established under the Scoping Plan sets a statewide limit on sources responsible for 85 percent of California's GHG emissions, and has established a market for long-term investment in energy efficiency and cleaner fuels since 2012.

Executive Order S-3-05

In 2005 the California Governor issued Executive Order S 3-05, GHG Emission, which established the following reduction targets:

- 2010: Reduce greenhouse gas emissions to 2000 levels;
- 2020: Reduce greenhouse gas emissions to 1990 levels;
- 2050: Reduce greenhouse gas emissions to 80 percent below 1990 levels.

The Executive Order directed the secretary of the California Environmental Protection Agency (CalEPA) to coordinate a multi-agency effort to reduce GHG emissions to the target levels. To comply with the Executive Order, the secretary of CalEPA created the California Climate Action Team (CAT), made up of members from various state agencies and commissions. The team released its first report in March 2006. The report proposed to achieve the targets by building on the voluntary actions of businesses, local governments, and communities and through State incentive and regulatory programs. The State achieved its first goal of reducing GHG emissions to 2000 levels by 2010.

Assembly Bill 1493

AB 1493 or the Pavley Bill sets tailpipe GHG emissions limits for passenger vehicles in California as well as fuel economy standards and is described in more detail above in Section 5.1 under Energy Conservation Management.

6.4 Regional – Southern California

The SCAQMD is the agency principally responsible for comprehensive air pollution control in the Air Basin. To that end, as a regional agency, the SCAQMD works directly with SCAG, county transportation commissions, and local governments and cooperates actively with all federal and state agencies.

South Coast Air Quality Management District

SCAQMD develops rules and regulations, establishes permitting requirements for stationary sources, inspects emission sources, and enforces such measures through educational programs or fines, when necessary. SCAQMD is directly responsible for reducing emissions from stationary, mobile, and indirect sources. The SCAQMD is also responsible for GHG emissions for projects where it is the lead agency. However, for other projects in the Air Basin where it is not the lead agency, it is limited to providing resources to other lead agencies in order to assist them in determining GHG emission thresholds and GHG reduction measures. In order to assist local agencies with direction on GHG emissions, the SCAQMD organized a Working Group, which is described below.

SCAQMD Working Group

Since neither CARB nor the OPR has developed GHG emissions threshold, the SCAQMD formed a Working Group to develop significance thresholds related to GHG emissions. At the September 28, 2010 Working Group meeting, the SCAQMD released its most current version of the draft GHG emissions thresholds, which recommends a tiered approach that either provides a quantitative annual thresholds of 3,500 MTCO₂e for residential uses, 1,400 MTCO₂e for commercial uses, 3,000 MTCO₂e for mixed uses, and 10,000 MTCO₂e for industrial uses.

Southern California Association of Governments

The SCAG is the regional planning agency for Los Angeles, Orange, Ventura, Riverside, San Bernardino, and Imperial Counties and addresses regional issues relating to transportation, the economy, community development and the environment. SCAG is the federally designated Metropolitan Planning Organization (MPO) for the majority of the southern California region and is the largest MPO in the nation. With respect to air quality planning, SCAG has prepared the Connect SoCal and 2019 FTIP addresses regional development and growth forecasts. Although the Connect SoCal and 2019 FTIP are primarily planning documents for future transportation projects a key component of these plans are to integrate land use planning with transportation planning that promotes higher density infill development in close proximity to existing transit service. These plans form the basis for the land use and transportation components of the AQMP, which are utilized in the preparation of air quality forecasts and in the consistency analysis included in the AQMP. The Connect SoCal, 2019FTIP, and AQMP are based on projections originating within the City and County General Plans.

6.5 Local - County of San Bernardino

Local jurisdictions, such as the County of San Bernardino, have the authority and responsibility to reduce GHG emissions through their police power and decision-making authority. Specifically, the County is responsible for the assessment and mitigation of GHG emissions resulting from its land use decisions. In accordance with CEQA requirements and the CEQA review process, the County assesses the global climate change potential of new development projects, requires mitigation of potentially significant global climate change impacts by conditioning discretionary permits, and monitors and enforces implementation of such mitigation.

The County of San Bernardino Greenhouse Gas Emissions Reduction Plan (GHG Plan), prepared September, 2011, requires the reduction of 159,423 metric tons of CO₂ equivalent emissions (MTCO₂e) per year from new development by 2020 as compared to the unmitigated conditions. The Greenhouse Gas Emissions Development Review Processes (GHG Review Processes), prepared for the County of San Bernardino, March 2015, provides project level direction on how the County plans to achieve the reduction in GHG Emissions.

7.0 ATMOSPHERIC SETTING

7.1 South Coast Air Basin

The project site is located within western San Bernardino County, which is part of the South Coast Air Basin (Air Basin) that includes the non-desert portions of Riverside, San Bernardino, and Los Angeles Counties and all of Orange County. The Air Basin is located on a coastal plain with connecting broad valleys and low hills to the east. Regionally, the Air Basin is bounded by the Pacific Ocean to the southwest and high mountains to the east forming the inland perimeter.

7.2 Local Climate

The climate of western San Bernardino County, technically called an interior valley subclimate of the Southern California's Mediterranean-type climate, is characterized by hot dry summers, mild moist winters with infrequent rainfall, moderate afternoon breezes, and generally fair weather. Occasional periods of strong Santa Ana winds and winter storms interrupt the otherwise mild weather pattern. The clouds and fog that form along the area's coastline rarely extend as far inland as western San Bernardino County. When morning clouds and fog form, they typically burn off quickly after sunrise. The most important weather pattern from an air quality perspective is associated with the warm season airflow across the densely populated areas located west of the project site. This airflow brings polluted air into western San Bernardino County late in the afternoon. This transport pattern creates unhealthful air quality that may extend to the project site particularly during the summer months.

Winds are an important parameter in characterizing the air quality environment of a project site because they both determine the regional pattern of air pollution transport and control the rate of dispersion near a source. Daytime winds in western San Bernardino County are usually light breezes from off the coast as air moves regionally onshore from the cool Pacific Ocean to the warm Mojave Desert interior of Southern California. These winds allow for good local mixing, but as discussed above, these coastal winds carry significant amounts of industrial and automobile air pollutants from the densely urbanized western portion of the Air Basin into the interior valleys which become trapped by the mountains that border the eastern and northern edges of the Air Basin.

In the summer, strong temperature inversions may occur that limit the vertical depth through which air pollution can be dispersed. Air pollutants concentrate because they cannot rise through the inversion layer and disperse. These inversions are more common and persistent during the summer months. Over time, sunlight produces photochemical reactions within this inversion layer that creates ozone, a particularly harmful air pollutant. Occasionally, strong thermal convections occur which allows the air pollutants to rise high enough to pass over the mountains and ultimately dilute the smog cloud.

In the winter, light nocturnal winds result mainly from the drainage of cool air off of the mountains toward the valley floor while the air aloft over the valley remains warm. This forms a type of inversion known as a radiation inversion. Such winds are characterized by stagnation and poor local mixing and trap pollutants such as automobile exhaust near their source. While these inversions may lead to air pollution "hot spots" in heavily developed coastal areas of the Air Basin, there is not enough traffic in inland valleys to cause any winter air pollution problems. Despite light wind conditions, especially at night and in the early morning, winter is generally a period of good air quality in the project vicinity.

The temperature and precipitation levels for the Fontana Kaiser Station, which is the nearest weather station to the project site with historical data is shown below in Table F. Table F shows that July is typically the warmest month and January is typically the coolest month. Rainfall in the project area varies considerably in both time and space. Almost all the annual rainfall comes from the fringes of mid-latitude storms from late November to early April, with summers being almost completely dry.

Table F – Monthly Climate Data

Month	Average Maximum Temperature (°F)	Average Minimum Temperature (°F)	Average Total Precipitation (inches)
January	66.8	44.0	3.65
February	69.4	45.0	2.85
March	70.1	46.3	2.80
April	74.5	48.4	1.13
May	79.9	52.6	0.26
June	86.7	56.6	0.04
July	95.0	62.2	0.01
August	94.4	62.9	0.11
September	91.3	61.3	0.34
October	83.0	55.4	0.34
November	73.6	48.5	1.72
December	68.3	44.4	2.07
Annual	79.4	52.3	15.32

Source: https://wrcc.dri.edu/cgi-bin/cliMAIN.pl?ca3120

7.3 Monitored Local Air Quality

The air quality at any site is dependent on the regional air quality and local pollutant sources. Regional air quality is determined by the release of pollutants throughout the Air Basin. Estimates of the existing emissions in the Air Basin provided in the 2012 AQMP, indicate that collectively, mobile sources account for 59 percent of the VOC, 88 percent of the NOx emissions and 40 percent of directly emitted PM2.5, with another 10 percent of PM2.5 from road dust. The 2016 AQMP found that since 2012 AQMP projections were made stationary source VOC emissions have decreased by approximately 12 percent, but mobile VOC emissions have increased by 5 percent. The percentage of NOx emissions remain unchanged between the 2012 and 2016 projections.

SCAQMD has divided the Air Basin into 38 air-monitoring areas with a designated ambient air monitoring station representative of each area. The project site is located in Air Monitoring Area 34, Central San Bernardino Valley, which covers the area from Fontana to the base of the San Bernardino Mountains. The nearest air monitoring station to the project site is the Fontana-Arrow Highway Monitoring Station (Fontana Station) that is located approximately five miles northwest of the project site at 14360 Arrow Boulevard, Fontana. It should be noted that due to the air monitoring station's distance from the project site, recorded air pollution levels at the Fontana Station reflect with varying degrees of accuracy, local air quality conditions at the project site. The monitoring data is presented in Table G and shows the most recent three years of monitoring data available from CARB. CO measurements have not been provided, since CO is currently in attainment in the Air Basin and monitoring of CO within the Air Basin ended on March 31, 2013.

Table G – Local Area Air Quality Monitoring Summary

		Year ¹	
Pollutant (Standard)	2018	2019	2020
Ozone:			
Maximum 1-Hour Concentration (ppm)	0.141	0.124	0.151
Days > CAAQS (0.09 ppm)	38	41	56
Maximum 8-Hour Concentration (ppm)	0.111	0.109	0.111
Days > NAAQS (0.070 ppm)	69	67	89
Days > CAAQs (0.070 ppm)	72	71	91
Nitrogen Dioxide:			
Maximum 1-Hour Concentration (ppb)	63.0	76.1	66.4
Days > NAAQS (100 ppb)	0	0	0
Days > CAAQS (180 ppb)	0	0	0
Inhalable Particulates (PM10):			
Maximum 24-Hour National Measurement (ug/m³)	64.1	88.8	76.8
Days > NAAQS (150 ug/m³)	0	0	0
Days > CAAQS (50 ug/m ³)	8	11	6
Annual Arithmetic Mean (AAM) (ug/m³)	34.6	35.3	37.2
Annual > NAAQS (50 ug/m³)	No	No	No
Annual > CAAQS (20 ug/m³)	Yes	Yes	Yes
Ultra-Fine Particulates (PM2.5):			
Maximum 24-Hour California Measurement (ug/m³)	29.2	81.3	57.6
Days > NAAQS (35 ug/m³)	0	3	4
Annual Arithmetic Mean (AAM) (ug/m³)	11.1	11.3	12.7
Annual > NAAQS and CAAQS (12 ug/m³)	No	No	Yes

Notes: Exceedances are listed in **bold.** CAAQS = California Ambient Air Quality Standard; NAAQS = National Ambient Air Quality Standard; ppm = parts per million; ppb = parts per billion; ND = no data available.

Source: http://www.arb.ca.gov/adam/

Ozone

During the last three years, the State 1-hour concentration standard for ozone has been exceeded between 38 and 56 days each year at the Fontana Station. The State 8-hour ozone standard has been exceeded between 71 and 91 days each year over the last three years at the Fontana Station. The Federal 8-hour ozone standard has been exceeded between 67 and 89 days each year over the last three years at the Fontana Station. Ozone is a secondary pollutant as it is not directly emitted. Ozone is the result of chemical reactions between other pollutants, most importantly hydrocarbons and NO₂, which occur only in the presence of bright sunlight. Pollutants emitted from upwind cities react during transport downwind to produce the oxidant concentrations experienced in the area. Many areas of Southern California contribute to the ozone levels experienced at this monitoring station, with the more significant areas being those directly upwind.

 $^{^{\}scriptsize 1}\,$ Data obtained from the Fontana Station.

Nitrogen Dioxide

The Fontana Station did not record an exceedance of either the Federal or State 1-hour NO₂ standards for the last three years.

Particulate Matter

The State 24-hour concentration standard for PM10 has been exceeded between 6 and 11 days each year over the past three years at the Fontana Station. Over the past three years the Federal 24-hour standard for PM10 has not been exceeded at the Fontana Station. The annual PM10 concentration at the Fontana Station has exceeded the State standard for the past three years and has not exceeded the Federal standard for the past three years.

Over the past three years the federal 24-hour concentration standard for PM2.5 has been exceeded between 0 and 4 days each year over the past three years at the Fontana Station. The annual PM2.5 concentrations at the Fontana Station has only exceeded the State and Federal standards in one of the past three years. There does not appear to be a noticeable trend for PM10 or PM2.5 in either maximum particulate concentrations or days of exceedances in the area. Particulate levels in the area are due to natural sources, grading operations, and motor vehicles.

According to the EPA, some people are much more sensitive than others to breathing fine particles (PM10 and PM2.5). People with influenza, chronic respiratory and cardiovascular diseases, and the elderly may suffer worsening illness and premature death due to breathing these fine particles. People with bronchitis can expect aggravated symptoms from breathing in fine particles. Children may experience decline in lung function due to breathing in PM10 and PM2.5. Other groups considered sensitive are smokers and people who cannot breathe well through their noses. Exercising athletes are also considered sensitive, because many breathe through their mouths during exercise.

7.4 Toxic Air Contaminant Levels in the Air Basin

In order to determine the Air Basin-wide risks associated with major airborne carcinogens, the SCAQMD conducted the Multiple Air Toxics Exposure Study (MATES) studies. According to the SCAQMD's MATES-IV study, the project site has an estimated cancer risk of 727 per million persons chance of cancer. In comparison, the average cancer risk for the Air Basin is 991 per million persons, which is based on the use of age-sensitivity factors detailed in the OEHHA Guidelines (OEHHA, 2015).

In order to provide a perspective of risk, it is often estimated that the incidence in cancer over a lifetime for the U.S. population ranges between 1 in 3 to 4 and 1 in 3, or a risk of about 300,000 per million persons. The MATES-III study referenced a Harvard Report on Cancer Prevention, which estimated that of cancers associated with known risk factors, about 30 percent were related to tobacco, about 30 percent were related to diet and obesity, and about 2 percent were associated with environmental pollution related exposures that includes hazardous air pollutants.

8.0 MODELING PARAMETERS AND ASSUMPTIONS

8.1 CalEEMod Model Input Parameters

The criteria air pollution and GHG emissions impacts created by the proposed project have been analyzed through use of CalEEMod Version 2020.4.0. CalEEMod is a computer model published by the SCAQMD for estimating air pollutant emissions. The CalEEMod program uses the EMFAC2017 computer program to calculate the emission rates specific for the South Coast Air Basin portion of San Bernardino County for employee, vendor and haul truck vehicle trips and the OFFROAD2011 computer program to calculate emission rates for heavy equipment operations. EMFAC2017 and OFFROAD2011 are computer programs generated by CARB that calculates composite emission rates for vehicles. Emission rates are reported by the program in grams per trip and grams per mile or grams per running hour.

The project characteristics in the CalEEMod model were set to a project location of the South Coast Air Basin portion of San Bernardino County, a Climate Zone of 10, utility company of Southern California Edison, and project opening year of 2023. In addition, the EMFAC off-model adjustment factors for gasoline light duty vehicle to account for the SAFE Vehicle rule was selected in the CalEEMod model run.

Land Use Parameters

The proposed project consists of development of an approximately 259,481 square foot high-cube warehouse building that would cover approximately 45 percent of the project site and 15 percent of the project site would be landscaped. A total of 131 passenger vehicle stalls and 85 trailer stalls would be included to the north and east of the proposed building. The paved area would cover approximately 5.29 acres of the 13.23 acre project site. The proposed project's land use parameters that were entered into the CalEEMod model are shown in Table H.

Table H - CalEEMod Land Use Parameters

Proposed Land Use	Land Use Subtype in CalEEMod	Land Use Size ¹	Lot Acreage ²	Building/Paving ³ (square feet)
Unrefrigerated Warehouse	Unrefrigerated Warehouse No Rail	259.481 TSF	7.94	259,481
Paved Area (Truck Loading Area, Driveways, and Parking Lots)	Parking Lot	5.29 AC	5.29	230,432

Notes:

Construction Parameters

Construction of the proposed project is anticipated to start around March 2022 and would be completed in 16 months. The construction-related GHG emissions were based on a 30-year amortization rate as recommended in the SCAQMD GHG Working Group meeting on November 19, 2009. The phases of construction activities that have been analyzed are detailed below and include: 1) Demolition; 2) Site Preparation; 3) Grading, 4) Building construction, 5) Paving; and 6) Application of architectural coatings.

The CalEEMod model provides the selection of "mitigation" to account for project conditions that would result in less emissions than a project without these conditions, however it should be noted that this "mitigation" may represent regulatory requirements. This includes the required to adherence to SCAQMD

¹ TSF = Thousand Square Feet; AC = Acre

² Lot acreage calculated based on the total project site of 13.23-acres.

³ Building/Paving square feet represent area where architectural coatings will be applied. Paved area based on CalEEMod default values.

Rule 403, which requires that the Best Available Control Measures be utilized to reduce fugitive dust emissions.

Demolition

The demolition phase would consist of demolishing the existing two single-family residences on the northwest and southwest corner of the project site, and three commercial/industrial buildings, that total approximate 16,800 square feet of building space. In addition, the existing parking lots, driveways and truck storage area on the project site would also need to be demolished, which has been estimated to cover 117,000 square feet of the project site. The pavement was assumed to be an average of 4-inches thick and weigh 145 pounds per square foot, which results in 2,828 tons of pavement that would be removed from the project site. For the existing structures to be demolished, CalEEMod utilizes a factor of 0.046 tons of debris of building material per building square foot. This results in 773 tons of debris that would be generated from demolition of the existing structures. Therefore, the combined demolition of the structures and pavement area would require the removal of 3,600 tons of debris that would be exported from the site and would require a total of 356 haul truck trips (average 17.8 haul truck trips per day over duration of demolition phase).

The demolition phase has been modeled as starting in March 2022 and would occur over four weeks, which is based on the CalEEMod default timing. The demolition activities would require 15 worker trips per day. In order to account for water truck emissions, six vendor truck emissions were added to the demolition phase. The onsite equipment would consist of one concrete/industrial saw, three excavators, and two rubber-tired dozers, which is based on the CalEEMod default equipment mix. The mitigation of water all exposed areas three times per day was chosen in order to account for the fugitive dust reduction that would occur through adhering to SCAQMD Rule 403, which requires that the Best Available Control Measures be utilized to reduce fugitive dust emissions.

Site Preparation

The site preparation phase would consist of removing any vegetation, tree stumps, and stones onsite prior to grading. The site preparation phase is anticipated to start after completion of the demolition phase and was modeled as occurring over two weeks, which is based on the CalEEMod default timing. The site preparation activities would require 18 worker trips per day. In order to account for water truck emissions, six vendor truck emissions were added to the site preparation phase. The onsite equipment would consist of three rubber-tired dozers, and four crawler tractors, which replaced the CalEEMod default value of four of either tractors, loaders, or backhoes, in order to provide a more conservative analysis. The mitigation of water all exposed areas three times per day was chosen in order to account for the fugitive dust reduction that would occur through adhering to SCAQMD Rule 403, which requires that the Best Available Control Measures be utilized to reduce fugitive dust emissions.

<u>Grading</u>

The grading phase would occur after completion of the site preparation phase and was modeled as occurring over six weeks, which is based on the CalEEMod default timing. The grading activities are anticipated to be balanced, which would not require any dirt to be imported or exported from the project site. The onsite equipment would consist of two excavators, one grader, one rubber-tired dozer, two scrapers, and two crawler tractors, which replaced the CalEEMod default value of two of either tractors, loaders, or backhoes, in order to provide a more conservative analysis. The mitigation of water all exposed areas three times per day was chosen in order to account for the fugitive dust reduction that would occur

through adhering to SCAQMD Rule 403, which requires that the Best Available Control Measures be utilized to reduce fugitive dust emissions.

Building Construction

The building construction would occur after the completion of the grading phase and was modeled as occurring over 14 months, which is based on the CalEEMod default timing. The building construction phase would generate 206 worker trips and 80 vendor trips per day. The onsite equipment would consist of the simultaneous operation of one crane, three forklifts, one generator, one welder, and three of either tractors, loaders, or backhoes, which is based on the CalEEMod default equipment mix.

Paving

The paving phase would consist of paving the truck loading area, driveways, and parking lots. The paving phase was modeled as occurring concurrently with the final six months of the building construction phase. The paving phase would generate 15 worker trips per day. The onsite equipment would consist of the simultaneous operation of two pavers, two paving equipment, and two rollers, which is based on the CalEEMod default equipment mix.

Architectural Coating

The application of architectural coatings was modeled as occurring concurrently with the final six months of the building construction phase and concurrent with the paving phase. The architectural coating phase was modeled based on covering 389,222 square feet of non-residential interior area, 129,741 square feet of non-residential exterior area, and 13,826 square feet of parking area. The architectural coating phase would generate 41 worker trips per day. The onsite equipment would consist of one air compressor, which is based on the CalEEMod default equipment mix.

Operational Emissions Modeling

The operations-related criteria air pollutant emissions and GHG emissions created by the proposed project have been analyzed through use of the CalEEMod model. The proposed project was analyzed in the CalEEMod model based on the land use parameters provided above and the parameters entered for each operational emission source is described below.

Mobile Sources

Mobile sources include emissions the additional vehicle miles generated from the proposed project. The daily vehicle trip rates associated with the proposed project have been obtained from *Alder Avenue/Slover Avenue Industrial Project Trip Generation and Vehicle Miles Traveled (VMT) Screening Analysis* (Trip Generation Analysis), prepared by EPD Solutions, Inc., November 18, 2021. The Trip Generation Analysis found that the proposed project would generate a total of 364 daily trips, which would consist of the following breakdown: 251 passenger cars, 25 2-axle trucks, 20 3-axle trucks, and 68 4+ axle trucks.

According to Review of SCAQMD Staff Comments and Testimony on Warehouse Projects, prepared by Southern California Leadership Council, March 14, 2014, SCAQMD requires that truck trip length should be set to 40 miles in CalEEMod. In order to account for the longer truck trip length in CalEEMod, the 75 daily truck trips were analyzed under the "Parking Lot" land use because the parking lot use generates no vehicle trips on its own (the row's default are "zeros") so it was an available placeholder allowing analysis solely of the project's trucks without mixing the trucks with any other trip-generating use. The passenger

car trip lengths were based on the default trip lengths. The vehicle trips rate utilized in the CalEEMod model are provided in Table I.

Table I – Inventory of Vehicle Trips During Operation of Proposed Project

			Daily Trip Generation Rates		
Land Use Type in CalEEMod	Vehicle Type	Land Use Size ¹	Trips Rates ²	Total Daily Trips	
Unrefrigerated Warehouse No Rail	Passenger Cars	259.481 TSF	1.11 per TSF	251	
Parking Lot	Trucks	5.29 AC	14.18 per AC	113	

Notes:

In order to account for the four 2-axle trucks, four 3-axle trucks, and 12 4+-axle trucks trips generated by the proposed project, the vehicle mixes utilized in the CalEEMod model for the Parking Lot land use were adjusted to match the truck generation rates provided in the Traffic Analysis. In addition, the vehicle mix for the Unrefrigerated Warehouse was also adjusted to remove the truck trips from this land use, since all truck trips generated from the proposed project were analyzed under the Parking Lot land use. The vehicle mixes utilized in the CalEEMod model are shown in Table J. No other changes were made to the CalEEMod default mobile source parameters.

Table J – Fleet Mix During Operation of Proposed Project

Land Use	LDA	LDT1	LDT2	MDV	LHD2	MHD	HHD	MCY
Unrefrigerated Warehouse No Rail – Autos	0.579	0.059	0.185	0.150	0	0	0	0.027
Parking Lot - Trucks	0	0	0	0	0.221	0.177	0.602	0

Notes:

LDA = Light Duty Auto; LDT1 = Light-Duty Trucks (less than 3,750 pounds gross vehicle weight rating [GVWR]); LDT2 = Light-Duty Trucks (3,751 to 6,000 pounds GVWR); MDV = Medium-Duty Trucks (6,000 to 8,500 pounds GVWR); LHD1 = Light-Heavy-Duty Trucks 1 (8,501 to 10,000 pounds GVWR); LHD2 = Light-Heavy-Duty Trucks 2 (GVWR 10,001 to 14,000 pounds); MHD = Medium-Heavy-Duty Trucks (GVWR 19,501 to 33,000 pounds); HHD = Heavy-Heavy-Duty Trucks (GVWR 33,000+ pounds); and MCY = motorcycles.

.

The CalEEMod model provides the selection of "mitigation" to account for project conditions that would result in less emissions than a project without these conditions, however it should be noted that this "mitigation" may represent current conditions, such as development that is in close proximity to an existing transit facility, where a project built at such location would create less vehicle trips and associated emissions than a project that was not built in close proximity to an existing transit facility. The mobile source emissions analysis for the project included the CalEEMod "mitigation" of improved pedestrian network on project site and connecting offsite and increase transit accessibility with 0.06 mile to the nearest transit to account for the existing Omnitrans Laurel at Slover Transit Bus Stop, that is located as near as 300 feet east of the project site.

Area Sources

Area sources include emissions from consumer products, landscape equipment, and architectural coatings. The area source emissions were based on the on-going use of the proposed project in the CalEEMod model. No changes were made to the default area source parameters in the CalEEMod model.

¹ TSF = Thousand Square Foot; AC = Acre.

² Daily Trip rates obtained from the Trip Generation Analysis (EPD Solutions, Inc., 2021).

¹ The Truck fleet mix was based on the Truck Fleet Mix provided in the VMT Memo (Urban Crossroads, 2021), with 2-axle trucks analyzed as LHD2, 3-axle trucks analyzed as MHD, and 4+-axle trucks analyzed as HHD.

Energy Usage

Energy usage includes emissions from electricity and natural gas used onsite. The energy usage was based on the ongoing use of the proposed project in the CalEEMod Model. No changes were made to the default energy usage parameters in the CalEEMod model.

Solid Waste

Waste includes the GHG emissions associated with the processing of waste from the proposed project as well as the GHG emissions from the waste once it is interred into a landfill. The analysis was based on the default CalEEMod waste generation rate of 244 tons of solid waste per year from the proposed project. No changes were made to the default solid waste parameters or mitigation measures in the CalEEMod model.

The CalEEMod mitigation of a 50 percent reduction in landfill waste was selected to account for implementation of AB 341 that provides strategies to reduce, recycle or compost solid waste by 75 percent by 2020. Only 50 percent was selected, since AB 341 builds upon the waste reduction measures of SB 939 and 1374 and therefore, it was assumed approximately 25 percent of the waste reduction target has already been accounted for in the CalEEMod model.

Water and Wastewater

Water includes the water used for the interior of the buildings as well as for landscaping and is based on the GHG emissions associated with the energy used to transport and filter the water. The analysis was based on the default CalEEMod water usage rate of 60,004,750 gallons per year of water use. No changes were made to the default water and wastewater parameters in the CalEEMod model.

The CalEEMod "mitigation" of the use of low flow faucets and toilets and use of smart irrigation system controllers were selected to account for the implementation of the 2019 CCR Title 24 Part 11 (CalGreen) requirements, which lowered the calculated water use for the proposed project to 50,624,500 gallons per year.

Off-Road Equipment

The primary activity that would require the use of off-road equipment would be associated with forklifts unloading/loading of truck deliveries. As detailed above, operation of the proposed project is anticipated to generate 113 daily truck trips. Based on 15 minutes of unloading/loading activities per truck trip, this would result in 28.25 hours of forklift activities per day, which was analyzed in CalEEMod as four forklifts operating 7 hours per day. In order to account for Project Design Feature 1, that restricts the operation of diesel-powered off-road equipment on the project site during long-term operations of the project, the forklifts were analyzed as being powered with compressed natural gas (CNG).

8.2 Energy Use Calculations

The proposed project is anticipated to consume energy during both construction and operation of the proposed project and the parameters utilized to calculate energy use from construction and operation of the proposed project are detailed separately below.

Construction-Related Energy Use

Construction of the proposed project is anticipated to use energy in the forms of petroleum fuel for both off-road equipment as well as from the transport of workers and materials to and from the project site and the calculations for each source are described below.

Off-Road Construction Equipment

The off-road construction equipment fuel usage was calculated through use of the CalEEMod model's default off-road equipment assumptions detailed above in Section 8.1. For each piece of off-road equipment, the fuel usage was calculated through use of the *2017 Off-road Diesel Emission Factors* spreadsheet, prepared by CARB (https://ww3.arb.ca.gov/msei/ordiesel.htm). The Spreadsheet provides the following formula to calculate fuel usage from off-road equipment:

Fuel Used = Load Factor x Horsepower x Total Operational Hours x BSFC / Unit Conversion

Where:

Load Factor - Obtained from CalEEMod default values

Horsepower - Obtained from CalEEMod default values

Total Operational Hours – Calculated by multiplying CalEEMod default daily hours by CalEEMod default number of working days for each phase of construction

BSFC – Brake Specific Fuel Consumption (pounds per horsepower-hour) – If less than 100 Horsepower = 0.408, if greater than 100 Horsepower = 0.367

Unit Conversion – Converts pounds to gallons = 7.109

Table K shows the off-road construction equipment fuel calculations based on the above formula. Table K shows that the off-road equipment utilized during construction of the proposed project would consume 71,940 gallons of fuel.

Table K – Off-Road Equipment and Fuel Consumption from Construction of the Proposed Project

Equipment Type	Equipment Quantity	Horse- power	Load Factor	Operating Hours per Day	Total Operational Hours ¹	Fuel Used (gallons)
Demolition	-	.		•		<u>, , , , , , , , , , , , , , , , , , , </u>
Concrete/Industrial Saw	1	81	0.73	8	160	543
Excavators	3	158	0.38	8	480	1,488
Rubber Tired Dozers	2	247	0.4	8	320	1,632
Site Preparation						
Rubber Tired Dozers	3	247	0.4	8	240	1,224
Crawler Tractors	4	212	0.43	8	320	1,506
Grading						
Excavators	2	158	0.38	8	480	1,488
Graders	1	187	0.41	8	240	950
Rubber Tired Dozers	1	247	0.4	8	240	1,224
Scrapers	2	367	0.48	8	240	1,224
Crawler Tractors	2	212	0.43	8	480	2,259
Building Construction		_			·	
Cranes	1	231	0.29	7	2,100	7,263
Forklifts	3	89	0.2	8	7,200	7,355

Equipment Type	Equipment Quantity	Horse- power	Load Factor	Operating Hours per Day	Total Operational Hours ¹	Fuel Used (gallons)
Generator Sets	1	84	0.74	8	2,400	8,562
Tractors/Loaders/Backhoes	3	97	0.37	7	6,300	12,977
Welders	1	46	0.45	8	2,400	2,851
Paving						
Pavers	2	130	0.42	8	2,080	5,863
Paving Equipment	2	132	0.36	8	2,080	5,103
Rollers	2	80	0.38	8	2,080	3,629
Architectural Coating						
Air Compressor	1	78	0.48	6	780	1,676
	Total Off-	Road Equi	pment Fu	el Used during Coi	nstruction (gallons)	71,940

Notes:

Source: CalEEMod Version 2020.4.0 (see Appendix A); CARB, 2017.

On-Road Construction-Related Vehicle Trips

The on-road construction-related vehicle trips fuel usage was calculated through use of the construction vehicle trip assumptions from the CalEEMod model run as detailed above in Section 8.1. The calculated total construction miles were then divided by the fleet average for the South Coast Air Basin miles per gallon rates for the year 2022 calculated through use of the EMFAC2017 model (https://www.arb.ca.gov/emfac/2017/) and the EMFAC2017 model printouts are shown in Appendix B. The worker trips were based on the entire fleet average miles per gallon rate for gasoline powered vehicles and the vendor trips were based on the Heavy-Heavy Duty Truck (HHDT), Medium Duty Vehicle (MDV), and Medium Heavy Duty Vehicle (MHDV) fleet average miles per gallon rate for diesel-powered vehicles. Table L shows the on-road construction vehicle trips modeled in CalEEMod and the fuel usage calculations.

Table L – On-Road Vehicle Trips and Fuel Consumption from Construction of the Proposed Project

Vehicle Trip Types	Daily Trips	Trip Length (miles)	Total Miles per Day	Total Miles per Phase ¹	Fleet Average Miles per Gallon ²	Fuel Used (gallons)
Demolition	, ,	(,	<u> </u>		,	10/
Worker Trips	15	14.7	221	4,410	26.0	170
Vendor Truck Trips	6	6.9	41	828	8.2	101
Haul Truck Trips	17.8	20	356	7,120	8.2	866
Site Preparation						
Worker Trips	18	14.7	265	2,646	26.0	102
Vendor Truck Trips	6	6.9	41	414	8.2	50
Grading						
Worker Trips	20	14.7	294	8,820	26.0	339
Vendor Truck Trips	6	6.9	41	1,242	8.2	151
Building Construction						
Worker Trips	206	14.7	3,028	908,460	26.0	34,956
Vendor Truck Trips	80	6.9	552	165,600	8.2	20,134
Paving					<u> </u>	

¹ Based on: 20 days for Demolition, 10 days for Site Preparation, 30 days for Grading; 300 days for Building Construction; 130 days for Paving; and 130 days for Architectural Coating.

Architectural Coating						
Worker Trips	41	6.9	603 sed from On-I	78,351	26.0 Vehicles (gallons)	3,015 60,987

Notes:

Source: CalEEMod Version 2020.4.0; CARB, 2018.

Table L shows that the on-road construction-related vehicle trips would consume 60,987 gallons of fuel and as detailed above, Table K shows that the off-road construction equipment would consume 71,940 gallons of fuel. This would result in the total consumption of 132,926 gallons of petroleum fuel from construction of the proposed project.

Operations-Related Energy Use

The operation of the proposed project is anticipated to use energy in the forms of petroleum fuel, electricity, and natural gas, and the calculations for each source are described below.

Operational Petroleum Fuel

The on-road operations-related vehicle trips fuel usage was calculated through use of the total annual vehicle miles traveled assumptions from the CalEEMod model run as detailed above in Section 8.1, which found that operation of the proposed project would generate 818,435 vehicle miles traveled per year from autos and would generate 1,248,255 vehicle miles traveled per year from trucks. The calculated total operational miles were then divided by the South Coast Air Basin fleet average rates of 26.0 miles per gallon for automobiles and the fleet average rate of 8.2 miles per gallon for trucks, which was calculated through use of the EMFAC2017 model and based on the year 2022. The EMFAC2017 model printouts are shown in Appendix B. Based on the above calculation methodology, the operation of automobiles would consume 31,492 gallons per year and from trucks would consume 151,764 gallons per year. The total petroleum use from operation of the proposed project would be 183,256 gallons per year.

Operational Electricity Use

The operations-related electricity usage was calculated in the CalEEMod model run that is detailed above in Section 8.1 that depicts the electricity use from each land use that are shown below in kilo-watt hours (kWh) per year:

- Parking Lot (Truck Loading Area, Driveways, and Parking Lots) 80,651 kWh/year
- Unrefrigerated Warehouse 601,996 kWh/year

Based on the above, it is anticipated that the proposed project would utilize 682,647 kWh per year of electricity.

Operational Natural Gas Use

The operations-related natural gas usage was calculated in the CalEEMod model run that is detailed above in Section 8.1 that depicts the natural gas use from each land use that are shown below in kilo British Thermal Units (kBTU) per year (CalEEMod land use shown in brackets):

¹ Based on: 20 days for Demolition, 10 days for Site Preparation, 30 days for Grading; 300 days for Building Construction; 130 days for Paving; and 130 days for Architectural Coating.

² From EMFAC 2017 model (see Appendix B). Worker Trips based on entire fleet of gasoline vehicles and Vendor Trips based on only truck portion fleet of diesel vehicles.

- Parking Lot (Truck Loading Area, Driveways, and Parking Lots) 0 kBTU/year
- Unrefrigerated Warehouse 521,557 kBTU/year

Based on the above, it is anticipated that the proposed project will use 485,396 kBTU per year, which is equivalent to 485 mega-British Thermal units (MBTU) per year of natural gas.

8.3 Toxic Air Contaminant Emissions Modeling

The dispersion modeling utilized for analyzing the TAC emissions in this analysis has been based on the recommended methodology described in *Health Risk Assessment Guidance for Analyzing Cancer Risks from Mobile Source Diesel idling Emissions for CEQA Air Quality Analysis* (SCAQMD HRA Guidance), prepared by SCAQMD, 2003, *Air Toxics Hot Spots Program Risk Assessment Guidelines* (OEHHA Guidelines), prepared by Office of Environmental Health Hazard, February 2015, and *Risk Assessment Procedures for Rules 1401, 1401.1 and 212* (SCAQMD Risk Assessment Procedures), prepared by SCAQMD, September 1, 2017. Important issues that affect the dispersion modeling include the following: 1) Model Selection, 2) Source Treatment, 3) Meteorological Data, and 4) Receptor Grid. Each of these issues is addressed below.

Model Selection

The AERMOD View Version 11.0.1 Model was used for all dispersion modeling. Key dispersion modeling options selected included the regulatory default options and urban modeling option for San Bernardino County with a population of 2,035,210. Flagpole receptor height was set to 0 meters, which is based on SCAQMD recommended modeling parameters. AERMAP (the terrain pre-processor for AERMOD) was run with a USGS 7.5-meter map of Fontana that covers the local project area.

Meteorological Data

Meteorological data from the SCAQMD's Perris Monitoring Site was selected for this modeling application. The SCAQMD's meteorological data is provided at: https://www.aqmd.gov/home/airquality/meteorological-data/data-for-aermod. Five full years of meteorological data were collected at the Fontana Station by the SCAQMD for 2011, 2012, 2013, 2015, and 2016. The SCAQMD processed the data for input to the model. An elevation of 367 meters was utilized for the Fontana Station per SCAQMD guidance.

Receptor Grid

The nearest sensitive receptors to the project site are the single-family homes that are located adjacent to the south side of the project site, where the residential structures are located as close as 30 feet south of the project site. The nearest school is Bloomington High School, which is located as near as 330 feet south of the project site. There are also several older residential structures located on all sides of the project site, that are likely currently utilized for non-residential purposes, however since it is unknown if a person is living at these structures, they have also been analyzed in the AERMOD model. Discrete receptors were placed at 12 representative nearby sensitive receptors in the AERMOD model. In addition, a Non-Uniform Cartesian Grid Receptor Network with 50 meter space between receptors was placed on the south side of the project site and covered the area of the homes to the south and Bloomington High School. Figure 3 shows the locations of the sources and receptors modeled in the AERMOD model for TAC emissions.

Building Inputs

In order to account for building downwash (air turbulence caused by wind blowing over the proposed warehouse) attributes associated with the proposed project, the proposed warehouse structure was inputted into the AERMOD model as a polygonal building with a 50-foot (15.24 meter) height.

EMFAC2017 Model

The truck travel and truck idling emission rates were obtained from the EMFAC2017 model Version 1.0.3. The EMFAC2017 model is the latest emissions inventory model released by CARB that calculates motor vehicle emissions from vehicles operating on roads in California. The EMFAC2017 includes the latest data on California's car and truck fleets and travel activity and also reflects the emissions reductions associated with CARB's recent rulemaking, including on-road diesel fleet rules, Advanced Clean Car Standards, and the Smartway/Phase I Heavy-Duty Vehicle GHG Regulations.

The operational 3-axle and 4+-axle truck trips were modeled in the EMFAC2017 model through use of the Truck 2 Vehicle Category that covers all truck classifications over 14,000 pounds. The operational 2-axle (small truck) trips were modeled in the EMFAC2017 model through use of the Truck 1 Vehicle Category that covers all truck classifications between 8,500 and 14,000 pounds. Since vehicle emission factors are dependent on vehicle speed, emission factors were obtained for 10 and 40 miles per hour and idling rates. The EMFAC2017 model run printout is provided in Appendix B.

The cancer risk analysis is based on a 30-year analysis period. Therefore, the analysis period was segmented into three age sensitivity time periods, consistent with the cancer risk estimation methodology. The DPM PM10 truck running emission rates utilized in this assessment are shown in Table M; the DPM PM10 truck idling emission rates utilized in this assessment are shown in Table N.

Table M – EMFAC2017 Diesel Truck Running PM10 Emission Rates

	Speed	EMFAC2017 PM10 Running Emissions Rates (grams/mile)						
Vehicle Class	(mph)	2023 to 2025	2026 to 2040	2041 to 2052				
Truck 1	10	0.0451	0.0268	0.0168				
Truck 1	40	0.0158	0.0107	0.0077				
Truck 2	10	0.0093	0.0083	0.0078				
Truck 2	40	0.0089	0.0086	0.0084				

Source: EMFAC2017 version 1.0.3.

Table N – EMFAC2017 Diesel Truck Idling PM10 Emission Rates

	EMFAC2017 PM10 Idling Emissions Rates (grams/hour)					
Vehicle Class	2023 to 2025	2026 to 2040	2041 to 2052			
Truck 1	0.792	0.792	0.797			
Truck 2	0.015	0.011	0.010			

Source: EMFAC2017 version 1.0.3.

TAC Emission Sources

Operational DPM emissions would be generated from diesel truck running and idling emissions. Project Design Feature 1 requires all off-road equipment used during operation of the project, including forklifts,

are restricted from being diesel-powered. As such, no DPM emissions would be created from off-road equipment during operation of the proposed project.

Operational Truck Travel

As detailed above in Section 8.1 and in the Trip Generation Analysis (EPD Solutions, Inc., 2021), the operation of the proposed project would generate 25 2-axle trucks, 20 3-axle trucks, and 68 4+ axle daily truck trips. The 25 2-axle truck trips were analyzed based on the Truck 1 and the 88 3-axle and 4+-axle trucks were analyzed based on the Truck 2 emission rates from the EMFAC2017 model. The project-related truck emissions have been analyzed separately for truck travel and truck idling that utilized emission rates from the EMFAC model.

Since the Trip Generation Analysis did not include any truck trip distribution information, it has been assumed that 50 percent of the truck trips would travel west on Slover Avenue and 50 percent would travel east on Slover Avenue, since the project site is approximately equidistant between the ramps on Interstate 10 at Sierra Avenue and Cedar Avenue. For the three project driveways, it was assumed that one third of the truck trips would utilize each driveway and each truck would travel to the center of the loading dock area.

The emission rates utilized in the AERMOD model were calculated by converting the emissions created for one truck to grams per second and then calculating the time it takes to travel the road length and multiplying this time by the per day and then dividing by 24 hours. The calculated emission rates are shown in Table O. The diesel truck line volume source truck routes were modeled with a 6-foot height and 12-foot width for the onsite driveways and Alder Avenue and a 40-foot width on Slover Avenue.

Table O – AERMOD Model Operational DPM Truck Travel Emissions Sources

	Daily Truck	Length of Truck	DPM Emiss	ion Rates (gra	ams/second)				
Description	Trips ¹	Route (meters)	2023-2025	2026-2040	2041-2052				
Onsite Roads									
2-axle Truck Trips	8		3.88E-07	2.30E-07	1.44E-07				
3-axle and 4+-axle Truck Trips	29	143	2.82E-07	2.51E-07	2.36E-07				
Project Driveway 1 (Alder Avenue)	38		6.70E-07	4.82E-07	3.81E-07				
2-axle Truck Trips	8		2.15E-07	1.28E-07	8.01E-08				
3-axle and 4+-axle Truck Trips	29	80	1.57E-07	1.40E-07	1.31E-07				
Project Driveway 2 (Slover Ave West)	38	- 80	3.72E-07	2.68E-07	2.11E-07				
2-axle Truck Trips	8		4.61E-07	2.74E-07	1.71E-07				
3-axle and 4+-axle Truck Trips	29	171	3.35E-07	2.99E-07	2.81E-07				
Project Driveway 3 (Slover Ave East)	38	1/1	7.96E-07	5.73E-07	4.53E-07				
	Offsite	Roads							
2-axle Truck Trips	8		5.00E-08	3.38E-08	2.42E-08				
3-axle and 4+-axle Truck Trips	29	53	9.86E-08	9.57E-08	9.38E-08				
DW 1 to Slover Ave	38		1.49E-07	1.30E-07	1.18E-07				
2-axle Truck Trips	13	1101	1.69E-06	1.15E-06	8.20E-07				
3-axle and 4+-axle Truck Trips	44	1191	3.34E-06	3.24E-06	3.18E-06				
	2-axle Truck Trips 3-axle and 4+-axle Truck Trips Project Driveway 1 (Alder Avenue) 2-axle Truck Trips 3-axle and 4+-axle Truck Trips Project Driveway 2 (Slover Ave West) 2-axle Truck Trips 3-axle and 4+-axle Truck Trips Project Driveway 3 (Slover Ave East) 2-axle Truck Trips 3-axle and 4+-axle Truck Trips DW 1 to Slover Ave 2-axle Truck Trips	Description Trips¹ Onsite 2-axle Truck Trips 3-axle and 4+-axle Truck Trips Project Driveway 1 (Alder Avenue) 38 2-axle Truck Trips 3-axle and 4+-axle Truck Trips Project Driveway 2 (Slover Ave West) 2-axle Truck Trips 3-axle and 4+-axle Truck Trips 29 Project Driveway 3 (Slover Ave East) Offsite 2-axle Truck Trips 38 Offsite 2-axle Truck Trips 8 3-axle and 4+-axle Truck Trips 29 Project Driveway 3 (Slover Ave East) Offsite 2-axle Truck Trips 8 3-axle and 4+-axle Truck Trips 9 DW 1 to Slover Ave 38	DescriptionTrips¹Route (meters)Onsite Roads2-axle Truck Trips83-axle and 4+-axle Truck Trips29143Project Driveway 1 (Alder Avenue)2-axle Truck Trips83-axle and 4+-axle Truck Trips2980Project Driveway 2 (Slover Ave West)2-axle Truck Trips83-axle and 4+-axle Truck Trips29171Project Driveway 3 (Slover Ave East)Offsite Roads2-axle Truck Trips83-axle and 4+-axle Truck Trips2953DW 1 to Slover Ave382-axle Truck Trips382-axle Truck Trips13	Description Trips¹ Noute (meters) 2023-2025 Onsite Roads 2-axle Truck Trips 8 3.88E-07 3-axle and 4+-axle Truck Trips 29 143 2.82E-07 Project Driveway 1 (Alder Avenue) 38 6.70E-07 2-axle Truck Trips 8 2.15E-07 3-axle and 4+-axle Truck Trips 29 80 Project Driveway 2 (Slover Ave West) 8 4.61E-07 3-axle and 4+-axle Truck Trips 29 171 3.35E-07 Project Driveway 3 (Slover Ave East) 38 7.96E-07 East) 7.96E-07 7.96E-07 2-axle Truck Trips 8 5.00E-08 3-axle and 4+-axle Truck Trips 29 53 9.86E-08 DW 1 to Slover Ave 38 1.49E-07 2-axle Truck Trips 38 1.69E-06	Consite Roads 3.88E-07 2.30E-07				

Source		Daily Truck	Length of Truck	DPM Emiss	ion Rates (gra	ams/second)
ID	Description	Trips ¹	Route (meters)	2023-2025	2026-2040	2041-2052
	Seaton Ave	57	-	5.03E-06	4.39E-06	4.00E-06

Notes:

Onsite Truck Idling

The onsite diesel truck idling emissions were modeled as one point source located in the center of the loading area. The analysis was based on each truck delivery idling on the project site for 15 minutes or 5 minutes for arriving to the loading area, 5 minutes for leaving the loading area, and 5 minutes for queueing activities at the loading area. The 5-minute period is based on Section 2485 of the California Code of Regulations that limits commercial truck idling to 5 minutes at any location.

The idling point source was modeled in the AERMOD model with a 12.6-foot height, a 0.1-meter diameter, a velocity of 50 meters per second, and a temperature of 366°K. The idling point source emission rates entered into the AERMOD model are shown in Table P. The idling source emissions were determined by multiplying 15 minutes by the daily truck operations and dividing it by 24 hours in order to determine the percent of daily idling time. The daily idling time was then multiplied by the EMFAC2017 emissions rates that are detailed above and were converted to grams per second.

Table P – AERMOD Model Operational DPM Truck Idling Emissions Sources

		Daily Truck	DPM Emission Rates (grams/second)		
Source ID	Description	Deliveries ¹	2023-2025	2026-2040	2041-2052
	2-axle Truck Trips	13	2.86E-05	2.87E-05	2.88E-05
IDLING	3-axle and 4+-axle Truck Trips	44	1.89E-06	1.46E-06	1.28E-06
	Idling Total	57	3.05E-05	3.01E-05	3.01E-05

Notes:

¹ Daily truck trips represent one-way trips (i.e., entering the project site or leaving the project site equal one trip). Source: Vista Environmental; EMFAC2017.

¹ Each daily truck delivery represent two trips (i.e., one entering the project site and one leaving the project site). Source: Vista Environmental; EMFAC2017.



9.0 THRESHOLDS OF SIGNIFICANCE

9.1 Regional Air Quality

Many air quality impacts that derive from dispersed mobile sources, which are the dominate pollution generators in the Air Basin, often occurs hours later and miles away after photochemical processes have converted primary exhaust pollutants into secondary contaminants such as ozone. The incremental regional air quality impact of an individual project is generally very small and difficult to measure. Therefore, SCAQMD has developed significance thresholds based on the volume of pollution emitted rather than on actual ambient air quality because the direct air quality impact of a project is not quantifiable on a regional scale. The SCAQMD CEQA Handbook states that any project in the Air Basin with daily emissions that exceed any of the identified significance thresholds should be considered as having an individually and cumulatively significant air quality impact. For the purposes to this air quality impact analysis, a regional air quality impact would be considered significant if emissions exceed the SCAQMD significance thresholds identified in Table Q.

Table Q – SCAQMD Regional Criteria Pollutant Emission Thresholds of Significance

		Pollutant Emissions (pounds/day)							
	VOC NOx CO SOx PM10 PM2.5 Lead								
Construction	75	100	550	150	150	55	3		
Operation	55	55	550	150	150	55	3		

9.2 Local Air Quality

Project-related construction air emissions may have the potential to exceed the State and Federal air quality standards in the project vicinity, even though these pollutant emissions may not be significant enough to create a regional impact to the Air Basin. In order to assess local air quality impacts the SCAQMD has developed Localized Significant Thresholds (LSTs) to assess the project-related air emissions in the project vicinity. SCAQMD has also provided *Final Localized Significance Threshold Methodology* (LST Methodology), July 2008, which details the methodology to analyze local air emission impacts. The LST Methodology found that the primary emissions of concern are NO₂, CO, PM10, and PM2.5.

The LST Methodology provides Look-Up Tables with different thresholds based on the location and size of the project site and distance to the nearest sensitive receptors. As detailed above in Section 7.3, the project site is located in Monitoring Area 34, which covers the Central San Bernardino Valley.

The Look-Up Tables include site acreage sizes of 1-acre, 2-acres and 5-acres. The Fact Sheet for Applying CalEEMod to Localized Significance Thresholds, prepared by SCAQMD, 2015, provides guidance on how to determine the appropriate site acreage size to utilize for a project. The Fact Sheet details the site acreage should be based on the maximum number of acres disturbed on the peak day of construction that is calculated on the construction equipment list utilized in the CalEEMod model, where crawler tractors, graders, and rubber-tired dozers are all assumed to disturb 0.5-acre in an 8-hour day and scrapers are assumed to disturb 1.0-acre in an 8-hour day. It should be noted that the methodology in the Fact Sheet was developed from the CalEEMod User Guide Appendix A, page 9, where the same acres disturbed per equipment type is detailed and is utilized in the CalEEMod model in order to determine the acres per day disturbed during site preparation and grading phases.

Table R lists all of the construction equipment modeled in CalEEMod and utilizes the methodology in the Fact Sheet to calculate the acres disturbed per day. As shown in Table R, the maximum disturbed per day would occur during the grading phase when 4-acres would be disturbed. As such, the 2-acre and 5-acre project sites shown in the Look-Up Tables were interpolated in order to calculate the 4-acre threshold that has been utilized in this analysis.

Table R - Construction Equipment Modeled in CalEEMod and Acres Disturbed per Day

Construction Activity	Equipment Type	Equipment Quantity	Acres Disturbed per piece of Equipment per Day¹	Operating Hours per Day	Acres Disturbed per Day		
	Concrete/Industrial Saw	1	0	8	0		
Demolition	Excavators	3	0	8	0		
Demontion	Rubber Tired Dozers	2	0.5	8	1.0		
		Total Acres Disturbed per Day During Demolition					
Site	Rubber Tired Dozers	3	0.5	8	1.5		
Preparation	Crawler Tractors	4	0.5	8	2.0		
Freparation		Total Acres Disturbed per Day Durin					
	Graders	1	0.5	8	0.5		
Grading	Excavators	2	0	8	0		
	Rubber Tired Dozers	1	0.5	8	0.5		
	Scrapers	2	1.0	8	2.0		
	Crawler Tractors	2	0.5	8	1.0		
		Total A	cres Disturbed per Day D	uring Grading	4.0		
	Cranes	1	0	7	0		
	Forklifts	3	0	8	0		
Building	Generator Sets	1	0	8	0		
Construction	Tractors/Loaders/Backhoes	3	0	7	0		
	Welders	1	0	8	0		
	Tota	al Acres Disturbed	d per Day During Building	Construction	0		
	Pavers	2	0	8	0		
Daving	Paving Equipment	2	0	8	0		
Paving	Rollers	2	0	8	0		
		Total	Acres Disturbed per Day	During Paving	0		
Architectural	Air Compressor	1	0	6	0		
Coating	Tota	al Acres Disturbe	d per Day During Archite	ctural Coating	0		
Maximum Acres Disturbed during All Construction Activities							

Notes

The nearest sensitive receptors to the project site are the single-family homes that are located adjacent to the south side of the project site, where the residential structures are located as close as 30 feet (11 meters) south of the project site. According to LST Methodology, any receptor located closer than 25 meters (82 feet) shall be based on the 25 meter thresholds.

¹ Based on the Fact Sheet for Applying CalEEMod to Localized Significance Thresholds where crawler tractors, graders, and rubber-tired dozers disturb 0.5-acre in an 8-hour day and scrapers disturb 1.0-acre in an 8-hour day. All other equipment disturb 0 acres per 8-hour day. Source: CalEEMod Version 2020.4.0; SCAQMD, 2015.

In order to provide a conservative analysis, the 25-meter threshold was utilized. Table S below shows the LSTs for NO₂, PM10 and PM2.5 for both construction and operational activities.

Table S – SCAQMD Local Air Quality Thresholds of Significance

	Allowable Emissions (pounds/day) ¹						
Activity	NOx CO PM10 PM2.5						
Construction	237	1,488	12	7			
Operation	237	1,488	3	2			

Notes:

9.3 Toxic Air Contaminants

According to the SCAQMD CEQA Handbook, any project that has the potential to expose the public to toxic air contaminants in excess of the following thresholds would be considered to have a significant air quality impact:

- If the Maximum Incremental Cancer Risk is 10 in one million or greater; or
- Toxic air contaminants from the proposed project would result in a Hazard Index increase of 1 or greater.

In order to determine if the proposed project may have a significant impact related to toxic air contaminants (TACs), the *Health Risk Assessment Guidance for analyzing Cancer Risks from Mobile Source Diesel Idling Emissions for CEQA Air Quality Analysis*, (Diesel Analysis) prepared by SCAQMD, August 2003, recommends that if the proposed project is anticipated to create TACs through stationary sources or regular operations of diesel trucks on the project site, then the proximity of the nearest receptors to the source of the TAC and the toxicity of the HAP should be analyzed through a comprehensive facility-wide health risk assessment (HRA).

The comprehensive HRA for both construction and operation of the proposed project can be found below in Section 10.4.

9.4 Odor Impacts

The SCAQMD CEQA Handbook states that an odor impact would occur if the proposed project creates an odor nuisance pursuant to SCAQMD Rule 402, which states:

"A person shall not discharge from any source whatsoever such quantities of air contaminants or other material which cause injury, detriment, nuisance, or annoyance to any considerable number of persons to the public, or which endanger the comfort, repose, health or safety of any such persons or the public, or which cause, or have a natural tendency to cause, injury or damage to business or property.

The provisions of this rule shall not apply to odors emanating from agricultural operations necessary for the growing of crops or the raising of fowl or animals."

If the proposed project results in a violation of Rule 402 with regards to odor impacts, then the proposed project would create a significant odor impact.

¹ The nearest sensitive receptors to the project site are single-family homes located as close as 30 feet (11 meters) south of the project site. According to SCAQMD methodology, all receptors closer than 25 meters are based on the 25-meter threshold.

Source: Calculated from SCAQMD's Mass Rate Look-up Tables for two and five acres in Air Monitoring Area 34, Central San Bernardino Valley.

9.5 Energy Conservation

The 2018 amendments and additions to the CEQA Checklist now include an Energy Section that analyzes the proposed project's energy consumption in order to avoid or reduce inefficient, wasteful or unnecessary consumption of energy. Appendix F of the 2020 CEQA Statute and Guidelines, states the following:

The goal of conserving energy implies the wise and efficient use of energy. The means of achieving this goal include:

- (1) Decreasing overall per capita energy consumption,
- (2) Decreasing reliance on fossil fuels such as coal, natural gas and oil, and
- (3) Increasing reliance on renewable energy sources.

Since the Energy Section was recently added, no state or local agencies have adopted specific criteria or thresholds to be utilized in an energy impact analysis. However, the 2018 *Guidelines for the Implementation of the California Environmental Quality Act,* provide the following direction on how to analyze a project's energy consumption:

"If analysis of the project's energy use reveals that the project may result in significant environmental effects due to wasteful, inefficient, or unnecessary use of energy, or wasteful use of energy resources, the EIR shall mitigate that energy use. This analysis should include the project's energy use for all project phases and components, including transportation-related energy, during construction and operation. In addition to building code compliance, other relevant considerations may include, among others, the project's size, location, orientation, equipment use and any renewable energy features that could be incorporated into the project. (Guidance on information that may be included in such an analysis is presented in Appendix F.) This analysis is subject to the rule of reason and shall focus on energy use that is caused by the project. This analysis may be included in related analyses of air quality, greenhouse gas emissions, transportation or utilities in the discretion of the lead agency."

If the proposed project creates inefficient, wasteful or unnecessary consumption of energy during construction or operation activities or conflicts with a state or local plan for renewable energy or energy efficiency, then the proposed project would create a significant energy impact.

9.6 Greenhouse Gas Emissions

The County of San Bernardino GHG Emissions Reduction Plan (GHG Plan) requires the reduction of 159,423 metric tons of CO₂ equivalent emissions (MTCO₂e) per year from new development by 2020 as compared to the unmitigated conditions. The GHG Review Processes, provides project level direction on how the County plans to achieve the reduction in GHG Emissions. The GHG Review Processes determined that projects that do not exceed 3,000 MTC per year will be consistent with the GHG Plan and determined to have a less than significant individual and cumulative impact for GHG emissions. For projects that exceed 3,000 MTC per year of GHG emissions the applicant may choose to either: utilize the Screening Tables, which consist of a list of mitigation measures, rated for their effectiveness and provide mitigation to reach 100 points; or provide a detailed GHG analysis that quantifies project design features or mitigation measures in order to reduce GHG emissions by 31 percent or more over year 2020 unmitigated GHG emissions levels.

10.0 IMPACT ANALYSIS

10.1 CEQA Thresholds of Significance

Consistent with CEQA and the State CEQA Guidelines, a significant impact related to air quality, energy, and GHG emissions would occur if the proposed project is determined to:

- Conflict with or obstruct implementation of the applicable air quality plan;
- Result in a cumulatively considerable net increase of any criteria pollutant for which the project region is in non-attainment under an applicable federal or state ambient air quality standard;
- Expose sensitive receptors to substantial pollutant concentrations;
- Result in other emissions (such as those leading to odors) adversely affecting a substantial number of people;
- Result in potentially significant environmental impact due to wasteful, inefficient, or unnecessary consumption of energy resources, during project construction or operation;
- Conflict with or obstruct a state or local plan for renewable energy;
- Generate GHG emissions, either directly or indirectly, that may have a significant impact on the environment; or
- Conflict with any applicable plan, policy or regulation of an agency adopted for the purpose of reducing the emissions of GHGs.

10.2 Air Quality Compliance

The proposed project would not conflict with or obstruct implementation of the SCAQMD Air Quality Management Plan (AQMP). The following section discusses the proposed project's consistency with the SCAQMD AQMP.

SCAQMD Air Quality Management Plan

The California Environmental Quality Act (CEQA) requires a discussion of any inconsistencies between a proposed project and applicable General Plans and regional plans (CEQA Guidelines Section 15125). The regional plan that applies to the proposed project includes the SCAQMD AQMP. Therefore, this section discusses any potential inconsistencies of the proposed project with the AQMP.

The purpose of this discussion is to set forth the issues regarding consistency with the assumptions and objectives of the AQMP and discuss whether the proposed project would interfere with the region's ability to comply with Federal and State air quality standards. If the decision-makers determine that the proposed project is inconsistent, the lead agency may consider project modifications or inclusion of mitigation to eliminate the inconsistency.

The SCAQMD CEQA Handbook states that "New or amended GP Elements (including land use zoning and density amendments), Specific Plans, and significant projects must be analyzed for consistency with the AQMP." Strict consistency with all aspects of the plan is usually not required. A proposed project should be considered to be consistent with the AQMP if it furthers one or more policies and does not obstruct other policies. The SCAQMD CEQA Handbook identifies two key indicators of consistency:

- (1) Whether the project will result in an increase in the frequency or severity of existing air quality violations or cause or contribute to new violations, or delay timely attainment of air quality standards or the interim emission reductions specified in the AQMP.
- (2) Whether the project will exceed the assumptions in the AQMP or increments based on the year of project buildout and phase.

Both of these criteria are evaluated in the following sections.

<u>Criterion 1 - Increase in the Frequency or Severity of Violations?</u>

Based on the air quality modeling analysis contained in this report, short-term regional construction air emissions would not result in significant impacts based on SCAQMD regional thresholds of significance discussed above in Section 9.1 or local thresholds of significance discussed above in Section 9.2. The ongoing operation of the proposed project would generate air pollutant emissions that are inconsequential on a regional basis and would not result in significant impacts based on SCAQMD thresholds of significance discussed above in Section 9.1. The analysis for long-term local air quality impacts showed that local pollutant concentrations would not exceed the air quality standards. Therefore, a less than significant long-term impact would occur and no mitigation would be required.

Therefore, based on the information provided above, the proposed project would be consistent with the first criterion.

Criterion 2 - Exceed Assumptions in the AQMP?

Consistency with the AQMP assumptions is determined by performing an analysis of the proposed project with the assumptions in the AQMP. The emphasis of this criterion is to ensure that the analyses conducted for the proposed project are based on the same forecasts as the AQMP. The AQMP is developed through use of the planning forecasts provided in the Connect SoCal and 2019 FTIP. The Connect SoCal is a major planning document for the regional transportation and land use network within Southern California. The Connect SoCal is a long-range plan that is required by federal and state requirements placed on SCAG and is updated every four years. The 2019 FTIP provides long-range planning for future transportation improvement projects that are constructed with state and/or federal funds within Southern California. Local governments are required to use these plans as the basis of their plans for the purpose of consistency with applicable regional plans under CEQA. For this project, the County of San Bernardino General Plan's Land Use Plan and more specifically the Bloomington Community Plan defines the assumptions that are represented in AQMP.

The project site is currently designated Community Industrial (IC) in the General Plan and is zoned Limited Industrial (LI). The proposed project is consistent with the current land use designations and would not require a Specific Plan Amendment or zone change. As such, the proposed project is not anticipated to exceed the AQMP assumptions for the project site and is found to be consistent with the AQMP for the second criterion.

Based on the above, the proposed project will not result in an inconsistency with the SCAQMD AQMP. Therefore, a less than significant impact will occur in relation to implementation of the AQMP.

Level of Significance

Less than significant impact.

10.3 Cumulative Net Increase in Non-Attainment Pollution

The proposed project would not result in a cumulatively considerable net increase of any criteria pollutant for which the project region is non-attainment under an applicable Federal or State ambient air quality standard.

The SCAQMD has published a report on how to address cumulative impacts from air pollution: White Paper on Potential Control Strategies to Address Cumulative Impacts from Air Pollution (http://www.aqmd.gov/docs/default-source/Agendas/Environmental-Justice/cumulative-impacts-working-group/cumulative-impacts-white-paper.pdf). In this report the AQMD clearly states (Page D-3):

"...the AQMD uses the same significance thresholds for project specific and cumulative impacts for all environmental topics analyzed in an Environmental Assessment or Environmental Impact Report (EIR). The only case where the significance thresholds for project specific and cumulative impacts differ is the Hazard Index (HI) significance threshold for TAC emissions. The project specific (project increment) significance threshold is HI > 1.0 while the cumulative (facility- wide) is HI > 3.0. It should be noted that the HI is only one of three TAC emission significance thresholds considered (when applicable) in a CEQA analysis. The other two are the maximum individual cancer risk (MICR) and the cancer burden, both of which use the same significance thresholds (MICR of 10 in 1 million and cancer burden of 0.5) for project specific and cumulative impacts. Projects that exceed the project-specific significance thresholds are considered by the SCAQMD to be cumulatively considerable. This is the reason project-specific and cumulative significance thresholds are the same. Conversely, projects that do not exceed the project-specific thresholds are generally not considered to be cumulatively significant."

Therefore, this analysis assumes that individual projects that do not generate operational or construction emissions that exceed the SCAQMD's recommended daily thresholds for project- specific impacts would also not cause a cumulatively considerable increase in emissions for those pollutants for which the Basin is in nonattainment, and, therefore, would not be considered to have a significant, adverse air quality impact. Alternatively, individual project-related construction and operational emissions that exceed SCAQMD thresholds for project-specific impacts would be considered cumulatively considerable. The following section calculates the potential air emissions associated with the construction and operations of the proposed project and compares the emissions to the SCAQMD standards.

Construction Emissions

The construction activities for the proposed project are anticipated to include demolition of the existing structures and parking lots on the project sit, site preparation and grading of the 13.23 acre project site, building construction of the warehouse, paving of the truck loading area, driveways, and parking lots, and application of architectural coatings. The construction emissions have been analyzed for both regional and local air quality impacts.

Construction-Related Regional Impacts

The CalEEMod model has been utilized to calculate the construction-related regional emissions from the proposed project and the input parameters utilized in this analysis have been detailed in Section 8.1. The worst-case summer or winter daily construction-related criteria pollutant emissions from the proposed project for each phase of construction activities are shown below in Table T and the CalEEMod daily printouts are shown in Appendix A. Since it is possible that building construction, paving, and architectural

coating activities may occur concurrently towards the end of the building construction phase, Table T also shows the combined regional criteria pollutant emissions from building construction (year 2023), paving and architectural coating phases of construction.

Table T – Construction-Related Regional Criteria Pollutant Emissions

	Pollutant Emissions (pounds/day)					
Activity	voc	NOx	СО	SO ₂	PM10	PM2.5
Demolition (Year 2022) ¹						
Onsite ²	2.64	25.72	20.59	0.04	2.74	1.38
Offsite ³	0.14	2.87	1.35	0.01	0.55	0.17
Total	2.78	28.58	21.94	0.05	3.29	1.55
Site Preparation (Year 2022) ¹						
Onsite ²	4.48	50.41	20.01	0.06	10.65	6.02
Offsite ³	0.09	0.33	0.84	<0.00	0.24	0.07
Total	4.57	50.74	20.84	0.06	10.90	6.08
Grading (Year 2022) ¹						
Onsite ²	4.28	47.51	29.20	0.72	5.91	3.23
Offsite ³	0.10	0.33	0.92	<0.00	0.27	0.07
Total	4.37	47.84	30.12	0.72	6.18	3.30
Building Construction (Year 2022)						
Onsite	1.71	15.62	16.36	0.03	0.81	0.76
Offsite	1.01	4.26	9.77	0.04	2.87	0.81
Total	2.72	19.87	26.14	0.07	3.68	1.57
Combined Year 2023 Building Constructio	n, Paving, a	nd Archited	tural Coatir	igs		
Onsite	21.90	25.88	32.64	0.05	1.28	1.20
Offsite	1.12	3.61	11.06	0.04	3.48	0.96
Total	23.02	29.49	43.70	0.09	4.75	2.15
Maximum Daily Construction Emissions	23.02	50.74	43.70	0.72	10.90	6.08
SCQAMD Thresholds	75	100	550	150	150	55
Exceeds Threshold?	No	No	No	No	No	No

Source: CalEEMod Version 2020.4.0.

Table T shows that none of the analyzed criteria pollutants would exceed the regional emissions thresholds during either demolition, site preparation, grading, or the combined building construction, paving and architectural coatings phases. Therefore, a less than significant regional air quality impact would occur from construction of the proposed project.

Construction-Related Local Impacts

Construction-related air emissions may have the potential to exceed the State and Federal air quality standards in the project vicinity, even though these pollutant emissions may not be significant enough to create a regional impact to the Air Basin.

¹ Demolition, Site Preparation and Grading based on adherence to fugitive dust suppression requirements from SCAQMD Rule 403.

² Onsite emissions from equipment not operated on public roads.

³ Offsite emissions from vehicles operating on public roads.

The local air quality emissions from construction were analyzed through utilizing the methodology described in *Localized Significance Threshold Methodology* (LST Methodology), prepared by SCAQMD, revised October 2009. The LST Methodology found the primary criteria pollutant emissions of concern are NOx, CO, PM10, and PM2.5. In order to determine if any of these pollutants require a detailed analysis of the local air quality impacts, each phase of construction was screened using the SCAQMD's Mass Rate LST Look-up Tables. The Look-up Tables were developed by the SCAQMD in order to readily determine if the daily onsite emissions of CO, NOx, PM10, and PM2.5 from the proposed project could result in a significant impact to the local air quality.

Table U shows the onsite emissions from the CalEEMod model for the different construction phases and the calculated localized emissions thresholds that have been detailed above in Section 9.2. Since it is possible that building construction, paving, and architectural coating activities may occur concurrently towards the end of the building construction phase, Table U also shows the combined local criteria pollutant emissions from year 2023 building construction, paving and architectural coating phases of construction.

Table U – Construction-Related Local Criteria Pollutant Emissions

	Pollutant Emissions (pounds/day) ¹			
Construction Phase	NOx	СО	PM10	PM2.5
Demolition ²	26.08	20.76	2.81	1.40
Site Preparation ²	50.45	20.11	10.68	6.02
Grading ²	47.55	29.31	5.94	3.23
Building Construction (Year 2022)	16.15	17.58	1.17	0.86
Combined Building Construction (Year 2023), Paving and Architectural Coatings	27.66	34.24	1.83	1.42
Maximum Daily Construction Emissions	50.45	34.24	10.68	6.02
SCAQMD Local Construction Thresholds ³	237	1,488	12	7
Exceeds Threshold?	No	No	No	No

Notes:

The data provided in Table U shows that none of the analyzed criteria pollutants would exceed the local emissions thresholds during either site preparation, grading, or the combined building construction, paving, and architectural coatings phases. Therefore, a less than significant local air quality impact would occur from construction of the proposed project.

Operational Emissions

The ongoing operation of the proposed project would result in a long-term increase in air quality emissions. This increase would be due to emissions from the project-generated vehicle trips, emissions from energy usage, onsite area source emissions, and off-road equipment created from the on-going use of the proposed project. The following section provides an analysis of potential long-term air quality impacts due to regional air quality and local air quality impacts with the on-going operations of the proposed project.

¹ The Pollutant Emissions include 100% of the On-Site emissions (off-road equipment and fugitive dust) and 1/8 of the Off-Site emissions (on road trucks and worker vehicles), in order to account for the on-road emissions that occur within a ¼ mile of the project site.

² Demolition, Site Preparation and Grading phases based on adherence to fugitive dust suppression requirements from SCAQMD Rule 403.

³ The nearest offsite sensitive receptors to the project site are single-family homes located as close as 30 feet (11 meters) south of the project site. According to SCAQMD methodology, all receptors closer than 25 meters are based on the 25-meter threshold.

Source: Calculated from SCAQMD's Mass Rate Look-up Tables for two and five acres in Air Monitoring Area 34, Central San Bernardino Valley.

Operations-Related Regional Criteria Pollutant Analysis

The operations-related regional criteria air quality impacts created by the proposed project have been analyzed through use of the CalEEMod model and the input parameters utilized in this analysis have been detailed in Section 8.1. The worst-case summer or winter VOC, NOx, CO, SO₂, PM10, and PM2.5 daily emissions created from the proposed project's long-term operations have been calculated and are summarized below in Table V and the CalEEMod daily emissions printouts are shown in Appendix A.

Table V – Operatio	nal Regional Criteria	Pollutant Emissions
--------------------	-----------------------	----------------------------

	Pollutant Emissions (pounds/day)					
Activity	VOC	NOx	СО	SO₂	PM10	PM2.5
Area Sources ¹	5.90	<0.00	0.03	<0.00	<0.00	<0.00
Energy Usage ²	0.02	0.14	0.12	< 0.00	0.01	0.01
Mobile Sources ³	1.07	15.55	12.41	0.10	4.93	1.47
Off-Road Equipment⁴	0.05	2.48	32.44	0.01	0.04	0.04
Total Emissions	7.03	18.17	45.00	0.10	4.98	1.52
SCQAMD Operational Thresholds	55	55	550	150	150	55
Exceeds Threshold?	No	No	No	No	No	No

Notes:

Source: Calculated from CalEEMod Version 2020.4.0.

The data provided in Table V shows that none of the analyzed criteria pollutants would exceed the regional emissions thresholds. Therefore, a less than significant regional air quality impact would occur from operation of the proposed project.

Friant Ranch Case

The operations-related regional criteria air quality impacts In *Sierra Club v. County of Fresno* (2018) 6 Cal.5th 502 (also referred to as "*Friant Ranch*"), the California Supreme Court held that when an EIR concluded that when a project would have significant impacts to air quality impacts, an EIR should "make a reasonable effort to substantively connect a project's air quality impacts to likely health consequences." In order to determine compliance with this Case, the Court developed a multi-part test that includes the following:

1) The air quality discussion shall describe the specific health risks created from each criteria pollutant, including diesel particulate matter.

This Analysis details the specific health risks created from each criteria pollutant above in Section 4.1 and specifically in Table C – State and Federal Criteria Pollutant Standards. In addition, the specific health risks created from diesel particulate matter is detailed above in Section 2.2 of this analysis. As such, this analysis meets the part 1 requirements of the Friant Ranch Case.

2) The analysis shall identify the magnitude of the health risks created from the Project. The Ruling details how to identify the magnitude of the health risks. Specifically, on page 24 of the ruling it states "The Court of Appeal identified several ways in which the EIR could have framed the

¹ Area sources consist of emissions from consumer products, architectural coatings, and landscaping equipment.

² Energy usage consist of emissions from natural gas usage.

³ Mobile sources consist of emissions from vehicles and road dust.

⁴ Off-road equipment consists of emissions from forklifts utilized onsite (Project Design Feature 1 requires all off-road equipment to be non-diesel-powered).

analysis so as to adequately inform the public and decision makers of possible adverse health effects. The County could have, for example, identified the Project's impact on the days of nonattainment per year."

The Friant Ranch Case found that an EIR's air quality analysis must meaningfully connect the identified air quality impacts to the human health consequences of those impacts, or meaningfully explain why that analysis cannot be provided. As noted in the Brief of Amicus Curiae by the SCAQMD in the Friant Ranch case (https://www.courts.ca.gov/documents/9-s219783-ac-south-coast-air-quality-mgt-dist-041315.pdf) (Brief), SCAQMD has among the most sophisticated air quality modeling and health impact evaluation capability of any of the air districts in the State, and thus it is uniquely situated to express an opinion on how lead agencies should correlate air quality impacts with specific health outcomes. The SCAQMD discusses that it may be infeasible to quantify health risks caused by projects similar to the proposed Project, due to many factors. It is necessary to have data regarding the sources and types of air toxic contaminants, location of emission points, velocity of emissions, the meteorology and topography of the area, and the location of receptors (worker and residence). The Brief states that it may not be feasible to perform a health risk assessment for airborne toxics that will be emitted by a generic industrial building that was built on "speculation" (i.e., without knowing the future tenant(s)). Even where a health risk assessment can be prepared, however, the resulting maximum health risk value is only a calculation of risk, it does not necessarily mean anyone will contract cancer as a result of the Project. The Brief also cites the author of the CARB methodology, which reported that a PM2.5 methodology is not suited for small projects and may yield unreliable results. Similarly, SCAQMD staff does not currently know of a way to accurately quantify ozone-related health impacts caused by NOX or VOC emissions from relatively small projects, due to photochemistry and regional model limitations. The Brief concludes, with respect to the Friant Ranch EIR, that although it may have been technically possible to plug the data into a methodology, the results would not have been reliable or meaningful.

On the other hand, for extremely large regional projects (unlike the proposed project), the SCAQMD states that it has been able to correlate potential health outcomes for very large emissions sources – as part of their rulemaking activity, specifically 6,620 pounds per day of NOx and 89,180 pounds per day of VOC were expected to result in approximately 20 premature deaths per year and 89,947 school absences due to ozone. As shown above in Table T, project-related construction activities would generate a maximum of 23.02 pounds per day of VOC and 50.74 pounds per day of NOx and as shown above in Table V, operation of the proposed project would generate 7.03 pounds per day of VOC and 18.17 pounds per day NOx. The proposed project would not generate anywhere near these levels of 6,620 pounds per day of NOx or 89,190 pounds per day of VOC emissions. Therefore, the proposed project's emissions are not sufficiently high enough to use a regional modeling program to correlate health effects on a basin-wide level.

Notwithstanding, this analysis does evaluate the proposed project's localized impact to air quality for emissions of CO, NOX, PM10, and PM2.5 by comparing the proposed project's onsite emissions to the SCAQMD's applicable LST thresholds. As evaluated in this analysis, the proposed project would not result in emissions that exceeded the SCAQMD's LSTs. Therefore, the proposed project would not be expected to exceed the most stringent applicable federal or state ambient air quality standards for emissions of CO, NOX, PM10, and PM2.5.

Operations-Related Local Air Quality Impacts

Project-related air emissions may have the potential to exceed the State and Federal air quality standards in the project vicinity, even though these pollutant emissions may not be significant enough to create a regional impact to the Air Basin. The proposed project has been analyzed for the potential local CO emission impacts from the project-generated vehicular trips and from the potential local air quality impacts from on-site operations. The following analyzes the vehicular CO emissions and local impacts from on-site operations.

Local CO Hotspot Impacts from Project-Generated Vehicular Trips

CO is the pollutant of major concern along roadways because the most notable source of CO is motor vehicles. For this reason, CO concentrations are usually indicative of the local air quality generated by a roadway network and are used as an indicator of potential local air quality impacts. Local air quality impacts can be assessed by comparing future without and with project CO levels to the State and Federal CO standards of 20 ppm over one hour or 9 ppm over eight hours.

At the time of the 1993 Handbook, the Air Basin was designated nonattainment under the CAAQS and NAAQS for CO. With the turnover of older vehicles, introduction of cleaner fuels, and implementation of control technology on industrial facilities, CO concentrations in the Air Basin and in the state have steadily declined. In 2007, the Air Basin was designated in attainment for CO under both the CAAQS and NAAQS. SCAQMD conducted a CO hot spot analysis for attainment at the busiest intersections in Los Angeles during the peak morning and afternoon periods and did not predict a violation of CO standards³. Since the nearby intersections to the proposed project are much smaller with less traffic than what was analyzed by the SCAQMD, no local CO Hotspot are anticipated to be created from the proposed project and no CO Hotspot modeling was performed. Therefore, a less than significant long-term air quality impact is anticipated to local air quality with the on-going use of the proposed project.

Local Criteria Pollutant Impacts from Onsite Operations

Project-related air emissions from onsite sources such as architectural coatings, landscaping equipment, and onsite usage of natural gas appliances may have the potential to create emissions areas that exceed the State and Federal air quality standards in the project vicinity, even though these pollutant emissions may not be significant enough to create a regional impact to the Air Basin.

The local air quality emissions from onsite operations were analyzed using the SCAQMD's Mass Rate LST Look-up Tables and the methodology described in LST Methodology. The Look-up Tables were developed by the SCAQMD in order to readily determine if the daily emissions of CO, NOx, PM10, and PM2.5 from the proposed project could result in a significant impact to the local air quality. Table N shows the onsite emissions from the CalEEMod model that includes area sources, energy usage, onsite off-road equipment, and vehicles operating in the immediate vicinity of the project site and the calculated emissions thresholds.

³ The four intersections analyzed by the SCAQMD were: Long Beach Boulevard and Imperial Highway; Wilshire Boulevard and Veteran Avenue; Sunset Boulevard and Highland Avenue; and La Cienega Boulevard and Century Boulevard. The busiest intersection evaluated (Wilshire and Veteran) had a daily traffic volume of approximately 100,000 vehicles per day with LOS E in the morning and LOS F in the evening peak hour.

Table W - Operations-Related Local Criteria Pollutant Emissions

	Po	llutant Emissio	ons (pounds/d	ay)
Onsite Emission Source	NOx	СО	PM10	PM2.5
Area Sources	<0.00	0.03	<0.00	<0.00
Energy Usage	0.14	0.12	0.01	0.01
Mobile Sources ¹	1.94	1.55	0.62	0.18
Off-Road Equipment ²	2.48	32.44	0.04	0.04
Total Emissions	4.57	34.14	0.67	0.23
SCAQMD Local Operational Thresholds ³	237	1,488	3	2
Exceeds Threshold?	No	No	No	No

Motac.

The data provided in Table N shows that the on-going operations of the proposed project would not exceed the local NOx, CO, PM10 and PM2.5 thresholds of significance discussed above in Section 9.2. Therefore, the on-going operations of the proposed project would create a less than significant operations-related impact to local air quality due to onsite emissions and no mitigation would be required.

Therefore, the proposed project would not result in a cumulatively considerable net increase of any criteria pollutant.

Level of Significance

Less than significant impact.

10.4 Sensitive Receptors

The proposed project would not expose sensitive receptors to substantial pollutant concentrations. The local concentrations of criteria pollutant emissions produced in the nearby vicinity of the proposed project, which may expose sensitive receptors to substantial concentrations have been calculated above in Section 10.3 for both construction and operations, which are discussed separately below. The discussion below also includes an analysis of the potential impacts from local criteria pollutant and toxic air contaminant emissions. The nearest sensitive receptors to the project site are the single-family homes that are located adjacent to the south side of the project site, where the residential structures are located as close as 30 feet south of the project site. The nearest school is Bloomington High School, which is located as near as 330 feet south of the project site.

Construction-Related Sensitive Receptor Impacts

Construction activities may expose sensitive receptors to substantial pollutant concentrations of localized criteria pollutant concentrations and from toxic air contaminant emissions created from onsite construction equipment, which are described below.

³ Mobile sources based on 1/8 of the gross vehicular emissions, which is the estimated portion of vehicle emissions occurring within a quarter mile of the project site.

² Off-road equipment consists of emissions from forklifts utilized onsite (Project Design Feature 1 requires all off-road equipment to be non-diesel-powered).

³ The nearest sensitive receptors to the project site are single-family homes located as close as 30 feet (11 meters) south of the project site. According to SCAQMD methodology, all receptors closer than 25 meters are based on the 25-meter threshold.

Source: Calculated from SCAQMD's Mass Rate Look-up Tables for two and five acres in Air Monitoring Area 34, Central San Bernardino Valley.

Local Criteria Pollutant Impacts from Construction

The local air quality impacts from construction of the proposed project have been analyzed above in Section 10.3 and found that the construction of the proposed project would not exceed the local NOx, CO, PM10 and PM2.5 thresholds of significance discussed above in Section 9.2. Therefore, construction of the proposed project would create a less than significant construction-related impact to local air quality and no mitigation would be required.

Toxic Air Contaminants Impacts from Construction

Construction activities are anticipated to generate TAC emissions from diesel particulate matter (DPM) associated with the operation of trucks and off-road equipment and from possible asbestos in the structures to be demolished.

Diesel Particulate Matter Emissions

The greatest potential for toxic air contaminant emissions would be related to DPM emissions associated with heavy equipment operations during construction of the proposed project. According to SCAQMD methodology, health effects from carcinogenic air toxics are usually described in terms of "individual cancer risk". "Individual Cancer Risk" is the likelihood that a person exposed to concentrations of toxic air contaminants over a 70-year lifetime will contract cancer, based on the use of standard risk-assessment methodology. It should be noted that the most current cancer risk assessment methodology recommends analyzing a 30-year exposure period for the nearby sensitive receptors (OEHHA, 2015).

Given the relatively limited number of heavy-duty construction equipment, the varying distances that construction equipment would operate to the nearby sensitive receptors, and the short-term construction schedule, the proposed project would not result in a long-term (i.e., 30 or 70 years) substantial source of toxic air contaminant emissions and corresponding individual cancer risk. In addition, California Code of Regulations Title 13, Article 4.8, Chapter 9, Section 2449 regulates emissions from off-road diesel equipment in California. This regulation limits idling of equipment to no more than five minutes, requires equipment operators to label each piece of equipment and provide annual reports to CARB of their fleet's usage and emissions. This regulation also requires systematic upgrading of the emission Tier level of each fleet, and currently no commercial operator is allowed to purchase Tier 0 or Tier 1 equipment and by January 2023 no commercial operator is allowed to purchase Tier 2 equipment. In addition to the purchase restrictions, equipment operators need to meet fleet average emissions targets that become more stringent each year between years 2014 and 2023. Therefore, due to the limitations in off-road construction equipment DPM emissions from implementation of Section 2448, a less than significant short-term TAC impacts would occur during construction of the proposed project from DPM emissions.

Asbestos Emissions

It is possible that the existing onsite structures to be demolished contains asbestos. According to SCAQMD Rule 1403 requirements, prior to the start of demolition activities, the existing structures located onsite shall be thoroughly surveyed for the presence of asbestos by a person that is certified by Cal/OSHA for asbestos surveys. Rule 1403 requires that the SCAQMD be notified a minimum of 10 days before any demolition activities begin with specific details of all asbestos to be removed, start and completion dates of demolition, work practices and engineering controls to be used to contain the asbestos emissions, estimates on the amount of asbestos to be removed, the name of the waste disposal site where the asbestos will be taken, and names and addresses of all contractors and transporters that will be involved in the asbestos removal process. Therefore, through adherence to the asbestos removal requirements,

detailed in SCAQMD Rule 1403, a less than significant asbestos impact would occur during construction of the proposed project

As such, construction of the proposed project would result in a less than significant exposure of sensitive receptors to substantial pollutant concentrations.

Operations-Related Sensitive Receptor Impacts

The ongoing operations of the proposed project may expose sensitive receptors to substantial pollutant concentrations of local CO emission impacts from the project-generated vehicular trips and from the potential local air quality impacts from onsite operations. The following analyzes the vehicular CO emissions. Local criteria pollutant impacts from onsite operations, and toxic air contaminant impacts.

Local CO Hotspot Impacts from Project-Generated Vehicle Trips

CO is the pollutant of major concern along roadways because the most notable source of CO is motor vehicles. For this reason, CO concentrations are usually indicative of the local air quality generated by a roadway network and are used as an indicator of potential impacts to sensitive receptors. The analysis provided above in Section 10.3 shows that no local CO Hotspots are anticipated to be created at any nearby intersections from the vehicle traffic generated by the proposed project. Therefore, operation of the proposed project would result in a less than significant exposure of offsite sensitive receptors to substantial pollutant concentrations.

Local Criteria Pollutant Impacts from Onsite Operations

The local air quality impacts from the operation of the proposed project would occur from onsite sources such as architectural coatings, landscaping equipment, and onsite usage of natural gas appliances. The analysis provided above in Section 10.3 found that the operation of the proposed project would not exceed the local NOx, CO, PM10 and PM2.5 thresholds of significance discussed above in Section 9.2. Therefore, the on-going operations of the proposed project would create a less than significant operations-related impact to local air quality due to on-site emissions and no mitigation would be required.

Operations-Related Toxic Air Contaminant Impacts

The proposed project consists of development of a warehouse that would generate DPM emissions from diesel truck operations and from transport refrigeration units (TRUs), which are known sources of TACs. The TAC impacts to the nearby sensitive receptors have been analyzed through use of the AERMOD model and the model input parameters detailed above in Section 8.3. Health risks from TACs are twofold. First, TACs are carcinogens according to the State of California. Second, short-term acute and long-term chronic exposure to TACs can cause health effects to the respiratory system. Each of these health risks is discussed below.

Cancer Risks

According to the OEHHA Guidance (OEHHA, 2015) and *Risk Assessment Procedures for Rules 1401, 1401.1 and 212*, (SCAQMD, 2017), the cancer risk should be calculated using the following formula:

Cancer Risk = [Dose-inh (mg/(Kg-day)] * [Cancer Potency Factor (kg-day)/mg]* $[1x10^6]$ * Age Sensitivity Factor * Fraction of Time at Home

Dose-inh =
$$(C_{air} * DBR * A * EF * ED * 10^6) / AT$$

Where:

 C_{air} [Concentration in air ($\mu g/m^3$)] = (Calculated by AERMOD Model)

DBR [Daily breathing rate (L/kg body weight – day)]

A [Inhalation absorption factor]

EF [Exposure frequency (days/year)]

ED [Exposure duration (years)]

10⁶ [Micrograms to milligrams conversion]

AT [Average time period over which exposure is averaged in days]

The cancer risk parameters used in this evaluation for the nearby residential and temple uses are shown in Table X.

Table X – Cancer Risk Calculation Parameters

	0	perations	
Parameter	2023 – 2025	2026 – 2040	2041 – 2052
	(3 rd Trimester to 2 years)	(2 to 16 years)	(16 to 30 years)
Cancer Potency Factor (mg/kg-day) for DPM	1.1	1.1	1.1
Daily Breathing Rate (L/kg body weight-day)	1,009 ⁽¹⁾	572	261
Inhalation Absorption Factor	1	1	1
Exposure Frequency (days/year)	350	350	350
Exposure Duration (years)	2.25	14	13.75
Age Sensitivity Factor	10	3	1
Fraction of Time at Home	1.0	1.0	1.0
Averaging Time ² (days)	25,550	25,550	25,550
Potential Cancer Risk =	Cair * 342	C _{air} * 362	Cair * 39.5

Notes:

Table Y provides a summary of the calculated diesel emission concentrations at the nearest sensitive receptors. Receptor 8 is located at Bloomington High School, south of the project site and all other receptors are located at nearby residential structures. Appendices C, D, and E provide the AERMOD printouts.

¹ Based on 95th percentile breathing rate of 361 for 3rd trimester for 3 months and 1,090 for 0 to 2 years for 24 months (OEHHA, 2015; SCAQMD, 2017).

² Based on a 70-year average lifetime (OEHHA, 2015; SCAQMD, 2017)

Table Y – Project Operational DPM Emissions Cancer Risks at Nearby Sensitive Receptors

Sensitive -	Recept	or Location	Annual PM	110 Concentration	n (μg/m³)	Cancer Risk Per Million
Receptor ¹	X	Y	2023-2025	2026-2040	2041-2052	People ²
1	461,352	3,769,256	0.0007	0.0006	0.0006	0.5
2	461,484	3,769,257	0.0011	0.0010	0.0009	0.8
3	461,729	3,769,204	0.0020	0.0019	0.0018	1.4
4	461,780	3,769,203	0.0013	0.0013	0.0013	1.0
5	461,786	3,769,062	0.0005	0.0004	0.0004	0.3
6	461,726	3,769,022	0.0005	0.0005	0.0004	0.3
7	461,645	3,769,015	0.0005	0.0005	0.0005	0.4
8	461,568	3,768,930	0.0009	0.0008	0.0008	0.6
9	461,434	3,769,023	0.0012	0.0011	0.0011	0.9
10	461,372	3,769,044	0.0009	0.0009	0.0009	0.7
11	461,382	3,769,140	0.0008	0.0007	0.0007	0.6
12	461,286	3,769,219	0.0007	0.0006	0.0006	0.5
Max Grid ³	461,477	3,768,876	0.0008	0.0008	0.0008	0.6
				Threshol	d of Significance	10
				Ex	ceed Threshold?	No

Notes:

Source: Calculated from ISC-AERMOD View Version 11.0.1.

Table Y shows that the cancer risk from the proposed project's DPM emissions would be as high as 1.4 per million persons at the residential structure, that may or may not be utilized as a residence, located east of the project site. The TAC concentrations at the nearby sensitive receptors would be within the SCAQMD's threshold of 10 per million persons. Therefore, operation of the proposed project would result in a less than significant impact due to the cancer risk from TAC emissions.

Non-Cancer Risks

In addition to the cancer risk from exposure to TAC emissions there is also the potential TAC exposure may result in adverse health impacts from acute and chronic illnesses, which are detailed below.

Chronic Health Impacts

Chronic health effects are characterized by prolonged or repeated exposure to a TAC over many days, months, or years. Symptoms from chronic health impacts may not be immediately apparent and are often irreversible. The chronic hazard index is based on the most impacted sensitive receptor from the proposed project and is calculated from the annual average concentrations of PM10. The relationship for non-cancer chronic health effects is given by the equation:

 $HI_{DPM} = C_{DPM} / REL_{DPM}$

Where,

 $^{^{\}rm 1}$ The locations of each Sensitive Receptor are shown above in Figure 3.

² The residential cancer risk based on: C_{air} (2023-2025) * 342 + C_{air} (2026-2040) * 362 + C_{air} (2041-2052) * 39.5.

³ The Max Grid represent the grid receptor location with the highest measured concentration.

HI_{DPM} = Hazard Index; an expression of the potential for non-cancer health effects.

 C_{DPM} = Annual average diesel particulate matter concentration in $\mu g/m^3$.

REL_{DPM}= Reference Exposure Level (REL) for diesel particulate matter; the diesel particulate matter

concentration at which no adverse health effects are anticipated.

The REL_{DPM} is 5 μ g/m³. The Office of Environmental Health Hazard Assessment has established this concentration as protective for the respiratory system. As shown above in Table Y, the AERMOD model found that the highest annual off-site concentration is 0.0011 μ g/m³ for DPM chronic non-cancer risk emissions. The resulting Hazard Index is:

$$HI_{DPM} = 0.002 / 5 = 0.0004$$

The criterion for significance is a Chronic Hazard Index increase of 1.0 or greater, which is detailed above in Section 9.3. Therefore, the on-going operations of the proposed project would result in a less than significant impact due to the non-cancer chronic health risk from TAC emissions created by the proposed project.

Acute Health Impacts

Acute health effects are characterized by sudden and severe exposure and rapid absorption of a TAC. Normally, a single large exposure is involved. Acute health effects are often treatable and reversible. The acute hazard index is calculated from the maximum 24-hour concentrations of PM10 at the point of maximum impact (PMI), which has been calculated with the AERMOD model and the parameters detailed above in Section 8.3. The relationship for non-cancer acute health effects is given by the equation:

Where,

AHI = Acute Hazard Index; an expression of the potential for non-cancer health effects.

C = Maximum hourly concentration of either PM10 in $\mu g/m^3$.

AREL = Acute Reference Exposure Level.

No acute risk has been found to be directly created from DPM, so there is no AREL assigned to DPM, however in order to provide an DPM equivalent AREL, the ARELs from all of the other TACs that are emitted in diesel exhaust were added together based on their diesel weighting shown above in Table A. This resulted in a diesel emission weighted equivalent AREL of 2,189 μ g/m³. The AERMOD model found that the highest 24-hour concentration at the PMI is 0.0026 μ g/m³ for DPM equivalent acute non-cancer risk emissions and Appendix C provides the 24-hour concentrations during year 2023-2025 operations, which was found to create the highest 24-hour DPM concentrations in the AERMOD model. The resulting Hazard Index is:

$$AHI = 0.0048 / 2,189 = 0.0000021$$

The criterion for significance is an Acute Hazard Index increase of 1.0 or greater, which is detailed above in Section 9.3. Therefore, the on-going operations of the proposed project would result in a less than significant impact due to the non-cancer acute health risk from TAC emissions created by the proposed project.

Therefore, operation of the proposed project would result in a less than significant exposure of sensitive receptors to substantial pollutant concentrations.

Level of Significance

Less than significant impact.

10.5 Odor Emissions

The proposed project would not create objectionable odors affecting a substantial number of people. Individual responses to odors are highly variable and can result in a variety of effects. Generally, the impact of an odor results from a variety of factors such as frequency, duration, offensiveness, location, and sensory perception. The frequency is a measure of how often an individual is exposed to an odor in the ambient environment. The intensity refers to an individual's or group's perception of the odor strength or concentration. The duration of an odor refers to the elapsed time over which an odor is experienced. The offensiveness of the odor is the subjective rating of the pleasantness or unpleasantness of an odor. The location accounts for the type of area in which a potentially affected person lives, works, or visits; the type of activity in which he or she is engaged; and the sensitivity of the impacted receptor.

Sensory perception has four major components: detectability, intensity, character, and hedonic tone. The detection (or threshold) of an odor is based on a panel of responses to the odor. There are two types of thresholds: the odor detection threshold and the recognition threshold. The detection threshold is the lowest concentration of an odor that will elicit a response in a percentage of the people that live and work in the immediate vicinity of the project site and is typically presented as the mean (or 50 percent of the population). The recognition threshold is the minimum concentration that is recognized as having a characteristic odor quality, this is typically represented by recognition by 50 percent of the population. The intensity refers to the perceived strength of the odor. The odor character is what the substance smells like. The hedonic tone is a judgment of the pleasantness or unpleasantness of the odor. The hedonic tone varies in subjective experience, frequency, odor character, odor intensity, and duration. Potential odor impacts have been analyzed separately for construction and operations below.

Construction-Related Odor Impacts

Potential sources that may emit odors during construction activities include the application of coatings such as asphalt pavement, paints and solvents and from emissions from diesel equipment. Standard construction requirements that limit the time of day when construction may occur as well as SCAQMD Rule 1108 that limits VOC content in asphalt and Rule 1113 that limits the VOC content in paints and solvents would minimize odor impacts from construction. As such, the objectionable odors that may be produced during the construction process would be temporary and would not likely be noticeable for extended periods of time beyond the project site's boundaries. Through compliance with the applicable regulations that reduce odors and due to the transitory nature of construction odors, a less than significant odor impact would occur and no mitigation would be required.

Operations-Related Odor Impacts

The proposed project would consist of the development of a warehouse. Operation of the proposed project may create odors from diesel truck emissions, and from trash storage bins. Pursuant to County regulations, permanent trash enclosures that protect trash bins from rain as well as limit air circulation would be required for the trash storage areas. Diesel truck emissions odors would be generated intermittently from truck loading and unloading activities at the project site and would not likely be noticeable for extended periods of time beyond the project site boundaries. Due to the distance of the nearest receptors from the project site and through compliance with SCAQMD's Rule 402 and County trash storage regulations, no significant impact related to odors would occur during the on-going

operations of the proposed project. Therefore, a less than significant odor impact would occur and no mitigation would be required.

Level of Significance

Less than significant impact

10.6 Energy Consumption

The proposed project would impact energy resources during construction and operation. Energy resources that would be potentially impacted include electricity, natural gas, and petroleum based fuel supplies and distribution systems. This analysis includes a discussion of the potential energy impacts of the proposed projects, with particular emphasis on avoiding or reducing inefficient, wasteful, and unnecessary consumption of energy. A general definition of each of these energy resources are provided below.

Electricity, a consumptive utility, is a man-made resource. The production of electricity requires the consumption or conversion of energy resources, including water, wind, oil, gas, coal, solar, geothermal, and nuclear resources, into energy. The delivery of electricity involves a number of system components, including substations and transformers that lower transmission line power (voltage) to a level appropriate for on-site distribution and use. The electricity generated is distributed through a network of transmission and distribution lines commonly called a power grid. Conveyance of electricity through transmission lines is typically responsive to market demands. In 2019, Southern California Edison, who provides electricity to the project vicinity provided 80,913 Gigawatt-hours per year of electricity⁴.

Natural gas is a combustible mixture of simple hydrocarbon compounds (primarily methane) that is used as a fuel source. Natural gas consumed in California is obtained from naturally occurring reservoirs, mainly located outside the State, and delivered through high-pressure transmission pipelines. The natural gas transportation system is a nationwide network and, therefore, resource availability is typically not an issue. Natural gas satisfies almost one-third of the State's total energy requirements and is used in electricity generation, space heating, cooking, water heating, industrial processes, and as a transportation fuel. Natural gas is measured in terms of cubic feet. In 2019, San Bernardino County consumed 547.27 Million Therms of natural gas⁵.

Petroleum-based fuels currently account for a majority of the California's transportation energy sources and primarily consist of diesel and gasoline types of fuels. However, the state has been working on developing strategies to reduce petroleum use. Over the last decade California has implemented several policies, rules, and regulations to improve vehicle efficiency, increase the development and use of alternative fuels, reduce air pollutants and GHG emissions from the transportation sector, and reduce vehicle miles traveled (VMT). Accordingly, petroleum-based fuel consumption in California has declined. In 2017, 993 million gallons of gasoline and 265 million gallons of diesel was sold in San Bernardino County⁶.

⁴ Obtained from: http://www.ecdms.energy.ca.gov/elecbyutil.aspx
5 Obtained from: http://www.ecdms.energy.ca.gov/elecbyutil.aspx

⁶ Obtained from: https://ww2.energy.ca.gov/almanac/transportation-data/gasoline/

The following section calculates the potential energy consumption associated with the construction and operations of the proposed project and provides a determination if any energy utilized by the proposed project is wasteful, inefficient, or unnecessary consumption of energy resources.

Construction Energy

The construction activities for the proposed project are anticipated to include demolition of the existing structures and parking lots on the project sit, site preparation and grading of the 13.23 acre project site, building construction of the warehouse, paving of the truck loading area, driveways, and parking lots, and application of architectural coatings. The proposed project would consume energy resources during construction in three (3) general forms:

- 1. Petroleum-based fuels used to power off-road construction vehicles and equipment on the project site, construction worker travel to and from the project site, as well as delivery and haul truck trips (e.g. hauling of material to disposal facilities);
- Electricity associated with the conveyance of water that would be used during project construction for dust control (supply and conveyance) and electricity to power any necessary lighting during construction, electronic equipment, or other construction activities necessitating electrical power; and,
- 3. Energy used in the production of construction materials, such as asphalt, steel, concrete, pipes, and manufactured or processed materials such as lumber and glass.

Construction-Related Electricity

During construction the proposed project would consume electricity to construct the proposed warehouse and infrastructure. Electricity would be supplied to the project site by Southern California Edison and would be obtained from the existing electrical lines in the vicinity of the project site. The use of electricity from existing power lines rather than temporary diesel or gasoline powered generators would minimize impacts on fuel consumption. Electricity consumed during project construction would vary throughout the construction period based on the construction activities being performed. Various construction activities include electricity associated with the conveyance of water that would be used during project construction for dust control (supply and conveyance) and electricity to power any necessary lighting during construction, electronic equipment, or other construction activities necessitating electrical power. Such electricity demand would be temporary, nominal, and would cease upon the completion of construction. Overall, construction activities associated with the proposed project would require limited electricity consumption that would not be expected to have an adverse impact on available electricity supplies and infrastructure. Therefore, the use of electricity during project construction would not be wasteful, inefficient, or unnecessary.

Since there are currently power lines in the vicinity of the project site, it is anticipated that only nominal improvements would be required to Southern California Edison distribution lines and equipment with development of the proposed project. Compliance with County's guidelines and requirements would ensure that the proposed project fulfills its responsibilities relative to infrastructure installation, coordinates any electrical infrastructure removals or relocations, and limits any impacts associated with construction of the project. Construction of the project's electrical infrastructure is not anticipated to adversely affect the electrical infrastructure serving the surrounding uses or utility system capacity.

Construction-Related Natural Gas

Construction of the proposed project typically would not involve the consumption of natural gas. Natural gas would not be supplied to support construction activities, thus there would be no demand generated by construction. Since the project site is currently has natural gas service in the vicinity of the project site, construction of the proposed project would be limited to installation of new natural gas connections within the project site. Development of the proposed project would likely not require extensive infrastructure improvements to serve the project site. Construction-related energy usage impacts associated with the installation of natural gas connections are expected to be confined to trenching in order to place the lines below surface. In addition, prior to ground disturbance, the proposed project would notify and coordinate with SoCal Gas to identify the locations and depth of all existing gas lines and avoid disruption of gas service. Therefore, construction-related impacts to natural gas supply and infrastructure would be less than significant.

Construction-Related Petroleum Fuel Use

Petroleum-based fuel usage represents the highest amount of transportation energy potentially consumed during construction, which would be utilized by both off-road equipment operating on the project site and on-road automobiles transporting workers to and from the project site and on-road trucks transporting equipment and supplies to the project site.

The off-road construction equipment fuel usage was calculated through use of the off-road equipment assumptions and fuel use assumptions shown above in Section 8.2, which found that the off-road equipment utilized during construction of the proposed project would consume 71,940 gallons of fuel. The on-road construction trips fuel usage was calculated through use of the construction vehicle trip assumptions and fuel use assumptions shown above in Section 8.2, which found that the on-road trips generated from construction of the proposed project would consume 60,987 gallons of fuel. As such, the combined fuel used from off-road construction equipment and on-road construction trips for the proposed project would result in the consumption of 132,926 gallons of petroleum fuel. This equates to 0.01 percent of the gasoline and diesel consumed annually in San Bernardino County. As such, the construction-related petroleum use would be nominal, when compared to current county-wide petroleum usage rates.

Construction activities associated with the proposed project would be required to adhere to all State and SCAQMD regulations for off-road equipment and on-road trucks, which provide minimum fuel efficiency standards. As such, construction activities for the proposed project would not result in the wasteful, inefficient, and unnecessary consumption of energy resources. Impacts regarding transportation energy would be less than significant. Development of the project would not result in the need to manufacture construction materials or create new building material facilities specifically to supply the proposed project. It is difficult to measure the energy used in the production of construction materials such as asphalt, steel, and concrete, it is reasonable to assume that the production of building materials such as concrete, steel, etc., would employ all reasonable energy conservation practices in the interest of minimizing the cost of doing business.

Operational Energy

The on-going operation of the proposed project would require the use of energy resources for multiple purposes including, but not limited to, heating/ventilating/air conditioning (HVAC), refrigeration, lighting,

appliances, and electronics. Energy would also be consumed during operations related to water usage, solid waste disposal, landscape equipment and vehicle trips.

Operations-Related Electricity

Operation of the proposed project would result in consumption of electricity at the project site. As detailed above in Section 8.3 the proposed project would consume 682,647 kilowatt-hours per year of electricity. This equates to 0.0008 percent of the electricity consumed annually by Southern California Edison. As such, the operations-related electricity use would be nominal, when compared to current electricity usage rates in the Southern California Edison service area.

It should be noted that, the proposed project would comply with all Federal, State, and County requirements related to the consumption of electricity, that includes CCR Title 24, Part 6 *Building Energy Efficiency Standards* and CCR Title 24, Part 11: *California Green Building Standards*. The CCR Title 24, Part 6 and Part 11 standards require numerous energy efficiency measures to be incorporated into the proposed warehouse, including enhanced insulation, use of energy efficient lighting and appliances as well as requiring a variety of other energy-efficiency measures to be incorporated into the proposed structures. Therefore, it is anticipated the proposed project will be designed and built to minimize electricity use and that existing and planned electricity capacity and electricity supplies would be sufficient to support the proposed project's electricity demand. Thus, the project would not result in the wasteful or inefficient use of electricity and no mitigation measures would be required.

Operations-Related Natural Gas

Operation of the proposed project would result in increased consumption of natural gas at the project site. As detailed above in Section 8.3 the proposed project would consume 522 MBTU per year of natural gas. This equates to 0.00095 percent of the natural gas consumed annually in San Bernardino County. As such, the operations-related natural gas use would be nominal, when compared to current natural gas usage rates in the County.

It should be noted that, the proposed project would comply with all Federal, State, and County requirements related to the consumption of natural gas, that includes CCR Title 24, Part 6 *Building Energy Efficiency Standards* and CCR Title 24, Part 11: *California Green Building Standards*. The CCR Title 24, Part 6 and Part 11 standards require numerous energy efficiency measures to be incorporated into the proposed warehouse, including enhanced insulation as well as use of efficient natural gas appliances and HVAC units. Therefore, it is anticipated the proposed project will be designed and built to minimize natural gas use and that existing and planned natural gas capacity and natural gas supplies would be sufficient to support the proposed project's natural gas demand. Thus, impacts with regard to natural gas supply and infrastructure capacity would be less than significant and no mitigation measures would be required

Operations-Related Vehicular Petroleum Fuel Usage

Operation of the proposed project would result in increased consumption of petroleum-based fuels related to vehicular travel to and from the project site. As detailed above in Section 8.2 the proposed project would consume 183,256 gallons of petroleum fuel per year from vehicle travel. This equates to 0.01 percent of the gasoline and diesel consumed annually in San Bernardino County. As such, the operations-related petroleum use would be nominal, when compared to current county-wide petroleum usage rates. Therefore, it is anticipated the proposed project will be designed and built to minimize

transportation energy and it is anticipated that existing and planned capacity and supplies of transportation fuels would be sufficient to support the proposed project's demand. Thus, impacts with regard transportation energy supply and infrastructure capacity would be less than significant and no mitigation measures would be required.

In conclusion, the proposed project would comply with regulatory compliance measures outlined by the State and County related to Air Quality, GHG emissions, Transportation/Circulation, and Water Supply. Additionally, the proposed project would be constructed in accordance with all applicable County Building and Fire Codes. Therefore, the proposed project would not result in the wasteful, inefficient, or unnecessary consumption of energy resources during project construction or operation. Impacts would be less than significant.

Level of Significance

Less than significant impact.

10.7 Energy Plan Consistency

The proposed project would not conflict with or obstruct a state or local plan for renewable energy or energy efficiency. The applicable energy plan for the proposed project is the *County of San Bernardino General Plan Renewable Energy and Conservation Element*, Amended February 2019. The proposed project's consistency with the applicable energy-related policies in the General Plan are shown in Table Z.

Table Z – Proposed Project Compliance with Applicable General Plan Energy Policies

Policy No.	General Plan Policy	Proposed Project Implementation Actions
1.4	Encourage residents and businesses to conserve energy.	Consistent. The proposed warehouse will be designed to meet the 2019 Title 24 Part 6 building standards that require enhanced insulation in order to reduce energy usage that will conserve energy.
2.1	Support solar energy generation, solar water heating, wind energy and bioenergy systems that are consistent with the orientation, siting and environmental compatibility policies of the General Plan.	Consistent. The proposed structures will be designed to meet the 2019 Title 24 Part 6 building standards that require all new non-residential structures to be designed to be solar ready.
2.2	Promote use of energy storage technologies that are appropriate for the character of the proposed location.	Consistent. The proposed structures will be designed to meet the 2019 Title 24 Part 6 building standards that require the electrical system in non-residential buildings to be designed to handle future solar PV systems and battery storage systems.
2.3	Encourage the use of feasible emerging and experimental renewable energy technologies that are compatible with County regulatory standards.	Consistent. The proposed structures will be designed to meet the 2019 Title 24 Part 6 building standards that require the electrical system in non-residential buildings to be designed to handle future renewable energy technologies.
2.6	Encourage energy efficiency through appropriate renewable energy systems.	Consistent. The proposed structures will be designed to meet the 2019 Title 24 Part 6 building standards that require the electrical system in non-residential buildings to be designed to handle future solar PV systems and battery storage systems.

Policy		
No.	General Plan Policy	Proposed Project Implementation Actions
3.1	Prioritize, facilitate, and encourage onsite accessory RE generation to serve the unincorporated county, with a primary focus on rooftop and parking lot solar energy generation.	Consistent. The proposed structures will be designed to meet the 2019 Title 24 Part 6 building standards that require the electrical system in non-residential buildings to be designed to handle future solar PV systems and battery storage systems.

Source: County of San Bernardino, 2019.

As shown in Table Z, the proposed project would be consistent with all applicable energy-related policies from the General Plan. Therefore, the proposed project would not conflict with or obstruct a state or local plan for renewable energy or energy efficiency. Impacts would be less than significant.

Level of Significance

Less than significant impact.

10.8 Generation of Greenhouse Gas Emissions

The proposed project would not generate GHG emissions, either directly or indirectly, that may have a significant impact on the environment. The proposed project would consist of the development of a warehouse. The proposed project is anticipated to generate GHG emissions from area sources, energy usage, mobile sources, waste disposal, water usage, and construction equipment. The project's GHG emissions have been calculated with the CalEEMod model based on the construction and operational parameters detailed in Section 7.1 above. A summary of the results is shown below in Table AA and the CalEEMod model run annual printouts are provided in Appendix F.

Table AA – Project Related Greenhouse Gas Annual Emissions

	Greenhou	se Gas Emissions (Metric Tons per	Year)
Category	CO ₂	CH ₄	N ₂ O	CO₂e
Area Sources ¹	0.01	<0.00	<0.00	0.01
Energy Usage ²	148.90	0.01	<0.00	149.69
Mobile Sources ³	1,654.10	0.06	0.22	1,719.70
Off-Road Equipment ⁴	79.82	0.03	<0.00	80.46
Solid Waste ⁵	24.76	1.46	<0.00	61.33
Water and Wastewater ⁶	133.02	1.66	0.04	186.49
Construction ⁷	39.31	0.01	<0.00	39.89
Total Emissions	2,079.90	3.22	0.26	2,237.56
County of San Bernardino GHG Emi	ssions Reduction Plan Scree	ening Threshold		3,000
Exceed Screening Threshold?				No

Notes:

¹ Area sources consist of GHG emissions from consumer products, architectural coatings, and landscaping equipment.

² Energy usage consists of GHG emissions from electricity and natural gas usage.

³ Mobile sources consist of GHG emissions from vehicles.

⁴ Off-road equipment consists of emissions from forklifts utilized onsite (Project Design Feature 1 requires all off-road equipment to be non-diesel-powered).

⁵ Waste includes the CO₂ and CH₄ emissions created from the solid waste placed in landfills.

⁶ Water includes GHG emissions from electricity used for transport of water and processing of wastewater.

⁷ Construction emissions amortized over 30 years as recommended in the SCAQMD GHG Working Group on November 19, 2009. Source: CalEEMod Version 2020.4.0.

The data provided in Table AA shows that the proposed project would create 2,237.56 MTCO₂e per year. The County's GHG Emission Reduction Plan, small projects that do not exceed 3,000 MTCO₂e per year will considered to be consistent with the Plan and determined to have a less than significant individual and cumulative impact for GHG emissions. Since the proposed project's GHG emissions are below the County's screening threshold, the proposed project would not create a significant cumulative impact from GHG emissions. Impacts would be less than significant.

Level of Significance

Less than significant impact.

10.9 Greenhouse Gas Plan Consistency

The proposed project would not conflict with any applicable plan, policy or regulation of an agency adopted for the purpose of reducing GHG emissions. The applicable plan for the proposed project is the *County of San Bernardino Greenhouse Gas Emissions Reduction Plan* (GHG Plan), September 2011. In addition, the *Greenhouse Gas Emissions Development Review Processes* (GHG Review Processes), prepared for the County of San Bernardino, updated March 2015, provide direction for conformity of new development projects to the GHG Plan. The GHG Review Processes determined that projects that do not exceed 3,000 MTCO₂e per year will be consistent with the GHG Plan and determined to have a less than significant individual and cumulative impact for GHG emissions. For projects that exceed 3,000 MTCO₂e per year of GHG emissions, the GHG Review Processes has determined that implementation of 100 or greater points associated with mitigation measures listed on its Screen Tables, will adequately reduce the proposed project's GHG emissions, when considered with other future development and existing development to allow the County to meet its 2020 target GHG reductions and support reductions in GHG emissions beyond 2020.

As shown in Section 9.6 above, the proposed project would create 2,237.56 MTCO₂e per year, which is well below the 3,000 MTCO₂e per year threshold provided in the GHG Review Processes. Therefore, the proposed project would not conflict with any applicable plan, policy, or regulation of an agency adopted for the purpose of reducing the emissions of greenhouse gases. Impacts would be less than significant.

Level of Significance

Less than significant impact.

11.0 REFERENCES

Breeze Software, California Emissions Estimator Model (CalEEMod) version 2020.4.0.

California Air Resources Board, 2017 Off-Road Diesel Emission Factor Update for NOx and PM, 2017.

California Air Resources Board, Appendix VII Risk Characterization Scenarios, October 2000.

California Air Resources Board, California's 2017 Climate Change Scoping Plan, November 2017.

California Air Resources Board, First Update to the Climate Change Scoping Plan, May 2014.

California Air Resources Board, Resolution 08-43, December 12, 2008.

California Air Resources Board, *Recommended Approaches for Setting Interim Significance Thresholds for Greenhouse Gases under the California Environmental Quality Act*, on October 24, 2008.

California Air Resources Board, Final Staff Report Proposed Update to the SB 375 Greenhouse Gas Emission Reduction Targets, October 2017.

California Air Resources Board, The California Almanac of Emissions and Air Quality 2013 Edition.

California Department of Conservation, A General Guide for Ultramafic Rocks in California – Areas More Likely to Contain Naturally Occurring Asbestos, August, 2000.

California Energy Commission, 2019 Building Energy Efficiency Standards Frequently Asked Questions, 2018.

County of San Bernardino, County of San Bernardino General Plan Renewable Energy and Conservation Element, Amended February 2019.

County of San Bernardino, Bloomington Community Plan, April 12, 2007.

County of San Bernardino, County of San Bernardino Greenhouse Gas Emissions Reduction Plan, September, 2011.

County of San Bernardino, *Greenhouse Gas Emissions Development Review Processes County of San Bernardino, California*, March 2015.

Environmental Protection Agency, Nonattainment Major New Source Review Implementation Under 8-Hour Ozone National Ambient Air Quality Standard: Reconsideration, June 30, 2005.

Environmental Protection Agency, *Inventory of U.S. Greenhouse Gas Emissions and Sinks 1990-2018*, April 13, 2020.

EPD Solutions, Inc., Alder Avenue / Slover Avenue Industrial Project Trip Generation and Vehicle Miles Traveled (VMT) Screening Analysis, November 18, 2021.

International Code Council, *Guide to the 2016 California Green Building Standards Code Nonresidential,* January 2017.

Office of Environmental Health Hazard Assessment (OEHHA), Air Toxics Hot Spots Program Risk Assessment Guidelines Guidance Manual for Preparation of Health Risk Assessments, February 2015

South Coast Air Quality Management District, 2007 Air Quality Management Plan, June 1, 2007.

South Coast Air Quality Management District, *Appendix A Calculation Details for CalEEMod*, February 2011.

South Coast Air Quality Management District, CEQA Air Quality Handbook, April 1993.

South Coast Air Quality Management District, Final 2012 Air Quality Management Plan, December, 2012.

South Coast Air Quality Management District, Final 2016 Air Quality Management Plan, March, 2017.

South Coast Air Quality Management District, *Final Localized Significance Threshold Methodology*, Revised July 2008.

South Coast Air Quality Management District, Revised Draft – 2012 Lead State Implementation Plan Los Angeles County, May 4, 2012.

South Coast Air Quality Management District, Rule 402 Nuisance, Adopted May 7, 1976.

South Coast Air Quality Management District, Rule 403 Fugitive Dust, Amended June 3, 2005.

South Coast Air Quality Management District, Rule 1108 Cutback Asphalt, Amended February 1, 1985.

South Coast Air Quality Management District, *Rule 1108.1 Emulsified Asphalt*, Amended November 4, 1983.

South Coast Air Quality Management District, *Rule 1113 Architectural Coatings*, Amended September 6, 2013.

South Coast Air Quality Management District, *Rule 1143 Consumer Paint Thinners & Multi-Purpose Solvents*, Amended December 3, 2010.

South Coast Air Quality Management District, *Rule 1403 Asbestos Emissions from Demolition/ Renovation Activities*, Amended October 5, 2007.

South Coast Air Quality Management District, SCAQMD Air Quality Significance Thresholds, March 2015.

South Coast Air Quality Management District, *Draft Report Multiple Air Toxics Exposure Study in the South Coast Air Basin, MATES III*, January 2008.

South Coast Air Quality Management District, *Draft Report Multiple Air Toxics Exposure Study in the South Coast Air Basin, MATES-IV*, October 2014.

Southern California Association of Governments, 2020-2045 Regional Transportation Plan/Sustainable Communities Strategy (Connect SoCal), September 3, 2020.

Southern California Association of Governments, 2019 Federal Transportation Improvement Program (FTIP) Guidelines, September 2018.

University of California, Davis, Transportation Project-Level Carbon Monoxide Protocol, December 1997.

U.S. Geological Survey, *Reported Historic Asbestos Mines, Historic Asbestos Prospects, and Other Natural Occurrences of Asbestos in California*, 2011.

APPENDIX A

CalEEMod Model Daily Printouts

CalEEMod Version: CalEEMod.2020.4.0

Page 1 of 28

Date: 2/7/2022 2:16 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Slover-Alder Avenue Industrial

San Bernardino-South Coast County, Summer

1.0 Project Characteristics

1.1 Land Usage

Land Uses	Size	Metric	Lot Acreage	Floor Surface Area	Population
Unrefrigerated Warehouse-No Rail		1000sqft	7.94	259,481.00	0
Parking Lot 5.29		Acre 5.29 230,432.40 0	5.29	230,432.40	0

1.2 Other Project Characteristics

Urbanization	Urban	Wind Speed (m/s)	2.2	Precipitation Freq (Days)	32
Climate Zone	10			Operational Year	2023
Utility Company	Southern California Edison				
CO2 Intensity (Ib/MWhr)	390.98	CH4 Intensity (Ib/MWhr)	0.033	N2O Intensity (Ib/MWhr)	0.004

1.3 User Entered Comments & Non-Default Data

Project Characteristics -

Land Use - Total Project Site = 13.23 acres

Construction Phase - Construction schedule provided by applicant

Off-road Equipment - Grading - 2 Excavators, 1 Grader, 1 Rubber Tired Dozer, 2 Scrapers, 2 Crawler Tractors

Off-road Equipment - Site Preparation - 3 Rubber Tired Dozers and 4 Crawler Tractors

Trips and VMT - 6 vendor trucks added to Demolition, Site Prep, and Grading Phases to account for water truck emissions

Demolition - 16,800 sq ft of building space = 773 tons + 117,000 sq ft of pavement = 2,828 tons

Grading -

Architectural Coating -

Vehicle Trips - Truck Trips analyzed under Parking Lot Land use and the Auto Trips analyzed under the Unrefrigerated Warehouse Land Use

Water And Wastewater -

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Solid Waste -

Construction Off-road Equipment Mitigation - Water Exposed Area 3x per day selected to account for SCAQMD Rule 403 minimum requirements Mobile Land Use Mitigation - Improve Pedestrian Network on Project Site and Connecting Offsite and 0.06 mile to nearest Transit Station

Energy Mitigation

Water Mitigation - Install Low-Flow fixtures and use water-efficient Irrigation Systems selected to account for Title 24 Part 11 requirements

Waste Mitigation - 50% reduction in solid waste selected to account for AB 341

Operational Off-Road Equipment - 4 Forklifts 7 hours per day. Per PDF 1, analyzed as CNG fuel

Fleet Mix - Vehicle Mix set to match Trip Generation Memo

New Value	129688	389064	130.00	130.00	09:0	00:00	00:00	0.58	0.00	0.06	0.00	0.19	0.00	0.00	0.22	0.00	0.00	0.03	0.00
Default Value	129741	389222	20.00	20.00	0.02	0.02	0.54	0.54	0.06	0.06	0.17	0.17	0.03	0.03	7.1960e-003	7.1960e-003	0.03	0.03	0.14
Column Name	Area_Nonresidential_Exterior	Area_Nonresidential_Interior	NumDays	NumDays	문	묲	LDA	LDA	LDT1	LDT1	LDT2	LDT2	LHD1	LHD1	LHD2	LHD2	MCY	MCY	MDV
Table Name	tblAreaCoating	tblAreaCoating	tblConstructionPhase	tblConstructionPhase	tblFleetMix														

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

0.15	0.00	0.00	0.18	0.00	0.00	0.00	0.00	0.00	0.00	0.00	259,481.00	7.94	CNG	7.00	4.00	6.00	6.00	6.00	40.00	100.00	100.00	21.36	76.0	21.36	0.97	21.36	0.97
0.14	5.0710e-003	5.0710e-003	0.01	0.01	5.5900e-004	5.5900e-004	9.5400e-004	9.5400e-004	2.5400e-004	2.5400e-004	259,480.00	5.96	Diesel	8.00	0.00	0.00	0.00	0.00	8.40	0.00	0.00	0.00	1.74	0.00	1.74	0.00	1.74
MDV	MH	TW TW	QHW	MHD	OBUS	OBUS	SBUS	SBUS	UBUS	UBUS	LandUseSquareFeet	LotAcreage	OperFuelType	OperHoursPerDay	OperOffRoadEquipmentNumber	VendorTripNumber	VendorTripNumber	VendorTripNumber		CC_TTP	PR_TP	ST_TR	ST_TR	SU_TR	SU_TR	WD_TR	WD_TR
tblFleetMix	tblLandUse	tblLandUse	tblOperationalOffRoadEquipment	tblOperationalOffRoadEquipment	tblOperationalOffRoadEquipment	tblTripsAndVMT	tblTripsAndVMT	tbITripsAndVMT	tblVehicleTrips	tblVehicleTrips	tbIVehicleTrips	tblVehicleTrips	tblVehicleTrips	tbIVehicleTrips	tblVehicleTrips	tblVehicleTrips	tbIVehicleTrips										

Date: 2/7/2022 2:16 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

2.0 Emissions Summary

2.1 Overall Construction (Maximum Daily Emission)

Unmitigated Construction

	ROG	×ON	00	S02	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Bio- CO2 NBio- CO2 Total CO2	CH4	N20	CO2e
Year					lb/day	day							lb/day	ay		
2022	4.5657 50.7234 30.1156 0.0747 22.0177	50.7234	30.1156	0.0747	22.0177		24.1808	10.3959	2.1631 24.1808 10.3959 1.9902	12.3861 0.0000 7,256.952 7,256.952 2.2490 0.2907 7,320.028		7,256.952 2	7,256.952 2	2.2490	0.2907	7,320.028 5
2023	23.0179 29.3038 43.6971 0.0932 3.441	29.3038	43.6971	0.0932	3.4411	1.3163	4.7574	0.9243	1.2321	1.3163 4.7574 0.9243 1.2321 2.1564		9,256.359 1	0.0000 9,256.359 9,256.359 1.4427 0.2897 9,378.749	1.4427	0.2897	9,378.749 7
Maximum	23.0179	23.0179 50.7234 43.6971 0.0932 22.0177	43.6971	0.0932		2.1631	24.1808	10.3959	1.9902	12.3861	0.0000	9,256.359	0.0000 9,256.359 9,256.359 2.2490	2.2490	0.2907 9,378.749	9,378.749 7

Mitigated Construction

ROG	XON	00	S02	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Bio- CO2 NBio- CO2 Total CO2 CH4	CH4	N20	CO2e
				5/qI	b/day							Ib/day	ay		
4.5657	, 50.7234	4.5657 50.7234 30.1156 0.0747 8.7331	0.0747	8.7331	2.1631	2.1631 10.8962	4.0937 1.9902		6.0839	0.000.0	7,256.952 2	0.0000 7,256.952 7,256.952 2.2490 0.2907 7,320.028	2.2490	0.2907	7,320.028 5
23.017	9 29.3038	23.0179 29.3038 43.6971 0.0932 3.4411	0.0932	3.4411	1.3163	4.7574	0.9243	1.2321	2.1564	0.0000	9,256.359 9,256	0.0000 9,256.359 9,256.359 1.4427	1.4427	0.2897	9,378.749 7
23.017	9 50.7234	23.0179 50.7234 43.6971 0.0932 8.7331	0.0932	8.7331	2.1631	10.8962	4.0937	1.9902	6:0839	0.000.0	9,256.359 1	0.0000 9,256.359 9,256.359	2.2490	0.2907 9,378.749	9,378.749 7

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

Date: 2/7/2022 2:16 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

C02e	00'0
N20	00'0
СН4	00'0
Total CO2	00.0
Bio- CO2 NBio-CO2 Total CO2	00.0
Bio- CO2	00'0
PM2.5 Total	43.34
Exhaust PM2.5	00:0
Fugitive PM2.5	29:62
PM10 Total	45.91
Exhaust PM10	00'0
Fugitive PM10	52.18
S02	00'0
00	00'0
NOX	00'0
ROG	0.00
	Percent Reduction

2.2 Overall Operational

Unmitigated Operational

CO2e		0.0618	169.1076	13,805.77 29	682.2526	14,657.19 48					
N20			3.0800e- 003	1.6962		1.6993					
CH4	ip/day	lb/day	lb/day	lb/day	lb/day	lb/day	1.5000e- 004	3.2200e- 003	0.4703	0.2189	0.6926
Total CO2							0.0580	168.1086 168.1086	13,288.54 56	676.7805	14,133.49 25
NBio- CO2		0.0580	168.1086	13,288.54 13,288.54 56 56	676.7805 676.7805	0.0000 14,133.49 14,133.49 25 25					
Bio- CO2 NBio- CO2 Total CO2					0.0000	0.000.0					
PM2.5 Total		1.0000e- 004	0.0107	1.9339	0.0400	1.9847					
Exhaust PM2.5				1.0000e- 004	0.0107	0.2011	0.0400	0.2519			
Fugitive PM2.5				1.7328		1.7328					
PM10 Total		1.0000e- 004	0.0107	6.4967	0.0400	6.5475					
Exhaust PM10	lb/day	1.0000e- 004	0.0107	0.2106	0.0400	0.2614					
Fugitive PM10		o/ql			6.2861		6.2861				
SO2		0.0000	8.4000e- 004	0.1244	5.3500e- 003	0.1306					
00		0.0270	0.1177	15.5487	32.4407 5.3500e- 003	48.1341					
×ON		5.8982 2.5000e- 0.0270 0.0000 004	0.1401	18.9848	2.4827	7.3511 21.6078 48.1341 0.1306					
ROG		5.8982	0.0154	1.3866	0.0510	7.3511					
	Category	Area	Energy	Mobile	Offroad	Total					

Page 6 of 28

Date: 2/7/2022 2:16 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

2.2 Overall Operational

Mitigated Operational

				' ~	٠								
CO2e		0.0618	169.1076	10,538.68 67	682.2526	11,390.10 86							
N20			3.0800e- 003	1.2989		1.3020							
CH4	ay	1.5000e- 004	3.2200e- 003	0.3656	0.2189	0.5879							
Total CO2	p/qI	lb/day	p/qI	p/qI	p/qI	p/qI	p/qI	0.0580	68.1086	10,142.47 30	676.7805	10,987.42 00	
Bio- CO2 NBio- CO2 Total CO2		0.0580	168.1086	10,142.47 10 30	676.7805	10,987.42 00							
Bio- CO2					0.0000	0.000.0							
PM2.5 Total		1.0000e- 004	0.0107	1.4676	0.0400	1.5184							
Exhaust PM2.5		1.0000e- 004	0.0107	0.1529	0.0400	0.2037							
Fugitive PM2.5										r 	1.3147		1.3147
PM10 Total		1.0000e- 004	0.0107	4.9296	0.0400	4.9804							
Exhaust PM10	łay	lb/day	1.0000e- 004	0.0107	0.1602	0.0400	0.2110						
Fugitive PM10	o/qı			4.7694	 	4.7694							
S02		0.000.0	8.4000e- 004	0.0950	5.3500e- 003	0.1012							
00		0.0270	0.1177	12.4149	32.4407	45.0003							
NOx				2.5000e- 0.0270 0.0000 004	0.1401	14.7889 12.4149	2.4827	17.4119					
ROG		5.8982	0.0154	1.2026	0.0510	7.1671							
	Category	Area	Energy	Mobile	Offroad	Total							

C02e	22.29
N20	23.38
CH4	15.12
Total CO2	22.26
Bio- CO2 NBio-CO2 Total CO2	22.26
Bio- CO2	0.00
PM2.5 Total	23.49
Exhaust PM2.5	19.12
Fugitive PM2.5	24.13
PM10 Total	23.93
Exhaust PM10	19.29
Fugitive PM10	24.13
802	22.55
03	6.51
NOX	19.42
ROG	2.50
	Percent Reduction

3.0 Construction Detail

Construction Phase

Phase Number	Phase Name	Phase Type	Start Date	End Date	Num Days Num Days Week	Num Days	Phase Description
	Demolition	Demolition	3/1/2022	3/28/2022	5	20	
	ıration	Site Preparation	3/29/2022	4/11/2022	5		
1	Grading	Grading	4/12/2022	5/23/2022	5	30	
	Building Construction	Building Construction	5/24/2022	7/17/2023	5	5 300	

Date: 2/7/2022 2:16 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

5	5 Paving 1/17/2023 7/17/2023 5 130	Paving	1/17/2023	7/17/2023	9	130	
9	Architectural Coating	Architectural Coating	1/17/2023	7/17/2023	5	130	

Acres of Grading (Site Preparation Phase): 35

Acres of Grading (Grading Phase): 120

Acres of Paving: 5.29

Residential Indoor: 0; Residential Outdoor: 0; Non-Residential Indoor: 389,222; Non-Residential Outdoor: 129,741; Striped Parking Area: 13,826 (Architectural Coating – sqft)

OffRoad Equipment

Phase Name	Offroad Equipment Type	Amount	Usage Hours	Horse Power	Load Factor
Demolition	Concrete/Industrial Saws	<u></u>	8.00	81	0.73
Demolition	Excavators	ε : : : : : : : : : : : : : : : : : : :	8.00	158	0.38
Demolition	Rubber Tired Dozers	2	8.00	247	0.40
Site Preparation	Crawler Tractors	4	8.00	212	0.43
Site Preparation	Rubber Tired Dozers	ε :	8.00	247	0.40
Grading	Crawler Tractors	2	8.00	212	0.43
	Excavators	2	8.00	158	0.38
	Graders		8.00	187	0.41
Grading	Rubber Tired Dozers		8.00	247	0.40
Grading	Scrapers	2	8.00	367	0.48
	Cranes	 	7.00	231	0.29
Building Construction	Forklifts	С	8.00	68	0.20
Building Construction	Generator Sets	 	8.00	84	0.74
	Tractors/Loaders/Backhoes	C	7.00	26	0.37
Building Construction	Welders		8.00	46	0.45
Paving	Pavers	2	8.00	130	0.42
Paving	Paving Equipment	2	8.00	132	0.36
Paving	Rollers	2	8.00	80	0.38

Page 8 of 28

Date: 2/7/2022 2:16 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

ule Applied	
Vehicle to Account for the SAFE Vehicle Rule Ap	0.48
ccount for the	82
ıty Vehicle to A	90.9
tment Factors for Gasoline Light Duty Ve	
f-Model Adjustment Factors	Air Compressors
EMFAC OF	Architectural Coating

Trips and VMT

Vendor Hauling /ehicle Class Vehicle Class	HDT_Mix HHDT	HDT_Mix HHDT	HDT_Mix HHDT	HDT_Mix HHDT	HDT_Mix HHDT	
Worker Vehicle Class	20.00 LD_Mix H	20.00 LD_Mix	20.00 LD_Mix	· · · · · · · · · · · · · · · · ·	20.00 LD_Mix	
Hauling Trip Length					! ! !	
Vendor Trip Length	06.9	6.90	6.90	6.90	6.90	
Worker Trip Length	14.70	14.70	14.70	14.70	14.70	
Hauling Trip Number	356.00	00.00	0.00	00.00	0.00	
Vendor Trip Number	00.9	00.9	00.9	80.00	00.0	
Worker Trip Number	15.00	18.00	20.00	206.00	15.00	. 00 44
Offroad Equipment Count	9		ω 	6	9	÷
Phase Name	Demolition	Site Preparation	Grading	Building Construction	Paving	2 ci+(0) - (1: +00+; 40 ×

3.1 Mitigation Measures Construction

Water Exposed Area

3.2 Demolition - 2022

Unmitigated Construction On-Site

CO2e		0.0000	3,773.092 0	3,773.092 0				
N20								
CH4	ay		1.0524	1.0524				
Total CO2	lb/di	lb/day	0.000.0	3,746.781 2	3,746.781 2			
Bio- CO2 NBio- CO2 Total CO2							3,746.781 3,746.781 1.0524 2 2	3,746.781 3,746.781 2 2
Bio- CO2								
PM2.5 Total		0.5832	1.1553	1.7385				
Exhaust PM2.5	lb/day	lb/day					1.1553	1.1553
Fugitive PM2.5			0.5832		0.5832			
PM10 Total				3.8518 0.5832	1.2427	5.0945		
Exhaust PM10			0.0000	1.2427	1.2427			
Fugitive PM10			3.8518		3.8518			
802			0.0388	0.0388				
00			20.5941	20.5941				
×ON				2.6392 25.7194 20.5941 0.0388	2.6392 25.7194 20.5941 0.0388			
ROG			2.6392	2.6392				
	Category	Fugitive Dust	Off-Road	Total				

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

Date: 2/7/2022 2:16 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.2 Demolition - 2022

Unmitigated Construction Off-Site

CO2e		1,195.084 2	125.4161	158.7050	1,479.205 4
N20		1,140.027 1,140.027 0.0488 0.1807 1,195.084 9 9 2	0.0178	3.9200e- 003	0.2023
CH4	lb/day	0.0488	3.2400e- 003	4.0900e- 003	0.0562
Total CO2)/q	1,140.027 9	120.0413 120.0413 3.2400e- 003	157.4352 4.0900e- 003	1,417.504 1,417.504 3 3
Bio- CO2 NBio- CO2 Total CO2		1,140.027 9	120.0413	157.4352	1,417.504 3
Bio- CO2					
PM2.5 Total		0.1099	0.0141	0.0453	0.1692
Exhaust PM2.5		0.0255 0.3372 0.0855 0.0244 0.1099	2.9900e- (003	8.1000e- 004	0.0282
Fugitive PM2.5		0.0855	0.0111	0.0445	0.1410
PM10 Total		0.3372	0.0416	0.1685	0.5473
Exhaust PM10	lb/day	0.0255	3.1300e- 003	8.8000e- 004	0.0295
Fugitive PM10)/qI	7	0.0384	0.1677	0.5178
802		0.0105	1.1200e- 003	1.5500e- 003	0.0131
00		0.6330	0.0964	0.6179	1.3473
NOX		2.4260	0.2627	0.0402	0.1413 2.7290 1.3473
ROG		0.0673 2.4260 0.6330 0.0105 0.311	0.0105	0.0635	0.1413
	Category	Hauling	Vendor	Worker	Total

Mitigated Construction On-Site

CO2e		0.0000	3,773.092 0	3,773.092 0			
N20							
CH4	ау		1.0524	1.0524			
Total CO2	lb/day	p/qI	0.000.0	3,746.781 2	3,746.781 2		
Bio- CO2 NBio- CO2 Total CO2						0.0000 3,746.781 3,746.781 1.0524 2 2	0.0000 3,746.781 3,746,781 1.0524
Bio- CO2			0.0000	0.000			
PM2.5 Total		0.2275	1.1553	1.3827			
Exhaust PM2.5	day	0.0000 1.5022 0.2275 0.0000 0.2275	1.1553	1.1553			
Fugitive PM2.5		lb/day			0.2275		0.2275
PM10 Total				1.5022	1.2427	2.7449	
Exhaust PM10			0.0000	1.2427 1.2427	1.2427		
Fugitive PM10	o/qı	1.5022		1.5022			
802			0.0388	0.0388			
00			20.5941	20.5941			
XON			25.7194 20.5941	2.6392 25.7194 20.5941 0.0388 1.5022			
ROG			2.6392	2.6392			
	Category	Fugitive Dust	Off-Road	Total			

Page 10 of 28

Date: 2/7/2022 2:16 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.2 Demolition - 2022

Mitigated Construction Off-Site

CO2e		1,140.027 1,140.027 0.0488 0.1807 1,195.084	125.4161	158.7050	1,479.205 4
N20		0.1807	0.0178	3.9200e- 003	0.2023
CH4	lb/day	0.0488	3.2400e- 003	4.0900e- 003	0.0562
Total CO2)/qI	1,140.027 9	120.0413 120.0413 3.2400e- 003	157.4352 157.4352 4.0900e- 3.9200e- 003 003	1,417.504 1,417.504 3 3
Bio- CO2 NBio- CO2 Total CO2		1,140.027 9	120.0413	157.4352	1,417.504 3
Bio- CO2		1-0-0-0-0	; ; ; ; ;		
PM2.5 Total		0.1099	0.0141	0.0453	0.1692
Exhaust PM2.5		0.0255 0.3372 0.0855 0.0244 0.1099	2.9900e- (003	8.1000e- 004	0.0282
Fugitive PM2.5		0.0855	0.0111	0.0445	0.1410
PM10 Total		0.3372	0.0416	0.1685	0.5473
Exhaust PM10	lb/day	0.0255	3.1300e- 003	8.8000e- 004	0.0295
Fugitive PM10)/q	7	0.0384	0.1677	0.5178
S02		0.0105	1.1200e- 003	9 1.5500e- C 003	0.0131
00		0.6330	0.0964	0.0402 0.6179	1.3473
NOx		2.4260	0.2627	0.0402	2.7290
ROG		0.0673 2.4260 0.6330 0.0105 0.311	0.0105 0.2627 0.0964 1.1200e-	0.0635	0.1413
	Category	Hauling	! ! !	Worker	Total

3.3 Site Preparation - 2022

Unmitigated Construction On-Site

CO2e		0.0000	5,561.845 1	5,561.845 1
NZO				
CH4	lay		1.7844	1.7844
Total CO2	lb/day	0.000.0	5,517.235 5	5,517.235 5
Bio- CO2 NBio- CO2 Total CO2			5,517.235 5,517.235 1.7844 5 5	5,517.235 5,517.235 5
Bio- CO2				
PM2.5 Total		10.3315	1.9862	12.3177
Exhaust PM2.5		0.0000 21.7780 10.3315 0.0000 10.3315	1.9862	1.9862
Fugitive PM2.5		10.3315	r	10.3315
PM10 Total		21.7780	2.1590	23.9370
Exhaust PM10	lay	0.0000	2.1590	2.1590
Fugitive PM10	lb/day	21.7780		21.7780
S02			0.0570	0.0570
00			20.0053	20.0053
×ON			50.4124	4.4790 50.4124 20.0053 0.0570 21.7780
ROG			4.4790 50.4124 20.0053	4.4790
	Category	Fugitive Dust	Off-Road	Total

Page 11 of 28 CalEEMod Version: CalEEMod.2020.4.0

Date: 2/7/2022 2:16 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Unmitigated Construction Off-Site 3.3 Site Preparation - 2022

2e		000	1161	1461	3622
CO2e		0.00	125.4161	190.4461	315.8622
NZO		0.0000	0.0178	4.7000e- 003	0.0225
CH4	ay	0.0000	3.2400e- 003	4.9100e- 003	8.1500e- 003
Total CO2	lb/day	0.0000 0.0000 0.0000 0.0000	120.0413 120.0413 3.2400e- 003	188.9222 188.9222 4.9100e-	308.9635
Bio- CO2 NBio- CO2 Total CO2		0.0000	120.0413	188.9222	308.9635
Bio- CO2					
PM2.5 Total		0.0000	0.0141	0.0543	0.0684
Exhaust PM2.5		0.0000	1 2.9900e- 003	9.7000e- 004	3.9600e- 003
Fugitive PM2.5		0.000.0	0.0111	0.0534	0.0644
PM10 Total		0.000.0	0.0416	0.2023	0.2438
Exhaust PM10	day	0.0000	3.1300e- 003	1.0600e- 003	4.1900e- 003
Fugitive PM10	lb/day	0.0000	0.0384	0.2012	0.2396
S02		0.0000	0.2627 0.0964 1.1200e-	1.8600e- 003	2.9800e- 003
00		0.0000	0.0964	0.7415	0.8380
NOX		0.0000	0.2627	0.0483	0.3110
ROG		0.0000	0.0105	0.0762	0.0867
	Category	Hauling 0.0000 0.0000 0.0000 0.0000 0.0000 0.0000 0.0000 0.0000	:	Worker	Total

Mitigated Construction On-Site

			ις	ιņ
CO2e		0.0000	5,561.845 1	5,561.845 1
N2O			-	
CH4	ay		1.7844	1.7844
Total CO2	lb/day	0.000.0	5,517.235 5	5,517.235 5
Bio- CO2 NBio- CO2 Total CO2			0.0000 5,517.235 5,517.235 1.7844 5 5	0.0000 5,517.235 5,517.235 5 5 5
Bio- CO2			0.0000	0.000.0
PM2.5 Total		4.0293	1.9862	6.0155
Exhaust PM2.5		0.0000 8.4934 4.0293 0.0000 4.0293	1.9862	1.9862
Fugitive PM2.5		4.0293		4.0293
PM10 Total		8.4934	2.1590	10.6524
Exhaust PM10	b/day	0.0000	2.1590	2.1590
Fugitive PM10	/qı	8.4934		8.4934
SO2			0.0570	0.0570
00			20.0053	20.0053
×ON			4.4790 50.4124 20.0053 0.0570	4.4790 50.4124 20.0053 0.0570 8.4934
ROG			4.4790	4.4790
	Category	Fugitive Dust	Off-Road	Total

Page 12 of 28

Date: 2/7/2022 2:16 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.3 Site Preparation - 2022 Mitigated Construction Off-Site

					01
CO2e		0.0000	125.4161	190.4461	315.8622
N20		0.0000	0.0178	э- 4.7000e- 003	0.0225
CH4	ау	0.000.0	3.2400 003	4.9100e- 003	8.1500e- 003
Total CO2	lb/day	0.0000 0.0000 0.0000 0.0000	120.0413	188.9222	308.9635
Bio- CO2 NBio- CO2 Total CO2		0.0000	120.0413 120.0413	188.9222	308.9635
Bio- CO2					
PM2.5 Total		0.0000	0.0141	0.0543	0.0684
Exhaust PM2.5			2.9900e- C 003	9.7000e- 004	3.9600e- 003
Fugitive PM2.5		0.000.0	0.0111	0.0534	0.0644
PM10 Total		0.0000 0.0000 0.0000	0.0416	0.2023	0.2438
Exhaust PM10	lb/day	0.0000	3.1300e- 003	1.0600e- 003	4.1900e- 003
Fugitive PM10	o/qı	0.000.0	0.0384	0.2012	0.2396
SO2		0.0000	1.1200e- 003	1.8600e- 003	2.9800e- 003
00		0.0000	0.0964 1.1200e- 0.0384 003	0.7415 1.8600e- 0.2012 003	0.8380
×ON		0.0000 0.0000 0.0000 0.0000	0.2627	0.0483	0.3110
ROG		0.0000	0.0105	0.0762	0.0867
	Category	Hauling	Vendor	Worker	Total

3.4 Grading - 2022
Unmitigated Construction On-Site

CO2e		0.0000	6,983.005 6	6,983.005 6
N20				
CH4	ау		2.2403	2.2403
Total CO2	lb/day	0.000.0	6,926.997 4	6,926.997 4
Bio- CO2 NBio- CO2 Total CO2			6,926.997 6,926.997 4 4	6,926.997 6,926.997 4 4
Bio- CO2				
PM2.5 Total		3.7683	1.7554	5.5237
Exhaust PM2.5		0.000.0	1.7554	1.7554
Fugitive PM2.5		0.0000 10.2641 3.7683 0.0000		3.7683
PM10 Total		10.2641	1.9081	1.9081 12.1722
Exhaust PM10	lb/day	0.0000	1.9081 1.9081	1.9081
Fugitive PM10)/q	10.2641		10.2641
			0.0715	0.0715
co soz			29.1953	29.1953
×ON			4.2792 47.5079 29.1953	47.5079 29.1953 0.0715 10.2641
ROG			4.2792	4.2792
	Category	Fugitive Dust	Off-Road	Total

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

Date: 2/7/2022 2:16 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.4 Grading - 2022

Unmitigated Construction Off-Site

	ROG	XON	00	S02	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	Bio- CO2 NBio- CO2 Total CO2	Total CO2	CH4	NZO	CO2e
Category					lb/day	lay							lb/day	ay		
Hauling	0.0000	0.0000	0.000.0	0.0000 0.0000 0.0000 0.0000		0.0000	0.000.0	0.0000	0.0000 0.0000 0.0000	0.0000		0.0000	0.0000 0.0000 0.0000 0.0000	0.000.0	0.0000	0.0000
Vendor	0.0105	0.2627	0.0964	0.2627 0.0964 1.1200e- 0.0384 003	[3.1300e- 003	0.0416	0.0111	2.9900e- 003	0.0141		120.0413	120.0413 120.0413 3.2400e- 003	3.2400e- 003	0.0178	125.4161
Worker	0.0847	0.0537	0.8239	0.8239 2.0600e- 0.2236 003	[1.1700e- 003	0.2247	0.0593	1.0800e- 003	0.0604	_	209.9136	209.9136 209.9136	5.4600e- 003	5.2200e- 003	211.6067
Total	0.0952	0.3164	0.9203	3.1800e- 003	0.2620	4.3000e- 003	0.2663	0.0704	4.0700e- 003	0.0744		329.9549	329.9549	8.7000e- 003	0.0230	337.0228

Mitigated Construction On-Site

29.1953
4.0792 47.5079 29.1953 0.0715

Page 14 of 28 CalEEMod Version: CalEEMod.2020.4.0 Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

Date: 2/7/2022 2:16 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.4 Grading - 2022

Mitigated Construction Off-Site

	ROG	×ON	00	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	Bio- CO2 NBio- CO2 Total CO2	Total CO2	CH4	N20	CO2e
Category)/qI	lb/day							lb/day	ah		
Hauling	0.0000	0.0000 0.0000 0.0000 0.0000 0.0000	0.000.0	0.0000	[0.0000 0.0000 0.0000 0.0000 0.0000	0.000.0	0.000.0	0.0000	0.0000		0.0000	0.0000 0.0000 0.0000 0.0000 0.0000	0.000.0	0.0000	0.0000
Vendor	0.0105	0.2627	0.0964	1.1200e- 003	0.0384	3.1300e- 003	0.0416	0.0111	2.9900e- 003	0.0141		120.0413	120.0413 120.0413 3.2400e- 003	3.2400e- 003	0.0178	125.4161
Worker	0.0847	0.0537	0.8239	0.8239 2.0600e- 0.2236 003	0.2236	1.1700e- 003	0.2247	0.0593	1.0800e- 003	0.0604		209.9136 209.9136	209.9136	5.4600e- 003	5.2200e- 003	211.6067
Total	0.0952	0.3164	0.9203	0.9203 3.1800e- 003	0.2620	4.3000e- 003	0.2663	0.0704	4.0700e- 003	0.0744		329.9549	329.9549	8.7000e- 003	0.0230	337.0228

3.5 Building Construction - 2022

Unmitigated Construction On-Site

CO2e		9.632 2	2,569.632 2
00		2,569.632 2	2,569
N20			
CH4	ay	0.6120	0.6120
Total CO2	lb/day	2,554.333 6	2,554.333 6
Bio- CO2 NBio- CO2 Total CO2		2,554.333 2,554.333 0.6120 6 6	2,554.333 2,554.333 0.6120 6 6
Bio- CO2			
PM2.5 Total		0.7612	0.7612
Exhaust PM2.5		0.7612 0.7612	0.7612
Fugitive PM2.5			
PM10 Total		0.8090 0.8090	0608'0
Exhaust PM10	day	0.8090	0.8090
Fugitive PM10	lb/day		
802		0.0269	0.0269
00		16.3634	16.3634
×ON		1.7062 15.6156 16.3634 0.0269	1.7062 15.6156 16.3634 0.0269
ROG		1.7062	1.7062
	Category	Off-Road	Total

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

Date: 2/7/2022 2:16 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.5 Building Construction - 2022 Unmitigated Construction Off-Site

	ROG	×ON	8	S02	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	Bio- CO2 NBio- CO2 Total CO2	Total CO2	CH4	N20	CO2e
Category					lb/day	day							lb/day	ay		
Hauling	0.0000	0.0000 0.0000 0.0000 0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000 0.0000 0.0000	0.0000		0.0000	0.000.0	0.000.0	0.000	0.0000
Vendor	0.1394	3.5032	1.2857	0.0149	0.5126	0.0417	0.5542	0.1476	0.0399	0.1875		1,600.550 1,600.550 0.0433	1,600.550 7	0.0433	0.236	9 1,672.214 8
Worker	0.8725	0.5526	8.4864	8.4864 0.0213	2.3026	0.0121	2.3147	0.6107	0.0111	0.6218		2,162.110 2,162.110 0 0	2,162.110 0	0.0562	0.0538	2,179.549 3
Total	1.0119	4.0558	9.7720	9.7720 0.0362	2.8151	0.0538	2.8689	0.7583	0.0510	0.8093		3,762.660 3,762.660 6 6	3,762.660 6	0.0995	0.2907	3,851.764 1

Mitigated Construction On-Site

CO2e		2,569.632 2	2,569.632 2
N2O			
CH4	ay	0.6120	0.6120
Total CO2	lb/day	2,554.333 6	2,554.333 6
Bio- CO2 NBio- CO2 Total CO2		0.0000 2,554.333 2,554.333 0.6120 6 6	0.0000 2,554.333 2,554.333 0.6120 6 6
Bio- CO2		0.0000	0.000.0
PM2.5 Total		0.7612	0.7612
Exhaust PM2.5		0.7612 0.7612	0.7612
Fugitive PM2.5			
PM10 Total		0.8090	0608.0
Exhaust PM10	day	0.8090 0.8090	0608'0
Fugitive PM10	lb/day		
SO2		0.0269	0.0269
00		16.3634	16.3634
×ON		15.6156	1.7062 15.6156 16.3634 0.0269
ROG		1.7062 15.6156 16.3634 0.0269	1.7062
	Category	Off-Road	Total

Page 16 of 28

Date: 2/7/2022 2:16 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.5 Building Construction - 2022 Mitigated Construction Off-Site

			'	•	
CO2e		0.0000	1,672.214 8	2,179.549 3	3,851.764 1
N20		0.0000 0.0000 0.0000 0.0000	0.2369	0.0538	0.2907
CH4	lay	0.0000	0.0433	0.0562	0.0995
Total CO2	lb/day	0.000.0	1,600.550 7	2,162,110 2,162,110 0.0562 0 0	3,762.660 3,762.660 6 6
Bio- CO2 NBio- CO2 Total CO2		0.0000	1,600.550 1,600.550 0.0433	2,162.110 0	3,762.660 6
Bio- CO2		1-8-8-8-8			
PM2.5 Total		0.0000	0.1875	0.6218	0.8093
Exhaust PM2.5		0.0000 0.0000 0.0000 0.0000	0.0399	0.0111	0.0510
Fugitive PM2.5		0.0000	0.1476	0.6107	0.7583
PM10 Total		0.000.0	0.5542	2.3147	2.8689
Exhaust PM10	lb/day	0.0000	0.0417	0.0121	0.0538
Fugitive PM10)/q	0.0000	0.5126	2.3026	2.8151
S02		0.0000	3.5032 1.2857 0.0149	8.4864 0.0213	0.0362
00		0.0000	1.2857	8.4864	9.7720
NOx		0.0000 0.0000 0.0000 0.0000	3.5032	0.5526	4.0558
ROG		0.0000	0.1394	0.8725	1.0119
	Category	Hauling	Vendor	Worker	Total

3.5 Building Construction - 2023 Unmitigated Construction On-Site

CO2e		2,570.406	2,570.406 1
N20			
CH4	ay	0.6079	0.6079
Total CO2	lb/day	2,555.209 9	2,555.209 2,555.209 9 9
Bio- CO2 NBio- CO2 Total CO2		2,555.209 2,555.209 0.6079 9 9	2,555.209 9
Bio- CO2			
PM2.5 Total		0.6584	0.6584
Exhaust PM2.5		0.6584	0.6584
Fugitive PM2.5			
PM10 Total		0.6997	2669'0
Exhaust PM10	lb/day	0.6997	2669'0
Fugitive PM10)/q		
S02		0.0269	0.0269
00		16.2440	16.2440
XON		14.3849	1.5728 14.3849 16.2440 0.0269
ROG		1.5728 14.3849 16.2440 0.0269	1.5728
	Category	Off-Road	Total

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

Date: 2/7/2022 2:16 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.5 Building Construction - 2023 **Unmitigated Construction Off-Site**

×ON	8	S02	Fugitive E	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	Bio- CO2 NBio- CO2 Total CO2	Total CO2	CH4	N20	CO2e
0000'0 : 0000'0 : 0000'0 : 0000'0	000	-	-	0.0000	0.0000	0.0000	0000.0	0.0000		0.0000	000000	0.0000	0000.0 • 0000.0 • 0000.0 • 0000.0	0.0000
1.1775 0.0143 0.5125	.0143	 	0.5125	0.0211	0.5336	0.1476	0.0202	0.1678		1,535.345 1,535.345 0.0401 4 4	1,535.345 4	0.0401	0.2267	1,603.913
7.7685 0.0206	0.0206		2.3026	0.0114	2.3140	0.6107	0.0105	0.6211		2,104.637 2,104.637 2 2 2	2,104.637 2	0.0503	0.0495	2,120.642
8.9459 0.0349			2.8151	0.0325	2.8476	0.7583	0.0306	0.7889		3,639.982 3,639.982 6 6	3,639.982 6	0.0904	0.2762	3,724.555 8

Mitigated Construction On-Site

CO2e		2,570.406 1	2,570.406 1
N20			
CH4	ау	0.6079	6209.0
Total CO2	lb/day	2,555.209 9	2,555.209 9
Bio- CO2 NBio- CO2 Total CO2		2,555.209 9	0.0000 2,555.209 2,555.209 9
Bio- CO2		0.0000	
PM2.5 Total		0.6584 0.6584 0.0000 2,555,209 2,555,209 0.6079	0.6584
Exhaust PM2.5		0.6584	0.6584
Fugitive PM2.5			
PM10 Total		0.6997	0.6997
Exhaust PM10	lb/day	7669.0 0.6997	2669'0
Fugitive PM10)/qI		
S02		0.0269	0.0269
00		16.2440	16.2440
NOx		14.3849	1.5728 14.3849 16.2440 0.0269
ROG		1.5728 14.3849 16.2440 0.0269	1.5728
	Category	Off-Road	Total

Page 18 of 28

Date: 2/7/2022 2:16 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.5 Building Construction - 2023

Mitigated Construction Off-Site

CO2e		0.0000	1,603.913 7	2,120.642 1	3,724.555 8
N20		0.0000 0.0000 0.0000 0.0000	0.2267 1,603.913 7	0.0495	0.2762
CH4	lay	0.000.0	0.0401	0.0503	0.0904
Total CO2	lb/day	0.000.0	1,535.345 1,535.345 0.0401 4 4	2,104.637 2	3,639.982 3,639.982 6 6
Bio- CO2 NBio- CO2 Total CO2		0.0000	1,535.345 4	2,104.637 2,104.637 2 2	3,639.982 6
Bio- CO2		1-8-8-8-8	, , , , , ,		
PM2.5 Total		0.0000	0.1678	0.6211	0.7889
Exhaust PM2.5		0.0000 0.0000 0.0000 0.0000	0.0202	0.0105	0.0306
Fugitive PM2.5		0.0000	0.1476	0.6107	0.7583
PM10 Total		0.0000	0.5336	2.3140	2.8476
Exhaust PM10	lb/day	0.0000	0.0211	0.0114	0.0325
Fugitive PM10)/q	0.0000		2.3026	2.8151
802		0.0000	0.0143	0.0206	0.0349
00		0.0000	1.1775	7.7685	8.9459
NOx		0.0000	2.8061	0.4860	3.2921
ROG		0.0000 0.0000 0.0000 0.0000	0.0936 2.8061 1.1775 0.0143	0.8055	0.8991
	Category	Hauling	Vendor	Worker	Total

3.6 Paving - 2023

Unmitigated Construction On-Site

	ROG	XON	00	802	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Bio- CO2 NBio- CO2 Total CO2	CH4	N20	CO2e
Category					lb/day	lay							lb/day	ay		
Off-Road	1.0327 10.1917 14.5842 0.0228	10.1917	14.5842	0.0228		0.5102 0.5102	0.5102		0.4694 0.4694	0.4694	1-0-0-	2,207.584 1	2,207.584 2,207.584 0.7140	0.7140		2,225.433 6
Paving	0.1066					0.0000	0.0000		0.0000	0.0000		0.0000	0.0000			0.0000
Total	1.1394	1.1394 10.1917 14.5842 0.0228	14.5842	0.0228		0.5102	0.5102		0.4694	0.4694		2,207.584	2,207.584 2,207.584	0.7140		2,225.433 6

CalEEMod Version: CalEEMod.2020.4.0

Page 19 of 28

Date: 2/7/2022 2:16 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.6 Paving - 2023

Unmitigated Construction Off-Site

				۲.	2
CO2e		0.0000	0.0000	154.4157	154.4157
N20		0.0000 0.0000 0.0000 0.0000	0.0000	3.6600e- 3.6000e- 003 003	3.6000e- 003
CH4	lb/day	0.0000	0.0000	3.6600e- 003	3.6600e- 003
Total CO2)/qı	0.0000	0.0000	153.2503	153.2503
Bio- CO2 NBio- CO2 Total CO2		0.0000	0.0000	153.2503	153.2503
Bio- CO2		1-8-8-8-8	 		
PM2.5 Total		0.0000	0.0000	0.0452	0.0452
Exhaust PM2.5		0.0000 0.0000 0.0000 0.0000	0.0000	7.6000e- 004	7.6000e- 004
Fugitive PM2.5		0.0000	0.0000	0.0445	0.0445
PM10 Total		0.0000	0.0000	0.1685	0.1685
Exhaust PM10	lb/day	0.0000	0.0000	8.3000e- 004	8.3000e- 004
Fugitive PM10	/qı	0.0000	0.0000	0.1677	0.1677
805		0.0000	0.0000	1.5000e- 003	1.5000e- 003
00		0.0000 0.0000 0.0000 0.0000	0.0000 0.0000 0.0000 0.0000	0.0354 0.5657 1.5000e- 0.1677 003	0.5657 1.5000e- 003
NOx		0.0000	0.0000	0.0354	0.0354
ROG		0.0000	0.0000	0.0587	0.0587
	Category	Hauling	Vendor	Worker	Total

	ROG	XON	00	802	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	Bio- CO2 NBio- CO2 Total CO2	Total CO2	CH4	N20	CO2e
Category					lb/day	lay							lb/day	ay		
Off-Road	1.0327	10.1917		0.0228		0.5102 0.5102	0.5102		0.4694	0.4694 0.4694 0.0000 2,207.584 2,207.584 0.7140	0.0000	2,207.584 1	2,207.584	0.7140		2,225.433 6
Paving	0.1066					0.0000	0.0000		0.000.0	0.0000			0.0000			0.0000
Total	1.1394	10.1917	1.1394 10.1917 14.5842 0.0228	0.0228		0.5102	0.5102		0.4694	0.4694	0.0000	0.0000 2,207.584 2,207.584	2,207.584	0.7140		2,225.433 6

Page 20 of 28 CalEEMod Version: CalEEMod.2020.4.0

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

Date: 2/7/2022 2:16 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Mitigated Construction Off-Site 3.6 Paving - 2023

o)		0	Q	57	22	
CO2e		0.000	0.0000	154.4157	154.4157	
N20		0.0000 0.0000 0.0000 0.0000	0.0000	3.6600e- 3.6000e- 003 003	3.6000e- 003	
CH4	lb/day	0.0000	0.0000	3.6600e- 003	3.6600e- 003	
Total CO2	/qı	0.0000	0.0000	153.2503 153.2503	153.2503	
Bio- CO2 NBio- CO2 Total CO2		0.0000	0.0000	153.2503	153.2503	
Bio- CO2		1-8-8-8-8	; ; ; ; ; ;			
PM2.5 Total		0.0000	0.0000	0.0452	0.0452	
Exhaust PM2.5		0.0000 0.0000 0.0000 0.0000	0.0000	7.6000e- 004	7.6000e- 004	
Fugitive PM2.5			0.0000	0.0000	0.0445	0.0445
PM10 Total		0.000.0	0.000.0	0.1685	0.1685	
Exhaust PM10	lb/day	0.0000	0.0000	8.3000e- 004	8.3000e- 004	
Fugitive PM10)/qI	0.0000	0.0000	0.1677	0.1677	
S02		0.0000	0.0000	0.0354 0.5657 1.5000e- 0.1677 003	1.5000e- 003	
00		0.0000	0.0000	0.5657	0.5657	
NOx		0.0000 0.0000 0.0000 0.0000	0.0000 0.0000 0.0000 0.0000	0.0354	0.0354	
ROG		0.0000	0.0000	0.0587	0.0587	
	Category	Hauling	Vendor	Worker	Total	

3.7 Architectural Coating - 2023 **Unmitigated Construction On-Site**

Fugitive	Exhaust PM10 Fugitive Exhaust PM2.5 Bio- CO2 NBio- CO2 Total CX Total CX Total CX Diagram Total Total Total CX Diagram Total CX Tot	Fugitive	CO SO2 Fugitive Exhaust PM10 Fugitive Exhaust PM2.5 Bio-CO2 NBio-CO2 Total CX Total CX Lotal CX LOTAL CO3	N2 CH4 N2O CO2e	lb/day	000000	
Exhaust PM10 Fugitive Exhaust PM2.5 Total Total	Fugitive	SO2 Fugitive Exhaust PM10 Fugitive Exhaust PM2.5 PM10 Fugitive Exhaust PM2.5 Total Ib/day 0.0000	CO SO2 Fugitive Exhaust PM10 Fugitive Exhaust PM2.5 PM2.5 Total lb/day 0.0000 0.0000 0.0000 0.0000 0.0000	NBio- CO2 Total CC		0.0000	•
Exhaust PM10 Fugitive Exhaust PM2.5 PM2.5	Fugitive	SO2 Fugitive Exhaust PM10 Fugitive Exhaust PM10 PM2.5 PM2.5	CO SO2 Fugitive Exhaust PM10 Fugitive Exhaust PM10 Total PM2.5 PM2.5 PM2.5				
Exhaust PM10 Fugitive PM2.5	Fugitive Exhaust PM10 Fugitive PM10 PM2.5 Ib/day	SO2 Fugitive Exhaust PM10 Fugitive PM10 PM2.5 Ib/day	CO SO2 Fugitive Exhaust PM10 Fugitive PM2.5			0.0000	-
Exhaust PM10 PM10 PM10 y/day	Fugitive Exhaust PM10 PM10 PM10 Total lb/day	SO2 Fugitive Exhaust PM10 Total Ib/day 0.0000 0.0000	CO SO2 Fugitive Exhaust PM10 Total Ib/day 0.0000 0.0000	Exhaust PM2.5		0.0000	
Exhaust PM10 5/day	Fugitive Exhaust PM10 PM10 Ib/day	SO2 Fugitive Exhaust PM10 PM10 lb/day	CO SO2 Fugitive Exhaust PM10 PM10 lb/day	Fugitive PM2.5		ļ 	
% · · · ·	Fugitive PM10	SO2 Fugitive PM10	CO SO2 Fugitive	PM10 Total		0.0000	
Fugitive PM10	PM10	SO2 Fugitiv	CO SO2 Fugitiv	Exhaust PM10	/day	0.0000	
	802		00		'qı		
ŎZ	ROG NOX	ROG 18.9960			Category	Archit. Coating 18.9960	_

Page 21 of 28 CalEEMod Version: CalEEMod.2020.4.0

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

Date: 2/7/2022 2:16 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.7 Architectural Coating - 2023 **Unmitigated Construction Off-Site**

				96	9
CO2e		0.0000	0.0000	422.0696	422.0696
N2O		0.0000 0.0000 0.0000 0.0000	0.0000	9.8500e- 003	9.8500e- 003
CH4	lb/day	0.0000	0.0000	0.0100	0.0100
Total CO2)/qI	0.0000	0.0000	418.8841 418.8841	418.8841
Bio- CO2 NBio- CO2 Total CO2		0.0000	0.0000	418.8841	418.8841
Bio- CO2		1-8-8-8-8			
PM2.5 Total		0.0000	0.0000	0.1236	0.1236
Exhaust PM2.5		0.0000 0.0000 0.0000 0.0000	0.0000	2.0800e- 003	2.0800e- 003
Fugitive PM2.5		0.0000	0.0000	0.1215	0.1215
PM10 Total		0.0000	0.0000	0.4606	0.4606
Exhaust PM10	lb/day		0.0000	2.2600e- 003	2.2600e- 003
Fugitive PM10	/qı	0.0000		0.4583	0.4583
S02		0.0000	0.0000	4.0900e- 003	4.0900e- 003
00		0.0000	0.0000 0.0000 0.0000 0.0000	1.5462 4.0900e- (1.5462 4.0900e-
NOx		0.0000	0.0000	0.0967	0.0967
ROG		0.0000 0.0000 0.0000 0.0000	0.0000	0.1603	0.1603
	Category	Hauling	Vendor	Worker	Total

				ı
CO2e		0.0000	281.8690	281.8690
N20				
CH4	ау		0.0168	0.0168
Total CO2	lb/day	0.0000	281.4481	281.4481
Bio- CO2 NBio- CO2 Total CO2			0.0000 281.4481 281.4481	0.0000 281.4481 281.4481
Bio- CO2			0.0000	0.000.0
PM2.5 Total		0.0000	0.0708	0.0708
Exhaust PM2.5		0.0000 0.0000	0.0708	0.0708
Fugitive PM2.5				
PM10 Total		0.000.0	0.0708	0.0708
Exhaust PM10	lb/day	0.0000 0.0000	0.0708	0.0708
Fugitive PM10)/q			
SO2			2.9700e- 003	2.9700e- 003
00			1.8111	1.8111
×ON			1.3030	19.1876 1.3030 1.8111 2.9700e-
ROG		18.9960	0.1917 1.3030 1.8111 2.9700e- 003	19.1876
	Category	Archit. Coating 18.9960	Off-Road	Total

CalEEMod Version: CalEEMod.2020.4.0

Page 22 of 28

Date: 2/7/2022 2:16 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.7 Architectural Coating - 2023 Mitigated Construction Off-Site

C02e		0.0000	0.0000	422.0696	422.0696
N20		0.0000 0.0000 0.0000 0.0000	0.0000	9.8500e- 003	9.8500e- 003
CH4	ay	0.000.0	0.0000	0.0100	0.0100
Total CO2	lb/day	0.000.0	0.0000	418.8841 418.8841	418.8841
NBio- CO2 Total CO2		0.0000	0.0000	418.8841	418.8841
Bio- CO2					
PM2.5 Total		0.0000	0.0000	0.1236	0.1236
Exhaust PM2.5			0.000.0	2.0800e- 003	2.0800e- 003
Fugitive PM2.5	o/day	0.0000 0.0000 0.0000	0.0000	0.1215	0.1215
PM10 Total		0.0000	0.0000	0.4606	0.4606
Exhaust PM10		0.0000	0.0000	2.2600e- 003	2.2600e- 003
Fugitive PM10)/q	0.0000	0.0000	0.4583	0.4583
S02		0.0000	0.0000	0.0967 1.5462 4.0900e- 003	1.5462 4.0900e- 003
00		0.000.0	0.000.0	1.5462	
NOx		0.0000			0.0967
ROG		0.0000 0.0000 0.0000 0.0000	0.0000	0.1603	0.1603
	Category	Hauling	Vendor	Worker	Total

4.0 Operational Detail - Mobile

4.1 Mitigation Measures Mobile

Increase Transit Accessibility

Improve Pedestrian Network

Page 23 of 28

Date: 2/7/2022 2:16 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

CO2e),538.68 67	3,805.77 29
N20		1.2989 11	1.6962 13
CH4	У	0.3656	0.4703
Total CO2	lb/day	10,142.47 30	13,288.54 56
Bio- CO2 NBio- CO2 Total CO2		10,142.47 10,142.47 0.3656 1.2989 10,538.68 30 30 57	13,288.54 13,288.54 0.4703 1.6962 13,805.77 56 56 29
Bio- CO2			
PM2.5 Total		1.4676	1.9339
Exhaust PM2.5		0.1602 4.9296 1.3147 0.1529 1.4676	0.2106 6.4967 1.7328 0.2011 1.9339
Fugitive PM2.5		1.3147	1.7328
PM10 Total		4.9296	6.4967
Exhaust PM10	day	0.1602	0.2106
Fugitive PM10	lb/day		6.2861
S02		1.2026 14.7889 12.4149 0.0950 4.7694	0.1244
00		12.4149	15.5487
ROG NOx		14.7889	18.9848
ROG		1.2026	1.3866
	Category	Mitigated	Unmitigated 1.3866 18.9848 15.5487 0.1244 6.2861

4.2 Trip Summary Information

	Avei	Average Daily Trip Rate	ite	Unmitigated	Mitigated
Land Use	Weekday	Saturday	Sunday	Annual VMT	Annual VMT
Parking Lot	112.99	112.99	112.99	1,645,198	1,248,255
Unrefrigerated Warehouse-No Rail	'`'	251.70	251.70	1,078,696	818,435
Total	364.69	364.69	364.69	2,723,895	2,066,689

4.3 Trip Type Information

			<u> </u>
% ә	Pass-by	0	6.90 59.00 0.00 41.00 92 5
Trip Purpose %	Diverted	0	5
	Primary	100	92
	H-O or C-NW	0.00	41.00
Trip %	H-S or C-C	100.00	00.00
	H-W or C-W	00:00	59.00
	H-W or C-W H-S or C-C H-O or C-NW H-W or C-W H-S or C-C H-O or C-NW	9:30	6.90
Miles	H-S or C-C		
	H-W or C-W	16.60	16.60
	Land Use	Parking Lot	Unrefrigerated Warehouse-No 16.60 8.40

4.4 Fleet Mix

Page 24 of 28 CalEEMod Version: CalEEMod.2020.4.0

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

Date: 2/7/2022 2:16 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

5.0 Energy Detail

Historical Energy Use: N

5.1 Mitigation Measures Energy

C02e		169.1076	169.1076
N20		168.1086 168.1086 3.2200e- 3.0800e- 169.1076 003	168.1086 168.1086 3.2200e- 3.0800e- 169.1076 003 003
CH4	lay	3.2200e- 003	3.2200e- 003
Total CO2	lb/day	168.1086	168.1086
NBio- CO2		168.1086	168.1086
Bio- CO2 NBio- CO2 Total CO2			
PM2.5 Total		0.0107	0.0107
Exhaust PM2.5		0.0107 0.0107	0.0107
Fugitive PM2.5			
PM10 Total		0.0107	0.0107
Exhaust PM10	lay	0.0107 0.0107	0.0107 0.0107
Fugitive PM10	lb/day		
SO2		8.4000e- 004	8.4000e- 004
CO		0.1177	0.1177
×ON		0.1401	0.1401
ROG		0.0154	0.0154 0.1401 0.1177 8.4000e-
	Category	NaturalGas 0.0154 0.1401 0.1177 8.4000e- Mitigated 0.004	NaturalGas Unmitigated

Page 25 of 28 CalEEMod Version: CalEEMod.2020.4.0

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

Date: 2/7/2022 2:16 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

5.2 Energy by Land Use - NaturalGas

Unmitigated

C02e		0.0000	169.1076	169.1076
N2O		0.0000	e- 3.0800e- 003	3.0800e- 003
CH4	ay	0.000.0	3.2200e- 003	3.2200e- 003
Total CO2	lb/day	0.0000 0.0000 0.0000 0.0000	168.1086	168.1086 168.1086
Bio- CO2 NBio- CO2 Total CO2		0.000.0	168.1086 168.1086 3.2200e- 003	168.1086
Bio- CO2				
PM2.5 Total		0.0000	0.0107	0.0107
Exhaust PM2.5		0.0000 0.0000	0.0107	0.0107
Fugitive PM2.5				
PM10 Total		0.000.0	0.0107	0.0107
Exhaust PM10	lb/day	0.000 0.0000	0.0107	0.0107
Fugitive PM10	/QI			
802		0.0000	8.4000e- 004	8.4000e- 004
00		0.0000	0.1177	0.1177
NOx		0.000.0	0.1401 0.1177	0.1401 0.1177 8.4000e-
ROG		0.0000	1428.92 0.0154	0.0154
NaturalGa ROG s Use	kBTU/yr	0		
	Land Use	Parking Lot 0 10000 0.0000 0.0000 0.0000	Unrefrigerated Warehouse-No Rail	Total

Mitigated

C02e		0.0000	169.1076	169.1076
N20		0.0000	3.0800e- 003	3.0800e- 16 003
CH4	ay	0.0000	3.2200e- 003	3.2200e- 003
Total CO2	lb/day	0.0000 0.0000 0.0000 0.0000	168.1086 168.1086	168.1086 168.1086 3.2200e- 003
Bio- CO2 NBio- CO2 Total CO2		0.000.0	168.1086	168.1086
Bio- CO2				
PM2.5 Total		0.0000	0.0107	0.0107
Exhaust PM2.5		0.0000	0.0107	0.0107
Fugitive PM2.5				
PM10 Total		0.0000	0.0107	0.0107
Exhaust PM10	b/day	0.000 0.0000	0.0107	0.0107
Fugitive PM10	/QI			
805		0.0000	8.4000e- 004	8.4000e- 004
00		0.0000	0.1177	0.1177
×ON		0.000.0	0.1401	0.0154 0.1401 0.1177 8.4000e-
ROG		0.0000	1.42892 0.0154 0.1401	0.0154
NaturalGa s Use	kBTU/yr	0	1.42892	
	Land Use	Parking Lot 0 0.0000 0.0000 0.0000 0.0000	Unrefrigerated Warehouse-No Rail	Total

Date: 2/7/2022 2:16 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

6.1 Mitigation Measures Area

CO2e		0.0618	0.0618
N20			
CH4	ay	1.5000e- 004	1.5000e- 004
Bio- CO2 NBio- CO2 Total CO2	lb/day	0.0580	0.0580
NBio- CO2		0.0580	0.0580
Bio- CO2			
PM2.5 Total		1.0000e- 004	1.0000e- 004
Exhaust PM2.5		1.0000e- 1.0000e- 004 004	1.0000e- 1.0000e- 004 004
Fugitive PM2.5			
PM10 Total		1.0000e- 004	.0000e- 1.0000e- 004 004
Exhaust PM10	day	1.0000e- 1.0000e- 004 004	1.0000e- 004
SO2 Fugitive PM10	lb/day		
S02		0.0000	0.0000
00		0.0270	0.0270
XON		2.5000e- 004	2.5000e- 004
ROG		5.8982 2.5000e- 0.0270 0.0000 004	5.8982 2.5000e- 0.0270 0.0000 004
	Category	Mitigated	Unmitigated

6.2 Area by SubCategory

Unmitigated

				•	I
CO2e		0.0000	0.0000	0.0618	0.0618
N20					
CH4	ay			1.5000e- 004	1.5000e- 004
Total CO2	lb/day	0.000.0	0.000.0	0.0580	0.0580
NBio- CO2 Total CO2				0.0580	0.0580
Bio- CO2					
PM2.5 Total		0.0000	0.0000	1.0000e- 004	1.0000e- 004
Exhaust PM2.5		0.0000 0.0000	0.000.0	1.0000e- 004	1.0000e- 004
Fugitive PM2.5					
PM10 Total		0.0000	0.0000	1.0000e- 004	1.0000e- 004
Exhaust PM10	ı/day	0.0000	0.0000	1.0000e- 004	1.0000e- 004
Fugitive PM10)/ql				
SO2				0.0000	0.000.0
00				0.0270	0.0270
×ON				2.5000e- 004	5.8981 2.5000e- 0.0270 004
ROG		0.6763	5.2193	2.5000e- 2.5000e- 0.0270 003 004	5.8981
	SubCategory		Consumer Products	Landscaping	Total

CalEEMod Version: CalEEMod.2020.4.0

Page 27 of 28

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

Date: 2/7/2022 2:16 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

6.2 Area by SubCategory

Mitigated

CO2e		0.0000	0.0000	0.0618	0.0618
N20					
CH4	ay		 	1.5000e- 004	1.5000e- 004
Total CO2	lb/day	0.000.0	0.000.0	0.0580	0.0580
Bio- CO2 NBio- CO2 Total CO2			 	0.0580	0.0580
Bio- CO2			 	 : : : : :	
PM2.5 Total		0.0000	0.000	1.0000e- 004	1.0000e- 004
Exhaust PM2.5		0.000.0	0.000.0	1.0000e- 004	1.0000e- 004
Fugitive PM2.5			 		
PM10 Total		0.0000	0.0000	1.0000e- 004	1.0000e- 004
Exhaust PM10	day	0.0000	0.0000	1.0000e- 004	1.0000e- 1
Fugitive PM10	lb/day				
805				0.0000	0.0000
00				0.0270	0.0270
×ON				2.5000e- 004	5.8981 2.5000e- 0.0270 004
ROG		0.6763	5.2193	2.5000e- 2.5000e- 003 004	5.8981
	SubCategory			Landscaping	Total

7.0 Water Detail

7.1 Mitigation Measures Water

Install Low Flow Bathroom Faucet

Install Low Flow Kitchen Faucet

Install Low Flow Toilet

Use Water Efficient Irrigation System

8.0 Waste Detail

8.1 Mitigation Measures Waste

Institute Recycling and Composting Services

9.0 Operational Offroad

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Fuel Type	0.20 CNG
Load Factor	0.20
Horse Power	68
Days/Year	260
Hours/Day	2.00
Number	4
Equipment Type	Forklifts

UnMitigated/Mitigated

Se Se		526	526
CO2e		682.2526	682.2526
N20			
CH4	ау	0.2189	0.2189
Total CO2	lb/day	676.7805	676.7805
NBio- CO2		676.7805	0.0000 676.7805 676.7805
Bio- CO2 NBio- CO2 Total CO2		0.0000 676.7805 676.7805 0.2189	0.0000
PM2.5 Total			0.0400
Exhaust PM2.5		0.0400 0.0400	0.0400
Fugitive PM2.5			
PM10 Total		0.0400	0.0400
Exhaust PM10	day	0.0400	0.0400
Fugitive PM10	lb/day		
802		5.3500e- 003	5.3500e- 003
00		32.4407	32.4407
XON		0.0510 2.4827 32.4407 5.3500e-	0.0510 2.4827 32.4407 5.3500e-
ROG		0.0510	0.0510
	Equipment Type	Forklifts	Total

10.0 Stationary Equipment

Fire Pumps and Emergency Generators

	Boilers
Indiliber	
i iodis/Day	
i iodis/ i edi	
I TO SO T OWO!	
Load I actor	
i del 1ype	

Fuel Type
Boiler Rating
Heat Input/Year
Heat Input/Day
Number
Equipment Type

User Defined Equipment

Number	
Equipment Type	

11.0 Vegetation

CalEEMod Version: CalEEMod.2020.4.0

Page 1 of 28

Date: 2/7/2022 2:17 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Slover-Alder Avenue Industrial

San Bernardino-South Coast County, Winter

1.0 Project Characteristics

1.1 Land Usage

Population	0	0
Floor Surface Area		. ,
Lot Acreage	7.94	5.29
Metric	1000sqft	Acre 5.29 230,432.40
Size		
Land Uses	Unrefrigerated Warehouse-No Rail	Parking Lot 5.29

1.2 Other Project Characteristics

Urbanization	Urban	Wind Speed (m/s)	2.2	Precipitation Freq (Days)	32
Climate Zone	10			Operational Year	2023
Utility Company	Southern California Edison				
CO2 Intensity (Ib/MWhr)	390.98	CH4 Intensity (Ib/MWhr)	0.033	N2O Intensity 0. (Ib/MWhr)	0.004

1.3 User Entered Comments & Non-Default Data

Project Characteristics -

Land Use - Total Project Site = 13.23 acres

Construction Phase - Construction schedule provided by applicant

Off-road Equipment - Grading - 2 Excavators, 1 Grader, 1 Rubber Tired Dozer, 2 Scrapers, 2 Crawler Tractors

Off-road Equipment - Site Preparation - 3 Rubber Tired Dozers and 4 Crawler Tractors

Trips and VMT - 6 vendor trucks added to Demolition, Site Prep, and Grading Phases to account for water truck emissions

Demolition - 16,800 sq ft of building space = 773 tons + 117,000 sq ft of pavement = 2,828 tons

Grading -

Architectural Coating -

Vehicle Trips - Truck Trips analyzed under Parking Lot Land use and the Auto Trips analyzed under the Unrefrigerated Warehouse Land Use

Water And Wastewater -

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Solid Waste -

Construction Off-road Equipment Mitigation - Water Exposed Area 3x per day selected to account for SCAQMD Rule 403 minimum requirements Mobile Land Use Mitigation - Improve Pedestrian Network on Project Site and Connecting Offsite and 0.06 mile to nearest Transit Station

Energy Mitigation

Water Mitigation - Install Low-Flow fixtures and use water-efficient Irrigation Systems selected to account for Title 24 Part 11 requirements

Waste Mitigation - 50% reduction in solid waste selected to account for AB 341

Operational Off-Road Equipment - 4 Forklifts 7 hours per day. Per PDF 1, analyzed as CNG fuel

Fleet Mix - Vehicle Mix set to match Trip Generation Memo

New Value	129688	389064	130.00	130.00	09:0	00:00	00:00	0.58	0.00	90.0	0.00	0.19	0.00	0.00	0.22	0.00	0.00	0.03	0.00
Default Value	129741	389222	20.00	20.00	0.02	0.02	0.54	0.54	0.06	0.06	0.17	0.17	0.03	0.03	7.1960e-003	7.1960e-003	0.03	0.03	0.14
Column Name	Area_Nonresidential_Exterior	Area_Nonresidential_Interior	NumDays	NumDays	댶	묲	LDA	LDA	LDT1	LDT1	LDT2	LDT2	LHD1	LHD1	LHD2	LHD2	MCY	MCY	MDV
Table Name	tblAreaCoating	tblAreaCoating	tblConstructionPhase	tblConstructionPhase	tblFleetMix														

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Γ	-		<u> </u>	:	:	i	;	;	i	<u> </u>	;	•		;	;	;		:	i	;	:	i	i			:	:	i
0 7 7	cl.:0	0.00	0.00	0.18	0.00	0.00	0.00	0.00	0.00	0.00	0.00	259,481.00	7.94	CNG	7.00	4.00	6.00	6.00	0.09	40.00	100.00	100.00	21.36	0.97	21.36	76.0	21.36	0.97
	0.14	5.0710e-003	5.0710e-003	0.01	0.01	5.5900e-004	5.5900e-004	9.5400e-004	9.5400e-004	2.5400e-004	2.5400e-004	259,480.00	5.96	Diesel	8.00	0.00	0.00	0.00	0.00	8.40	0.00	0.00	0.00	1.74	0.00	1.74	0.00	1.74
XV	A CIM	HW	HW	QHW	QHW	OBUS	OBUS	SBUS	SBUS	UBUS	UBUS	LandUseSquareFeet	LotAcreage	OperFuelType	OperHoursPerDay	OperOffRoadEquipmentNumber	VendorTripNumber	VendorTripNumber	VendorTripNumber	CC_TL	CC_TTP	PR_TP	ST_TR	ST_TR	SU_TR	SU_TR	WD_TR	WD_TR
	XIIXIIXIIXI	tblFleetMix	tblLandUse	tblLandUse	tblOperationalOffRoadEquipment	tblOperationalOffRoadEquipment	tblOperationalOffRoadEquipment	tblTripsAndVMT	tblTripsAndVMT	tblTripsAndVMT	tblVehicleTrips	tblVehicleTrips	tblVehicleTrips	tbIVehicleTrips	tblVehicleTrips	tblVehicleTrips	tblVehicleTrips	tbIVehicleTrips	tbIVehicleTrips									

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

Date: 2/7/2022 2:17 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

2.0 Emissions Summary

2.1 Overall Construction (Maximum Daily Emission)

Unmitigated Construction

	ROG	×ON	00	S02	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Bio- CO2 NBio- CO2 Total CO2	CH4	NZO	CO2e
Year					lb/day	day							lb/day	ay		
2022	4.5623 50.7390 29.9719 0.0745 22.0177	50.7390	29.9719	0.0745	22.0177	2.1631	24.1808	10.3959	2.1631 24.1808 10.3959 1.9902	12.3861 0.0000 7,237.288 7,237.288 2.2490 0.2928 7,300.424 9 9 0	0.0000	7,237.288 9	7,237.288 9	2.2490	0.2928	7,300.424
2023	22.9737	22.9737 29.4934 41.9851 0.0908 3.441	41.9851	0.0908	3.4411	1.3164	4.7575	0.9243	1.3164 4.7575 0.9243 1.2322	2.1564		9,008.398 0	0.0000 9,008.398 9,008.398 1.4425 0.2924 9,131.595 0 0 4	1.4425	0.2924	9,131.595 4
Maximum	22.9737	22.9737 50.7390 41.9851	41.9851	0.0908 22.0177		2.1631	24.1808	10.3959	1.9902	12.3861	0.0000	9,008.398 0	0.0000 9,008.398 9,008.398 2.2490 0 0	2.2490	0.2928 9,131.595 4	9,131.595 4

Mitigated Construction

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

C02e	00'0
N20	00:0
CH4	0.00
Total CO2	0.00
Bio- CO2 NBio-CO2 Total CO2	00'0
Bio- CO2	00'0
PM2.5 Total	43.34
Exhaust PM2.5	00'0
Fugitive PM2.5	25.67
PM10 Total	45.91
Exhaust PM10	00'0
Fugitive PM10	52.18
802	0.00
00	0.00
NOX	00'0
ROG	0.00
	Percent Reduction

2.2 Overall Operational

Unmitigated Operational

CO2e		0.0618	169.1076	13,625.81 82	682.2526	14,477.24 01
N20			3.0800e- 003	1.7008		1.7038
CH4	ay	1.5000e- 004	3.2200e- 003	0.4716	0.2189	0.6938
Total CO2	lb/day	0.0580 1.5000e-	168.1086 168.1086	13,107.20 13,107.20 66 66	676.7805	13,952.15 36
Bio- CO2 NBio- CO2 Total CO2		0.0580	168.1086	13,107.20 66	676.7805	13,952.15 13,952.15 36 36
Bio- CO2					0.0000	0.000.0
PM2.5 Total		1.0000e- 004	0.0107	1.9340	0.0400	1.9848
Exhaust PM2.5		1.0000e- 004	0.0107	0.2012	0.0400	0.2520
Fugitive PM2.5				1.7328		1.7328
PM10 Total		1.0000e- 004	0.0107	6.4969	0.0400	6.5477
Exhaust PM10	lb/day	1.0000e- 1.0000e- 004 004	0.0107	0.2108	0.0400	0.2616
Fugitive PM10)/q			6.2861		6.2861
S02		0.0000	8.4000e- 004	0.1226	5.3500e- 003	0.1288
00		0.0270	0.1177	19.9414 14.2675	32.4407	46.8529
NOX		2.5000e- 0.0270 0.0000 004	0.1401	19.9414	2.4827	22.5644
ROG		5.8982	0.0154	1.2581	0.0510	7.2226
	Category	Area	Energy	Mobile	Offroad	Total

Page 6 of 28

Date: 2/7/2022 2:17 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

2.2 Overall Operational

Mitigated Operational

		1				
CO2e		0.0618	169.1076	10,403.91 63	682.2526	11,255.33 82
N20			3.0800e- 003	1.3027		1.3058
CH4	ay	1.5000e- 004	3.2200e- 003	0.3676	0.2189	0.5899
Total CO2	lb/day	0.0580	168.1086	10,006.50 76	676.7805	10,851.45 46
Bio- CO2 NBio- CO2 Total CO2		0.0580	168.1086	10,006.50 76	676.7805	10,851.45 46
Bio- CO2			: : : : :		0.0000	0.0000
PM2.5 Total		1.0000e- 004	0.0107	1.4678	0.0400	1.5186
Exhaust PM2.5		1.0000e- 004	0.0107	0.1531	0.0400	0.2039
Fugitive PM2.5			 	1.3147	 	1.3147
PM10 Total		1.0000e- 004	0.0107	4.9298	0.0400	4.9806
Exhaust PM10	lb/day	1.0000e- 004	0.0107	0.1603	0.0400	0.2111
Fugitive PM10	p/ql		 	4.7694		4.7694
S02		0.0000	8.4000e- 004	0.0936	5.3500e- 003	0.0998
00		0.0270	0.1177	11.5047	32.4407	44.0901
×ON		2.5000e- 0.0270 0.0000 004	0.1401	15.5457	2.4827	18.1687
ROG		5.8982	0.0154	1.0764	0.0510	7.0409
	Category	Area	Energy	Mobile	Offroad	Total

CO2e	22.25
N20	23.36
СН4	14.98
Total CO2	22.22
Bio- CO2 NBio-CO2 Total CO2	22.22
Bio- CO2	00:0
PM2.5 Total	23.49
Exhaust PM2.5	19.12
Fugitive PM2.5	24.13
PM10 Total	23.93
Exhaust PM10	19.29
Fugitive PM10	24.13
S02	22.51
8	5.90
NOX	19.48
ROG	2.52
	Percent Reduction

3.0 Construction Detail

Construction Phase

Phase Number	Phase Name	Phase Type	Start Date	End Date	Num Days Num Days Week	Num Days	Phase Description
1	Demolition			3/28/2022	5	20	
7	Site Preparation	Site Preparation	3/29/2022	4/11/2022	5	5 10	
ဗ	Grading			5/23/2022	5	5 30	
4	Building Construction	Building Construction	5/24/2022	7/17/2023	5	5 300	

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

Date: 2/7/2022 2:17 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

2	Paving	Paving	1/17/2023	7/17/2023	5	130	1/17/2023 7/17/2023 5 130
9	6 Architectural Coating Architect	Architectural Coating	1/17/2023	7/17/2023	5	130	

Acres of Grading (Site Preparation Phase): 35

Acres of Grading (Grading Phase): 120

Acres of Paving: 5.29

Residential Indoor: 0; Residential Outdoor: 0; Non-Residential Indoor: 389,222; Non-Residential Outdoor: 129,741; Striped Parking Area: 13,826 (Architectural Coating – sqft)

OffRoad Equipment

Phase Name	Offroad Equipment Type	Amount	Usage Hours	Horse Power	Load Factor
Demolition	Concrete/Industrial Saws		8.00	81	0.73
Demolition	Excavators	: : : : : : : : : : : :	8.00	158	0.38
Demolition	Rubber Tired Dozers	Z	8.00	247	0.40
Site Preparation	Crawler Tractors	4	8.00	212	0.43
Site Preparation	Rubber Tired Dozers	(C)	8.00	247	0.40
Grading	Crawler Tractors	2	8.00	212	0.43
Grading	Excavators	2	8.00	158	0.38
Grading	Graders		8.00	187	0.41
Grading	Rubber Tired Dozers	 	8.00	247	0.40
Grading	Scrapers	2	8.00	367	0.48
Building Construction	Cranes		2.00	231	0.29
Building Construction	Forklifts	r	8.00	68	0.20
Building Construction	Generator Sets		8.00	84	0.74
Building Construction	Tractors/Loaders/Backhoes	e	7.00	26	0.37
Building Construction	Welders		8.00	46	0.45
Paving	Pavers	2	8.00	130	0.42
Paving	Paving Equipment	2	8.00	132	0.36
Paving	Rollers	2	8.00	80	0.38

Page 8 of 28

Date: 2/7/2022 2:17 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

Rule Applied	
ccount for the SAFE Vehicle Rule A	0.48
ccount for the	28
y Vehicle to A	00.9
actors for Gasoline Light Dut	
lodel Adjustment F	Air Compressors
EMFAC Off-N	Architectural Coating

Trips and VMT

15.00	00.9	356.00)	Lengtn	Class	Vallera Class	Vehicle Class
			14.70	06.90	20.00	20.00 LD_Mix	HDT_Mix	HHDT
18.00	00.9	00.00	14.70	06.90		20.00 LD_Mix	HDT_Mix	HHDT
20:00	9.00	00:00	14.70	06.9		20.00 LD_Mix	HDT_Mix	HHDT
206.00	80.00	00:00	14.70	06.90		20.00 LD_Mix	HDT_Mix	HHDT
15.00	0.00	00:00	14.70	06.90		LD_Mix	HDT_Mix	HHDT
41.00	0.00	00:00	14.70	06.9	20.00	LD_Mix	HDT_Mix	HHDT
i	15.00		0.00	0.00	0.00 0.00 14.70	0.00 0.00 14.70 6.90 0.00 0.00 14.70 6.90	0.00 0.00 14.70 6.90 20.00 LD_Mix 0.00 0.00 14.70 6.90 20.00 LD_Mix	0.00 0.00 14.70 6.90 20.00 LD_Mix 0.00 0.00 14.70 6.90 20.00 LD_Mix

3.1 Mitigation Measures Construction

Water Exposed Area

3.2 Demolition - 2022

CO2e		0.0000	3,773.092 0	3,773.092 0			
N20							
CH4	уя	/te	Я	λγ		1.0524	1.0524
Total CO2	lb/day	0.000.0	3,746.781 2	3,746.781 2			
Bio- CO2 NBio- CO2 Total CO2			3,746.781 3,746.781 1.0524 2 2	3,746.781 3,746.781 2 2			
Bio- CO2							
PM2.5 Total		0.5832	1.1553	1.7385			
Exhaust PM2.5		0.0000 3.8518 0.5832 0.0000 0.5832	1.1553	1.1553			
Fugitive PM2.5		0.5832		0.5832			
PM10 Total		3.8518	1.2427	5.0945			
Exhaust PM10	lay	0.0000	1.2427	1.2427			
Fugitive PM10	lb/day	3.8518		3.8518			
802			0.0388	0.0388			
00			20.5941	20.5941			
×ON			2.6392 25.7194 20.5941 0.0388	2.6392 25.7194 20.5941 0.0388			
ROG			2.6392	2.6392			
	Category	Fugitive Dust	Off-Road	Total			

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.2 Demolition - 2022

Unmitigated Construction Off-Site

	ROG	×ON	00	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	Bio- CO2 NBio- CO2 Total CO2	Total CO2	CH4	NZO	CO2e
					lb/day	day							lb/day	ay		
	0.0645	2.5472	0.6473	0.0645 2.5472 0.6473 0.0105 0.311	0.311	7 0.0255 0.3372 0.0855 0.0244 0.1099	0.3372	0.0855	0.0244	0.1099		1,140.879 0	1,140.879 1,140.879 0.0487 0.1808 1,195.972 0 0 3	0.0487	0.1808	1,195.972 3
	0.0101	0.2758	0.0998	1.1200e- 003	0.0384	3.1400e- 003	0.0416	0.0111	3.0000e- 003	0.0141		120.1737	120.1737 120.1737 3.2200e- 003	3.2200e- 003	0.0178	125.5572
: : : : l	0.0610	0.0423	0.507	6 1.4000e- (003	.1677	8.8000e- 004	0.1685	0.0445	8.1000e- (004	0.0453		142.5884	142.5884 142.5884 4.0800e- 4.0400e- 003 003	4.0800e- 003	4.0400e- 003	143.8959
	0.1356	2.8653 1.2547	1.2547	0.0130	0.5178	0.0295	0.5474	0.1410	0.0282	0.1693		1,403.641	1,403.641 1,403.641	0.0560	0.2026 1,465.425	1,465.425 3

CO2e		0.0000	3,773.092 0	3,773.092 0
N20				
CH4	ау		1.0524	1.0524
Total CO2	lb/day	0.000.0	3,746.781 2	3,746.781 2
Bio- CO2 NBio- CO2 Total CO2			0.0000 3,746.781 3,746.781 1.0524	0.0000 3,746.781 3,746.781
Bio- CO2			0.0000	
PM2.5 Total		0.2275	1.1553	1.3827
Exhaust PM2.5		0.0000 1.5022 0.2275 0.0000 0.2275	1.1553	1.1553
Fugitive PM2.5		0.2275		0.2275
PM10 Total		1.5022	1.2427	2.7449
Exhaust PM10	b/day	0.0000	1.2427	1.2427
Fugitive PM10)/q	1.5022		1.5022
SO2			0.0388	0.0388
00			20.5941	20.5941
XON			2.6392 25.7194 20.5941 0.0388	2.6392 25.7194 20.5941 0.0388 1.5022
ROG			2.6392	2.6392
	Category	Fugitive Dust	Off-Road	Total

Page 10 of 28

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

Date: 2/7/2022 2:17 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Mitigated Construction Off-Site 3.2 Demolition - 2022

CO2e		1,195.972 3	125.5572	143.8959	1,465.425 3
N20		0.1808	0.0178	4.0400e- 003	0.2026
CH4	ay	0.0487	3.2200e- 003	4.0800e- 003	0.0560
Total CO2	lb/day	1,140.879 0	120.1737		1,403.641 1
Bio- CO2 NBio- CO2 Total CO2		1,140.879 1,140.879 0.0487 0.1808 1,195.972 0 0 3	120.1737 120.1737	142.5884 142.5884	1,403.641 1,403.641
Bio- CO2					
PM2.5 Total		0.1099	0.0141	0.0453	0.1693
Exhaust PM2.5		0.0255 0.3372 0.0855 0.0244 0.1099	3.0000e- 003	8.1000e- 004	0.0282
Fugitive PM2.5		0.0855	0.0111	0.0445	0.1410
PM10 Total		0.3372	0.0416	0.1685	0.5474
Exhaust PM10	lay	0.0255	3.1400e- 003	8.8000e- 004	0.0295
Fugitive PM10	lb/day	0.3117	0.0384	0.1677	0.5178
802		0.0105	0.0998 1.1200e- 0.0384 003	0.5076 1.4000e- 003	0.0130 0.5178
00		0.6473	0.0998	0.5076	1.2547
×ON		0.0645 2.5472 0.6473 0.0105 0.3117	0.0101 0.2758	0.0423	2.8653
ROG		0.0645	0.0101	0.0610	0.1356
	Category	Hauling	Vendor	Worker	Total

Unmitigated Construction On-Site 3.3 Site Preparation - 2022

			•	
CO2e		0.0000	5,561.845 1	5,561.845 1
N20				
CH4	ay		1.7844	1.7844
Total CO2	lb/day	0.000.0	5,517.235 5	5,517.235 5
NBio- CO2			5,517.235 5,517.235 1.7844 5 5	5,517.235 5,517.235 5 5
PM2.5 Bio- CO2 NBio- CO2 Total CO2 Total				
PM2.5 Total		10.3315	1.9862	12.3177
Exhaust PM2.5		0.0000 21.7780 10.3315 0.0000 10.3315	1.9862	1.9862
Fugitive PM2.5		10.3315		23.9370 10.3315
PM10 Total		21.7780	2.1590	23.9370
Exhaust PM10	lay	0.0000	2.1590	2.1590
Fugitive PM10	lb/day	21.7780		21.7780
S02			0.0570	0.0570 21.7780
00			20.0053	20.0053
×ON			4.4790 50.4124 20.0053 0.0570	4.4790 50.4124 20.0053
ROG			4.4790	4.4790
	Category	Fugitive Dust	Off-Road	Total

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.3 Site Preparation - 2022
Unmitigated Construction Off-Site

e,		0	572	750	322
CO2e		0.000	125.5572	172.6750	298.2322
N20		0.0000	0.0178	4.8500e- 17 003	0.0226
CH4	lb/day	0.0000	3.2200e- 003	4.9000e- 003	8.1200e- 003
Total CO2)/q	0.0000 0.0000 0.0000 0.0000	120.1737	171.1060 171.1060 4.9000e- 003	291.2797
Bio- CO2 NBio- CO2 Total CO2		0.0000	120.1737 120.1737 3.2200e- 003	171.1060	291.2797
Bio- CO2		1-8-8-8-8	 	 	
PM2.5 Total		0.0000	0.0141	0.0543	0.0684
Exhaust PM2.5		0.000.0	3.0000e- 003	9.7000e- 004	3.9700e- 003
Fugitive PM2.5		0.000 0.0000 0.0000	0.0111	0.0534	0.0644
PM10 Total		0.000.0	0.0416	0.2023	0.2438
Exhaust PM10	lb/day	0.0000	3.1400e- 003	1.0600e- 003	4.2000e- 003
Fugitive PM10)/q	0.0000	0.0384	0.2012	0.2396
805		0.0000	0.0998 1.1200e- C	1.6800e- 003	0.7089 2.8000e- 003
00		0.0000	0.0998	0.6091	0.7089
NOx		0.0000 0.0000 0.0000 0.0000	0.2758	0.0508	0.3266
ROG		0.0000	0.0101	0.0732	0.0833
	Category	Hauling	Vendor	Worker	Total

CO2e		0.0000	5,561.845 1	5,561.845 1
N20				
CH4	ay		1.7844	1.7844
Total CO2	lb/day	0.000.0	5,517.235 5	5,517.235 5
Bio- CO2 NBio- CO2 Total CO2			0.0000 5,517.235 5,517.235 1.7844 5	0.0000 5,517.235 5,517.235 1.7844 5
Bio- CO2			0.0000	
PM2.5 Total			1.9862	6.0155
Exhaust PM2.5		0.0000 8.4934 4.0293 0.0000 4.0293	1.9862	1.9862
Fugitive PM2.5		4.0293		4.0293
PM10 Total		8.4934	2.1590	10.6524
Exhaust PM10	day	0.0000	2.1590	2.1590
Fugitive PM10	lb/day	8.4934		8.4934
S02			0.0570	0.0570
00			20.0053	20.0053
×ON			4.4790 50.4124 20.0053	4.4790 50.4124 20.0053 0.0570 8.4934
ROG			4.4790	4.4790
	Category	Fugitive Dust	Off-Road	Total

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Mitigated Construction Off-Site 3.3 Site Preparation - 2022

0		0	72	20	22
CO2e		0.0000	125.5572	172.6750	298.2322
NZO		0.0000	0.0178	4.9000e- 4.8500e- 003 003	0.0226
CH4	lay	0.0000	3.2200e- 003	4.9000e- 003	8.1200e- 003
Total CO2	lb/day	0.0000 0.0000 0.0000 0.0000	120.1737 120.1737 3.2200e- 003	171.1060 171.1060	291.2797
Bio-CO2 NBio-CO2 Total CO2		0.0000	120.1737	171.1060	291.2797
Bio- CO2		1-8-8-8-8			
PM2.5 Total		0.0000	0.0141	0.0543	0.0684
Exhaust PM2.5		0.0000 0.0000 0.0000 0.0000	3.0000e- 003	9.7000e- 004	3.9700e- 003
Fugitive PM2.5		0.0000	0.0111	0.0534	0.0644
PM10 Total		0.000.0	0.0416	0.2023	0.2438
Exhaust PM10	lb/day	0.0000	3.1400e- 003	1.0600e- 003	4.2000e- 003
Fugitive PM10)/qI	0.0000	0.0384	0.2012	0.2396
S02		0.0000	1.1200e- 003	0.6091 1.6800e- C	0.7089 2.8000e- 003
00		0.0000	0.0998	0.6091	6802'0
NOx		0.0000 0.0000 0.0000 0.0000	0.2758	0.0508	0.3266
ROG		0.0000	0.0101	0.0732	0.0833
	Category	Hauling	Vendor	Worker	Total

Unmitigated Construction On-Site 3.4 Grading - 2022

CO2e		0.0000	6,983.005 6	6,983.005 6
N20				
CH4	ay		2.2403	2.2403
Total CO2	lb/day	0.000.0	6,926.997 6,926.997 2.2403 4 4	6,926.997 6,926.997 4 4
NBio- CO2			6,926.997 4	6,926.997 4
Bio- CO2 NBio- CO2 Total CO2				
PM2.5 Total		3.7683	1.7554	5.5237
Exhaust PM2.5		0.0000 10.2641 3.7683 0.0000 3.7683	1.7554	1.7554
Fugitive Exhaust PM2.5		3.7683	 	3.7683
PM10 Total		10.2641	1.9081	12.1722
Exhaust PM10	lay	0.0000	1.9081	1.9081
Fugitive PM10	lb/day	10.2641		10.2641
S02			0.0715	0.0715
00			29.1953	29.1953
XON			4.2792 47.5079 29.1953 0.0715	4.2792 47.5079 29.1953 0.0715 10.2641
ROG			4.2792	4.2792
	Category	Fugitive Dust	Off-Road	Total

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Unmitigated Construction Off-Site 3.4 Grading - 2022

C02e		0.0000	125.5572	191.8611	317.4183
N20		0.0000	0.0178	5.3900e- 003	0.0232
CH4	ау	0.000.0	3.2200e- 003	5.4400e- 003	8.6600e- 003
Total CO2	lb/day	0.0000 0.0000 0.0000 0.0000	120.1737	190.1178	310.2915
Bio- CO2 NBio- CO2 Total CO2		0.0000	120.1737 120.1737	190.1178 190.1178	310.2915
Bio- CO2			 		
PM2.5 Total		0.0000	0.0141	0.0604	0.0744
Exhaust PM2.5		0.000.0	1 3.0000e- 003	1.0800e- 003	4.0800e- 003
Fugitive PM2.5		0.0000 0.0000 0.0000	0.0111	0.0593	0.0704
PM10 Total		0.000.0	0.0416	0.2247	0.2663
Exhaust PM10	lb/day	0.0000	3.1400e- 003	1.1700e- 003	4.3100e- 003
Fugitive PM10)/q	0.0000	0.0384	0.2236	0.2620
S02		0.000.0	1.1200e- 003	1.8700e- 003	2.9900e- 003
00		0.000.0	0.0998 1.1200e- 0.0384 003	0.6768 1.8700e- 003	0.7766
XON		0.0000 0.0000 0.0000 0.0000	0.2758	0.0564	0.3323
ROG		0.0000	0.0101	0.0814	0.0914
	Category	Hauling	Vendor	Worker	Total

			52	Ω
CO2e		0.0000	6,983.005 6	6,983.005 6
N20				
CH4	ay		2.2403	2.2403
Total CO2	lb/day	0.0000	6,926.997 4	6,926.997 4
Bio- CO2 NBio- CO2 Total CO2			0.0000 6,926.997 6,926.997 2.2403 4 4	0.0000 6,926.997 6,926.997 4 4
Bio- CO2			0.0000	0000'0
PM2.5 Total		1.4696	1.7554 1.7554	3.2251
Exhaust PM2.5		0.0000 4.0030 1.4696 0.0000	1.7554	1.7554
Fugitive PM2.5		1.4696		1.4696
PM10 Total		4.0030	1.9081	5.9111
Exhaust PM10	lb/day	0.0000	1.9081	1.9081
Fugitive PM10)/qı	4.0030		4.0030
SOS			0.0715	0.0715
00			29.1953	29.1953
XON			47.5079	47.5079 29.1953 0.0715
ROG			4.2792 47.5079 29.1953 0.0715	4.2792
	Category	Fugitive Dust	Off-Road	Total

.0 Page 14 of 28

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Date: 2/7/2022 2:17 PM

3.4 Grading - 2022
Mitigated Construction Off-Site

<u> </u>	34
0.2620	0.7766 2.9900e- 0.2620 4.3100e- 0.2663 003 003
	.2758 0.0998 1.1200e .0564 0.6768 1.8700e .3323 0.7766 2.9900e

3.5 Building Construction - 2022 Unmitigated Construction On-Site

CO2e		2,569.632 2	2,569.632 2
N20			
CH4	ay	0.6120	0.6120
Total CO2	lb/day	2,554.333 6	2,554.333 2,554.333 0.6120 6 6
Bio- CO2 NBio- CO2 Total CO2		2,554.333 2,554.333 0.6120 6 6	2,554.333 6
Bio- CO2			
PM2.5 Total		0.7612	0.7612
Exhaust PM2.5		0.7612 0.7612	0.7612
Fugitive PM2.5			
PM10 Total		0.8090 0.8090	0.8090
Exhaust PM10	lb/day	0.8090	0.8090
Fugitive PM10)/q		
SO2		0.0269	0.0269
00		16.3634	16.3634
×ON		1.7062 15.6156 16.3634 0.0269	1.7062 15.6156 16.3634 0.0269
ROG		1.7062	1.7062
	Category	Off-Road	Total

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

Date: 2/7/2022 2:17 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.5 Building Construction - 2022 Unmitigated Construction Off-Site

	ROG	×ON	00	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	Bio- CO2 NBio- CO2 Total CO2	Total CO2	CH4	N20	CO2e
Category					lb/day	lay							lb/day	ay		
Hauling	0.0000	0.0000 0.0000 0.0000 0.0000	0.0000	0.0000	0.0000	0.0000	0.000.0	0.000.0	0.0000 0.0000 0.0000 0.0000	0.0000		0.0000	0.000.0	0.000.0	0.0000 0.0000 0.0000 0.0000 0.0000	0.0000
Vendor	0.1340	3.6776	3.6776 1.3309 0.0150 0.5126	0.0150	0.5126	0.0418	0.5544	0.1476	0.0400	0.1876		1,602.316 1,602.316 0.0430	1,602.316		0.2373	1,674.096 0
Worker	0.8381	0.5812	6.9710 0.0193	0.0193	2.3026	0.0121	2.3147	0.6107	0.0111	0.6218		1,958.213 1,958.213 4	1,958.213 4	0.0561	0.0556	1,976.169 6
Total	0.9721	4.2588	8.3019	0.0342	2.8151	0.0539	2.8690	0.7583	0.0511	0.8094		3,560.529 3,560.529 5 5		0.0991	0.2928	3,650.265 7

ROG	XON	00	805	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Bio- CO2 NBio- CO2 Total CO2	CH4	N20	CO2e
				lb/day	day							lb/day	ay		
62	1.7062 15.6156 16.3634 0.0269	16.3634	0.0269		0.8090	0.8090 0.8090		0.7612	0.7612 0.7612	0.0000	2,554.333 6	0.0000 2,554.333 2,554.333 0.6120 6 6	0.6120		2,569.632 2
62	1.7062 15.6156 16.3634	16.3634	0.0269		0.8090	0.8090		0.7612	0.7612		2,554.333 6	0.0000 2,554.333 2,554.333 0.6120 6 6	0.6120		2,569.632 2

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

Page 16 of 28

Date: 2/7/2022 2:17 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.5 Building Construction - 2022 Mitigated Construction Off-Site

0.0150	0.0000 0.0000 0.0000 0.0000 0.0000 0.0000 0.0000 0.0000 0.0000 0.0340 3.6776 1.3309 0.0150 0.5126 0.8381 0.5812 6.9710 0.0193 2.3026
3026 0.0121 2.3147 0.6107 8151 0.0539 2.8690 0.7583	2.3026 0.0121 2.3147 2.8151 0.0539 2.8690

3.5 Building Construction - 2023 **Unmitigated Construction On-Site**

C02e		2,570.406 1	2,570.406 1
N20			
CH4	ау	0.6079	0.6079
Total CO2	lb/day	2,555.209 9	2,555.209
Bio- CO2 NBio- CO2 Total CO2		2,555.209 2,555.209 0.6079 9	2,555.209 2,555.209 0.6079 9 9
Bio- CO2			
PM2.5 Total		0.6584	0.6584
Exhaust PM2.5		0.6584 0.6584	0.6584
Fugitive PM2.5			
PM10 Total		0.6997	0.6997
Exhaust PM10	lb/day	7669.0 7669.0	0.6997
Fugitive PM10)/qI		
805		0.0269	0.0269
00		16.2440	16.2440
×ON		14.3849	1.5728 14.3849 16.2440 0.0269
ROG		1.5728 14.3849 16.2440 0.0269	1.5728
	Category	Off-Road	Total

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.5 Building Construction - 2023 Unmitigated Construction Off-Site

					_
CO2e		0.0000	1,607.839 0	0.0511 1,923.228 4	3,531.067 4
N20		0.0000	0.2274	0.0511	0.2785
CH4	ay	0.000.0	0.0398	0.0503	0.0901
Total CO2	lb/day	0.000.0	1,539.068 8	1,906.747 8	
NBio- CO2		0.0000 0.0000 0.0000 0.0000	1,539.068 1,539.068 8 8	1,906.747 1,906.747 8 8	3,445.816 3,445.816 6 6
Bio- CO2 NBio- CO2 Total CO2			 		
PM2.5 Total		0.0000	0.1678	0.6211	0.7890
Exhaust PM2.5		0.0000 0.0000 0.0000 0.0000	0.0203	0.0105	0.0307
Fugitive PM2.5		0.000.0	0.1476 0.0203	0.6107	0.7583
PM10 Total		0.000.0	0.5337	2.3140	2.8477
Exhaust PM10	lay	0.0000	0.0212	0.0114	0.0326
Fugitive PM10	lb/day	0.0000	0.5125	2.3026	2.8151
S02		0.000.0	0.0144	0.0186	0:0330
00		0.0000	1.2138	6.3939	7.6076
NOX		0.0000 0.0000 0.0000 0.0000	2.9639	0.5111	3.4750
ROG		0.0000	0.0871	0.7759	0.8630
	Category	Hauling	Vendor	Worker	Total

CO2e		2,570.406 1	2,570.406 1
N20			
CH4	ay	0.6079	0.6079
Total CO2	lb/day	2,555.209 9	2,555.209 9
Bio- CO2 NBio- CO2 Total CO2		0.0000 2,555.209 2,555.209 0.6079	0.0000 2,555.209 2,555.209 9 9
Bio- CO2		0.0000	0.000.0
PM2.5 Total		0.6584	0.6584
Exhaust PM2.5		0.6584	0.6584
Fugitive PM2.5			
PM10 Total		0.6997	0.6997
Exhaust PM10	day	0.6997	0.6997
Fugitive PM10	lb/day		
S02		0.0269	0.0269
00		16.2440	16.2440
XON		14.3849	1.5728 14.3849 16.2440 0.0269
ROG		1.5728 14.3849 16.2440 0.0269	1.5728
	Category	Off-Road	Total

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.5 Building Construction - 2023

Mitigated Construction Off-Site

Φ		8	839	228	290
CO2e		0.000	1,607.839 0	1,923.228 4	3,531.067 4
NZO		0.0000	0.2274	0.0511	0.2785
CH4	lay	0.0000	0.0398	0.0503	0.0901
Total CO2	lb/day	0.0000 0.0000 0.0000 0.0000	1,539.068 8	1,906.747 8	3,445.816 3,445.816 6 6
Bio- CO2 NBio- CO2 Total CO2		0.0000	1,539.068 1,539.068 0.0398 8 8	1,906.747 1,906.747 0.0503 8 8	3,445.816 6
Bio- CO2					
PM2.5 Total		0.0000	0.1678	0.6211	0.7890
Exhaust PM2.5		0.0000 0.0000 0.0000 0.0000	0.0203	0.0105	0.0307
Fugitive PM2.5		0.000.0	0.1476	0.6107	0.7583
PM10 Total		0.0000	0.5337	2.3140 0.6107	2.8477
Exhaust PM10	lb/day	0.0000	0.0212	0.0114	0.0326
Fugitive PM10)/q	0.0000	0.5125	2.3026	2.8151
SO2		0.0000	0.0144	0.0186	0:0330
00		0.0000	0.0871 2.9639 1.2138	0.5111 6.3939	3.4750 7.6076
XON		0.0000	2.9639	0.5111	
ROG		0.0000 0.0000 0.0000 0.0000	0.0871	0.7759	0.8630
	Category	Hauling	Vendor	Worker	Total

3.6 Paving - 2023

CO2e		2,225.433 6	0.0000	2,225.433 6
N20				
CH4	ay	0.7140		0.7140
Total CO2	lb/day	2,207.584	0.0000	2,207.584
Bio- CO2 NBio- CO2 Total CO2				2,207.584 2,207.584
Bio- CO2				
PM2.5 Total		0.4694	0.0000	0.4694
Exhaust PM2.5		0.4694 0.4694	0.000	0.4694
Fugitive PM2.5				
PM10 Total		0.5102	0.000.0	0.5102
Exhaust PM10	day	0.5102 0.5102	0.000	0.5102
Fugitive PM10	lb/day			
2OS		0.0228		0.0228
00		14.5842		14.5842
XON		10.1917	•	1.1394 10.1917 14.5842
ROG		1.0327 10.1917 14.5842 0.0228	0.1066	1.1394
	Category	Off-Road	Paving	Total

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.6 Paving - 2023

Unmitigated Construction Off-Site

CO2e		0.0000	0.0000	140.0409	140.0409
N20		0.0000 0.0000 0.0000	0.0000	3.7200e- 003	3.7200e- 003
CH4	lay	0.000.0	0.000.0	138.8409 138.8409 3.6600e- 003	3.6600e- 003
Total CO2	lb/day	0.000.0	0.000.0	138.8409	138.8409 3.6600e- 003
Bio- CO2 NBio- CO2 Total CO2		0.0000	0.0000	138.8409	138.8409
Bio- CO2		1-0-0-0-0	; ; ; ; ;		
PM2.5 Total		0.0000	0.0000	0.0452	0.0452
Exhaust PM2.5		0.0000 0.0000 0.0000	0.0000	7.6000e- 004	7.6000e- 004
Fugitive PM2.5		0.000.0	0.000.0	0.0445	0.0445
PM10 Total		0.000.0	0.000.0	0.1685	0.1685
Exhaust PM10	lb/day		0.0000	7 8.3000e- 004	8.3000e- 004
Fugitive PM10)/q	0.0000	0.0000	0.1677	0.1677
S02		0.0000	0.0000	0.4656 1.3600e- 003	0.0372 0.4656 1.3600e- 0.1677 003
00		0.0000	0.0000	0.4656	0.4656
NOX		0.0000	0.0000 0.0000 0.0000	0.0372	
ROG		0.0000 0.0000 0.0000 0.0000	0.0000	0.0565	0.0565
	Category	Hauling	Vendor	Worker	Total

X O N	00	S02	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	Bio- CO2 NBio- CO2 Total CO2	Total CO2	CH4	N20	CO2e
			lb/day	ay							lb/day	ay		
1.0327 10.1917 14.5842 0.0228	0.0228			0.5102 0.5102	0.5102		0.4694	0.4694 0.4694 0.0000 2,207.584 2,207.584 0.7140	0.0000	2,207.584 1	2,207.584 1	0.7140		2,225.433 6
				0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
1.1394 10.1917 14.5842 0.0228	0.0228			0.5102	0.5102		0.4694	0.4694	0.0000	0.0000 2,207.584 2,207.584	2,207.584	0.7140		2,225.433 6

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Mitigated Construction Off-Site 3.6 Paving - 2023

	ROG	XON	8	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio-CO2	Bio- CO2 NBio- CO2 Total CO2	Total CO2	CH4	N20	CO2e
Category					lb/day	lay							lb/day	a		
Hauling	0.0000	0.0000 0.0000 0.0000 0.0000 0.0000	0.000.0	0.0000	[0.0000 0.0000 0.0000 0.0000 0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.000.0	0.000.0	0.0000 0.0000 0.0000 0.0000 0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.000.0	0.0000	0.0000	0.0000
Worker	0.0565	0.0372	0.4656 1.3600e- 0.1677 003	1.3600e- 003	0.1677	8.3000e- 004	0.1685	0.0445	7.6000e- 004	0.0452		138.8409 138.8409	138.8409	3.6600e- 003	3.7200e- 003	140.0409
Total	0.0565	0.0372	0.4656 1.3600e- 003	1.3600e- 003	0.1677	8.3000e- 004	0.1685	0.0445	7.6000e- 004	0.0452		138.8409	138.8409	3.6600e- 003	3.7200e- 003	140.0409

3.7 Architectural Coating - 2023 **Unmitigated Construction On-Site**

		•		
eCO2e		0.0000	281.8690	281.8690
N20				
CH4	ay		0.0168	0.0168
Total CO2	lb/day	0.000.0	281.4481 281.4481	281.4481 281.4481
Bio- CO2 NBio- CO2 Total CO2			281.4481	281.4481
Bio- CO2				
PM2.5 Total		0.0000	0.0708	0.0708
Exhaust PM2.5		0.0000 0.0000	0.0708	0.0708
Fugitive PM2.5				
PM10 Total		0.000.0	0.0708	0.0708
Exhaust PM10	b/day	0.0000 0.0000	0.0708	0.0708
Fugitive PM10)/qI			
805			2.9700e- 003	2.9700e- 003
00			1.8111	1.8111
×ON			0.1917 1.3030 1.8111 2.9700e- 003	19.1876 1.3030 1.8111 2.9700e- 003
ROG		18.9960	0.1917	19.1876
	Category	Archit. Coating 18.9960	Off-Road	Total

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.7 Architectural Coating - 2023 Unmitigated Construction Off-Site

	ROG	×ON	00	802	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	Bio- CO2 NBio- CO2 Total CO2	Total CO2	CH4	N20	CO2e
Category)/qı	lb/day							lb/day	ay		
Hauling	0.0000	0.0000 0.0000 0.0000 0.0000	0.000.0	0.0000		0.0000 0.0000 0.0000 0.0000	0.000.0	0.0000	0.0000	0.0000		0.0000	0.0000 0.0000 0.0000 0.0000 0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000 0.0000 0.0000 0.0000	0.000.0	0.0000	0.0000	0.0000	0.0000	0.0000	0.000.0	0.0000		0.0000	0.0000	0.000.0	0.0000	0.0000
Worker	0.1544	0.1544 0.1017	1.2726	1.2726 3.7100e- 0.4583 003	0.4583	2.2600e- 003	0.4606	0.1215	2.0800e- 003	0.1236		379.4984	379.4984 379.4984	0.0100	0.0102	382.7785
Total	0.1544	0.1544 0.1017 1.2726 3.7100e- 0.4583 0.4583	1.2726	3.7100e- 003	0.4583	2.2600e- 003	0.4606	0.1215	2.0800e- 003	0.1236		379.4984	379.4984 379.4984	0.0100	0.0102	382.7785

N2O CO2e		0.0000	281.8690	281.8690
CH4 N3	ay		0.0168	0.0168
Total CO2	lb/day	0.0000	281.4481	281.4481
Bio- CO2 NBio- CO2 Total CO2			0.0000 281.4481 281.4481	0.0000 281.4481 281.4481
Bio-CO2		1-8-8-8-8	0.0000	0.000
PM2.5 Total		0.0000	0.0708	0.0708
Exhaust PM2.5		0.0000 0.0000	0.0708	0.0708
Fugitive PM2.5				
PM10 Total		0.0000	0.0708	0.0708
Exhaust PM10	b/day	0.0000 0.0000	0.0708	0.0708
Fugitive PM10	/ql			
SO2			2.9700e- 003	2.9700e- 003
00			1.8111	1.8111
XON			0.1917 1.3030 1.8111 2.9700e- 003	19.1876 1.3030 1.8111 2.9700e- 003
ROG		18.9960	0.1917	19.1876
	Category	Archit. Coating 18.9960	Off-Road	Total

CalEEMod Version: CalEEMod.2020.4.0

Page 22 of 28

Date: 2/7/2022 2:17 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.7 Architectural Coating - 2023 Mitigated Construction Off-Site

				10	10
CO2e		0.0000	0.0000	382.7785	382.7785
NZO		0.0000	0.0000	0.0102	0.0102
CH4	ау	0.000.0	0.000.0	0.0100	0.0100
Total CO2	lb/day	0.0000 0.0000 0.0000	0.0000	379.4984 379.4984	379.4984
Bio- CO2 NBio- CO2 Total CO2		0.000.0	0.000.0	379.4984	379.4984
Bio- CO2					
PM2.5 Total		0.0000	0.0000	0.1236	0.1236
Exhaust PM2.5			0.0000	2.0800e- 003	2.0800e- 003
Fugitive PM2.5		0.0000 0.0000 0.0000	0.000.0	0.1215	0.1215
PM10 Total		0.000.0	0.000.0	0.4606	0.4606
Exhaust PM10	b/day	0.0000	0.0000	2.2600e- 003	2.2600e- 003
Fugitive PM10	p/ql	0.0000	0.0000	0.4583	0.4583
S02		0.000.0	0.0000	.7100e- 003	3.7100e- 003
00		0.000.0	0.000.0	1.2726	0.1017 1.2726 3.7100e-
×ON		0.0000	0.0000	0.1017	0.1017
ROG		0.0000 0.0000 0.0000 0.0000	0.0000	0.1544	0.1544
	Category	Hauling	Vendor	Worker	Total

4.0 Operational Detail - Mobile

4.1 Mitigation Measures Mobile

Increase Transit Accessibility

Improve Pedestrian Network

Page 23 of 28

Date: 2/7/2022 2:17 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

CO2e		10,403.91 63	13,625.81 82
N20		1.3027	1.7008
CH4	ау	0.3676	0.4716
Total CO2	lb/day	10,006.50 76	13,107.20 66
Bio- CO2 NBio- CO2 Total CO2 CH4		10,006.50 10,006.50 0.3676 1.3027 10,403.91 76 76 53	13,107.20 13,107.20 0.4716 1.7008 13,625.81 66 66 8
PM2.5 Total		1.4678	1.9340
		0.1603 4.9298 1.3147 0.1531 1.4678	0.2108 6.4969 1.7328 0.2012 1.9340
Fugitive Exhaust PM2.5	lay	1.3147	6.4969 1.7328 0.2012
PM10 Total		4.9298	6.4969
Exhaust PM10		0.1603	0.2108
Fugitive PM10	lb/day		
S02		0.0936	0.1226
00		11.5047	14.2675
×ON		1.0764 15.5457 11.5047 0.0936 4.7694	19.9414
ROG		1.0764	1.2581
	Category	Mitigated	Unmitigated 1.2581 19.9414 14.2675 0.1226 6.2861

4.2 Trip Summary Information

	Avei	Average Daily Trip Rate	ite	Unmitigated	Mitigated
Land Use	Weekday	Saturday	Sunday	Annual VMT	Annual VMT
Parking Lot	112.99	112.99	112.99	1,645,198	1,248,255
Unrefrigerated Warehouse-No Rail	'`'	251.70	251.70	1,078,696	818,435
Total	364.69	364.69	364.69	2,723,895	2,066,689

4.3 Trip Type Information

% :	Pass-by	6.90 0.00 100.00 0.00 100 0	က
Trip Purpose %	Diverted	0	5
	Primary	100	92
	H-O or C-NW	0.00	41.00
Trip %	H-S or C-C	100.00	00.00
	H-W or C-W	00.0	29.00
	H-O or C-NW H-W or C-W H-S or C-C H-O or C-NW	9.90	96.90
Miles	H-S or C-C	40.00	8.40
	H-W or C-W H-S or C-C	16.60	16.60
	Land Use	Parking Lot 16.60 40.00	Unrefrigerated Warehouse-No

4.4 Fleet Mix

Land Use	PDA	LDT1	LDT2	MDV	LHD1	LHD2	MHD	ОНН	OBUS	NBUS	MCY	SBUS	MH
Parking Lot	0.000000	0.000000	0.000000 0.000000 0.000000 0.000000	0.000000	0.00000.0	0.221000	0.221000 0.177000	0.602000	0.000000	0.000000	0.000000	0.00000.0	0.000000
Unrefrigerated Warehouse-No 0.579000 Rail	0.579000	0.059000	0.579000 0.059000 0.185000 0.150	0.150000	0.000000	0.000000	0.000000 0.000000 0.0000000 0.0000000 0.000000	0.000000 0.000000	0.00000.0	0.00000.0	0.027000	0.00000.0	0.000000

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

5.0 Energy Detail

Historical Energy Use: N

5.1 Mitigation Measures Energy

CO2e		169.1076	169.1076	
N2O		168.1086 168.1086 3.2200e- 3.0800e- 169.1076 003	168.1086 168.1086 3.2200e- 3.0800e- 169.1076 003 003	
CH4	lay	3.2200e- 003	3.2200e- 003	
Total CO2	lb/day	168.1086	168.1086	
Bio- CO2 NBio- CO2 Total CO2		168.1086	168.1086	
Bio- CO2				
PM2.5 Total		0.0107	0.0107	
Exhaust PM2.5		0.0107 0.0107	0.0107 0.0107	
Fugitive PM2.5				
PM10 Total	ау		0.0107	0.0107
Exhaust PM10		0.0107	0.0107 0.0107	
Fugitive PM10	lb/day			
SO2		8.4000e- 004	8.4000e- 004	
00		0.1177	0.1177	
NOx		0.1401	0.1401	
ROG		0.0154 0.1401 0.1177 8.4000e-	0.0154 0.1401 0.1177 8.4000e-	
	Category		NaturalGas Unmitigated	

Page 25 of 28 CalEEMod Version: CalEEMod.2020.4.0

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

Date: 2/7/2022 2:17 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

5.2 Energy by Land Use - NaturalGas

Unmitigated

C02e		0.0000	169.1076	169.1076
NZO		0.0000	3.0800e- 003	3.0800e- 003
CH4	я̀у	0.0000		3.2200e- 003
Total CO2	lb/day	0.0000 0.0000 0.0000 0.0000	168.1086 168.1086 3.2200e-	3 168.1086 3.2200e- 003
Bio- CO2 NBio- CO2 Total CO2		0.0000	168.1086	168.1086
Bio- CO2				
PM2.5 Total		0.0000	0.0107	0.0107
Exhaust PM2.5		0.0000	0.0107	0.0107
Fugitive PM2.5				
PM10 Total		0.0000	0.0107	0.0107
Exhaust PM10	lb/day	0.0000 0.0000	0.0107	0.0107
Fugitive PM10	/qı			
S02		0.0000	8.4000e- 004	8.4000e- 004
00		0.0000	0.1177	0.1177
NOx		0.0000	0.1401 0.1177	0.1401 0.1177 8.4000e-
ROG		0.0000	1428.92 0.0154	0.0154
NaturalGa s Use	kBTU/yr	0	1428.92	
	Land Use	Parking Lot 0.0000 0.0000 0.0000 0.0000	Unrefrigerated Warehouse-No Rail	Total

Mitigated

C02e		0.0000	169.1076	169.1076		
N2O		0.0000 0.0000 0.0000 0.0000	3.0800e- 003	3.0800e- 16 003		
CH4	ay	0.0000	3.2200e- 003	3.2200e- 003		
Total CO2	lb/day	0.000.0	168.1086 168.1086 3.2200e-	168.1086 168.1086 3.2200e-		
Bio- CO2 NBio- CO2 Total CO2		0.000.0	168.1086	168.1086		
Bio- CO2						
PM2.5 Total		0.0000	0.0107	0.0107		
Exhaust PM2.5		0.000.0	0.0107	0.0107		
Fugitive PM2.5						
PM10 Total	lb/day			0.000.0	0.0107	0.0107
Exhaust PM10		0.000.0 0.000.0	0.0107	0.0107		
Fugitive PM10)/qI					
SO2		0.0000	8.4000e- 004	8.4000e- 004		
00		0.0000	0.1177	0.1401 0.1177 8.4000e-		
NOx		0.0000	0.1401	0.1401		
ROG		0.0000 0.0000 0.0000	1.42892 0.0154 0.1401 0.1177	0.0154		
NaturalGa s Use	kBTU/yr	0	1.42892			
	Land Use	Parking Lot	Unrefrigerated Warehouse-No Rail	Total		

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

6.1 Mitigation Measures Area

CO2e		0.0618	0.0618
N20	/kep/qI		
CH4		1.5000e- 004) 1.5000e- 004
Total CO2		0.058(0.058(
Bio- CO2 NBio- CO2 Total CO2		0.0580 0.0580 1.5000e-	0.0580
Bio- CO2			
PM2.5 Total	lb/day	1.0000e- 1.0000e- 004 004	1.0000e- 004
Exhaust PM2.5		1.0000e- 004	1.0000e- 004
Fugitive PM2.5			
PM10 Total		1.0000e- 1.0000e- 004 004	1.0000e- 004
Exhaust PM10		1.0000e- 004	1.0000e- 004
Fugitive PM10			
SO2		0.000.0	0.0000
00		0.0270	0.0270
XON		5.8982 2.5000e- 0.0270 0.0000 004	2.5000e- 004
ROG		5.8982	5.8982 2.5000e- 0.0270 0.0000 004
	Category	Mitigated	Unmitigated

6.2 Area by SubCategory

Unmitigated

CO2e	lb/day	0.0000	0.0000	0.0618	0.0618
N20					
CH4				1.5000e- 004	1.5000e- 004
Total CO2		0.000.0	0.0000	0.0580	0.0580
Bio- CO2 NBio- CO2 Total CO2				0.0580	0.0580
Bio- CO2					
PM2.5 Total	lb/day	0.0000	0.0000	1.0000e- 004	1.0000e- 004
Exhaust PM2.5		0.000.0	0.000.0	1.0000e- 004	1.0000e- 004
Fugitive PM2.5					
PM10 Total		0.0000	0.0000	- 1.0000e- 004	1.0000e- 004
Exhaust PM10		0.0000	0.0000	1.0000e- 004	1.0000e- 1 004
Fugitive PM10					
SO2				0.0000	0.0000
CO				0.0270	0.0270
XON				2.5000e- 004	5.8981 2.5000e- 0.0270 004
ROG		0.6763	5.2193	2.5000e- 2.5000e- (003 004	5.8981
	SubCategory		•	Landscaping	Total

Page 27 of 28

Date: 2/7/2022 2:17 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

6.2 Area by SubCategory

Mitigated

CO2e		0.0000	0.0000	0.0618	0.0618									
N20														
CH4	зу			1.5000e- 004	1.5000e- 004									
Total CO2	lb/c	lb/day	p/qI	p/qI	lb/ds	p/dl	lb/ds	lb/da)/qI	p/qı	0.0000	0.0000	0.0580	0.0580
NBio- CO2				 	0.0580	0.0580								
Bio- CO2 NBio- CO2 Total CO2			L ! ! ! !	L ! ! ! !										
PM2.5 Total		0.000	0.000.0	1.0000e- 004	1.0000e- 004									
Exhaust PM2.5	lb/day						1.0000e- 004	1.0000e- 004						
Fugitive PM2.5														
PM10 Total		0.0000	0.0000	1.0000e- 004	1.0000e- 004									
Exhaust PM10		0.000.0	0.0000	1.0000e- 004	1.0000e- 004									
Fugitive PM10			 	 										
S02			 	0.000.0	0.000									
00			 	0.0270	0.0270									
×ON			 	- 2.5000e- 0.0270 (2.5000e- 004									
ROG		0.6763	5.2193	2.5000e- 2.	5.8981									
	SubCategory		Consumer Products	Landscaping	Total									

7.0 Water Detail

7.1 Mitigation Measures Water

Install Low Flow Bathroom Faucet

Install Low Flow Kitchen Faucet

Install Low Flow Toilet

Use Water Efficient Irrigation System

8.0 Waste Detail

8.1 Mitigation Measures Waste

Institute Recycling and Composting Services

9.0 Operational Offroad

Date: 2/7/2022 2:17 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Fuel Type	0.20 CNG
Load Factor	0.20
Horse Power	68
Days/Year	260
Hours/Day	2.00
Number	4
Equipment Type	Forklifts

UnMitigated/Mitigated

Φ		526	926
CO2e		682.2526	682.2526
N20			
CH4	ay	0.2189	0.2189
Total CO2	lb/day	676.7805	676.7805
NBio- CO2		676.7805	0.0000 676.7805 676.7805
Bio- CO2 NBio- CO2 Total CO2		0.0000	0.0000
PM2.5 Total		0.0400 0.0400 0.0000 676.7805 676.7805 0.2189	0.0400
Exhaust PM2.5		0.0400	0.0400
Fugitive PM2.5			
PM10 Total		0.0400	0.0400
Exhaust PM10	lb/day	0.0400 0.0400	0.0400
Fugitive PM10			
S02		5.3500e- 003	2.4827 32.4407 5.3500e-
00		32.4407	32.4407
NOx		2.4827	2.4827
ROG		0.0510 2.4827 32.4407 5.3500e-	0.0510
	Equipment Type	Forklifts	Total

10.0 Stationary Equipment

Fire Pumps and Emergency Generators

Edaibilielle Lype	Boilers
Namber	
nouis/Day	
nodis/ redi	
Load Factor	
ruel i ype	

Fuel Type	
Boiler Rating	
Heat Input/Year	
Heat Input/Day	
Number	
Equipment Type	

User Defined Equipment

11.0 Vegetation

APPENDIX B

EMFAC2017 Model Printouts

EMFAC2017 (v1.0.2) Emissions Inventory

Region Type: Air Basin Region: SOUTH COAST

Calendar Year: 2022

Season: Annual

Vehicle Classification: EMFAC2007 Categories

Units: miles/day for VMT, trips/day for Trips, tons/day for Emissions, 1000 gallons/day for Fuel Consumption. Note 'day' in the unit is operation day.

1.875688287	7989.700531	1003.18171	3339.886942	583.2281345	110.1260053	54.92216124	2704.447563	62.96118679	259.391887	47.77312679	11.26572543	18.40085629
1544.534	30101253	3305301	10234301	2552988	432791.1	577512.7	7077024	3410.439	495865	116687.7	10252.29	3808.584
7790.40352	246404319.3	26563674.69	82381240.23	6138928.512	1009215.767	1994249.265	54105469.86	324253.0827	1316472.619	240794.901	102707.6059	952.146 89255.99818 3808.584
77.19581	6370883	716397.4	2182002	171358.6	29049.29	288756.3	1530646	34090.76	24783.34	5832.051	2563.073	952.146
Aggregater Aggregater GAS	Aggregater Aggregater GAS	Aggregater Aggregater GAS	Aggregater Aggregater GAS	Aggregater Aggregater GAS	Aggregater Aggregater GAS	Aggregater Aggregater GAS	Aggregater Aggregater GAS	Aggregater Aggregater GAS	Aggregater Aggregater GAS	Aggregater Aggregater GAS	Aggregater Aggregater GAS	Aggregater Aggregater GAS
2022 HHDT	2022 LDA	2022 LDT1	2022 LDT2	2022 LHDT1	2022 LHDT2	2022 MCY	2022 MDV	2022 MH	2022 MHDT	2022 OBUS	2022 SBUS	2022 UBUS
SOUTH CO,	SOUTH CO,	SOUTH CO,	SOUTH CO,	SOUTH CO,	SOUTH CO,	SOUTH CO,	SOUTH CO,	SOUTH CO,	SOUTH CO,	SOUTH CO,	SOUTH CO,	SOUTH CO.
	2022 HHDT Aggregater Aggregater GAS 77.19581 7790.40352 1544.534	2022 HHDT Aggregater Aggregater GAS 77.19581 7790.40352 1544.534 2022 LDA Aggregater Aggregater GAS 6370883 246404319.3 30101253	2022 HHDT Aggregater Aggregater GAS 77.19581 7790.40352 1544.534 1 2022 LDA Aggregater Aggregater GAS 6370883 246404319.3 30101253 7 2022 LDT1 Aggregater Aggregater GAS 716397.4 26563674.69 3305301	2022 HHDT Aggregater Aggregater GAS 77.19581 7790.40352 1544.534 2022 LDA Aggregater Aggregater GAS 6370883 246404319.3 30101253 2022 LDT1 Aggregater Aggregater GAS 716397.4 26563674.69 3305301 2022 LDT2 Aggregater Aggregater GAS 2182002 82381240.23 10234301	2022 HHDT Aggregater Aggregater GAS 77.19581 7790.40352 1544.534 2022 LDA Aggregater Aggregater GAS 6370883 246404319.3 30101253 2022 LDT1 Aggregater Aggregater GAS 716397.4 26563674.69 3305301 2022 LDT2 Aggregater Aggregater GAS 2182002 82381240.23 10234301 2022 LHDT1 Aggregater Aggregater GAS 171358.6 6138928.512 2552988	2022 HHDT Aggregatec Aggregatec GAS 77.19581 7790.40352 1544.534 2022 LDA Aggregatec Aggregatec GAS 6370883 246404319.3 30101253 2022 LDT Aggregatec Aggregatec GAS 716397.4 26563674.69 3305301 2022 LDT Aggregatec Aggregatec GAS 2182002 82381240.23 10234301 2022 LHDT Aggregatec Aggregatec GAS 171358.6 6138928.512 2552988 2022 LHDT Aggregatec Aggregatec GAS 29049.29 1009215.767 432791.1	2022 HHDT Aggregater Aggregater GAS 77.19581 7790.40352 1544.534 2022 LDA Aggregater Aggregater GAS 6370883 246404319.3 30101253 2022 LDT1 Aggregater Aggregater GAS 716397.4 26563674.69 3305301 2022 LDT2 Aggregater Aggregater GAS 2182002 82381240.23 10234301 2022 LHDT1 Aggregater Aggregater GAS 171358.6 6138928.512 2552988 2022 LHDT2 Aggregater Aggregater GAS 29049.29 1009215.767 432791.1 2022 LHDT3 Aggregater Aggregater GAS 288756.3 1994249.265 577512.7	2022 HHDT Aggregater Aggregater GAS 77.19581 7790.40352 1544.534 2022 LDA Aggregater Aggregater GAS 716397.4 26563674.69 3305301 2022 LDT2 Aggregater Aggregater GAS 2182002 82381240.23 10234301 2022 LHDT Aggregater Aggregater GAS 171358.6 6138928.512 2552988 2022 LHDT Aggregater Aggregater GAS 29049.29 1009215.767 432791.1 2022 LHDT Aggregater Aggregater GAS 288756.3 1994249.265 577512.7 2022 MDV Aggregater Aggregater GAS 1530646 54105469.86 7077024	2022 HHDT Aggregater Aggregater GAS 77.19581 7790.40352 1544.534 2022 LDA Aggregater Aggregater GAS 6370883 246404319.3 30101253 2022 LDT Aggregater Aggregater GAS 716397.4 26563674.69 3305301 2022 LDT2 Aggregater Aggregater GAS 171358.6 6138928.512 2552988 2022 LHDT3 Aggregater Aggregater GAS 29049.29 1009215.767 432791.1 2022 LHDT2 Aggregater Aggregater GAS 288756.3 1994249.265 577512.7 2022 MCY Aggregater Aggregater GAS 1530646 54105469.86 7077024 2022 MDV Aggregater Aggregater GAS 34090.76 324253.0827 3410.439	2022 HHDT Aggregater Aggregater GAS 77.19581 7790.40352 1544.534 1 2022 LDA Aggregater Aggregater GAS 716397.4 26563674.69 3305301 3 2022 LDT1 Aggregater Aggregater GAS 2182002 82381240.23 10234301 3 2022 LDT2 Aggregater Aggregater GAS 171358.6 6138928.512 2552988 5 2022 LHDT2 Aggregater Aggregater GAS 29049.29 1009215.767 432791.1 1 2022 LHDT2 Aggregater Aggregater GAS 288756.3 1994249.265 577512.7 5 2022 MCY Aggregater Aggregater GAS 1530646 54105469.86 7077024 2 2022 MDV Aggregater Aggregater GAS 34090.76 324253.0827 3410.439 6 2022 MHDT Aggregater Aggregater GAS 24783.34 1316472.619 495865 6	2022 HHDT Aggregatec Aggregatec GAS 77.19581 7790.40352 1544.534 1 2022 LDA Aggregatec Aggregatec GAS 716397.4 26563674.69 3305301 3 2022 LDT1 Aggregatec Aggregatec GAS 2182002 82381240.23 10234301 3 2022 LDT2 Aggregatec Aggregatec GAS 171358.6 6138928.512 2552988 5 2022 LHDT2 Aggregatec Aggregatec GAS 29049.29 1009215.767 432791.1 1 2022 LHDT2 Aggregatec Aggregatec GAS 288756.3 1994249.265 577512.7 5 2022 MCY Aggregatec Aggregatec GAS 1530646 54105469.86 7077024 2 2022 MDV Aggregatec Aggregatec GAS 34090.76 324253.0827 3410.439 6 2022 MH Aggregatec Aggregatec GAS 24783.34 1316472.619 495865 4 2022 MHDT Aggregatec Aggregatec GAS 24783.34 1316472.619 495865 4	2022 HHDT Aggregater Aggregater GAS 77.19581 7790.40352 1544.534 1 2022 LDA Aggregater Aggregater GAS 71.6397.4 26563674.69 3305301 7 2022 LDT2 Aggregater Aggregater GAS 2182002 82381240.23 10234301 3 2022 LDT2 Aggregater Aggregater GAS 171358.6 6138928.512 2552988 5 2022 LHDT2 Aggregater Aggregater GAS 29049.29 1009215.767 432791.1 1 2022 LHDT2 Aggregater Aggregater GAS 288756.3 1994249.265 577512.7 5 2022 MCY Aggregater Aggregater GAS 1530646 54105469.86 7077024 2 2022 MDV Aggregater Aggregater GAS 34090.76 324253.0827 3410.439 6 2022 MHDT Aggregater Aggregater GAS 24783.34 1316472.619 495865 2022 OBUS Aggregater Aggregater GAS 5832.051 240794.901 116687.7 4 2022 SBUS Aggregater Aggregater GAS 2563.073 102707.6059 10252.29 1

16,187 1,000 gall per day 16,187,162 gallons per day 420678372 vehicle miles per day (All Categories)

Fleet Avg Miles per gallon 26.0

EMFAC2017 (v1.0.2) Emissions Inventory

Region Type: Air Basin

Region: SOUTH COAST Calendar Year: 2022

Season: Annual

Vehicle Classification: EMFAC2007 Categories

Units: miles/day for VMT, trips/day for Trips, tons/day for Emissions, 1000 gallons/day for Fuel Consumption. Note 'day' in the unit is operation day.

Region	Calendar Y Vehicle C	Region Calendar Y Vehicle Cat Model Yea Speed Fuel	Population VMT		Trips	Fuel Consumption
SOUTH CO	2022 HHDT	Aggregater Aggregater DSL	98507.93	11795119.18	98507.93 11795119.18 994224.5278 1762.986535	1762.986535
SOUTH CO.		Aggregater Aggregater DSL	57443	2304136.238	57443 2304136.238 272823.0302 47.39159146	47.39159146
SOUTH CO		Aggregater Aggregater DSL	378.1209	8809.098622	378.1209 8809.098622 1319.110799 0.391172549	0.391172549
SOUTH CO.		Aggregater Aggregater DSL	13854.2	592642.9638	13854.2 592642.9638 68308.95137 16.65070839	16.65070839
SOUTH CO		Aggregater Aggregater DSL	115788.9	4681447.455	115788.9 4681447.455 1456478.318 217.1134019	217.1134019
SOUTH CO		Aggregater Aggregater DSL	45909.32	1809192.293	45909.32 1809192.293 577481.5034 92.8866097	92.8866097
SOUTH CO		Aggregater Aggregater DSL	32417.61	1305872.927	32417.61 1305872.927 158948.6889 47.80332863	47.80332863
SOUTH CO.		Aggregater Aggregater DSL	12198.84	117488.268	12198.84 117488.268 1219.883938 11.12023591	11.12023591
SOUTH CO.		Aggregater Aggregater DSL	119796	7716034.126	119796 7716034.126 1201941.571 720.1602731	720.1602731
SOUTH CO.		Aggregater Aggregater DSL	4149.674	316404.315	4149.674 316404.315 40441.57981 37.45917989	37.45917989
SOUTH CO.	2022 SBUS	Aggregater Aggregater DSL	6354.465	200786.3158	6354,465 200786.3158 73329.64442 26.4174734	26.4174734
SOUTH CO.		Aggregater Aggregater DSL	14.14142	1478.085683	14.14142 1478.085683 56.56567323 0.246796198	0.246796198

Diesel Truck (HHDT, MDV, MHDT) vehicle miles per day 20,817,026

2,531 1,000 gall per day 2,530,950 gallons per day

Diesel Truck Fleet Avg Miles per gallon

8.2

calendar	season	vehicle		relativ	e		speed		emission
year	month	sub_area class	fuel	tempe humid	ity	process	time	pollutant	rate
2023	Annual	San Bernardin Truck1	Dsl	52	50	RUNEX	10	PM10	0.048205
2023	Annual	San Bernardin Truck1	Dsl	52	50	RUNEX	40	PM10	0.016652
2023	Annual	San Bernardin Truck1	Gas	52	50	RUNEX	10	PM10	0.004982
2023	Annual	San Bernardin Truck1	Gas	52	50	RUNEX	40	PM10	0.000991
2023	Annual	San Bernardin Truck2	Dsl	52	50	RUNEX	10	PM10	0.009399
2023	Annual	San Bernardin Truck2	Dsl	52	50	RUNEX	40	PM10	0.008777
2023	Annual	San Bernardin Truck2	Gas	52	50	RUNEX	10	PM10	0.004484
2023	Annual	San Bernardin Truck2	Gas	52	50	RUNEX	40	PM10	0.000866
2023	Annual	San Bernardin Truck2	NG	52	50	RUNEX	10	PM10	0.009576
2023	Annual	San Bernardin Truck2	NG	52	50	RUNEX	40	PM10	0.004291
2023	Annual	San Bernardin Truck1	Dsl			IDLEX		PM10	0.791841
2023	Annual	San Bernardin Truck1	Dsl			PMTW		PM10	0.012
2023	Annual	San Bernardin Truck1	Dsl			PMBW		PM10	0.079945
2023	Annual	San Bernardin Truck1	Gas			PMTW		PM10	0.008
2023	Annual	San Bernardin Truck1	Gas			PMBW		PM10	0.078334
2023	Annual	San Bernardin Truck2	Dsl			IDLEX		PM10	0.015552
2023	Annual	San Bernardin Truck2	Dsl			PMTW		PM10	0.027433
2023	Annual	San Bernardin Truck2	Dsl			PMBW		PM10	0.086228
2023	Annual	San Bernardin Truck2	Gas			PMTW		PM10	0.01205
2023	Annual	San Bernardin Truck2	Gas			PMBW		PM10	0.129908
2023	Annual	San Bernardin Truck2	NG			IDLEX		PM10	0.063031
2023	Annual	San Bernardin Truck2	NG			PMTW		PM10	0.036
2023	Annual	San Bernardin Truck2	NG			PMBW		PM10	0.06174
2024	Annual	San Bernardin Truck1	Dsl	52	50	RUNEX	10	PM10	0.045028
2024	Annual	San Bernardin Truck1	Dsl	52	50	RUNEX	40	PM10	0.015802
2024	Annual	San Bernardin Truck1	Gas	52	50	RUNEX	10	PM10	0.004926
2024	Annual	San Bernardin Truck1	Gas	52	50	RUNEX	40	PM10	0.000974
2024	Annual	San Bernardin Truck2	Dsl	52	50	RUNEX	10	PM10	0.009348
2024	Annual	San Bernardin Truck2	Dsl	52	50	RUNEX	40	PM10	0.008893
2024	Annual	San Bernardin Truck2	Gas	52	50	RUNEX	10	PM10	0.004489
2024	Annual	San Bernardin Truck2	Gas	52	50	RUNEX	40	PM10	0.000864
2024	Annual	San Bernardin Truck2	NG	52	50	RUNEX	10	PM10	0.009024
2024	Annual	San Bernardin Truck2	NG	52	50	RUNEX	40	PM10	0.004103
2024	Annual	San Bernardin Truck1	Dsl			IDLEX		PM10	0.791262
2024	Annual	San Bernardin Truck1	Dsl			PMTW		PM10	0.012
2024	Annual	San Bernardin Truck1	Dsl			PMBW		PM10	0.079957
2024	Annual	San Bernardin Truck1	Gas			PMTW		PM10	0.008
2024	Annual	San Bernardin Truck1	Gas			PMBW		PM10	0.078328
2024	Annual	San Bernardin Truck2	Dsl			IDLEX		PM10	0.01483
2024	Annual	San Bernardin Truck2	Dsl			PMTW		PM10	0.027427
2024	Annual	San Bernardin Truck2	Dsl			PMBW		PM10	0.086244
2024	Annual	San Bernardin Truck2	Gas			PMTW		PM10	0.012053
2024	Annual	San Bernardin Truck2	Gas			PMBW		PM10	0.129888

calendar	season		vehicle		relative	9		speed		emission
year	month	sub_area	class	fuel	tempe humidi	ty	process	time	pollutant	rate
-	Annual	San Bernardi	n Truck2	NG	•	•	IDLEX		PM10	0.057624
2024	Annual	San Bernardi	n Truck2	NG			PMTW		PM10	0.036
2024	Annual	San Bernardi	n Truck2	NG			PMBW		PM10	0.06174
2025	Annual	San Bernardi	n Truck1	Dsl	52	50	RUNEX	10	PM10	0.042095
2025	Annual	San Bernardi	n Truck1	Dsl	52	50	RUNEX	40	PM10	0.015013
2025	Annual	San Bernardi	n Truck1	Gas	52	50	RUNEX	10	PM10	0.004888
2025	Annual	San Bernardi	n Truck1	Gas	52	50	RUNEX	40	PM10	0.000962
2025	Annual	San Bernardi	n Truck2	Dsl	52	50	RUNEX	10	PM10	0.009235
2025	Annual	San Bernardi	n Truck2	Dsl	52	50	RUNEX	40	PM10	0.008925
2025	Annual	San Bernardi	n Truck2	Gas	52	50	RUNEX	10	PM10	0.004514
2025	Annual	San Bernardi	n Truck2	Gas	52	50	RUNEX	40	PM10	0.000866
2025	Annual	San Bernardi	n Truck2	NG	52	50	RUNEX	10	PM10	0.008514
2025	Annual	San Bernardi	n Truck2	NG	52	50	RUNEX	40	PM10	0.003933
2025	Annual	San Bernardi	n Truck1	Dsl			IDLEX		PM10	0.791555
2025	Annual	San Bernardi	n Truck1	Dsl			PMTW		PM10	0.012
2025	Annual	San Bernardi	n Truck1	Dsl			PMBW		PM10	0.079968
2025	Annual	San Bernardi	n Truck1	Gas			PMTW		PM10	0.008
2025	Annual	San Bernardi	n Truck1	Gas			PMBW		PM10	0.07832
2025	Annual	San Bernardi	n Truck2	Dsl			IDLEX		PM10	0.014209
2025	Annual	San Bernardi	n Truck2	Dsl			PMTW		PM10	0.027429
2025	Annual	San Bernardi	n Truck2	Dsl			PMBW		PM10	0.086238
2025	Annual	San Bernardi	n Truck2	Gas			PMTW		PM10	0.012055
2025	Annual	San Bernardi	n Truck2	Gas			PMBW		PM10	0.129868
2025	Annual	San Bernardi	n Truck2	NG			IDLEX		PM10	0.052635
2025	Annual	San Bernardi	n Truck2	NG			PMTW		PM10	0.036
2025	Annual	San Bernardi	n Truck2	NG			PMBW		PM10	0.06174
2026	Annual	San Bernardi	n Truck1	Dsl	52	50	RUNEX	10	PM10	0.039322
2026	Annual	San Bernardi	n Truck1	Dsl	52	50	RUNEX	40	PM10	0.01426
2026	Annual	San Bernardi	n Truck1	Gas	52	50	RUNEX	10	PM10	0.004863
2026	Annual	San Bernardi	n Truck1	Gas	52	50	RUNEX	40	PM10	0.000953
2026	Annual	San Bernardi	n Truck2	Dsl	52	50	RUNEX	10	PM10	0.009093
	Annual	San Bernardi		Dsl	52		RUNEX	40	PM10	0.008908
2026	Annual	San Bernardi	n Truck2	Gas	52	50	RUNEX	10	PM10	0.00455
	Annual	San Bernardi		Gas	52		RUNEX		PM10	0.000872
	Annual	San Bernardi		NG	52		RUNEX		PM10	0.008077
	Annual	San Bernardi		NG	52	50	RUNEX	40	PM10	0.003779
	Annual	San Bernardi		Dsl			IDLEX		PM10	0.791961
	Annual	San Bernardi		Dsl			PMTW		PM10	0.012
	Annual	San Bernardi		Dsl			PMBW		PM10	0.079978
	Annual	San Bernardi		Gas			PMTW		PM10	0.008
	Annual	San Bernardi		Gas			PMBW		PM10	0.07831
	Annual	San Bernardi		Dsl			IDLEX		PM10	0.013664
2026	Annual	San Bernardi	n Truck2	Dsl			PMTW		PM10	0.027438

calendar	season	vehicle		relative		speed		emission
year	month	sub_area class	fuel	tempe humidity	process	time	pollutant	rate
2026	Annual	San Bernardin Truck2	Dsl		PMBW		PM10	0.086214
2026	Annual	San Bernardin Truck2	Gas		PMTW		PM10	0.012057
2026	Annual	San Bernardin Truck2	Gas		PMBW		PM10	0.129847
2026	Annual	San Bernardin Truck2	NG		IDLEX		PM10	0.048338
2026	Annual	San Bernardin Truck2	NG		PMTW		PM10	0.036
2026	Annual	San Bernardin Truck2	NG		PMBW		PM10	0.06174
2027	Annual	San Bernardin Truck1	Dsl	52 50	RUNEX	10	PM10	0.036739
2027	Annual	San Bernardin Truck1	Dsl	52 50	RUNEX	40	PM10	0.013553
2027	Annual	San Bernardin Truck1	Gas	52 50	RUNEX	10	PM10	0.004863
2027	Annual	San Bernardin Truck1	Gas	52 50	RUNEX	40	PM10	0.00095
2027	Annual	San Bernardin Truck2	Dsl	52 50	RUNEX	10	PM10	0.008928
2027	Annual	San Bernardin Truck2	Dsl	52 50	RUNEX	40	PM10	0.008865
2027	Annual	San Bernardin Truck2	Gas	52 50	RUNEX	10	PM10	0.004587
2027	Annual	San Bernardin Truck2	Gas	52 50	RUNEX	40	PM10	0.000878
2027	Annual	San Bernardin Truck2	NG	52 50	RUNEX	10	PM10	0.007693
2027	Annual	San Bernardin Truck2	NG	52 50	RUNEX	40	PM10	0.003641
2027	Annual	San Bernardin Truck1	Dsl		IDLEX		PM10	0.792008
2027	Annual	San Bernardin Truck1	Dsl		PMTW		PM10	0.012
	Annual	San Bernardin Truck1	Dsl		PMBW		PM10	0.079987
2027	Annual	San Bernardin Truck1	Gas		PMTW		PM10	0.008
2027	Annual	San Bernardin Truck1	Gas		PMBW		PM10	0.078298
2027	Annual	San Bernardin Truck2	Dsl		IDLEX		PM10	0.013086
2027	Annual	San Bernardin Truck2	Dsl		PMTW		PM10	0.027446
2027	Annual	San Bernardin Truck2	Dsl		PMBW		PM10	0.08619
2027	Annual	San Bernardin Truck2	Gas		PMTW		PM10	0.01206
2027	Annual	San Bernardin Truck2	Gas		PMBW		PM10	0.129826
2027	Annual	San Bernardin Truck2	NG		IDLEX		PM10	0.044553
2027	Annual	San Bernardin Truck2	NG		PMTW		PM10	0.036
2027	Annual	San Bernardin Truck2	NG		PMBW		PM10	0.06174
	Annual	San Bernardin Truck1	Dsl	52 50	RUNEX	10	PM10	0.034364
2028	Annual	San Bernardin Truck1	Dsl		RUNEX	40	PM10	0.012895
	Annual	San Bernardin Truck1	Gas		RUNEX	10	PM10	0.004869
2028	Annual	San Bernardin Truck1	Gas	52 50	RUNEX	40	PM10	0.000948
2028	Annual	San Bernardin Truck2	Dsl	52 50	RUNEX	10	PM10	0.008804
2028	Annual	San Bernardin Truck2	Dsl		RUNEX	40	PM10	0.008828
	Annual	San Bernardin Truck2	Gas		RUNEX	10	PM10	0.004626
	Annual	San Bernardin Truck2	Gas		RUNEX		PM10	0.000884
	Annual	San Bernardin Truck2	NG		RUNEX		PM10	0.007422
	Annual	San Bernardin Truck2	NG	52 50	RUNEX	40	PM10	0.003523
	Annual	San Bernardin Truck1	Dsl		IDLEX		PM10	0.792393
	Annual	San Bernardin Truck1	Dsl		PMTW		PM10	0.012
	Annual	San Bernardin Truck1	Dsl		PMBW		PM10	0.079995
2028	Annual	San Bernardin Truck1	Gas		PMTW		PM10	0.008

calendar	season	vehicle		relative		speed		emission
year	month	sub_area class	fuel	tempe humidity	process	time	pollutant	rate
2028	Annual	San Bernardin Truck1	Gas		PMBW		PM10	0.078286
2028	Annual	San Bernardin Truck2	Dsl		IDLEX		PM10	0.012697
2028	Annual	San Bernardin Truck2	Dsl		PMTW		PM10	0.027463
2028	Annual	San Bernardin Truck2	Dsl		PMBW		PM10	0.086141
2028	Annual	San Bernardin Truck2	Gas		PMTW		PM10	0.012062
2028	Annual	San Bernardin Truck2	Gas		PMBW		PM10	0.129806
2028	Annual	San Bernardin Truck2	NG		IDLEX		PM10	0.041513
2028	Annual	San Bernardin Truck2	NG		PMTW		PM10	0.036
2028	Annual	San Bernardin Truck2	NG		PMBW		PM10	0.06174
2029	Annual	San Bernardin Truck1	Dsl	52 50	RUNEX	10	PM10	0.032167
2029	Annual	San Bernardin Truck1	Dsl	52 50	RUNEX	40	PM10	0.012281
2029	Annual	San Bernardin Truck1	Gas	52 50	RUNEX	10	PM10	0.004874
2029	Annual	San Bernardin Truck1	Gas	52 50	RUNEX	40	PM10	0.000944
2029	Annual	San Bernardin Truck2	Dsl	52 50	RUNEX	10	PM10	0.008666
2029	Annual	San Bernardin Truck2	Dsl	52 50	RUNEX	40	PM10	0.008775
2029	Annual	San Bernardin Truck2	Gas	52 50	RUNEX	10	PM10	0.004662
2029	Annual	San Bernardin Truck2	Gas	52 50	RUNEX	40	PM10	0.00089
2029	Annual	San Bernardin Truck2	NG	52 50	RUNEX	10	PM10	0.007109
	Annual	San Bernardin Truck2	NG	52 50	RUNEX	40	PM10	0.003419
2029	Annual	San Bernardin Truck1	Dsl		IDLEX		PM10	0.791921
2029	Annual	San Bernardin Truck1	Dsl		PMTW		PM10	0.012
2029	Annual	San Bernardin Truck1	Dsl		PMBW		PM10	0.080003
2029	Annual	San Bernardin Truck1	Gas		PMTW		PM10	0.008
2029	Annual	San Bernardin Truck1	Gas		PMBW		PM10	0.078275
2029	Annual	San Bernardin Truck2	Dsl		IDLEX		PM10	0.012283
2029	Annual	San Bernardin Truck2	Dsl		PMTW		PM10	0.027482
	Annual	San Bernardin Truck2	Dsl		PMBW		PM10	0.086088
2029	Annual	San Bernardin Truck2	Gas		PMTW		PM10	0.012064
2029	Annual	San Bernardin Truck2	Gas		PMBW		PM10	0.129788
	Annual	San Bernardin Truck2	NG		IDLEX		PM10	0.038425
	Annual	San Bernardin Truck2	NG		PMTW		PM10	0.036
2029	Annual	San Bernardin Truck2	NG		PMBW		PM10	0.06174
	Annual	San Bernardin Truck1	Dsl		RUNEX		PM10	0.030175
	Annual	San Bernardin Truck1	Dsl		RUNEX		PM10	0.011717
	Annual	San Bernardin Truck1	Gas		RUNEX		PM10	0.004872
	Annual	San Bernardin Truck1	Gas		RUNEX		PM10	0.000939
	Annual	San Bernardin Truck2	Dsl		RUNEX		PM10	0.008532
	Annual	San Bernardin Truck2	Dsl		RUNEX		PM10	0.008718
	Annual	San Bernardin Truck2	Gas		RUNEX		PM10	0.004698
	Annual	San Bernardin Truck2	Gas		RUNEX		PM10	0.000897
	Annual	San Bernardin Truck2	NG		RUNEX		PM10	0.006902
	Annual	San Bernardin Truck2	NG	52 50	RUNEX	40	PM10	0.003333
2030	Annual	San Bernardin Truck1	Dsl		IDLEX		PM10	0.791719

calendar	season	vehicle		relative		speed		emission
year	month	sub_area class	fuel	tempe humidity	process	time	pollutant	rate
2030	Annual	San Bernardin Truck1	Dsl		PMTW		PM10	0.012
2030	Annual	San Bernardin Truck1	Dsl		PMBW		PM10	0.080009
2030	Annual	San Bernardin Truck1	Gas		PMTW		PM10	0.008
2030	Annual	San Bernardin Truck1	Gas		PMBW		PM10	0.078263
2030	Annual	San Bernardin Truck2	Dsl		IDLEX		PM10	0.011879
2030	Annual	San Bernardin Truck2	Dsl		PMTW		PM10	0.027503
2030	Annual	San Bernardin Truck2	Dsl		PMBW		PM10	0.086027
2030	Annual	San Bernardin Truck2	Gas		PMTW		PM10	0.012066
2030	Annual	San Bernardin Truck2	Gas		PMBW		PM10	0.129774
2030	Annual	San Bernardin Truck2	NG		IDLEX		PM10	0.035948
2030	Annual	San Bernardin Truck2	NG		PMTW		PM10	0.036
2030	Annual	San Bernardin Truck2	NG		PMBW		PM10	0.06174
2031	Annual	San Bernardin Truck1	Dsl	52 50	RUNEX	10	PM10	0.02839
2031	Annual	San Bernardin Truck1	Dsl	52 50	RUNEX	40	PM10	0.011206
2031	Annual	San Bernardin Truck1	Gas	52 50	RUNEX	10	PM10	0.004867
2031	Annual	San Bernardin Truck1	Gas	52 50	RUNEX	40	PM10	0.000933
2031	Annual	San Bernardin Truck2	Dsl	52 50	RUNEX	10	PM10	0.008412
2031	Annual	San Bernardin Truck2	Dsl	52 50	RUNEX	40	PM10	0.008667
2031	Annual	San Bernardin Truck2	Gas	52 50	RUNEX	10	PM10	0.004732
2031	Annual	San Bernardin Truck2	Gas	52 50	RUNEX	40	PM10	0.000903
2031	Annual	San Bernardin Truck2	NG	52 50	RUNEX	10	PM10	0.006711
2031	Annual	San Bernardin Truck2	NG	52 50	RUNEX	40	PM10	0.00326
2031	Annual	San Bernardin Truck1	Dsl		IDLEX		PM10	0.791242
2031	Annual	San Bernardin Truck1	Dsl		PMTW		PM10	0.012
2031	Annual	San Bernardin Truck1	Dsl		PMBW		PM10	0.080015
2031	Annual	San Bernardin Truck1	Gas		PMTW		PM10	0.008
2031	Annual	San Bernardin Truck1	Gas		PMBW		PM10	0.078251
2031	Annual	San Bernardin Truck2	Dsl		IDLEX		PM10	0.011528
2031	Annual	San Bernardin Truck2	Dsl		PMTW		PM10	0.027519
2031	Annual	San Bernardin Truck2	Dsl		PMBW		PM10	0.085981
2031	Annual	San Bernardin Truck2	Gas		PMTW		PM10	0.012068
2031	Annual	San Bernardin Truck2	Gas		PMBW		PM10	0.129761
2031	Annual	San Bernardin Truck2	NG		IDLEX		PM10	0.033764
2031	Annual	San Bernardin Truck2	NG		PMTW		PM10	0.036
2031	Annual	San Bernardin Truck2	NG		PMBW		PM10	0.06174
	Annual	San Bernardin Truck1	Dsl		RUNEX	10	PM10	0.026818
	Annual	San Bernardin Truck1	Dsl		RUNEX	40	PM10	0.01075
	Annual	San Bernardin Truck1	Gas		RUNEX		PM10	0.004865
	Annual	San Bernardin Truck1	Gas		RUNEX		PM10	0.000928
	Annual	San Bernardin Truck2	Dsl		RUNEX		PM10	0.008319
	Annual	San Bernardin Truck2	Dsl		RUNEX		PM10	0.008625
	Annual	San Bernardin Truck2	Gas		RUNEX		PM10	0.004759
2032	Annual	San Bernardin Truck2	Gas	52 50	RUNEX	40	PM10	0.000908

calendar	season	vehicle		relati	ve		speed		emission
year	month	sub_area class	fuel	tempe humi	dity	process	time	pollutant	rate
2032	Annual	San Bernardin Truck2	NG	52	50	RUNEX	10	PM10	0.006524
2032	Annual	San Bernardin Truck2	NG	52	50	RUNEX	40	PM10	0.003193
2032	Annual	San Bernardin Truck1	Dsl			IDLEX		PM10	0.791768
2032	Annual	San Bernardin Truck1	Dsl			PMTW		PM10	0.012
2032	Annual	San Bernardin Truck1	Dsl			PMBW		PM10	0.08002
2032	Annual	San Bernardin Truck1	Gas			PMTW		PM10	0.008
2032	Annual	San Bernardin Truck1	Gas			PMBW		PM10	0.078238
2032	Annual	San Bernardin Truck2	Dsl			IDLEX		PM10	0.011322
2032	Annual	San Bernardin Truck2	Dsl			PMTW		PM10	0.027536
2032	Annual	San Bernardin Truck2	Dsl			PMBW		PM10	0.085933
2032	Annual	San Bernardin Truck2	Gas			PMTW		PM10	0.012069
2032	Annual	San Bernardin Truck2	Gas			PMBW		PM10	0.12975
2032	Annual	San Bernardin Truck2	NG			IDLEX		PM10	0.031668
2032	Annual	San Bernardin Truck2	NG			PMTW		PM10	0.036
2032	Annual	San Bernardin Truck2	NG			PMBW		PM10	0.06174
2033	Annual	San Bernardin Truck1	Dsl	52	50	RUNEX	10	PM10	0.02543
2033	Annual	San Bernardin Truck1	Dsl	52	50	RUNEX	40	PM10	0.010342
2033	Annual	San Bernardin Truck1	Gas	52	50	RUNEX	10	PM10	0.004854
2033	Annual	San Bernardin Truck1	Gas	52	50	RUNEX	40	PM10	0.000926
2033	Annual	San Bernardin Truck2	Dsl	52	50	RUNEX	10	PM10	0.008228
2033	Annual	San Bernardin Truck2	Dsl	52	50	RUNEX	40	PM10	0.008584
2033	Annual	San Bernardin Truck2	Gas	52	50	RUNEX	10	PM10	0.004782
2033	Annual	San Bernardin Truck2	Gas	52	50	RUNEX	40	PM10	0.000913
2033	Annual	San Bernardin Truck2	NG	52	50	RUNEX	10	PM10	0.006404
2033	Annual	San Bernardin Truck2	NG	52	50	RUNEX	40	PM10	0.003139
2033	Annual	San Bernardin Truck1	Dsl			IDLEX		PM10	0.79231
2033	Annual	San Bernardin Truck1	Dsl			PMTW		PM10	0.012
2033	Annual	San Bernardin Truck1	Dsl			PMBW		PM10	0.080024
2033	Annual	San Bernardin Truck1	Gas			PMTW		PM10	0.008
2033	Annual	San Bernardin Truck1	Gas			PMBW		PM10	0.078226
2033	Annual	San Bernardin Truck2	Dsl			IDLEX		PM10	0.011129
2033	Annual	San Bernardin Truck2	Dsl			PMTW		PM10	0.027554
2033	Annual	San Bernardin Truck2	Dsl			PMBW		PM10	0.08588
2033	Annual	San Bernardin Truck2	Gas			PMTW		PM10	0.01207
2033	Annual	San Bernardin Truck2	Gas			PMBW		PM10	0.129741
2033	Annual	San Bernardin Truck2	NG			IDLEX		PM10	0.030319
2033	Annual	San Bernardin Truck2	NG			PMTW		PM10	0.036
2033	Annual	San Bernardin Truck2	NG			PMBW		PM10	0.06174
2034	Annual	San Bernardin Truck1	Dsl	52	50	RUNEX	10	PM10	0.024156
2034	Annual	San Bernardin Truck1	Dsl	52	50	RUNEX	40	PM10	0.009962
2034	Annual	San Bernardin Truck1	Gas	52	50	RUNEX	10	PM10	0.00482
2034	Annual	San Bernardin Truck1	Gas	52	50	RUNEX	40	PM10	0.00092
2034	Annual	San Bernardin Truck2	Dsl	52	50	RUNEX	10	PM10	0.008131

calendar	season	vehicle		relat	ive		speed		emission
year	month	sub_area class	fuel	tempe humi	idity	process	time	pollutant	rate
2034	Annual	San Bernardin Truck2	Dsl	52	50	RUNEX	40	PM10	0.008534
2034	Annual	San Bernardin Truck2	Gas	52	50	RUNEX	10	PM10	0.004801
2034	Annual	San Bernardin Truck2	Gas	52	50	RUNEX	40	PM10	0.000916
2034	Annual	San Bernardin Truck2	NG	52	50	RUNEX	10	PM10	0.006298
2034	Annual	San Bernardin Truck2	NG	52	50	RUNEX	40	PM10	0.003095
2034	Annual	San Bernardin Truck1	Dsl			IDLEX		PM10	0.791977
2034	Annual	San Bernardin Truck1	Dsl			PMTW		PM10	0.012
2034	Annual	San Bernardin Truck1	Dsl			PMBW		PM10	0.080027
2034	Annual	San Bernardin Truck1	Gas			PMTW		PM10	0.008
2034	Annual	San Bernardin Truck1	Gas			PMBW		PM10	0.078215
2034	Annual	San Bernardin Truck2	Dsl			IDLEX		PM10	0.010938
2034	Annual	San Bernardin Truck2	Dsl			PMTW		PM10	0.027575
2034	Annual	San Bernardin Truck2	Dsl			PMBW		PM10	0.085823
2034	Annual	San Bernardin Truck2	Gas			PMTW		PM10	0.012071
2034	Annual	San Bernardin Truck2	Gas			PMBW		PM10	0.129734
2034	Annual	San Bernardin Truck2	NG			IDLEX		PM10	0.028852
2034	Annual	San Bernardin Truck2	NG			PMTW		PM10	0.036
2034	Annual	San Bernardin Truck2	NG			PMBW		PM10	0.06174
2035	Annual	San Bernardin Truck1	Dsl	52	50	RUNEX	10	PM10	0.022928
2035	Annual	San Bernardin Truck1	Dsl	52	50	RUNEX	40	PM10	0.009593
2035	Annual	San Bernardin Truck1	Gas	52	50	RUNEX	10	PM10	0.004793
2035	Annual	San Bernardin Truck1	Gas	52	50	RUNEX	40	PM10	0.000915
2035	Annual	San Bernardin Truck2	Dsl	52	50	RUNEX	10	PM10	0.008044
2035	Annual	San Bernardin Truck2	Dsl	52	50	RUNEX	40	PM10	0.008487
2035	Annual	San Bernardin Truck2	Gas	52	50	RUNEX	10	PM10	0.00482
2035	Annual	San Bernardin Truck2	Gas	52	50	RUNEX	40	PM10	0.00092
2035	Annual	San Bernardin Truck2	NG	52	50	RUNEX	10	PM10	0.006209
2035	Annual	San Bernardin Truck2	NG	52	50	RUNEX	40	PM10	0.003059
2035	Annual	San Bernardin Truck1	Dsl			IDLEX		PM10	0.791354
2035	Annual	San Bernardin Truck1	Dsl			PMTW		PM10	0.012
2035	Annual	San Bernardin Truck1	Dsl			PMBW		PM10	0.08003
2035	Annual	San Bernardin Truck1	Gas			PMTW		PM10	0.008
2035	Annual	San Bernardin Truck1	Gas			PMBW		PM10	0.078205
2035	Annual	San Bernardin Truck2	Dsl			IDLEX		PM10	0.010771
2035	Annual	San Bernardin Truck2	Dsl			PMTW		PM10	0.027595
2035	Annual	San Bernardin Truck2	Dsl			PMBW		PM10	0.085764
2035	Annual	San Bernardin Truck2	Gas			PMTW		PM10	0.012071
2035	Annual	San Bernardin Truck2	Gas			PMBW		PM10	0.129728
2035	Annual	San Bernardin Truck2	NG			IDLEX		PM10	0.027793
2035	Annual	San Bernardin Truck2	NG			PMTW		PM10	0.036
2035	Annual	San Bernardin Truck2	NG			PMBW		PM10	0.06174
2036	Annual	San Bernardin Truck1	Dsl	52	50	RUNEX	10	PM10	0.02196
2036	Annual	San Bernardin Truck1	Dsl	52	50	RUNEX	40	PM10	0.009299

calendar	season		vehicle		relativ	е		speed		emission
year	month	sub_area	class	fuel	tempe humid	ity	process	time	pollutant	rate
-	Annual	San Bernardi	n Truck1	Gas	52	-	RUNEX	10	PM10	0.004804
2036	Annual	San Bernardi	n Truck1	Gas	52	50	RUNEX	40	PM10	0.000917
2036	Annual	San Bernardi	n Truck2	Dsl	52	50	RUNEX	10	PM10	0.007979
2036	Annual	San Bernardi	n Truck2	Dsl	52	50	RUNEX	40	PM10	0.008457
2036	Annual	San Bernardi	n Truck2	Gas	52	50	RUNEX	10	PM10	0.004837
2036	Annual	San Bernardi	n Truck2	Gas	52	50	RUNEX	40	PM10	0.000923
2036	Annual	San Bernardi	n Truck2	NG	52	50	RUNEX	10	PM10	0.006151
2036	Annual	San Bernardi	n Truck2	NG	52	50	RUNEX	40	PM10	0.003033
2036	Annual	San Bernardi	n Truck1	Dsl			IDLEX		PM10	0.791903
2036	Annual	San Bernardi	n Truck1	Dsl			PMTW		PM10	0.012
2036	Annual	San Bernardi	n Truck1	Dsl			PMBW		PM10	0.080033
2036	Annual	San Bernardi	n Truck1	Gas			PMTW		PM10	0.008
2036	Annual	San Bernardi	n Truck1	Gas			PMBW		PM10	0.078195
2036	Annual	San Bernardi	n Truck2	Dsl			IDLEX		PM10	0.01065
2036	Annual	San Bernardi	n Truck2	Dsl			PMTW		PM10	0.02762
2036	Annual	San Bernardi	n Truck2	Dsl			PMBW		PM10	0.085694
2036	Annual	San Bernardi	n Truck2	Gas			PMTW		PM10	0.012072
2036	Annual	San Bernardi	n Truck2	Gas			PMBW		PM10	0.129724
2036	Annual	San Bernardi	n Truck2	NG			IDLEX		PM10	0.026988
2036	Annual	San Bernardi	n Truck2	NG			PMTW		PM10	0.036
2036	Annual	San Bernardi	n Truck2	NG			PMBW		PM10	0.06174
2037	Annual	San Bernardi	n Truck1	Dsl	52	50	RUNEX	10	PM10	0.021052
2037	Annual	San Bernardi	n Truck1	Dsl	52	50	RUNEX	40	PM10	0.009021
2037	Annual	San Bernardi	n Truck1	Gas	52	50	RUNEX	10	PM10	0.004811
2037	Annual	San Bernardi	n Truck1	Gas	52	50	RUNEX	40	PM10	0.000918
2037	Annual	San Bernardi	n Truck2	Dsl	52	50	RUNEX	10	PM10	0.007934
2037	Annual	San Bernardi	n Truck2	Dsl	52	50	RUNEX	40	PM10	0.008435
2037	Annual	San Bernardi	n Truck2	Gas	52	50	RUNEX	10	PM10	0.00485
2037	Annual	San Bernardi	n Truck2	Gas	52	50	RUNEX	40	PM10	0.000926
2037	Annual	San Bernardi	n Truck2	NG	52	50	RUNEX	10	PM10	0.006072
2037	Annual	San Bernardi	n Truck2	NG	52	50	RUNEX	40	PM10	0.003009
2037	Annual	San Bernardi	n Truck1	Dsl			IDLEX		PM10	0.792455
2037	Annual	San Bernardi	n Truck1	Dsl			PMTW		PM10	0.012
2037	Annual	San Bernardi	n Truck1	Dsl			PMBW		PM10	0.080036
2037	Annual	San Bernardi	n Truck1	Gas			PMTW		PM10	0.008
2037	Annual	San Bernardi	n Truck1	Gas			PMBW		PM10	0.078187
2037	Annual	San Bernardi	n Truck2	Dsl			IDLEX		PM10	0.010556
2037	Annual	San Bernardi	n Truck2	Dsl			PMTW		PM10	0.027645
2037	Annual	San Bernardi	n Truck2	Dsl			PMBW		PM10	0.085622
2037	Annual	San Bernardi	n Truck2	Gas			PMTW		PM10	0.012072
2037	Annual	San Bernardi	n Truck2	Gas			PMBW		PM10	0.12972
2037	Annual	San Bernardi	n Truck2	NG			IDLEX		PM10	0.026059
2037	Annual	San Bernardi	n Truck2	NG			PMTW		PM10	0.036

calendar season	vehicle		rela	tive	speed	emission
year month	sub_area class	fuel	tempe hun	nidity proce	ss time pollutai	nt rate
2037 Annual	San Bernardin Truck2	NG		PMB\	V PM10	0.06174
2038 Annual	San Bernardin Truck1	Dsl	52	50 RUNE	X 10 PM10	0.020253
2038 Annual	San Bernardin Truck1	Dsl	52	50 RUNE	X 40 PM10	0.008771
2038 Annual	San Bernardin Truck1	Gas	52	50 RUNE	X 10 PM10	0.00482
2038 Annual	San Bernardin Truck1	Gas	52	50 RUNE	X 40 PM10	0.00092
2038 Annual	San Bernardin Truck2	Dsl	52	50 RUNE	X 10 PM10	0.007899
2038 Annual	San Bernardin Truck2	Dsl	52	50 RUNE	X 40 PM10	0.00842
2038 Annual	San Bernardin Truck2	Gas	52	50 RUNE	X 10 PM10	0.004861
2038 Annual	San Bernardin Truck2	Gas	52	50 RUNE	X 40 PM10	0.000928
2038 Annual	San Bernardin Truck2	NG	52	50 RUNE	X 10 PM10	0.005956
2038 Annual	San Bernardin Truck2	NG	52	50 RUNE	X 40 PM10	0.002982
2038 Annual	San Bernardin Truck1	Dsl		IDLEX	PM10	0.792845
2038 Annual	San Bernardin Truck1	Dsl		PMTV	V PM10	0.012
2038 Annual	San Bernardin Truck1	Dsl		PMB\	V PM10	0.080037
2038 Annual	San Bernardin Truck1	Gas		PMTV	V PM10	0.008
2038 Annual	San Bernardin Truck1	Gas		PMB\	V PM10	0.078179
2038 Annual	San Bernardin Truck2	Dsl		IDLEX	PM10	0.010471
2038 Annual	San Bernardin Truck2	Dsl		PMTV	V PM10	0.02767
2038 Annual	San Bernardin Truck2	Dsl		PMB\	V PM10	0.085549
2038 Annual	San Bernardin Truck2	Gas		PMTV	V PM10	0.012073
2038 Annual	San Bernardin Truck2	Gas		PMB\	V PM10	0.129717
2038 Annual	San Bernardin Truck2	NG		IDLEX	PM10	0.025117
2038 Annual	San Bernardin Truck2	NG		PMTV	V PM10	0.036
2038 Annual	San Bernardin Truck2	NG		PMB\	V PM10	0.06174
2039 Annual	San Bernardin Truck1	Dsl	52	50 RUNE	X 10 PM10	0.019536
2039 Annual	San Bernardin Truck1	Dsl	52	50 RUNE	X 40 PM10	0.008546
2039 Annual	San Bernardin Truck1	Gas	52	50 RUNE		0.004824
2039 Annual	San Bernardin Truck1	Gas	52	50 RUNE	X 40 PM10	0.000921
2039 Annual	San Bernardin Truck2	Dsl	52	50 RUNE	X 10 PM10	0.007875
2039 Annual	San Bernardin Truck2	Dsl	52	50 RUNE		0.008413
2039 Annual	San Bernardin Truck2	Gas	52	50 RUNE	X 10 PM10	0.004869
2039 Annual	San Bernardin Truck2	Gas	52	50 RUNE	X 40 PM10	0.000929
2039 Annual	San Bernardin Truck2	NG	52	50 RUNE		0.005826
2039 Annual	San Bernardin Truck2	NG	52	50 RUNE	X 40 PM10	0.002949
2039 Annual	San Bernardin Truck1	Dsl		IDLEX		0.793586
2039 Annual	San Bernardin Truck1	Dsl		PMTV		0.012
2039 Annual	San Bernardin Truck1	Dsl		PMB\		0.080038
2039 Annual	San Bernardin Truck1	Gas		PMTV		0.008
2039 Annual	San Bernardin Truck1	Gas		PMB\		0.078172
2039 Annual	San Bernardin Truck2	Dsl		IDLEX		0.010391
2039 Annual	San Bernardin Truck2	Dsl		PMTV		0.027695
2039 Annual	San Bernardin Truck2	Dsl		PMB\		0.085477
2039 Annual	San Bernardin Truck2	Gas		PMTV	V PM10	0.012073

calendar	season	vehicle		relative		speed		emission
year	month	sub_area class	fuel	tempe humidity	process	time	pollutant	rate
2039	Annual	San Bernardin Truck2	Gas		PMBW		PM10	0.129715
2039	Annual	San Bernardin Truck2	NG		IDLEX		PM10	0.024088
2039	Annual	San Bernardin Truck2	NG		PMTW		PM10	0.036
2039	Annual	San Bernardin Truck2	NG		PMBW		PM10	0.06174
2040	Annual	San Bernardin Truck1	Dsl	52 50	RUNEX	10	PM10	0.018922
2040	Annual	San Bernardin Truck1	Dsl	52 50	RUNEX	40	PM10	0.008351
2040	Annual	San Bernardin Truck1	Gas	52 50	RUNEX	10	PM10	0.004827
2040	Annual	San Bernardin Truck1	Gas	52 50	RUNEX	40	PM10	0.000921
2040	Annual	San Bernardin Truck2	Dsl	52 50	RUNEX	10	PM10	0.007857
2040	Annual	San Bernardin Truck2	Dsl	52 50	RUNEX	40	PM10	0.008411
2040	Annual	San Bernardin Truck2	Gas	52 50	RUNEX	10	PM10	0.004876
2040	Annual	San Bernardin Truck2	Gas	52 50	RUNEX	40	PM10	0.00093
2040	Annual	San Bernardin Truck2	NG	52 50	RUNEX	10	PM10	0.005658
2040	Annual	San Bernardin Truck2	NG	52 50	RUNEX	40	PM10	0.002906
2040	Annual	San Bernardin Truck1	Dsl		IDLEX		PM10	0.794221
2040	Annual	San Bernardin Truck1	Dsl		PMTW		PM10	0.012
2040	Annual	San Bernardin Truck1	Dsl		PMBW		PM10	0.080041
2040	Annual	San Bernardin Truck1	Gas		PMTW		PM10	0.008
2040	Annual	San Bernardin Truck1	Gas		PMBW		PM10	0.078167
2040	Annual	San Bernardin Truck2	Dsl		IDLEX		PM10	0.010317
2040	Annual	San Bernardin Truck2	Dsl		PMTW		PM10	0.027721
2040	Annual	San Bernardin Truck2	Dsl		PMBW		PM10	0.085404
2040	Annual	San Bernardin Truck2	Gas		PMTW		PM10	0.012073
2040	Annual	San Bernardin Truck2	Gas		PMBW		PM10	0.129713
2040	Annual	San Bernardin Truck2	NG		IDLEX		PM10	0.022819
2040	Annual	San Bernardin Truck2	NG		PMTW		PM10	0.036
2040	Annual	San Bernardin Truck2	NG		PMBW		PM10	0.06174
2041	Annual	San Bernardin Truck1	Dsl	52 50	RUNEX	10	PM10	0.018414
2041	Annual	San Bernardin Truck1	Dsl	52 50	RUNEX	40	PM10	0.008186
2041	Annual	San Bernardin Truck1	Gas	52 50	RUNEX	10	PM10	0.00484
2041	Annual	San Bernardin Truck1	Gas	52 50	RUNEX	40	PM10	0.000924
2041	Annual	San Bernardin Truck2	Dsl	52 50	RUNEX	10	PM10	0.00784
2041	Annual	San Bernardin Truck2	Dsl	52 50	RUNEX	40	PM10	0.00841
2041	Annual	San Bernardin Truck2	Gas	52 50	RUNEX	10	PM10	0.004881
2041	Annual	San Bernardin Truck2	Gas	52 50	RUNEX	40	PM10	0.000931
2041	Annual	San Bernardin Truck2	NG	52 50	RUNEX	10	PM10	0.005493
	Annual	San Bernardin Truck2	NG	52 50	RUNEX	40	PM10	0.002856
	Annual	San Bernardin Truck1	Dsl		IDLEX		PM10	0.794735
	Annual	San Bernardin Truck1	Dsl		PMTW		PM10	0.012
2041	Annual	San Bernardin Truck1	Dsl		PMBW		PM10	0.080045
2041	Annual	San Bernardin Truck1	Gas		PMTW		PM10	0.008
	Annual	San Bernardin Truck1	Gas		PMBW		PM10	0.078162
2041	Annual	San Bernardin Truck2	Dsl		IDLEX		PM10	0.010251

calendar	season	vehicle		relative		speed		emission
year	month	sub_area class	fuel	tempe humidity	process	time	pollutant	rate
2041	Annual	San Bernardin Truck2	Dsl		PMTW		PM10	0.027735
2041	Annual	San Bernardin Truck2	Dsl		PMBW		PM10	0.085365
2041	Annual	San Bernardin Truck2	Gas		PMTW		PM10	0.012073
2041	Annual	San Bernardin Truck2	Gas		PMBW		PM10	0.129712
2041	Annual	San Bernardin Truck2	NG		IDLEX		PM10	0.021586
2041	Annual	San Bernardin Truck2	NG		PMTW		PM10	0.036
2041	Annual	San Bernardin Truck2	NG		PMBW		PM10	0.06174
2042	Annual	San Bernardin Truck1	Dsl	52 50	RUNEX	10	PM10	0.017967
2042	Annual	San Bernardin Truck1	Dsl	52 50	RUNEX	40	PM10	0.008041
2042	Annual	San Bernardin Truck1	Gas	52 50	RUNEX	10	PM10	0.004849
2042	Annual	San Bernardin Truck1	Gas	52 50	RUNEX	40	PM10	0.000925
2042	Annual	San Bernardin Truck2	Dsl	52 50	RUNEX	10	PM10	0.007833
2042	Annual	San Bernardin Truck2	Dsl	52 50	RUNEX	40	PM10	0.008414
2042	Annual	San Bernardin Truck2	Gas	52 50	RUNEX	10	PM10	0.004886
2042	Annual	San Bernardin Truck2	Gas	52 50	RUNEX	40	PM10	0.000932
2042	Annual	San Bernardin Truck2	NG	52 50	RUNEX	10	PM10	0.005344
2042	Annual	San Bernardin Truck2	NG	52 50	RUNEX	40	PM10	0.002804
2042	Annual	San Bernardin Truck1	Dsl		IDLEX		PM10	0.795197
2042	Annual	San Bernardin Truck1	Dsl		PMTW		PM10	0.012
2042	Annual	San Bernardin Truck1	Dsl		PMBW		PM10	0.080049
2042	Annual	San Bernardin Truck1	Gas		PMTW		PM10	0.008
2042	Annual	San Bernardin Truck1	Gas		PMBW		PM10	0.078158
2042	Annual	San Bernardin Truck2	Dsl		IDLEX		PM10	0.010202
2042	Annual	San Bernardin Truck2	Dsl		PMTW		PM10	0.027757
2042	Annual	San Bernardin Truck2	Dsl		PMBW		PM10	0.085302
2042	Annual	San Bernardin Truck2	Gas		PMTW		PM10	0.012073
2042	Annual	San Bernardin Truck2	Gas		PMBW		PM10	0.129711
2042	Annual	San Bernardin Truck2	NG		IDLEX		PM10	0.020367
2042	Annual	San Bernardin Truck2	NG		PMTW		PM10	0.036
2042	Annual	San Bernardin Truck2	NG		PMBW		PM10	0.06174
2043	Annual	San Bernardin Truck1	Dsl	52 50	RUNEX	10	PM10	0.017622
2043	Annual	San Bernardin Truck1	Dsl	52 50	RUNEX	40	PM10	0.007927
2043	Annual	San Bernardin Truck1	Gas	52 50	RUNEX	10	PM10	0.004857
2043	Annual	San Bernardin Truck1	Gas	52 50	RUNEX	40	PM10	0.000927
2043	Annual	San Bernardin Truck2	Dsl	52 50	RUNEX	10	PM10	0.007827
2043	Annual	San Bernardin Truck2	Dsl	52 50	RUNEX	40	PM10	0.00842
2043	Annual	San Bernardin Truck2	Gas	52 50	RUNEX	10	PM10	0.004891
2043	Annual	San Bernardin Truck2	Gas	52 50	RUNEX	40	PM10	0.000933
2043	Annual	San Bernardin Truck2	NG		RUNEX	10	PM10	0.005204
2043	Annual	San Bernardin Truck2	NG	52 50	RUNEX	40	PM10	0.002754
2043	Annual	San Bernardin Truck1	Dsl		IDLEX		PM10	0.795537
2043	Annual	San Bernardin Truck1	Dsl		PMTW		PM10	0.012
2043	Annual	San Bernardin Truck1	Dsl		PMBW		PM10	0.080053

calendar	season	vehicle		relative		speed		emission
year	month	sub_area class	fuel	tempe humidity	process	time	pollutant	rate
2043	Annual	San Bernardin Truck1	Gas		PMTW		PM10	0.008
2043	Annual	San Bernardin Truck1	Gas		PMBW		PM10	0.078155
2043	Annual	San Bernardin Truck2	Dsl		IDLEX		PM10	0.010162
2043	Annual	San Bernardin Truck2	Dsl		PMTW		PM10	0.027778
2043	Annual	San Bernardin Truck2	Dsl		PMBW		PM10	0.08524
2043	Annual	San Bernardin Truck2	Gas		PMTW		PM10	0.012073
2043	Annual	San Bernardin Truck2	Gas		PMBW		PM10	0.129711
2043	Annual	San Bernardin Truck2	NG		IDLEX		PM10	0.019094
2043	Annual	San Bernardin Truck2	NG		PMTW		PM10	0.036
2043	Annual	San Bernardin Truck2	NG		PMBW		PM10	0.06174
2044	Annual	San Bernardin Truck1	Dsl	52 50	RUNEX	10	PM10	0.017271
2044	Annual	San Bernardin Truck1	Dsl	52 50	RUNEX	40	PM10	0.007815
2044	Annual	San Bernardin Truck1	Gas	52 50	RUNEX	10	PM10	0.004861
2044	Annual	San Bernardin Truck1	Gas	52 50	RUNEX	40	PM10	0.000928
2044	Annual	San Bernardin Truck2	Dsl	52 50	RUNEX	10	PM10	0.007821
2044	Annual	San Bernardin Truck2	Dsl	52 50	RUNEX	40	PM10	0.008427
2044	Annual	San Bernardin Truck2	Gas	52 50	RUNEX	10	PM10	0.004894
2044	Annual	San Bernardin Truck2	Gas	52 50	RUNEX	40	PM10	0.000934
2044	Annual	San Bernardin Truck2	NG	52 50	RUNEX	10	PM10	0.005089
2044	Annual	San Bernardin Truck2	NG	52 50	RUNEX	40	PM10	0.00271
2044	Annual	San Bernardin Truck1	Dsl		IDLEX		PM10	0.795944
2044	Annual	San Bernardin Truck1	Dsl		PMTW		PM10	0.012
2044	Annual	San Bernardin Truck1	Dsl		PMBW		PM10	0.080054
2044	Annual	San Bernardin Truck1	Gas		PMTW		PM10	0.008
2044	Annual	San Bernardin Truck1	Gas		PMBW		PM10	0.078153
2044	Annual	San Bernardin Truck2	Dsl		IDLEX		PM10	0.010118
2044	Annual	San Bernardin Truck2	Dsl		PMTW		PM10	0.0278
2044	Annual	San Bernardin Truck2	Dsl		PMBW		PM10	0.085178
2044	Annual	San Bernardin Truck2	Gas		PMTW		PM10	0.012073
2044	Annual	San Bernardin Truck2	Gas		PMBW		PM10	0.12971
2044	Annual	San Bernardin Truck2	NG		IDLEX		PM10	0.01797
2044	Annual	San Bernardin Truck2	NG		PMTW		PM10	0.036
2044	Annual	San Bernardin Truck2	NG		PMBW		PM10	0.06174
2045	Annual	San Bernardin Truck1	Dsl	52 50	RUNEX	10	PM10	0.01698
2045	Annual	San Bernardin Truck1	Dsl	52 50	RUNEX	40	PM10	0.007721
2045	Annual	San Bernardin Truck1	Gas	52 50	RUNEX	10	PM10	0.004864
2045	Annual	San Bernardin Truck1	Gas	52 50	RUNEX	40	PM10	0.000928
2045	Annual	San Bernardin Truck2	Dsl	52 50	RUNEX	10	PM10	0.007815
2045	Annual	San Bernardin Truck2	Dsl	52 50	RUNEX	40	PM10	0.008434
2045	Annual	San Bernardin Truck2	Gas	52 50	RUNEX	10	PM10	0.004897
	Annual	San Bernardin Truck2	Gas	52 50	RUNEX	40	PM10	0.000935
2045	Annual	San Bernardin Truck2	NG	52 50	RUNEX	10	PM10	0.004989
2045	Annual	San Bernardin Truck2	NG	52 50	RUNEX	40	PM10	0.002672

calendar s	season	vehicle		relative		speed		emission
year r	month	sub_area class	fuel	tempe humidity	process	time	pollutant	rate
2045 A	Annual	San Bernardin Truck1	Dsl		IDLEX		PM10	0.796279
2045 A	Annual	San Bernardin Truck1	Dsl		PMTW		PM10	0.012
2045 A	Annual	San Bernardin Truck1	Dsl		PMBW		PM10	0.080054
2045 A	Annual	San Bernardin Truck1	Gas		PMTW		PM10	0.008
2045 A	Annual	San Bernardin Truck1	Gas		PMBW		PM10	0.078153
2045 A	Annual	San Bernardin Truck2	Dsl		IDLEX		PM10	0.01008
2045 A	Annual	San Bernardin Truck2	Dsl		PMTW		PM10	0.027822
2045 A	Annual	San Bernardin Truck2	Dsl		PMBW		PM10	0.085117
2045 A	Annual	San Bernardin Truck2	Gas		PMTW		PM10	0.012073
2045 A	Annual	San Bernardin Truck2	Gas		PMBW		PM10	0.12971
2045 A	Annual	San Bernardin Truck2	NG		IDLEX		PM10	0.016873
2045 A	Annual	San Bernardin Truck2	NG		PMTW		PM10	0.036
2045 A	Annual	San Bernardin Truck2	NG		PMBW		PM10	0.06174
2046 /	Annual	San Bernardin Truck1	Dsl	52 50	RUNEX	10	PM10	0.016703
2046 A	Annual	San Bernardin Truck1	Dsl	52 50	RUNEX	40	PM10	0.007633
2046 A	Annual	San Bernardin Truck1	Gas	52 50	RUNEX	10	PM10	0.004865
2046 A	Annual	San Bernardin Truck1	Gas	52 50	RUNEX	40	PM10	0.000928
2046 A	Annual	San Bernardin Truck2	Dsl	52 50	RUNEX	10	PM10	0.007808
2046 A	Annual	San Bernardin Truck2	Dsl	52 50	RUNEX	40	PM10	0.00844
2046 A	Annual	San Bernardin Truck2	Gas	52 50	RUNEX	10	PM10	0.004899
2046 A	Annual	San Bernardin Truck2	Gas	52 50	RUNEX	40	PM10	0.000935
2046 A	Annual	San Bernardin Truck2	NG	52 50	RUNEX	10	PM10	0.004854
2046 A	Annual	San Bernardin Truck2	NG	52 50	RUNEX	40	PM10	0.002633
2046 A	Annual	San Bernardin Truck1	Dsl		IDLEX		PM10	0.796621
2046 A	Annual	San Bernardin Truck1	Dsl		PMTW		PM10	0.012
2046 A	Annual	San Bernardin Truck1	Dsl		PMBW		PM10	0.080054
2046 A		San Bernardin Truck1	Gas		PMTW		PM10	0.008
2046 A	Annual	San Bernardin Truck1	Gas		PMBW		PM10	0.078153
2046 A	Annual	San Bernardin Truck2	Dsl		IDLEX		PM10	0.010038
2046 A	Annual	San Bernardin Truck2	Dsl		PMTW		PM10	0.027839
2046 A	Annual	San Bernardin Truck2	Dsl		PMBW		PM10	0.085067
2046 A	Annual	San Bernardin Truck2	Gas		PMTW		PM10	0.012074
2046 A	Annual	San Bernardin Truck2	Gas		PMBW		PM10	0.12971
2046 A	Annual	San Bernardin Truck2	NG		IDLEX		PM10	0.015642
2046 A		San Bernardin Truck2	NG		PMTW		PM10	0.036
2046 A	Annual	San Bernardin Truck2	NG		PMBW		PM10	0.06174
2047 A		San Bernardin Truck1	Dsl	52 50	RUNEX		PM10	0.01648
	Annual	San Bernardin Truck1	Dsl		RUNEX	40	PM10	0.007562
		San Bernardin Truck1	Gas		RUNEX	10	PM10	0.004866
		San Bernardin Truck1	Gas		RUNEX	40	PM10	0.000929
		San Bernardin Truck2	Dsl		RUNEX		PM10	0.007802
		San Bernardin Truck2	Dsl		RUNEX		PM10	0.008445
2047 A	Annual	San Bernardin Truck2	Gas	52 50) RUNEX	10	PM10	0.004901

calendar	season		vehicle		relative	!		speed		emission
year	month	sub_area	class	fuel	tempe humidi	ty	process	time	pollutant	rate
2047	Annual	San Bernardi	n Truck2	Gas	52	50	RUNEX	40	PM10	0.000935
2047	Annual	San Bernardi	n Truck2	NG	52	50	RUNEX	10	PM10	0.004536
2047	Annual	San Bernardi	n Truck2	NG	52	50	RUNEX	40	PM10	0.002574
2047	Annual	San Bernardi	n Truck1	Dsl			IDLEX		PM10	0.796892
2047	Annual	San Bernardi	n Truck1	Dsl			PMTW		PM10	0.012
2047	Annual	San Bernardi	n Truck1	Dsl			PMBW		PM10	0.080055
2047	Annual	San Bernardi	n Truck1	Gas			PMTW		PM10	0.008
2047	Annual	San Bernardi	n Truck1	Gas			PMBW		PM10	0.078153
2047	Annual	San Bernardi	n Truck2	Dsl			IDLEX		PM10	0.009999
2047	Annual	San Bernardi	n Truck2	Dsl			PMTW		PM10	0.027856
2047	Annual	San Bernardi	n Truck2	Dsl			PMBW		PM10	0.085018
2047	Annual	San Bernardi	n Truck2	Gas			PMTW		PM10	0.012074
2047	Annual	San Bernardi	n Truck2	Gas			PMBW		PM10	0.129709
2047	Annual	San Bernardi	n Truck2	NG			IDLEX		PM10	0.01348
2047	Annual	San Bernardi	n Truck2	NG			PMTW		PM10	0.036
2047	Annual	San Bernardi	n Truck2	NG			PMBW		PM10	0.06174
2048	Annual	San Bernardi	n Truck1	Dsl	52	50	RUNEX	10	PM10	0.016266
2048	Annual	San Bernardi	n Truck1	Dsl	52	50	RUNEX	40	PM10	0.007494
2048	Annual	San Bernardi	n Truck1	Gas	52	50	RUNEX	10	PM10	0.004865
2048	Annual	San Bernardi	n Truck1	Gas	52	50	RUNEX	40	PM10	0.000928
2048	Annual	San Bernardi	n Truck2	Dsl	52	50	RUNEX	10	PM10	0.007804
2048	Annual	San Bernardi	n Truck2	Dsl	52	50	RUNEX	40	PM10	0.00845
2048	Annual	San Bernardi	n Truck2	Gas	52	50	RUNEX	10	PM10	0.004903
2048	Annual	San Bernardi	n Truck2	Gas	52	50	RUNEX	40	PM10	0.000936
2048	Annual	San Bernardi	n Truck2	NG	52	50	RUNEX	10	PM10	0.004478
2048	Annual	San Bernardi	n Truck2	NG	52	50	RUNEX	40	PM10	0.002524
2048	Annual	San Bernardi	n Truck1	Dsl			IDLEX		PM10	0.79717
2048	Annual	San Bernardi	n Truck1	Dsl			PMTW		PM10	0.012
2048	Annual	San Bernardi	n Truck1	Dsl			PMBW		PM10	0.080055
2048	Annual	San Bernardi	n Truck1	Gas			PMTW		PM10	0.008
2048	Annual	San Bernardi	n Truck1	Gas			PMBW		PM10	0.078154
	Annual	San Bernardi	n Truck2	Dsl			IDLEX		PM10	0.009976
2048	Annual	San Bernardi	n Truck2	Dsl			PMTW		PM10	0.027873
2048	Annual	San Bernardi	n Truck2	Dsl			PMBW		PM10	0.08497
2048	Annual	San Bernardi	n Truck2	Gas			PMTW		PM10	0.012074
	Annual	San Bernardi		Gas			PMBW		PM10	0.129709
	Annual	San Bernardi		NG			IDLEX		PM10	0.012594
	Annual	San Bernardi		NG			PMTW		PM10	0.036
2048	Annual	San Bernardi		NG			PMBW		PM10	0.06174
	Annual	San Bernardi		Dsl	52		RUNEX		PM10	0.016077
	Annual	San Bernardi		Dsl	52		RUNEX		PM10	0.007435
	Annual	San Bernardi		Gas	52		RUNEX		PM10	0.004876
2049	Annual	San Bernardi	n Truck1	Gas	52	50	RUNEX	40	PM10	0.000931

calendar	season		vehicle		r	elative		speed		emission
year	month	sub_area	class	fuel	tempe h	numidity	process	time	pollutant	rate
2049	Annual	San Bernardin	Truck2	Dsl	52	50	RUNEX	10	PM10	0.007808
2049	Annual	San Bernardin	Truck2	Dsl	52	50	RUNEX	40	PM10	0.008455
2049	Annual	San Bernardin	Truck2	Gas	52	50	RUNEX	10	PM10	0.004904
2049	Annual	San Bernardin	Truck2	Gas	52	50	RUNEX	40	PM10	0.000936
2049	Annual	San Bernardin	Truck2	NG	52	50	RUNEX	10	PM10	0.004429
2049	Annual	San Bernardin	Truck2	NG	52	50	RUNEX	40	PM10	0.002481
2049	Annual	San Bernardin	Truck1	Dsl			IDLEX		PM10	0.797424
2049	Annual	San Bernardin	Truck1	Dsl			PMTW		PM10	0.012
2049	Annual	San Bernardin	Truck1	Dsl			PMBW		PM10	0.080054
2049	Annual	San Bernardin	Truck1	Gas			PMTW		PM10	0.008
2049	Annual	San Bernardin	Truck1	Gas			PMBW		PM10	0.078154
2049	Annual	San Bernardin	Truck2	Dsl			IDLEX		PM10	0.009961
2049	Annual	San Bernardin	Truck2	Dsl			PMTW		PM10	0.02789
2049	Annual	San Bernardin	Truck2	Dsl			PMBW		PM10	0.084922
2049	Annual	San Bernardin	Truck2	Gas			PMTW		PM10	0.012074
2049	Annual	San Bernardin	Truck2	Gas			PMBW		PM10	0.129709
2049	Annual	San Bernardin	Truck2	NG			IDLEX		PM10	0.011839
2049	Annual	San Bernardin	Truck2	NG			PMTW		PM10	0.036
2049	Annual	San Bernardin	Truck2	NG			PMBW		PM10	0.06174
2050	Annual	San Bernardin	Truck1	Dsl	52	50	RUNEX	10	PM10	0.015862
2050	Annual	San Bernardin	Truck1	Dsl	52	50	RUNEX	40	PM10	0.00737
2050	Annual	San Bernardin	Truck1	Gas	52	50	RUNEX	10	PM10	0.004882
2050	Annual	San Bernardin	Truck1	Gas	52	50	RUNEX	40	PM10	0.000932
2050	Annual	San Bernardin	Truck2	Dsl	52	50	RUNEX	10	PM10	0.007813
2050	Annual	San Bernardin	Truck2	Dsl	52	50	RUNEX	40	PM10	0.008461
2050	Annual	San Bernardin	Truck2	Gas	52	50	RUNEX	10	PM10	0.004905
2050	Annual	San Bernardin	Truck2	Gas	52	50	RUNEX	40	PM10	0.000936
2050	Annual	San Bernardin	Truck2	NG	52	50	RUNEX	10	PM10	0.004393
2050	Annual	San Bernardin	Truck2	NG	52	50	RUNEX	40	PM10	0.002449
2050	Annual	San Bernardin	Truck1	Dsl			IDLEX		PM10	0.797745
2050	Annual	San Bernardin	Truck1	Dsl			PMTW		PM10	0.012
2050	Annual	San Bernardin	Truck1	Dsl			PMBW		PM10	0.08005
2050	Annual	San Bernardin	Truck1	Gas			PMTW		PM10	0.008
2050	Annual	San Bernardin	Truck1	Gas			PMBW		PM10	0.078154
2050	Annual	San Bernardin	Truck2	Dsl			IDLEX		PM10	0.009943
2050	Annual	San Bernardin	Truck2	Dsl			PMTW		PM10	0.027906
2050	Annual	San Bernardin	Truck2	Dsl			PMBW		PM10	0.084876
2050	Annual	San Bernardin	Truck2	Gas			PMTW		PM10	0.012074
2050	Annual	San Bernardin	Truck2	Gas			PMBW		PM10	0.129709
2050	Annual	San Bernardin	Truck2	NG			IDLEX		PM10	0.01126
2050	Annual	San Bernardin	Truck2	NG			PMTW		PM10	0.036
2050	Annual	San Bernardin	Truck2	NG			PMBW		PM10	0.06174

APPENDIX C

AERMOD Model Years 2023 – 2025 Operational PM10 Printouts

```
***********
** AERMOD Input Produced by:
** AERMOD View Ver. 11.0.1
** Lakes Environmental Software Inc.
** Date: 10/4/2022
** File: C:\Vista Env\2021\21060 SB Co\AERMOD\DPM2023A\DPM2023A.ADI
**********
* *
*********
** AERMOD Control Pathway
*********
**
* *
CO STARTING
  TITLEONE Slover / Alder Ave Industrial - 2023-2025 DPM
  TITLETWO PM10
  MODELOPT DFAULT CONC
  AVERTIME 24 ANNUAL
  URBANOPT 2035210 San Bernardino Co
  POLLUTID PM 10
  RUNORNOT RUN
  ERRORFIL DPM2023A.err
CO FINISHED
**********
** AERMOD Source Pathway
*********
* *
* *
SO STARTING
** Source Location **
** Source ID - Type - X Coord. - Y Coord. **
** -----
** Line Source Represented by Adjacent Volume Sources
** LINE VOLUME Source ID = DWY1
** DESCRSRC Project DWY 1 - Alder Ave
** PREFIX
** Length of Side = 3.66
** Configuration = Adjacent
** Emission Rate = 6.7E-07
** Vertical Dimension = 1.83
** SZINIT = 0.85
** Nodes = 3
** 461413.126, 3769172.571, 329.00, 0.00, 1.70
** 461470.310, 3769171.735, 328.44, 0.00, 1.70
** 461553.714, 3769149.977, 327.87, 0.00, 1.70
** -----
  LOCATION L0000329
                   VOLUME
                          461414.955 3769172.545 328.92
  LOCATION L0000330
                          461418.612 3769172.491 328.86
                   VOLUME
  LOCATION L0000331
                   VOLUME 461422.269 3769172.438 328.80
```

```
461425.926 3769172.384 328.75
  LOCATION L0000332
                      VOLUME
  LOCATION L0000333
                               461429.583 3769172.331 328.69
                      VOLUME
  LOCATION L0000334
                      VOLUME 461433.241 3769172.277 328.63
  LOCATION L0000335
                      VOLUME 461436.898 3769172.224 328.57
  LOCATION L0000336
                              461440.555 3769172.170 328.53
                      VOLUME
                              461444.212 3769172.117 328.53
  LOCATION L0000337
                      VOLUME
  LOCATION L0000338
                      VOLUME 461447.869 3769172.063 328.52
                      VOLUME 461451.527 3769172.009 328.52
  LOCATION L0000339
                      VOLUME 461455.184 3769171.956 328.52
  LOCATION L0000340
  LOCATION L0000341
                      VOLUME
                               461458.841 3769171.902 328.52
                               461462.498 3769171.849 328.52
  LOCATION L0000342
                      VOLUME
                      VOLUME 461466.156 3769171.795 328.51
  LOCATION L0000343
                               461469.813 3769171.742 328.51
  LOCATION L0000344
                      VOLUME
                              461473.368 3769170.937 328.43
  LOCATION L0000345
                      VOLUME
                      VOLUME 461476.907 3769170.014 328.34
  LOCATION L0000346
                      VOLUME 461480.446 3769169.090 328.27
  LOCATION L0000347
                              461483.985 3769168.167 328.21
  LOCATION L0000348
                      VOLUME
                               461487.525 3769167.244 328.15
  LOCATION L0000349
                      VOLUME
  LOCATION L0000350
                      VOLUME 461491.064 3769166.320 328.09
                      VOLUME 461494.603 3769165.397 328.05
  LOCATION L0000351
                      VOLUME 461498.142 3769164.474 328.01
  LOCATION L0000352
                      VOLUME 461501.681 3769163.551 328.00
  LOCATION L0000353
  LOCATION L0000354
                      VOLUME 461505.220 3769162.627 328.00
                      VOLUME 461508.759 3769161.704 328.00
  LOCATION L0000355
                      VOLUME 461512.299 3769160.781 328.00
  LOCATION L0000356
                      VOLUME 461515.838 3769159.858 328.00
  LOCATION L0000357
                      VOLUME 461519.377 3769158.934 328.00
  LOCATION L0000358
                      VOLUME 461522.916 3769158.011 328.00
  LOCATION L0000359
  LOCATION L0000360
                      VOLUME 461526.455 3769157.088 328.00
                      VOLUME 461529.994 3769156.165 328.00
  LOCATION L0000361
  LOCATION L0000362
                      VOLUME 461533.534 3769155.241 328.00
                      VOLUME 461537.073 3769154.318 327.98
  LOCATION L0000363
                      VOLUME 461540.612 3769153.395 327.96
  LOCATION L0000364
  LOCATION L0000365
                      VOLUME 461544.151 3769152.472 327.94
                      VOLUME 461547.690 3769151.548 327.90
  LOCATION L0000366
                      VOLUME 461551.229 3769150.625 327.86
  LOCATION L0000367
** End of LINE VOLUME Source ID = DWY1
** -----
** Line Source Represented by Adjacent Volume Sources
** LINE VOLUME Source ID = DWY2
** DESCRSRC Project Driveway 2 - Slover Ave West
** PREFIX
** Length of Side = 3.66
** Configuration = Adjacent
** Emission Rate = 3.72E-07
** Vertical Dimension = 1.83
** SZINIT = 0.85
** Nodes = 3
** 461531.677, 3769225.292, 328.91, 0.00, 1.70
** 461531.677, 3769168.387, 328.00, 0.00, 1.70
** 461552.877, 3769160.298, 327.96, 0.00, 1.70
** ______
                              461531.677 3769223.463 328.95
  LOCATION L0000368
                      VOLUME
  LOCATION L0000369 VOLUME 461531.677 3769219.806 328.94
```

```
461531.677 3769216.148 328.93
  LOCATION L0000370
                       VOLUME
  LOCATION L0000371
                               461531.677 3769212.490 328.81
                       VOLUME
  LOCATION L0000372
                               461531.677 3769208.833 328.70
                       VOLUME
  LOCATION L0000373
                       VOLUME
                               461531.677 3769205.175 328.58
  LOCATION L0000374
                               461531.677 3769201.518 328.47
                       VOLUME
                               461531.677 3769197.860 328.36
  LOCATION L0000375
                       VOLUME
                              461531.677 3769194.202 328.24
  LOCATION L0000376
                       VOLUME
  LOCATION L0000377
                       VOLUME 461531.677 3769190.545 328.13
                              461531.677 3769186.887 328.02
  LOCATION L0000378
                       VOLUME
                               461531.677 3769183.230 328.00
  LOCATION L0000379
                       VOLUME
                               461531.677 3769179.572 328.00
  LOCATION L0000380
                       VOLUME
                       VOLUME 461531.677 3769175.914 328.00
  LOCATION L0000381
                               461531.677 3769172.257 328.00
  LOCATION L0000382
                       VOLUME
                              461531.677 3769168.599 328.00
  LOCATION L0000383
                       VOLUME
                      VOLUME 461534.897 3769167.159 328.00
  LOCATION L0000384
                      VOLUME 461538.314 3769165.855 328.00
  LOCATION L0000385
                      VOLUME 461541.731 3769164.551 328.00
  LOCATION L0000386
                       VOLUME 461545.148 3769163.247 328.00
  LOCATION L0000387
  LOCATION L0000388
                      VOLUME 461548.566 3769161.943 328.00
                      VOLUME 461551.983 3769160.639 328.00
  LOCATION L0000389
** End of LINE VOLUME Source ID = DWY2
** ______
** Line Source Represented by Adjacent Volume Sources
** LINE VOLUME Source ID = DWY3
** DESCRSRC Project Driveway 3 - Slover Ave East
** PREFIX
** Length of Side = 3.66
** Configuration = Adjacent
** Emission Rate = 7.96E-07
** Vertical Dimension = 1.83
** SZINIT = 0.85
** Nodes = 3
** 461673.660, 3769226.129, 328.00, 0.00, 1.70
** 461673.102, 3769173.408, 327.64, 0.00, 1.70
** 461556.782, 3769154.719, 327.97, 0.00, 1.70
** ______
  LOCATION L0000390
                               461673.641 3769224.300 328.00
                       VOLUME
  LOCATION L0000391
                      VOLUME
                              461673.602 3769220.643 328.00
                      VOLUME 461673.563 3769216.985 328.00
  LOCATION L0000392
  LOCATION L0000393
                      VOLUME 461673.525 3769213.328 328.00
  LOCATION L0000394
                              461673.486 3769209.670 328.00
                      VOLUME
  LOCATION L0000395
                      VOLUME
                               461673.447 3769206.013 328.00
  LOCATION L0000396
                      VOLUME 461673.408 3769202.356 328.00
  LOCATION L0000397
                       VOLUME 461673.370 3769198.698 328.00
                               461673.331 3769195.041 328.00
  LOCATION L0000398
                       VOLUME
  LOCATION L0000399
                       VOLUME
                              461673.292 3769191.383 328.00
  LOCATION L0000400
                      VOLUME
                              461673.254 3769187.726 328.00
  LOCATION L0000401
                       VOLUME
                              461673.215 3769184.069 327.92
                               461673.176 3769180.411 327.80
  LOCATION L0000402
                       VOLUME
  LOCATION L0000403
                       VOLUME
                               461673.137 3769176.754 327.68
                               461672.794 3769173.359 327.57
  LOCATION L0000404
                      VOLUME
  LOCATION L0000405
                      VOLUME 461669.183 3769172.779 327.55
                              461665.572 3769172.198 327.53
  LOCATION L0000406
                       VOLUME
  LOCATION L0000407
                      VOLUME
                              461661.960 3769171.618 327.51
```

```
461658.349 3769171.038 327.49
  LOCATION L0000408
                       VOLUME
  LOCATION L0000409
                               461654.738 3769170.458 327.47
                       VOLUME
  LOCATION L0000410
                       VOLUME 461651.127 3769169.877 327.45
  LOCATION L0000411
                       VOLUME 461647.515 3769169.297 327.47
  LOCATION L0000412
                               461643.904 3769168.717 327.52
                       VOLUME
  LOCATION L0000413
                              461640.293 3769168.137 327.58
                       VOLUME
  LOCATION L0000414
                       VOLUME 461636.681 3769167.557 327.64
                       VOLUME 461633.070 3769166.976 327.71
  LOCATION L0000415
                       VOLUME 461629.459 3769166.396 327.78
  LOCATION L0000416
  LOCATION L0000417
                       VOLUME
                               461625.848 3769165.816 327.86
                       VOLUME 461622.236 3769165.236 327.94
  LOCATION L0000418
                       VOLUME 461618.625 3769164.655 328.00
  LOCATION L0000419
                               461615.014 3769164.075 328.00
  LOCATION L0000420
                       VOLUME
                              461611.402 3769163.495 328.00
  LOCATION L0000421
                       VOLUME
                       VOLUME 461607.791 3769162.915 328.00
  LOCATION L0000422
                       VOLUME 461604.180 3769162.334 328.00
  LOCATION L0000423
                              461600.569 3769161.754 328.00
  LOCATION L0000424
                       VOLUME
                              461596.957 3769161.174 328.00
  LOCATION L0000425
                       VOLUME
  LOCATION L0000426
                       VOLUME 461593.346 3769160.594 328.00
  LOCATION L0000427
                       VOLUME 461589.735 3769160.014 328.00
                              461586.123 3769159.433 328.00
  LOCATION L0000428
                       VOLUME
                       VOLUME 461582.512 3769158.853 328.00
  LOCATION L0000429
  LOCATION L0000430
                      VOLUME 461578.901 3769158.273 328.00
                      VOLUME 461575.290 3769157.693 328.00
  LOCATION L0000431
                       VOLUME 461571.678 3769157.112 328.00
  LOCATION L0000432
                       VOLUME 461568.067 3769156.532 328.00
  LOCATION L0000433
  LOCATION L0000434
                      VOLUME 461564.456 3769155.952 327.99
                       VOLUME 461560.844 3769155.372 327.97
  LOCATION L0000435
  LOCATION L0000436
                      VOLUME 461557.233 3769154.791 327.95
** End of LINE VOLUME Source ID = DWY3
** Line Source Represented by Adjacent Volume Sources
** LINE VOLUME Source ID = ALDER
** DESCRSRC Alder Ave - DWY 1 to Slover Ave
** PREFIX
** Length of Side = 3.66
** Configuration = Adjacent
** Emission Rate = 1.49E-07
** Vertical Dimension = 1.83
** SZINIT = 0.85
** Nodes = 2
** 461405.873, 3769224.734, 329.00, 0.00, 1.70
** 461405.873, 3769172.014, 329.00, 0.00, 1.70
** -----
                               461405.873 3769222.905 329.22
  LOCATION L0000437
                       VOLUME
  LOCATION L0000438
                       VOLUME
                              461405.873 3769219.248 329.10
  LOCATION L0000439
                      VOLUME 461405.873 3769215.590 329.00
  LOCATION L0000440
                      VOLUME 461405.873 3769211.932 329.00
                              461405.873 3769208.275 329.00
  LOCATION L0000441
                       VOLUME
  LOCATION L0000442
                       VOLUME 461405.873 3769204.617 329.00
                      VOLUME 461405.873 3769200.960 329.00
  LOCATION L0000443
  LOCATION L0000444
                       VOLUME 461405.873 3769197.302 329.00
                       VOLUME 461405.873 3769193.644 329.00
  LOCATION L0000445
  LOCATION L0000446
                      VOLUME 461405.873 3769189.987 329.00
```

```
461405.873 3769186.329 329.00
  LOCATION L0000447
                      VOLUME
  LOCATION L0000448
                       VOLUME 461405.873 3769182.672 329.00
  LOCATION L0000449
                      VOLUME 461405.873 3769179.014 329.00
  LOCATION L0000450
                      VOLUME 461405.873 3769175.356 329.00
** End of LINE VOLUME Source ID = ALDER
** ______
** Line Source Represented by Adjacent Volume Sources
** LINE VOLUME Source ID = SLOVER
** DESCRSRC Slover Ave
** PREFIX
** Length of Side = 12.19
** Configuration = Adjacent
** Emission Rate = 5.03E-06
** Vertical Dimension = 1.83
** SZINIT = 0.85
** Nodes = 5
** 460972.339, 3769234.573, 331.00, 0.00, 5.67
** 461117.706, 3769238.668, 330.83, 0.00, 5.67
** 461377.729, 3769233.550, 329.63, 0.00, 5.67
** 461809.736, 3769235.597, 328.00, 0.00, 5.67
** 462162.918, 3769234.573, 327.68, 0.00, 5.67
** ______
  LOCATION L0000451
                              460978.432 3769234.745 331.00
                      VOLUME
                              460990.619 3769235.088 331.00
  LOCATION L0000452
                      VOLUME
                              461002.807 3769235.432 331.00
  LOCATION L0000453
                       VOLUME
                              461014.994 3769235.775 331.00
  LOCATION L0000454
                       VOLUME
  LOCATION L0000455
                       VOLUME 461027.181 3769236.118 331.00
                       VOLUME 461039.368 3769236.462 331.00
  LOCATION L0000456
  LOCATION L0000457
                       VOLUME
                              461051.555 3769236.805 331.00
                              461063.742 3769237.148 331.00
  LOCATION L0000458
                       VOLUME
  LOCATION L0000459
                       VOLUME 461075.930 3769237.492 331.00
                       VOLUME
                              461088.117 3769237.835 330.92
  LOCATION L0000460
                              461100.304 3769238.178 330.81
  LOCATION L0000461
                       VOLUME
                               461112.491 3769238.521 330.74
  LOCATION L0000462
                       VOLUME
  LOCATION L0000463
                       VOLUME
                               461124.680 3769238.531 330.74
                       VOLUME 461136.869 3769238.291 330.73
  LOCATION L0000464
  LOCATION L0000465
                               461149.059 3769238.051 330.72
                       VOLUME
  LOCATION L0000466
                       VOLUME
                              461161.249 3769237.811 330.72
                              461173.438 3769237.571 330.62
  LOCATION L0000467
                       VOLUME
  LOCATION L0000468
                               461185.628 3769237.331 330.33
                       VOLUME
                               461197.817 3769237.091 330.04
  LOCATION L0000469
                       VOLUME
  LOCATION L0000470
                       VOLUME
                               461210.007 3769236.851 330.00
                               461222.197 3769236.611 330.00
  LOCATION L0000471
                       VOLUME
                               461234.386 3769236.371 330.00
  LOCATION L0000472
                       VOLUME
                               461246.576 3769236.132 330.00
  LOCATION L0000473
                       VOLUME
  LOCATION L0000474
                       VOLUME
                               461258.766 3769235.892 330.00
  LOCATION L0000475
                       VOLUME
                               461270.955 3769235.652 330.00
  LOCATION L0000476
                       VOLUME
                               461283.145 3769235.412 330.00
                               461295.335 3769235.172 329.93
  LOCATION L0000477
                       VOLUME
  LOCATION L0000478
                               461307.524 3769234.932 329.77
                       VOLUME
                               461319.714 3769234.692 329.61
  LOCATION L0000479
                       VOLUME
  LOCATION L0000480
                       VOLUME 461331.903 3769234.452 329.60
                              461344.093 3769234.212 329.60
  LOCATION L0000481
                       VOLUME
  LOCATION L0000482
                       VOLUME
                              461356.283 3769233.972 329.59
```

```
LOCATION L0000483
                                461368.472 3769233.732 329.58
                      VOLUME
LOCATION L0000484
                                461380.663 3769233.564 329.57
                      VOLUME
LOCATION L0000485
                                461392.854 3769233.621 329.58
                      VOLUME
LOCATION L0000486
                      VOLUME
                                461405.046 3769233.679 329.58
LOCATION L0000487
                                461417.238 3769233.737 329.58
                      VOLUME
LOCATION L0000488
                                461429.430 3769233.795 329.58
                      VOLUME
LOCATION L0000489
                      VOLUME
                                461441.622 3769233.853 329.54
LOCATION L0000490
                                461453.814 3769233.910 329.31
                      VOLUME
                                461466.006 3769233.968 329.07
LOCATION L0000491
                      VOLUME
                                461478.197 3769234.026 329.00
LOCATION L0000492
                      VOLUME
LOCATION L0000493
                                461490.389 3769234.084 329.00
                      VOLUME
                                461502.581 3769234.141 329.00
LOCATION L0000494
                      VOLUME
                                461514.773 3769234.199 329.00
LOCATION L0000495
                      VOLUME
LOCATION L0000496
                                461526.965 3769234.257 329.00
                      VOLUME
LOCATION L0000497
                                461539.157 3769234.315 328.87
                      VOLUME
                                461551.349 3769234.373 328.71
LOCATION L0000498
                      VOLUME
                                461563.540 3769234.430 328.60
LOCATION L0000499
                      VOLUME
LOCATION L0000500
                                461575.732 3769234.488 328.60
                      VOLUME
LOCATION L0000501
                                461587.924 3769234.546 328.61
                      VOLUME
LOCATION L0000502
                      VOLUME
                                461600.116 3769234.604 328.61
                                461612.308 3769234.662 328.61
LOCATION L0000503
                      VOLUME
                                461624.500 3769234.719 328.51
LOCATION L0000504
                      VOLUME
LOCATION L0000505
                      VOLUME
                                461636.692 3769234.777 328.26
                                461648.884 3769234.835 328.02
LOCATION L0000506
                      VOLUME
                                461661.075 3769234.893 328.00
LOCATION L0000507
                      VOLUME
                                461673.267 3769234.950 328.00
LOCATION L0000508
                      VOLUME
LOCATION L0000509
                                461685.459 3769235.008 328.00
                      VOLUME
                                461697.651 3769235.066 328.00
LOCATION L0000510
                      VOLUME
LOCATION L0000511
                                461709.843 3769235.124 328.00
                      VOLUME
                                461722.035 3769235.182 328.00
LOCATION L0000512
                      VOLUME
LOCATION L0000513
                      VOLUME
                                461734.227 3769235.239 328.00
                                461746.418 3769235.297 328.00
LOCATION L0000514
                      VOLUME
                                461758.610 3769235.355 328.00
LOCATION L0000515
                      VOLUME
LOCATION L0000516
                      VOLUME
                                461770.802 3769235.413 328.00
LOCATION L0000517
                      VOLUME
                                461782.994 3769235.470 328.00
LOCATION L0000518
                      VOLUME
                                461795.186 3769235.528 328.00
LOCATION L0000519
                                461807.378 3769235.586 328.00
                      VOLUME
LOCATION L0000520
                      VOLUME
                                461819.570 3769235.569 328.00
LOCATION L0000521
                                461831.762 3769235.533 328.00
                      VOLUME
LOCATION L0000522
                      VOLUME
                                461843.954 3769235.498 328.00
                                461856.146 3769235.463 328.00
LOCATION L0000523
                      VOLUME
LOCATION L0000524
                      VOLUME
                                461868.337 3769235.427 328.00
LOCATION L0000525
                                461880.529 3769235.392 328.00
                      VOLUME
LOCATION L0000526
                      VOLUME
                                461892.721 3769235.357 328.00
                                461904.913 3769235.321 328.00
LOCATION L0000527
                      VOLUME
LOCATION L0000528
                      VOLUME
                                461917.105 3769235.286 328.00
LOCATION L0000529
                      VOLUME
                                461929.297 3769235.251 328.00
                      VOLUME
LOCATION L0000530
                                461941.489 3769235.215 328.00
                                461953.681 3769235.180 327.95
LOCATION L0000531
                      VOLUME
LOCATION L0000532
                      VOLUME
                                461965.873 3769235.145 327.80
                                461978.065 3769235.109 327.64
LOCATION L0000533
                      VOLUME
LOCATION L0000534
                                461990.257 3769235.074 327.62
                      VOLUME
                                462002.449 3769235.039 327.62
LOCATION L0000535
                      VOLUME
LOCATION L0000536
                      VOLUME
                                462014.641 3769235.003 327.62
```

```
LOCATION L0000537
                                   462026.833 3769234.968 327.62
                         VOLUME
  LOCATION L0000538
                         VOLUME
                                   462039.025 3769234.933 327.62
  LOCATION L0000539
                                   462051.217 3769234.897 327.62
                         VOLUME
  LOCATION L0000540
                         VOLUME
                                   462063.409 3769234.862 327.62
  LOCATION L0000541
                                   462075.601 3769234.827 327.62
                         VOLUME
  LOCATION L0000542
                                   462087.793 3769234.791 327.61
                         VOLUME
                                   462099.985 3769234.756 327.61
  LOCATION L0000543
                         VOLUME
  LOCATION L0000544
                                   462112.176 3769234.721 327.61
                         VOLUME
  LOCATION L0000545
                                   462124.368 3769234.685 327.61
                         VOLUME
  LOCATION L0000546
                                   462136.560 3769234.650 327.61
                         VOLUME
  LOCATION L0000547
                                   462148.752 3769234.615 327.61
                         VOLUME
                                   462160.944 3769234.579 327.61
  LOCATION L0000548
                         VOLUME
** End of LINE VOLUME Source ID = SLOVER
  LOCATION IDLING
                                     461555.730 3769145.780
                                                                   327.690
                         POINT
** DESCRSRC Truck Idling
** Source Parameters **
** LINE VOLUME Source ID = DWY1
   SRCPARAM L0000329
                                             0.00
                                                       1.70
                         0.0000001718
                                                                  0.85
   SRCPARAM L0000330
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000331
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000332
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
                         0.0000001718
   SRCPARAM L0000333
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000334
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000335
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000336
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000337
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000338
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
                                                       1.70
   SRCPARAM L0000339
                         0.0000001718
                                             0.00
                                                                  0.85
   SRCPARAM L0000340
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000341
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000342
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000343
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
                                                       1.70
   SRCPARAM L0000344
                         0.0000001718
                                             0.00
                                                                  0.85
   SRCPARAM L0000345
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
                                                                  0.85
   SRCPARAM L0000346
                         0.0000001718
                                             0.00
                                                       1.70
   SRCPARAM L0000347
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000348
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000349
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
                         0.0000001718
                                             0.00
                                                       1.70
   SRCPARAM L0000350
                                                                  0.85
   SRCPARAM L0000351
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000352
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000353
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000354
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
  SRCPARAM L0000355
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
                                                       1.70
   SRCPARAM L0000356
                         0.0000001718
                                             0.00
                                                                  0.85
   SRCPARAM L0000357
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000358
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000359
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000360
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000361
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000362
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
  SRCPARAM L0000363
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000364
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
  SRCPARAM L0000365
                         0.0000001718
                                             0.00
                                                       1.70
                                                                  0.85
```

**		L0000367	0.00000001718 0.00000001718		1.70	0.85 0.85
	LINE VOLU SRCPARAM	ME Source II L0000368 L0000369 L0000370 L0000371 L0000373 L0000374 L0000375 L0000376 L0000377 L0000377 L0000381	0.0000001691 0.0000001691 0.00000001691 0.00000001691 0.00000001691 0.00000001691 0.00000001691 0.00000001691 0.00000001691 0.00000001691 0.00000001691 0.00000001691 0.00000001691 0.00000001691 0.00000001691 0.00000001691 0.00000001691 0.00000001691 0.00000001691 0.00000001691 0.00000001691	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00	1.70 1.70 1.70 1.70 1.70 1.70 1.70 1.70	0.85 0.85 0.85 0.85 0.85 0.85 0.85 0.85
**	SRCPARAM	L0000389	0.00000001691	0.00	1.70	0.85
**	SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM	L0000393 L0000394 L0000395 L0000396 L0000397 L0000399 L0000400 L0000401 L0000401 L0000403 L0000404 L0000405 L0000406 L0000407 L0000408 L0000410 L0000411 L0000412 L0000413 L0000414	0.00000001694 0.00000001694 0.00000001694 0.00000001694 0.00000001694 0.00000001694	0.00 0.00 0.00 0.00 0.00	1.70 1.70 1.70 1.70 1.70 1.70 1.70 1.70	

	SRCPARAM	L0000416		0.0000001694	0.00	1.70	0.85	
	SRCPARAM	L0000417		0.0000001694	0.00	1.70	0.85	
	SRCPARAM	L0000418		0.0000001694	0.00	1.70	0.85	
	SRCPARAM	L0000419		0.0000001694	0.00	1.70	0.85	
	SRCPARAM	L0000420		0.0000001694	0.00	1.70	0.85	
	SRCPARAM	L0000421		0.0000001694	0.00	1.70	0.85	
	SRCPARAM	L0000422		0.0000001694	0.00	1.70	0.85	
	SRCPARAM	L0000423		0.0000001694	0.00	1.70	0.85	
	SRCPARAM	L0000424		0.0000001694	0.00	1.70	0.85	
	SRCPARAM	L0000425		0.0000001694	0.00	1.70	0.85	
	SRCPARAM	L0000426		0.0000001694	0.00	1.70	0.85	
	SRCPARAM	L0000427		0.0000001694	0.00	1.70	0.85	
	SRCPARAM	L0000428		0.0000001694	0.00	1.70	0.85	
	SRCPARAM	L0000429		0.0000001694	0.00	1.70	0.85	
	SRCPARAM	L0000430		0.0000001694	0.00	1.70	0.85	
	SRCPARAM	L0000431		0.0000001694	0.00	1.70	0.85	
	SRCPARAM	L0000432		0.0000001694	0.00	1.70	0.85	
	SRCPARAM	L0000433		0.0000001694	0.00	1.70	0.85	
	SRCPARAM	L0000434		0.0000001694	0.00	1.70	0.85	
		L0000435		0.0000001694	0.00	1.70	0.85	
		L0000436		0.0000001694	0.00	1.70	0.85	
**					 	 	 	
**	LINE VOLU	JME Source	ΙD	= ALDER				
	SRCPARAM	L0000437		0.0000001064	0.00	1.70	0.85	
	SRCPARAM	L0000438		0.0000001064	0.00	1.70	0.85	
	SRCPARAM	L0000439		0.0000001064	0.00	1.70	0.85	
	SRCPARAM	L0000440		0.0000001064	0.00	1.70	0.85	
	SRCPARAM	L0000441		0.0000001064	0.00	1.70	0.85	
		L0000442		0.0000001064	0.00	1.70	0.85	
	SRCPARAM	L0000443		0.0000001064	0.00	1.70	0.85	
	SRCPARAM	L0000444		0.0000001064	0.00	1.70	0.85	
	SRCPARAM	L0000445		0.0000001064	0.00	1.70	0.85	
	SRCPARAM	L0000446		0.0000001064	0.00	1.70	0.85	
	SRCPARAM	L0000447		0.0000001064	0.00	1.70	0.85	
	SRCPARAM	L0000448		0.0000001064	0.00	1.70	0.85	
	SRCPARAM	L0000449		0.0000001064	0.00	1.70	0.85	
	SRCPARAM	L0000450		0.0000001064	0.00	1.70	0.85	
**					 	 	 	
**	LINE VOLU	JME Source	ΙD	= SLOVER				
	SRCPARAM	L0000451		0.00000005133	0.00	5.67	0.85	
	SRCPARAM	L0000452		0.00000005133	0.00	5.67	0.85	
	SRCPARAM	L0000453		0.00000005133	0.00	5.67	0.85	
	SRCPARAM	L0000454		0.00000005133	0.00	5.67	0.85	
	SRCPARAM	L0000455		0.00000005133	0.00	5.67	0.85	
	SRCPARAM	L0000456		0.00000005133	0.00	5.67	0.85	
	SRCPARAM	L0000457		0.00000005133	0.00	5.67	0.85	
	SRCPARAM	L0000458		0.00000005133	0.00	5.67	0.85	
	SRCPARAM	L0000459		0.00000005133	0.00	5.67	0.85	
	SRCPARAM	L0000460		0.00000005133	0.00	5.67	0.85	
	SRCPARAM			0.00000005133	0.00	5.67	0.85	
	SRCPARAM			0.0000005133	0.00	5.67	0.85	
		L0000463		0.0000005133	0.00	5.67	0.85	
		L0000464		0.0000005133	0.00	5.67	0.85	
		L0000465		0.0000005133	0.00	5.67	0.85	

SRCPARAM	L0000466	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000467	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000468	0.00000005133	0.00	5.67	0.85
	L0000469	0.00000005133	0.00	5.67	0.85
	L0000470	0.00000005133	0.00	5.67	0.85
	L0000471	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000472	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000473	0.00000005133	0.00	5.67	0.85
	L0000474	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000475	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000476	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000477	0.00000005133	0.00	5.67	0.85
	L0000478	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000479	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000480	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000481	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000482	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000483	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000484	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000485	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000486	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000487	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000488	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000489	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000490	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000491	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000492	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000493	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000494	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000495	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000496	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000497	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000498	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000499	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000500	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000501	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000502	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000503	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000504	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000505	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000506	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000507	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000508	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000509	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000510	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000511	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000512	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000513	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000514	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000515	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000516	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000517	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000518	0.00000005133	0.00	5.67	0.85
SRCPARAM	L0000519	0.00000005133	0.00	5.67	0.85

	SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM	L0000521 L0000522 L0000523 L0000524 L0000525 L0000527 L0000527 L0000529 L0000530 L0000531 L0000532	0.00 0.00 0.00 0.00 0.00 0.00 0.00	00000 00000 00000 00000 00000 00000 0000	5133 5133 5133 5133 5133 5133 5133 5133	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0	5.67 5.67 5.67 5.67 5.67 5.67 5.67 5.67	0.85 0.85 0.85 0.85 0.85 0.85 0.85 0.85	
	SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM	L0000535 L0000536 L0000537 L0000538 L0000539	0.00 0.00 0.00 0.00	00000 00000 00000 00000 00000	5133 5133 5133 5133 5133 5133	0.00 0.00 0.00 0.00 0.00	5.67 5.67 5.67 5.67 5.67 5.67 5.67	0.85 0.85 0.85 0.85 0.85	
	SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM	L0000541 L0000542 L0000543 L0000544 L0000545 L0000546	0.00 0.00 0.00 0.00 0.00	00000 00000 00000 00000 00000 00000	5133 5133 5133 5133 5133 5133 5133	0.00 0.00 0.00 0.00 0.00 0.00	5.67 5.67 5.67 5.67 5.67 5.67 5.67	0.85 0.85 0.85 0.85 0.85 0.85	
**							6.000		
**	BUILDHGT BUILDHGT BUILDHGT BUILDHGT	Downwash of IDLING IDLING IDLING IDLING IDLING IDLING IDLING	1 1 1 1	3.41 3.41 3.41 3.41 3.41 3.41	13.41	13.	41 13.41 41 13.41 41 13.41 41 13.41 41 13.41 41 13.41	13.41	13.41
	BUILDWID BUILDWID BUILDWID BUILDWID BUILDWID BUILDWID	IDLING IDLING IDLING IDLING	18 24 27 18	0.09 7.67 6.36 0.09 7.67 6.36	264.67 276.54	107. 274. 274. 107.	59 149.86 93 276.84 58 264.29 59 149.86	188.07 270.34 245.96 188.07	255.74 220.16
	BUILDLEN BUILDLEN BUILDLEN BUILDLEN BUILDLEN BUILDLEN	IDLING IDLING IDLING IDLING	27 26 14 27	9.86 6.84 4.29 9.86 6.84 4.29		255. 220. 220. 255.	74 270.09 16 187.67 57 246.36 74 270.09	276.54 149.48 264.67 276.54	274.58 107.59 274.93 274.58

```
-119.03 -136.14 -149.11 -157.55 -161.21 -159.96
  XBADJ
       TDLING
  XBADJ
                     -153.86 -143.08 -127.95 -127.18 -122.85 -114.78
         IDLING
        IDLING
                     -103.24 -88.55 -71.17 -51.63 -30.53
  XBADJ
  XBADJ
        IDLING
                     -30.83 -51.93 -71.45 -88.80 -103.46 -114.97
                     -122.99 -127.27 -127.79 -142.91 -153.69 -159.80
  XBADJ
         IDLING
                     -161.05 -157.41 -148.99 -136.04 -118.96
  XBADJ
         IDLING
  YBADJ
                     -7.87 -15.42 -22.51 -28.91 -34.43
        IDLING
       IDLING
                     -42.20 -44.22 -44.52 -44.10 -42.11 -38.83
  YBADJ
                      -34.37
                            -28.87
                                   -22.50
                                           -15.44
                                                    -7.91
  YBADJ
         IDLING
                       7.87
                             15.42
                                    22.51 28.91
                                                    34.43
        IDLING
  YBADJ
                                                   42.11
                      42.20
                             44.22
                                    44.52
                                            44.10
  YBADJ
         IDLING
                      34.37 28.87 22.50 15.44
         IDLING
                                                   7.91
  YBADJ
  URBANSRC ALL
  SRCGROUP ALL
SO FINISHED
* *
*********
** AERMOD Receptor Pathway
********
* *
RE STARTING
  INCLUDED DPM2023A.rou
RE FINISHED
*********
** AERMOD Meteorology Pathway
*********
* *
ME STARTING
  SURFFILE ..\FontanaADJU\FONT V9 ADJU\FONT v9.SFC
  PROFFILE ..\FontanaADJU\FONT V9 ADJU\FONT v9.PFL
  SURFDATA 3102 2011 Fontana
  UAIRDATA 3190 2011
  SITEDATA 99999 2011
  PROFBASE 367.0 METERS
ME FINISHED
* *
**********
** AERMOD Output Pathway
***********
**
* *
OU STARTING
  RECTABLE ALLAVE 1ST
  RECTABLE 24 1ST
** Auto-Generated Plotfiles
  PLOTFILE 24 ALL 1ST DPM2023A.AD\24H1GALL.PLT 31
  PLOTFILE ANNUAL ALL DPM2023A.AD\AN00GALL.PLT 32
  SUMMFILE DPM2023A.sum
OU FINISHED
```

-9.28

-98.31

-38.91

-0.08

38.91

38.83

0.08

* *

** Project Parameters

** PROJCTN CoordinateSystemUTM

** DESCPTN UTM: Universal Transverse Mercator

** DATUM World Geodetic System 1984

** DTMRGN Global Definition

** UNITS m

** ZONE 11

** ZONEINX 0

* *

О

* AERMOD (22112): Slover / A. * AERMET (16216):	Alder Ave Industrial	I	2023-2025 D	DPM			10/04/	2 2 2 3
MODELING OPTIONS USED:	gDFAULT	ELEV URBAN		JL V			`)
FILE OF ANNUAL	VALUE	ID ACROSS	5 YEARS	FOR	SOURCE GROUP	P: ALL		
FOR A IOIAL OF FORMAT: (3(1X,F13.5)	0 RECEPIORS.), 3 (1X, F8.2),	4, A6, 2X, A8	2X, I8.8	2X, A8)				
. > .	AVERAGE CONC	ZELEV	ZHILL	ZFLAG	AVE	GRP	NUM YRS	NET ID
461426.82000 3768525.5600	0.00023	321.40	675.00	00.0	ANNUAL	ALL	00000000	NCART1
.82000 376852	0.00022	321.00	673.00	00.00	ANNUAL	ALL	0000000	NCART1
000 3768525.5600	0.00021	21.0	9.0	00.00	ANNUAL	ALL	00000000	NCART1
576.82000 3768525.5600	.0001	21.0	9.0	0.	ANNUAL	ALL	000000	NCART1
61626.82000 3768525.5600	00	320.70	579.00	00.0	ANNUAL	ALL	0000000	NCART1
76.82000 3768525.5600	.0001	20.0	9.0	0.	ANNUAL	ALL	00000000	NCART1
61726.82000 3768525.5600	.0001	0.	9.0	0.	ANNUAL	ALL	000000	NCART1
.82000 3768525.5600	.0001	320.00	9.0	0.	ANNUAL	ALL	00000000	NCART1
.82000 3768575.5600	.0002	0.	0.6	0.	ANNUAL	ALL	000	NCART1
76.82000 3768575.5600	.0002	9	9.0	0.	ANNUAL	ALL	000	NCART1
26.82000 3768575.5600	.0002	9.	0.6	00.0	ANNUAL	ALL	00000000	NCART1
76.82000 3768575.5600	\sim	321.00	579.00	00.00	ANNUAL	ALL	000	NCART1
61626.82000 3768575.5600	.0001	0.	0.6	0.	ANNUAL	ALL	000000	NCART1
.82000 3768575.5600	.0001	0.	9.0	0.	ANNUAL	ALL	00000000	NCART1
26.82000 3768575.5600	.0001	9.	9.0	0.	ANNUAL	ALL	0000000	NCART1
61776.82000 3768575.5600	.0001		0.6	00.00	ANNUAL	ALL	00000000	NCART1
61426.82000 3768625.5600	.0003	ς.	9.0	0.	ANNUAL	ALL	00000000	NCART1
61476.82000 3768625.5600	.0003	322.00	579.00	00.00	ANNUAL	ALL	00000000	NCART1
61526.82000 3768625.5600	000.	0.	0.6	0.	ANNUAL	ALL	00000000	NCART1
76.82000 3768625.5600	.0002	0.	0.6	0.	ANNUAL	ALL	00000000	NCART1
.82000 3768625.5600	.0002	ς.	9.0	0.	ANNUAL	ALL	000000	NCART1
61676.82000 3768625.5600	00	321.30	თ	00.0	ANNUAL	ALL	00000	NCART1
000 3768625.5600	.0001	0.	0.6	0.	ANNUAL	ALL	000000	NCART1
.82000 3768625.5600	.0001	0.	0.6	0.	ANNUAL	ALL	000000	NCART1
426.82000 3768675.5600	.0003	23.0	0.6	0.	ANNUAL	ALL	00000000	NCART1
.82000 3768675.5600	0.00037	323.00	579.00	00.0	ANNUAL	ALL	0000000	NCART1
26.82000 3768675.5600	0.00034	322.10	579.00	0.	ANNUAL	ALL	00000000	NCART1
.82000 3768675.5600	.0003	322.00	579.00	00.0	ANNUAL	ALL	000000	NCART1
26.82000 3768675.5600	0.	22.0	0.6	0.	ANNUAL	ALL	000000	NCART1
61676.82000 3768675.5600	.0002	22.	0.6	00.0	ANNUAL	ALL	0000	NCART1
726.82000 3768675.5600	0.00018	322.00	579.00	00.0	ANNUAL	ALL	00000000	NCART1

005 NCART1 005 NCART1	0.0	005 NCART1		005 NCART1	005 NCART1	0.5		005 NCART1	005 NCART1	0005 NCART1	0005 NCART1	005 NCART1	\circ	005 NCART1				005 NCART1	005 NCART1	005 NCART1	0	0.2	05 NC	005 NCART1	005 NCART1	005	005	005	005	005	005						
00000	000	00000	00000	0000	0000	0000	00000	00000	0000	00000	0000	0000	0000	\circ	00000	00000	000	0000	00000	0000	0000		0000	00000	0000	0000	0000	0000	0000	0000	00000	00000	00000	00000	00000	00000	0000
L ALL	L ALL	L ALL	L ALL	L ALL	L ALL	L ALL	L ALL	L ALL	L ALL	L ALL	L ALL	L ALL			L ALL	_	L ALL	L ALL	L ALL	L ALL		_	_	_	L ALL												
ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAI	ANNUAI	ANNUAL	ANNUAI	ANNUAL	ANNUAL	ANNUAL	ANNUAI	ANNUAL	ANNUAI	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAI	ANNUAL	ANNUAI	ANNUAL	ANNUAI	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAI							
00.0		•	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	00.0	0.	0.	0.	0.	0.	0.	00.00	0.		0	0
579.00		0.6	579.00	0.6	о О	3.0	3.0	579.00	0.6	0.6	3.0	М	2.0	2.0	2.0	3.0	3.0	2.0	562.00	2.0	2.0	2.0	2.0	2.0	2.0	\	2.0	2.0	2.0	2.0	2.0	330.00	9.3	0.8		1.0	
321.00	23.0	\sim	22.8	22.6	22.1	22.0	22.0	24.0	23.8	23.3	23.1	23.0	23.0	23.0	22.3	24.4	24.0	24.0	24.0	24.0	23.1	23.0	23.0	25.0	25.0	24.	24.6	24.0	24.0	23.8	23.5	30.0	29.3	28.0	S	25.9	25.5
0.00016	00.	.0004	.0003	.0002	.0002	.0002	0.	.0005	.0005	.0004	.0004	.0003	.0002		.0001		9000.	.0005	000.	.0003	.0002	.0002	.0002	.0007	.0008	000.	9000.	0.	.0003	.0002	.0002	9000.	.0010	.001	.0013	0.00046	•
61776.82000 3768675.56000 61426.82000 3768725.56000	1476.82000 3768725.5600	1526.82000 3768725.5600	1576.82000 3768725.5600	1626.82000 3768725.5600	1676.82000 3768725.5600	1726.82000 3768725.5600	1776.82000 3768725.5600	1426.82000 3768775.5600	1476.82000 3768775.5600	1526.82000 3768775.5600	1576.82000 3768775.5600	1626.82000 3768775.5600	1676.82000 3768775.5600	1726.82000 3768775.5600	1776.82000 3768775.5600	1426.82000 3768825.5600	1476.82000 3768825.5600	1526.82000 3768825.5600	1576.82000 3768825.5600	1626.82000 3768825.5600	1676.82000 3768825.5600	1726.82000 3768825.5600	1776.82000 3768825.5600	1426.82000 3768875.5600	1476.82000 3768875.5600	1526.82000 3768875.5600	1576.82000 3768875.5600	1626.82000 3768875.5600	1676.82000 3768875.5600	1726.82000 3768875.5600	1776.82000 3768875.5600	1352.00000 3769256.0000	1484.00000 3769257.0000	1729.00000 3769204.0000	1780.00000 3769203.0000	1786.00000 3769062.0000	1726.00000 3769022.0000

461645.00000 3769015.00000	15.00000	0.00051	326.00	562.00	00.00	ANNUAL	ALL	0000000
461568.00000 3768930.00000	030.0000	0.00085	325.00	562.00	00.0	ANNUAL	ALL	0000000
461434.00000 3769023.00000	123.00000	0.00116	327.00	562.00	00.0	ANNUAL	ALL	0000000
461372.00000 3769044.00000	044.00000	0.00093	327.26	562.00	00.0	ANNUAL	ALL	00000000
461382.00000 3769140.00000	40.00000	0.00077	328.46	561.00	00.0	ANNUAL	ALL	0000000
461286.00000 3769219.00000	119.00000	0.00070	330.00	330.00	00.0	ANNUAL	ALL	0000000
** CONCUNIT ug/m^3								
** DEPUNIT g/m^2								

* AERMOD (22112): Slover / Alder Ave Industrial - 2023-2025 DPM
* AERMET (16216): PM10
* MODELING OPTIONS USED: RegDFAULT CONC ELEV URBAN ADJ_U*

* PLOT FILE OF HIGH 1ST HIGH 24-HR VALUES FOR SOURCE GROUP: ALL FOR A TOTAL OF 76 RECEPTORS.

* FOR A TOTAL OF 76 RECEPTORS.

* FORMAT: (3(1X,F13.5),3(1X,F8.2),3X,A5,2X,A8,2X,A8,2X,18)

	ID DAIE (CONC)	1 1310	1 1502	1 1309	12022924	T	T	1 1	1 1212	1310		1309	П		1110	П	1212	1310	П		1202	1	1110	1212	1212	1 1	150	1 1502	1 1202	1110	1212	121	1 1	Π	П	1 1502	1202	
	NET	NCART	NCART1	NCART	NCART1	NCARI	NCART	NCART1	NCART1	NCART1	NCART	NCART1	NCART1	NCART	NCART1																							
זוי גיר	KANA				1ST	1ST		1ST	1ST		1ST	1ST		1ST			1ST	1ST	1ST			1ST																
	A A A	HR ALL	-HR ALL	-HR ALL	HR ALL	HR ALL	HR ALL	-HR ALL	HR ALL	HR ALL	HR ALL	HR ALL	HR ALL	HR ALL	HR ALL	HR ALL	HR ALL	HR ALL	HR ALL	HR ALL																		
2X, I8)		4-	.00 24-F	4-	4-	4-	4-	24-	24-	4-	4-	4-	4-	24-	24-	24-	24-	24-	24-	24	0 24	24-	24-	24-	24	4-	24-	0 24-	0 24-	24-	24-	4-	.00 24-F	4-	24-	0 24-	4-	
5,2X,A8,2X,A5,5X,A8,2X,I	777	0	.00	.00		0	.00 00.	0	0		.00		.00	.00	0	.00					0	0	0	.00			0	0	0 0	0	.00 00.	.00 00.	.00			0 0		
2X, A8, 2X, I	LE V	75	\sim	\sim	\sim	79	\sim	.00 579	79	\sim	\sim	79	79	\sim	79	579	\sim	\sim	79	\sim	0 57	579	79	\sim	\sim	\sim	.00 579	_	579	579	\sim	\sim	.00 579	.30 579	Γ	.00 579	Γ	
3X, A5,		22 3		11 3	13	94	04 3	91 3	84 32	50 32	39 3	29 3	30 3	13 32	19 3	07 3	92	78 3	63 32	48 32	51 32	33 3	32 3	21	95 3	04 32	m	73 32	70 32	56 3	47 32	33 3	93	33	27 32	206 323	93 32	
5), 3(1X, F8.	LEAGE	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00.	00	00.	
(3(1X, F13.5)	н	8525.5600	8525.5600	8525.5600	8525.5600	8525.5600	8525.5600	8525.5600	8525.5600	8575.5600	8575.5600	8575.5600	8575.5600	8575.5600	8575.5600	8575.5600	8575.5600	8625.5600	8625.5600	8625.5600	8625.5600	8625.5600	8625.5600	8625.5600	8625.5600	8675.5600	8675.5600	8675.5600	8675.5600	8675.5600	8675.5600	8675.5600	8675.5600	8725.5600	8725.5600	8725.56000	8725.5600	
* FORMAT:	<	61426.82000 376	61476.82000 376	61526.82000 376	61576.82000 376	61626.82000 376	61676.82000 376	61726.82000 376	61776.82000 376	61426.82000 376	61476.82000 376	61526.82000 376	61576.82000 376	61626.82000 376	61676.82000 376	61726.82000 376	61776.82000 376	61426.82000 376	61476.82000 376	61526.82000 376	61576.82000 376	61626.82000 376	61676.82000 376	61726.82000 376	61776.82000 376	61426.82000 376	.82000 376	61526.82000 376	61576.82000 376	61626.82000 376	1676.82000 376	61726.82000 376	61776.82000 376	61426.82000 376	61476.82000 376	9	61576.82000 376	

12123024 12123024	101122	502072	502072	502072	203042	110112	212302	212302	104142	502072	502072	502072	203042	212302	212302	612112	203122	502072	502072	502072	203042	212302	212302	612112	203122	612312	612312	Ω	505292	311202	305242	212302	502072	611222	11219	601202	612312	
NCART1 NCART1	NCART1																																					
1ST 1ST	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	Ŋ	
R ALL R ALL	R ALL	R ALL	R ALL	R ALL	R ALL	R ALL	R ALL	R ALL	R ALL	R ALL	R ALL	R ALL		R ALL	R ALL	R ALL							R ALL		R ALL		R ALL		R ALL	R ALL	R ALL	R ALL						
24-HE 24-HE	4-H	4-		4-	24-HR	4-		4-H	4-H	4-H	4-H	4-H	4-H	4-H	4-H	4-H	4-H	4-H	4-H	4-H	4-H	4-H																
00.00	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	
579.00	73.0	79.0	79.0	79.0	73.0	73.0	62.0	62.0	62.0	73.0	73.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	30.0	29.3	28.0	27.8	61.0	61.0	62.0	62.0	62.0	62.0	61.0	30.0	
322.10	22.0	24.0	23.8	23.3	23.1	23.0	23.0	23.0	22.3	24.4	24.0	24.0	24.0	24.0	23.1	23.0	23.0	25.0	25.0	24.7	24.6	24.0	24.0	23.8	23.5	30.0	29.3	28.0	27.8	25.9	25.5	26.0	25.0	27.0	27.2	28.4	30.0	
0.00168	.0009	.0027	.0027	.0024	.0021	.0020	.0018	.0013	.0010	.0029	.0032	.0029	.0025	.0023	.0019	.0012	.0010	.0031	.0038	.0037	.0029	.0026	.0019	.0013	.0012	.0025	.0043	.0047	.0033	.0024	.0023	.0024	.0038	.0037	.0038	.0033	.0019	
461676.82000 3768725.56000 461726.82000 3768725.56000	61776.82000 3768725.5600	61426.82000 3768775.5600	61476.82000 3768775.5600	61526.82000 3768775.5600	61576.82000 3768775.5600	61626.82000 3768775.5600	61676.82000 3768775.5600	61726.82000 3768775.5600	61776.82000 3768775.5600	61426.82000 3768825.5600	61476.82000 3768825.5600	61526.82000 3768825.5600	61576.82000 3768825.5600	61626.82000 3768825.5600	61676.82000 3768825.5600	61726.82000 3768825.5600	61776.82000 3768825.5600	61426.82000 3768875.5600	61476.82000 3768875.5600	61526.82000 3768875.5600	61576.82000 3768875.5600	61626.82000 3768875.5600	61676.82000 3768875.5600	61726.82000 3768875.5600	61776.82000 3768875.5600	61352.00000 3769256.0000	61484.00000 3769257.0000	1729.00000 3769204.0000	61780.00000 3769203.0000	61786.00000 3769062.0000	61726.00000 3769022.0000	61645.00000 3769015.0000	61568.00000 3768930.0000	61434.00000 3769023.0000	372.00000 3769044.0000	61382.00000 3769140.0000	461286.00000 3769219.0000	** CONCUNIT ug/m^3 ** DEPUNIT g/m^2

APPENDIX D

AERMOD Model Years 2026 – 2040 Operational PM10 Printouts

```
***********
** AERMOD Input Produced by:
** AERMOD View Ver. 11.0.1
** Lakes Environmental Software Inc.
** Date: 10/4/2022
** File: C:\Vista Env\2021\21060 SB Co\AERMOD\DPM2026A\DPM2026A.ADI
**********
* *
*********
** AERMOD Control Pathway
*********
**
* *
CO STARTING
  TITLEONE Slover / Alder Ave Industrial - 2026-2040 DPM
  TITLETWO PM10
  MODELOPT DFAULT CONC
  AVERTIME 24 ANNUAL
  URBANOPT 2035210 San Bernardino Co
  POLLUTID PM 10
  RUNORNOT RUN
  ERRORFIL DPM2026A.err
CO FINISHED
**********
** AERMOD Source Pathway
*********
* *
* *
SO STARTING
** Source Location **
** Source ID - Type - X Coord. - Y Coord. **
** -----
** Line Source Represented by Adjacent Volume Sources
** LINE VOLUME Source ID = DWY1
** DESCRSRC Project DWY 1 - Alder Ave
** PREFIX
** Length of Side = 3.66
** Configuration = Adjacent
** Emission Rate = 4.82E-07
** Vertical Dimension = 1.83
** SZINIT = 0.85
** Nodes = 3
** 461413.126, 3769172.571, 329.00, 0.00, 1.70
** 461470.310, 3769171.735, 328.44, 0.00, 1.70
** 461553.714, 3769149.977, 327.87, 0.00, 1.70
** -----
  LOCATION L0000549
                   VOLUME
                          461414.955 3769172.545 328.98
  LOCATION L0000550
                          461418.612 3769172.491 328.95
                   VOLUME
  LOCATION L0000551
                   VOLUME 461422.269 3769172.438 328.91
```

```
461425.926 3769172.384 328.87
  LOCATION L0000552
                       VOLUME
  LOCATION L0000553
                               461429.583 3769172.331 328.84
                       VOLUME
  LOCATION L0000554
                       VOLUME 461433.241 3769172.277 328.80
  LOCATION L0000555
                       VOLUME 461436.898 3769172.224 328.77
                              461440.555 3769172.170 328.73
  LOCATION L0000556
                       VOLUME
                              461444.212 3769172.117 328.70
  LOCATION L0000557
                       VOLUME
  LOCATION L0000558
                      VOLUME 461447.869 3769172.063 328.66
                       VOLUME 461451.527 3769172.009 328.62
  LOCATION L0000559
                       VOLUME 461455.184 3769171.956 328.59
  LOCATION L0000560
                               461458.841 3769171.902 328.55
  LOCATION L0000561
                       VOLUME
                               461462.498 3769171.849 328.52
  LOCATION L0000562
                       VOLUME
                       VOLUME 461466.156 3769171.795 328.48
  LOCATION L0000563
                               461469.813 3769171.742 328.44
  LOCATION L0000564
                       VOLUME
                              461473.368 3769170.937 328.42
  LOCATION L0000565
                       VOLUME
                      VOLUME 461476.907 3769170.014 328.39
  LOCATION L0000566
                      VOLUME 461480.446 3769169.090 328.37
  LOCATION L0000567
                              461483.985 3769168.167 328.35
  LOCATION L0000568
                      VOLUME
                               461487.525 3769167.244 328.32
  LOCATION L0000569
                       VOLUME
                      VOLUME 461491.064 3769166.320 328.30
  LOCATION L0000570
                      VOLUME 461494.603 3769165.397 328.27
  LOCATION L0000571
                             461498.142 3769164.474 328.25
  LOCATION L0000572
                      VOLUME
                      VOLUME 461501.681 3769163.551 328.23
  LOCATION L0000573
  LOCATION L0000574
                      VOLUME 461505.220 3769162.627 328.20
                      VOLUME 461508.759 3769161.704 328.18
  LOCATION L0000575
                              461512.299 3769160.781 328.15
  LOCATION L0000576
                      VOLUME
                      VOLUME 461515.838 3769159.858 328.13
  LOCATION L0000577
                      VOLUME 461519.377 3769158.934 328.10
  LOCATION L0000578
                      VOLUME 461522.916 3769158.011 328.08
  LOCATION L0000579
  LOCATION L0000580
                      VOLUME 461526.455 3769157.088 328.06
                      VOLUME 461529.994 3769156.165 328.03
  LOCATION L0000581
  LOCATION L0000582
                      VOLUME 461533.534 3769155.241 328.01
                      VOLUME 461537.073 3769154.318 327.98
  LOCATION L0000583
                      VOLUME 461540.612 3769153.395 327.96
  LOCATION L0000584
  LOCATION L0000585
                      VOLUME 461544.151 3769152.472 327.94
                      VOLUME 461547.690 3769151.548 327.91
  LOCATION L0000586
                      VOLUME 461551.229 3769150.625 327.89
  LOCATION L0000587
** End of LINE VOLUME Source ID = DWY1
** -----
** Line Source Represented by Adjacent Volume Sources
** LINE VOLUME Source ID = DWY2
** DESCRSRC Project Driveway 2 - Slover Ave West
** PREFIX
** Length of Side = 3.66
** Configuration = Adjacent
** Emission Rate = 2.68E-07
** Vertical Dimension = 1.83
** SZINIT = 0.85
** Nodes = 3
** 461531.677, 3769225.292, 328.91, 0.00, 1.70
** 461531.677, 3769168.387, 328.00, 0.00, 1.70
** 461552.877, 3769160.298, 327.96, 0.00, 1.70
** ______
                              461531.677 3769223.463 328.88
  LOCATION L0000588
                      VOLUME
  LOCATION L0000589 VOLUME 461531.677 3769219.806 328.82
```

```
461531.677 3769216.148 328.76
  LOCATION L0000590
                       VOLUME
  LOCATION L0000591
                               461531.677 3769212.490 328.71
                       VOLUME
  LOCATION L0000592
                       VOLUME
                               461531.677 3769208.833 328.65
  LOCATION L0000593
                       VOLUME
                               461531.677 3769205.175 328.59
  LOCATION L0000594
                               461531.677 3769201.518 328.53
                       VOLUME
                              461531.677 3769197.860 328.47
  LOCATION L0000595
                       VOLUME
                       VOLUME 461531.677 3769194.202 328.41
  LOCATION L0000596
                       VOLUME 461531.677 3769190.545 328.35
  LOCATION L0000597
                              461531.677 3769186.887 328.30
  LOCATION L0000598
                       VOLUME
                               461531.677 3769183.230 328.24
  LOCATION L0000599
                       VOLUME
                               461531.677 3769179.572 328.18
  LOCATION L0000600
                       VOLUME
                       VOLUME 461531.677 3769175.914 328.12
  LOCATION L0000601
                               461531.677 3769172.257 328.06
  LOCATION L0000602
                       VOLUME
                              461531.677 3769168.599 328.00
  LOCATION L0000603
                       VOLUME
                      VOLUME 461534.897 3769167.159 327.99
  LOCATION L0000604
                      VOLUME 461538.314 3769165.855 327.99
  LOCATION L0000605
                      VOLUME 461541.731 3769164.551 327.98
  LOCATION L0000606
                       VOLUME 461545.148 3769163.247 327.97
  LOCATION L0000607
  LOCATION L0000608
                      VOLUME 461548.566 3769161.943 327.97
  LOCATION L0000609
                      VOLUME 461551.983 3769160.639 327.96
** End of LINE VOLUME Source ID = DWY2
** ______
** Line Source Represented by Adjacent Volume Sources
** LINE VOLUME Source ID = DWY3
** DESCRSRC Project Driveway 3 - Slover Ave East
** PREFIX
** Length of Side = 3.66
** Configuration = Adjacent
** Emission Rate = 5.73E-07
** Vertical Dimension = 1.83
** SZINIT = 0.85
** Nodes = 3
** 461673.660, 3769226.129, 328.00, 0.00, 1.70
** 461673.102, 3769173.408, 327.64, 0.00, 1.70
** 461556.782, 3769154.719, 327.97, 0.00, 1.70
** ______
  LOCATION L0000610
                               461673.641 3769224.300 327.99
                       VOLUME
  LOCATION L0000611
                      VOLUME
                              461673.602 3769220.643 327.96
                      VOLUME 461673.563 3769216.985 327.94
  LOCATION L0000612
  LOCATION L0000613
                      VOLUME 461673.525 3769213.328 327.91
  LOCATION L0000614
                              461673.486 3769209.670 327.89
                      VOLUME
  LOCATION L0000615
                      VOLUME
                               461673.447 3769206.013 327.86
                      VOLUME 461673.408 3769202.356 327.84
  LOCATION L0000616
  LOCATION L0000617
                      VOLUME 461673.370 3769198.698 327.81
                               461673.331 3769195.041 327.79
  LOCATION L0000618
                       VOLUME
  LOCATION L0000619
                       VOLUME
                               461673.292 3769191.383 327.76
  LOCATION L0000620
                      VOLUME
                              461673.254 3769187.726 327.74
  LOCATION L0000621
                       VOLUME
                              461673.215 3769184.069 327.71
                               461673.176 3769180.411 327.69
  LOCATION L0000622
                       VOLUME
  LOCATION L0000623
                               461673.137 3769176.754 327.66
                       VOLUME
                               461672.794 3769173.359 327.64
  LOCATION L0000624
                      VOLUME
  LOCATION L0000625
                      VOLUME 461669.183 3769172.779 327.65
                              461665.572 3769172.198 327.66
  LOCATION L0000626
                       VOLUME
  LOCATION L0000627
                      VOLUME
                              461661.960 3769171.618 327.67
```

```
461658.349 3769171.038 327.68
  LOCATION L0000628
                       VOLUME
  LOCATION L0000629
                               461654.738 3769170.458 327.69
                       VOLUME
  LOCATION L0000630
                               461651.127 3769169.877 327.70
                       VOLUME
  LOCATION L0000631
                       VOLUME 461647.515 3769169.297 327.71
  LOCATION L0000632
                               461643.904 3769168.717 327.72
                       VOLUME
  LOCATION L0000633
                               461640.293 3769168.137 327.73
                       VOLUME
  LOCATION L0000634
                       VOLUME 461636.681 3769167.557 327.74
                       VOLUME 461633.070 3769166.976 327.75
  LOCATION L0000635
                       VOLUME 461629.459 3769166.396 327.76
  LOCATION L0000636
  LOCATION L0000637
                       VOLUME
                               461625.848 3769165.816 327.77
                               461622.236 3769165.236 327.78
  LOCATION L0000638
                       VOLUME
                       VOLUME 461618.625 3769164.655 327.79
  LOCATION L0000639
                                461615.014 3769164.075 327.80
  LOCATION L0000640
                       VOLUME
                               461611.402 3769163.495 327.82
  LOCATION L0000641
                       VOLUME
                       VOLUME 461607.791 3769162.915 327.83
  LOCATION L0000642
                       VOLUME 461604.180 3769162.334 327.84
  LOCATION L0000643
                              461600.569 3769161.754 327.85
  LOCATION L0000644
                       VOLUME
                               461596.957 3769161.174 327.86
  LOCATION L0000645
                       VOLUME
  LOCATION L0000646
                       VOLUME 461593.346 3769160.594 327.87
  LOCATION L0000647
                       VOLUME 461589.735 3769160.014 327.88
                              461586.123 3769159.433 327.89
  LOCATION L0000648
                       VOLUME
                       VOLUME 461582.512 3769158.853 327.90
  LOCATION L0000649
  LOCATION L0000650
                      VOLUME 461578.901 3769158.273 327.91
                      VOLUME 461575.290 3769157.693 327.92
  LOCATION L0000651
                              461571.678 3769157.112 327.93
  LOCATION L0000652
                       VOLUME
                       VOLUME 461568.067 3769156.532 327.94
  LOCATION L0000653
                       VOLUME 461564.456 3769155.952 327.95
  LOCATION L0000654
                       VOLUME 461560.844 3769155.372 327.96
  LOCATION L0000655
  LOCATION L0000656
                      VOLUME 461557.233 3769154.791 327.97
** End of LINE VOLUME Source ID = DWY3
** Line Source Represented by Adjacent Volume Sources
** LINE VOLUME Source ID = ALDER
** DESCRSRC Alder Ave - DWY 1 to Slover Ave
** PREFIX
** Length of Side = 3.66
** Configuration = Adjacent
** Emission Rate = 1.3E-07
** Vertical Dimension = 1.83
** SZINIT = 0.85
** Nodes = 2
** 461405.873, 3769224.734, 329.00, 0.00, 1.70
** 461405.873, 3769172.014, 329.00, 0.00, 1.70
** -----
                               461405.873 3769222.905 329.00
  LOCATION L0000657
                       VOLUME
  LOCATION L0000658
                       VOLUME
                              461405.873 3769219.248 329.00
  LOCATION L0000659
                       VOLUME 461405.873 3769215.590 329.00
  LOCATION L0000660
                      VOLUME 461405.873 3769211.932 329.00
                              461405.873 3769208.275 329.00
  LOCATION L0000661
                       VOLUME
  LOCATION L0000662
                       VOLUME 461405.873 3769204.617 329.00
                      VOLUME 461405.873 3769200.960 329.00
  LOCATION L0000663
  LOCATION L0000664
                       VOLUME 461405.873 3769197.302 329.00
                              461405.873 3769193.644 329.00
  LOCATION L0000665
                       VOLUME
  LOCATION L0000666
                      VOLUME 461405.873 3769189.987 329.00
```

```
461405.873 3769186.329 329.00
  LOCATION L0000667
                      VOLUME
  LOCATION L0000668
                       VOLUME 461405.873 3769182.672 329.00
  LOCATION L0000669
                      VOLUME 461405.873 3769179.014 329.00
  LOCATION L0000670
                      VOLUME 461405.873 3769175.356 329.00
** End of LINE VOLUME Source ID = ALDER
** -----
** Line Source Represented by Adjacent Volume Sources
** LINE VOLUME Source ID = SLOVER
** DESCRSRC Slover Ave
** PREFIX
** Length of Side = 12.19
** Configuration = Adjacent
** Emission Rate = 4.39E-06
** Vertical Dimension = 1.83
** SZINIT = 0.85
** Nodes = 5
** 460972.339, 3769234.573, 331.00, 0.00, 5.67
** 461117.706, 3769238.668, 330.83, 0.00, 5.67
** 461377.729, 3769233.550, 329.63, 0.00, 5.67
** 461809.736, 3769235.597, 328.00, 0.00, 5.67
** 462162.918, 3769234.573, 327.68, 0.00, 5.67
** -----
  LOCATION L0000671
                              460978.432 3769234.745 330.99
                      VOLUME
                              460990.619 3769235.088 330.98
  LOCATION L0000672
                      VOLUME
                              461002.807 3769235.432 330.96
  LOCATION L0000673
                       VOLUME
                              461014.994 3769235.775 330.95
  LOCATION L0000674
                       VOLUME
                       VOLUME 461027.181 3769236.118 330.94
  LOCATION L0000675
                       VOLUME 461039.368 3769236.462 330.92
  LOCATION L0000676
  LOCATION L0000677
                               461051.555 3769236.805 330.91
                       VOLUME
                              461063.742 3769237.148 330.89
  LOCATION L0000678
                       VOLUME
  LOCATION L0000679
                       VOLUME 461075.930 3769237.492 330.88
                              461088.117 3769237.835 330.86
  LOCATION L0000680
                       VOLUME
                               461100.304 3769238.178 330.85
  LOCATION L0000681
                       VOLUME
                               461112.491 3769238.521 330.84
  LOCATION L0000682
                       VOLUME
  LOCATION L0000683
                       VOLUME
                               461124.680 3769238.531 330.80
                       VOLUME 461136.869 3769238.291 330.74
  LOCATION L0000684
  LOCATION L0000685
                               461149.059 3769238.051 330.69
                       VOLUME
  LOCATION L0000686
                       VOLUME
                              461161.249 3769237.811 330.63
                              461173.438 3769237.571 330.57
  LOCATION L0000687
                       VOLUME
  LOCATION L0000688
                              461185.628 3769237.331 330.52
                       VOLUME
                               461197.817 3769237.091 330.46
  LOCATION L0000689
                       VOLUME
  LOCATION L0000690
                       VOLUME
                               461210.007 3769236.851 330.40
                               461222.197 3769236.611 330.35
  LOCATION L0000691
                       VOLUME
  LOCATION L0000692
                               461234.386 3769236.371 330.29
                       VOLUME
                               461246.576 3769236.132 330.24
  LOCATION L0000693
                       VOLUME
  LOCATION L0000694
                       VOLUME
                               461258.766 3769235.892 330.18
  LOCATION L0000695
                       VOLUME
                              461270.955 3769235.652 330.12
  LOCATION L0000696
                       VOLUME
                               461283.145 3769235.412 330.07
                               461295.335 3769235.172 330.01
  LOCATION L0000697
                       VOLUME
  LOCATION L0000698
                               461307.524 3769234.932 329.95
                       VOLUME
                               461319.714 3769234.692 329.90
  LOCATION L0000699
                       VOLUME
  LOCATION L0000700
                       VOLUME 461331.903 3769234.452 329.84
                              461344.093 3769234.212 329.79
  LOCATION L0000701
                       VOLUME
  LOCATION L0000702
                      VOLUME
                              461356.283 3769233.972 329.73
```

```
LOCATION L0000703
                                461368.472 3769233.732 329.67
                      VOLUME
LOCATION L0000704
                                461380.663 3769233.564 329.62
                      VOLUME
LOCATION L0000705
                                461392.854 3769233.621 329.57
                      VOLUME
LOCATION L0000706
                      VOLUME
                                461405.046 3769233.679 329.53
LOCATION L0000707
                                461417.238 3769233.737 329.48
                      VOLUME
LOCATION L0000708
                                461429.430 3769233.795 329.43
                      VOLUME
LOCATION L0000709
                      VOLUME
                                461441.622 3769233.853 329.39
LOCATION L0000710
                                461453.814 3769233.910 329.34
                      VOLUME
                                461466.006 3769233.968 329.30
LOCATION L0000711
                      VOLUME
                                461478.197 3769234.026 329.25
LOCATION L0000712
                      VOLUME
                                461490.389 3769234.084 329.20
LOCATION L0000713
                      VOLUME
                                461502.581 3769234.141 329.16
LOCATION L0000714
                      VOLUME
                                461514.773 3769234.199 329.11
LOCATION L0000715
                      VOLUME
LOCATION L0000716
                                461526.965 3769234.257 329.07
                      VOLUME
                                461539.157 3769234.315 329.02
LOCATION L0000717
                      VOLUME
                                461551.349 3769234.373 328.97
LOCATION L0000718
                      VOLUME
                                461563.540 3769234.430 328.93
LOCATION L0000719
                      VOLUME
                                461575.732 3769234.488 328.88
LOCATION L0000720
                      VOLUME
LOCATION L0000721
                                461587.924 3769234.546 328.84
                      VOLUME
LOCATION L0000722
                      VOLUME
                                461600.116 3769234.604 328.79
                                461612.308 3769234.662 328.74
LOCATION L0000723
                      VOLUME
                                461624.500 3769234.719 328.70
LOCATION L0000724
                      VOLUME
LOCATION L0000725
                      VOLUME
                                461636.692 3769234.777 328.65
                                461648.884 3769234.835 328.61
LOCATION L0000726
                      VOLUME
                                461661.075 3769234.893 328.56
LOCATION L0000727
                      VOLUME
                                461673.267 3769234.950 328.51
LOCATION L0000728
                      VOLUME
LOCATION L0000729
                                461685.459 3769235.008 328.47
                      VOLUME
                                461697.651 3769235.066 328.42
LOCATION L0000730
                      VOLUME
LOCATION L0000731
                                461709.843 3769235.124 328.38
                      VOLUME
                                461722.035 3769235.182 328.33
LOCATION L0000732
                      VOLUME
LOCATION L0000733
                      VOLUME
                                461734.227 3769235.239 328.28
                                461746.418 3769235.297 328.24
LOCATION L0000734
                      VOLUME
                                461758.610 3769235.355 328.19
LOCATION L0000735
                      VOLUME
LOCATION L0000736
                      VOLUME
                                461770.802 3769235.413 328.15
                                461782.994 3769235.470 328.10
LOCATION L0000737
                      VOLUME
LOCATION L0000738
                      VOLUME
                                461795.186 3769235.528 328.05
LOCATION L0000739
                                461807.378 3769235.586 328.01
                      VOLUME
LOCATION L0000740
                      VOLUME
                                461819.570 3769235.569 327.99
LOCATION L0000741
                                461831.762 3769235.533 327.98
                      VOLUME
LOCATION L0000742
                      VOLUME
                                461843.954 3769235.498 327.97
                                461856.146 3769235.463 327.96
LOCATION L0000743
                      VOLUME
LOCATION L0000744
                      VOLUME
                                461868.337 3769235.427 327.95
LOCATION L0000745
                                461880.529 3769235.392 327.94
                      VOLUME
LOCATION L0000746
                      VOLUME
                                461892.721 3769235.357 327.92
                                461904.913 3769235.321 327.91
LOCATION L0000747
                      VOLUME
LOCATION L0000748
                      VOLUME
                                461917.105 3769235.286 327.90
LOCATION L0000749
                      VOLUME
                                461929.297 3769235.251 327.89
                      VOLUME
LOCATION L0000750
                                461941.489 3769235.215 327.88
                                461953.681 3769235.180 327.87
LOCATION L0000751
                      VOLUME
LOCATION L0000752
                      VOLUME
                                461965.873 3769235.145 327.86
                                461978.065 3769235.109 327.85
LOCATION L0000753
                      VOLUME
LOCATION L0000754
                                461990.257 3769235.074 327.84
                      VOLUME
                                462002.449 3769235.039 327.83
LOCATION L0000755
                      VOLUME
LOCATION L0000756
                      VOLUME
                               462014.641 3769235.003 327.81
```

```
LOCATION L0000757
                                   462026.833 3769234.968 327.80
                         VOLUME
  LOCATION L0000758
                         VOLUME
                                   462039.025 3769234.933 327.79
  LOCATION L0000759
                                   462051.217 3769234.897 327.78
                         VOLUME
  LOCATION L0000760
                         VOLUME
                                   462063.409 3769234.862 327.77
  LOCATION L0000761
                                   462075.601 3769234.827 327.76
                         VOLUME
  LOCATION L0000762
                                   462087.793 3769234.791 327.75
                         VOLUME
                                   462099.985 3769234.756 327.74
  LOCATION L0000763
                         VOLUME
  LOCATION L0000764
                                   462112.176 3769234.721 327.73
                         VOLUME
                                   462124.368 3769234.685 327.71
  LOCATION L0000765
                         VOLUME
  LOCATION L0000766
                                   462136.560 3769234.650 327.70
                         VOLUME
  LOCATION L0000767
                                   462148.752 3769234.615 327.69
                         VOLUME
                                   462160.944 3769234.579 327.68
  LOCATION L0000768
                         VOLUME
** End of LINE VOLUME Source ID = SLOVER
  LOCATION IDLING
                                     461555.730 3769145.780
                                                                   327.690
                         POINT
** DESCRSRC Truck Idling
** Source Parameters **
** LINE VOLUME Source ID = DWY1
   SRCPARAM L0000549
                                             0.00
                                                       1.70
                         0.0000001236
                                                                  0.85
   SRCPARAM L0000550
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000551
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000552
                                             0.00
                                                       1.70
                         0.0000001236
                                                                  0.85
                         0.0000001236
                                             0.00
   SRCPARAM L0000553
                                                       1.70
                                                                  0.85
   SRCPARAM L0000554
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000555
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000556
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000557
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000558
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
                                                       1.70
   SRCPARAM L0000559
                         0.0000001236
                                             0.00
                                                                  0.85
   SRCPARAM L0000560
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000561
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000562
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000563
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
                                                       1.70
   SRCPARAM L0000564
                         0.0000001236
                                             0.00
                                                                  0.85
   SRCPARAM L0000565
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000566
                                                                  0.85
                         0.0000001236
                                             0.00
                                                       1.70
   SRCPARAM L0000567
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000568
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000569
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
                         0.0000001236
                                             0.00
                                                       1.70
   SRCPARAM L0000570
                                                                  0.85
   SRCPARAM L0000571
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000572
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000573
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000574
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
  SRCPARAM L0000575
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
                                                       1.70
   SRCPARAM L0000576
                         0.0000001236
                                             0.00
                                                                  0.85
   SRCPARAM L0000577
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000578
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000579
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000580
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000581
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
                         0.0000001236
   SRCPARAM L0000582
                                             0.00
                                                       1.70
                                                                  0.85
  SRCPARAM L0000583
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
   SRCPARAM L0000584
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
  SRCPARAM L0000585
                         0.0000001236
                                             0.00
                                                       1.70
                                                                  0.85
```

**		L0000587	0.00000001236 0.00000001236	0.00	1.70 1.70	0.85 0.85
	LINE VOLU SRCPARAM	JME Source ID L0000588 L0000590 L0000591 L0000593 L0000594 L0000595 L0000596 L0000597 L0000598 L0000599 L0000600 L0000601 L0000601 L0000603 L0000605 L0000605 L0000606	0.0000001218 0.0000001218	0.00 0.00	1.70 1.70 1.70 1.70 1.70 1.70 1.70 1.70	0.85 0.85 0.85 0.85 0.85 0.85 0.85 0.85 0.85 0.85 0.85 0.85 0.85 0.85 0.85 0.85 0.85 0.85 0.85 0.85
	LINE VOLU SRCPARAM SRCPARAM SRCPARAM SRCPARAM	JME Source ID L0000610 L0000611 L0000612 L0000613 L0000614 L0000615			1.70 1.70 1.70 1.70 1.70 1.70 1.70 1.70	0.85 0.85 0.85 0.85 0.85 0.85 0.85
	SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM SRCPARAM	L0000617 L0000618 L0000619 L0000620 L0000621 L0000622 L0000623 L0000625 L0000625 L0000627 L0000627 L0000629 L0000630 L0000631 L0000632	0.0000001219 0.0000001219 0.00000001219 0.00000001219 0.00000001219 0.00000001219 0.00000001219 0.00000001219 0.0000001219 0.00000001219 0.00000001219 0.00000001219 0.00000001219 0.00000001219 0.00000001219 0.00000001219 0.00000001219	0.00	1.70 1.70 1.70 1.70 1.70 1.70 1.70 1.70 1.70 1.70 1.70 1.70 1.70 1.70 1.70	0.85 0.85 0.85 0.85 0.85 0.85 0.85 0.85 0.85 0.85 0.85 0.85 0.85 0.85 0.85

	SRCPARAM	L0000636		0.0000001219	0.00		0.85
		L0000637		0.0000001219	0.00		0.85
		L0000638		0.00000001219	0.00		0.85
		L0000639		0.0000001219	0.00		0.85
		L0000640		0.0000001219	0.00		0.85
		L0000641		0.0000001219	0.00		0.85
		L0000642		0.0000001219	0.00		0.85
		L0000643		0.0000001219	0.00		0.85
		L0000644		0.0000001219	0.00		0.85
	SRCPARAM			0.0000001219	0.00		0.85
	SRCPARAM	L0000646		0.0000001219	0.00	1.70	0.85
		L0000647		0.0000001219	0.00		0.85
	SRCPARAM			0.0000001219	0.00		0.85
		L0000649		0.0000001219	0.00		0.85
	SRCPARAM	L0000650		0.0000001219	0.00	1.70	0.85
		L0000651		0.0000001219	0.00	1.70	0.85
		L0000652		0.0000001219	0.00		0.85
	SRCPARAM	L0000653		0.0000001219	0.00	1.70	0.85
	SRCPARAM	L0000654		0.0000001219	0.00	1.70	0.85
		L0000655		0.0000001219	0.00		
	SRCPARAM	L0000656		0.0000001219	0.00	1.70	0.85
**							
* *		JME Source	ΙD				
		L0000657		0.000000009286			
		L0000658		0.000000009286	0.0		
		L0000659		0.000000009286	0.0		
		L0000660		0.000000009286	0.0		
		L0000661		0.000000009286	0.0		
		L0000662		0.000000009286	0.0		
	SRCPARAM			0.000000009286	0.0		
		L0000664		0.000000009286	0.0		
	SRCPARAM			0.000000009286	0.0		
		L0000666		0.000000009286	0.0		
		L0000667		0.000000009286	0.0		
		L0000668		0.000000009286	0.0		
		L0000669		0.000000009286	0.0		
	SRCPARAM	L0000670		0.000000009286	0.0	1.70	0.85
**							
**		JME Source	ID				
		L0000671		0.0000000448		5.67	
		L0000672		0.0000000448		5.67	0.85
		L0000673		0.0000000448	0.00	5.67	0.85
	SRCPARAM			0.0000000448	0.00	5.67	0.85
	SRCPARAM			0.0000000448	0.00	5.67	0.85
	SRCPARAM			0.0000000448	0.00	5.67	0.85
	SRCPARAM			0.0000000448	0.00	5.67	0.85
	SRCPARAM			0.0000000448	0.00	5.67	0.85
	SRCPARAM			0.0000000448	0.00	5.67	0.85
	SRCPARAM			0.000000448	0.00	5.67	0.85
	SRCPARAM			0.000000448	0.00	5.67	0.85
	SRCPARAM			0.0000000448	0.00	5.67	0.85
	SRCPARAM			0.000000448	0.00	5.67	0.85
		L0000684		0.0000000448	0.00	5.67	0.85
	SRCPARAM	L0000685		0.0000000448	0.00	5.67	0.85

	L0000686	0.0000000448	0.00	5.67	0.85
	L0000687	0.000000448	0.00	5.67	0.85
	L0000688	0.0000000448	0.00	5.67	0.85
	L0000689	0.0000000448	0.00	5.67	0.85
SRCPARAM	L0000690	0.0000000448	0.00	5.67	0.85
SRCPARAM	L0000691	0.0000000448	0.00	5.67	0.85
SRCPARAM	L0000692	0.0000000448	0.00	5.67	0.85
	L0000693	0.0000000448	0.00	5.67	0.85
	L0000694	0.0000000448	0.00	5.67	0.85
	L0000695	0.0000000448	0.00	5.67	0.85
	L0000696	0.000000448	0.00	5.67	0.85
	L0000697	0.000000448	0.00	5.67	0.85
	L0000698	0.000000448	0.00	5.67	0.85
	L0000699	0.000000448	0.00	5.67	0.85
	L0000700	0.000000448	0.00	5.67	0.85
	L0000701	0.0000000448	0.00	5.67	0.85
	L0000702	0.0000000448	0.00	5.67	0.85
	L0000702	0.0000000448	0.00	5.67	0.85
	L0000704	0.0000000448	0.00	5.67	0.85
	L0000705	0.0000000448	0.00	5.67	0.85
	L0000705	0.0000000448	0.00	5.67	0.85
	L0000707	0.0000000448	0.00	5.67	0.85
	L0000707	0.0000000448	0.00	5.67	0.85
	L0000708		0.00	5.67	
	L0000709	0.0000000448			0.85
		0.0000000448	0.00	5.67	0.85
	L0000711	0.0000000448	0.00	5.67	0.85
	L0000712	0.0000000448	0.00	5.67	0.85
	L0000713	0.0000000448	0.00	5.67	0.85
	L0000714	0.0000000448	0.00	5.67	0.85
	L0000715	0.0000000448	0.00	5.67	0.85
	L0000716	0.000000448	0.00	5.67	0.85
	L0000717	0.000000448	0.00	5.67	0.85
	L0000718	0.000000448	0.00	5.67	0.85
	L0000719	0.000000448	0.00	5.67	0.85
	L0000720	0.000000448	0.00	5.67	0.85
	L0000721	0.0000000448	0.00	5.67	0.85
	L0000722	0.0000000448	0.00	5.67	0.85
	L0000723	0.000000448	0.00	5.67	0.85
	L0000724	0.000000448	0.00	5.67	0.85
SRCPARAM	L0000725	0.000000448	0.00	5.67	0.85
	L0000726	0.000000448	0.00	5.67	0.85
SRCPARAM	L0000727	0.000000448	0.00	5.67	0.85
	L0000728	0.000000448	0.00	5.67	0.85
SRCPARAM	L0000729	0.0000000448	0.00	5.67	0.85
SRCPARAM	L0000730	0.0000000448	0.00	5.67	0.85
SRCPARAM	L0000731	0.0000000448	0.00	5.67	0.85
SRCPARAM	L0000732	0.000000448	0.00	5.67	0.85
SRCPARAM	L0000733	0.000000448	0.00	5.67	0.85
SRCPARAM	L0000734	0.000000448	0.00	5.67	0.85
	L0000735	0.000000448	0.00	5.67	0.85
	L0000736	0.000000448	0.00	5.67	0.85
	L0000737	0.000000448	0.00	5.67	0.85
	L0000738	0.000000448	0.00	5.67	0.85
	L0000739	0.000000448	0.00	5.67	0.85
	-	-			-

SRCPARAM L0000740 0.0000000448 0.00 5.67	0 05
SRCPARAM L0000741 0.000000448 0.00 5.67	
SRCPARAM L0000742 0.000000448 0.00 5.67	
SRCPARAM L0000743 0.000000448 0.00 5.67	
SRCPARAM L0000744 0.000000448 0.00 5.67	0.85
SRCPARAM L0000745 0.000000448 0.00 5.67	0.85
SRCPARAM L0000746 0.000000448 0.00 5.67	
SRCPARAM L0000747 0.000000448 0.00 5.67	
SRCPARAM L0000748	
SRCPARAM L0000749 0.0000000448 0.00 5.67	
SRCPARAM L0000750 0.000000448 0.00 5.67	
SRCPARAM L0000751 0.000000448 0.00 5.67	
SRCPARAM L0000752 0.000000448 0.00 5.67	
SRCPARAM L0000753 0.000000448 0.00 5.67	0.85
SRCPARAM L0000754 0.000000448 0.00 5.67	0.85
SRCPARAM L0000755 0.000000448 0.00 5.67	0.85
SRCPARAM L0000756 0.000000448 0.00 5.67	
SRCPARAM L0000757 0.000000448 0.00 5.67	
SRCPARAM L0000758	
SRCPARAM L0000759 0.0000000448 0.00 5.67	
SRCPARAM L0000761 0.0000000448 0.00 5.67	0.85
SRCPARAM L0000762 0.000000448 0.00 5.67	0.85
SRCPARAM L0000763 0.000000448 0.00 5.67	0.85
QDCDDDDM I 0000764 0 0000000448 0 00 5 67	0.85
5KC: AKAM 10000/04 0.000000440 0.00 5.0/	
SRCPARAM L0000764 0.000000448 0.00 5.67 SRCPARAM L0000765 0.000000448 0.00 5.67	0.85
SRCPARAM L0000765 0.000000448 0.00 5.67	0.85
SRCPARAM L0000765 0.000000448 0.00 5.67 SRCPARAM L0000766 0.000000448 0.00 5.67	7 0.85 7 0.85
SRCPARAM L0000765 0.0000000448 0.00 5.67 SRCPARAM L0000766 0.0000000448 0.00 5.67 SRCPARAM L0000767 0.0000000448 0.00 5.67	7 0.85 7 0.85 7 0.85
SRCPARAM L0000765 0.000000448 0.00 5.67 SRCPARAM L0000766 0.000000448 0.00 5.67	7 0.85 7 0.85 7 0.85
SRCPARAM L0000765	7 0.85 7 0.85 7 0.85 7 0.85
SRCPARAM L0000765 0.0000000448 0.00 5.67 SRCPARAM L0000766 0.0000000448 0.00 5.67 SRCPARAM L0000767 0.0000000448 0.00 5.67 SRCPARAM L0000768 0.0000000448 0.00 5.67	7 0.85 7 0.85 7 0.85 7 0.85
SRCPARAM L0000765	7 0.85 7 0.85 7 0.85 7 0.85
SRCPARAM L0000765	0.85 0.85 0.85 0.85 0.85
SRCPARAM L0000765	0.85 0.85 0.85 0.85 0.85 0.1 3.41 13.41 13.41 3.41 13.41 13.41 3.41 13.41 13.41 3.41 13.41 13.41
SRCPARAM L0000765	0.85 0.85 0.85 0.85 0.85 0.1 3.41 13.41 13.41 3.41 13.41 13.41 3.41 13.41 13.41 3.41 13.41 13.41 3.41 13.41 13.41
SRCPARAM L0000765	0.85 0.85 0.85 0.85 0.85 0.1 3.41 13.41 13.41 3.41 13.41 13.41 3.41 13.41 13.41 3.41 13.41 13.41 3.41 13.41 13.41
SRCPARAM L0000765	0.85 0.85 0.85 0.85 0.85 0.1 3.41 13.41 13.41 3.41 13.41 13.41 3.41 13.41 13.41 3.41 13.41 13.41 3.41 13.41 13.41 3.41 13.41 13.41
SRCPARAM L0000765	0.85 0.85 0.85 0.85 0.85 0.1 3.41 13.41 13.41 3.41 13.41 13.41 3.41 13.41 13.41 3.41 13.41 13.41 3.41 13.41 13.41
SRCPARAM L0000765	0.85 0.85 0.85 0.85 0.85 0.1 3.41 13.41 13.41 3.41 13.41 13.41 3.41 13.41 13.41 3.41 13.41 13.41 3.41 13.41 13.41 3.41 13.41 13.41
SRCPARAM L0000765	0.85 0.85 0.85 0.85 0.85 0.1 3.41 13.41 13.41 3.41 13.41 13.41
SRCPARAM L0000765	0.85 0.85 0.85 0.85 0.85 0.1 3.41 13.41 13.41 3.41 13.41 23.41 3.41 13.41 23.41 3.41 13.41 23.41 3.41 13.41 23.41
SRCPARAM L0000765	0.85 0.85 0.85 0.85 0.85 0.1 3.41 13.41 13.41 3.41 29 245.96 220.16 3.86 188.07 220.57 3.84 270.34 255.74 3.29 245.96 220.16
SRCPARAM L0000765 0.0000000448 0.00 5.67 SRCPARAM L0000767 0.0000000448 0.00 5.67 SRCPARAM L0000767 0.0000000448 0.00 5.67 SRCPARAM L0000768 0.0000000448 0.00 5.67 SRCPARAM L0000768 0.0000000448 0.00 5.67 ** Building Downwash ** BUILDHGT IDLING 13.41	0.85 0.85 0.85 0.85 0.85 0.1 3.41 13.41 13.41 3.41 13.41 2.55 3.86 188.07 220.57 3.86 188.07 220.57 3.86 188.07 220.57
SRCPARAM L0000765 0.0000000448 0.00 5.67 SRCPARAM L0000767 0.0000000448 0.00 5.67 SRCPARAM L0000767 0.0000000448 0.00 5.67 SRCPARAM L0000768 0.0000000448 0.00 5.67 SRCPARAM L0000768 0.0000000448 0.00 5.67 ** Building Downwash ** BUILDHGT IDLING 13.41	0.85 0.85 0.85 0.85 0.85 0.1 3.41 13.41 13.41 3.41 29 245.96 220.16 3.86 188.07 220.57 3.84 270.34 255.74 3.29 245.96 220.16
SRCPARAM L0000765	0.85 0.85 0.85 0.85 0.85 0.1 3.41 13.41 13.41 3.41 13.41 23.41 3.41 13.41 23.41
SRCPARAM L0000765	0.85 0.85 0.85 0.85 0.85 0.1 3.41 13.41 13.41 3.41 2.9 245.96 220.16 0.86 188.07 220.57 5.84 270.34 255.74 1.29 245.96 220.16 0.86 188.07 220.57 5.84 270.34 255.74 1.29 245.96 220.16 1.29 245.96 220.16 1.30 255.74 1.30 255.74
SRCPARAM L0000765	0.85 0.85 0.85 0.85 0.85 0.1 3.41 13.41 13.41 3.41 29 245.96 220.16 3.86 188.07 220.57 3.84 270.34 255.74 3.29 245.96 220.16 3.86 188.07 220.57 3.86 264.67 274.93 3.63 264.67 274.93 3.009 276.54 274.58
SRCPARAM L0000765	0.85 0.85 0.85 0.85 0.85 0.1 3.41 13.41 13.41 3.41 13.41 220.16 3.86 188.07 220.57 3.84 270.34 255.74 3.86 264.67 274.93 3.86 264.67 274.93 3.87 276.54 274.58 3.87 276.54 274.58 3.87 276.54 274.58 3.87 276.54 274.58 3.87 276.54 274.58 3.87 276.54 274.58 3.87 276.54 274.58
SRCPARAM L0000765	0.85 0.85 0.85 0.85 0.85 0.1 3.41 13.41 13.41 3.41 13.41 220.57 3.86 188.07 220.57 5.84 270.34 255.74 3.86 188.07 220.57 5.86 188.07 220.57 5.86 264.67 274.93 6.36 264.67 274.93 6.36 264.67 274.93 6.36 264.67 274.93
SRCPARAM L0000765	0.85 0.85 0.85 0.85 0.85 0.1 3.41 13.41 13.41 3.41 13.41 220.16 3.86 188.07 220.57 3.84 270.34 255.74 3.86 264.67 274.93 3.86 264.67 274.93 3.87 276.54 274.58 3.87 276.54 274.58 3.87 276.54 274.58 3.87 276.54 274.58 3.87 276.54 274.58 3.87 276.54 274.58 3.87 276.54 274.58

```
-119.03 -136.14 -149.11 -157.55 -161.21 -159.96
  XBADJ
       TDLING
  XBADJ
                     -153.86 -143.08 -127.95 -127.18 -122.85 -114.78
         IDLING
        IDLING
                     -103.24 -88.55 -71.17 -51.63 -30.53
  XBADJ
  XBADJ
        IDLING
                     -30.83 -51.93 -71.45 -88.80 -103.46 -114.97
                     -122.99 -127.27 -127.79 -142.91 -153.69 -159.80
  XBADJ
         IDLING
                     -161.05 -157.41 -148.99 -136.04 -118.96
  XBADJ
         IDLING
  YBADJ
                     -7.87 -15.42 -22.51 -28.91 -34.43
        IDLING
       IDLING
                     -42.20 -44.22 -44.52 -44.10 -42.11 -38.83
  YBADJ
                      -34.37
                            -28.87
                                   -22.50
                                           -15.44
                                                    -7.91
  YBADJ
         IDLING
                       7.87
                             15.42
                                    22.51 28.91
                                                    34.43
        IDLING
  YBADJ
                                                   42.11
                      42.20
                             44.22
                                    44.52
                                            44.10
  YBADJ
         IDLING
                      34.37 28.87 22.50 15.44
         IDLING
                                                   7.91
  YBADJ
  URBANSRC ALL
  SRCGROUP ALL
SO FINISHED
* *
*********
** AERMOD Receptor Pathway
********
* *
RE STARTING
  INCLUDED DPM2026A.rou
RE FINISHED
**********
** AERMOD Meteorology Pathway
*********
* *
ME STARTING
  SURFFILE ..\FontanaADJU\FONT V9 ADJU\FONT v9.SFC
  PROFFILE ..\FontanaADJU\FONT V9 ADJU\FONT v9.PFL
  SURFDATA 3102 2011 Fontana
  UAIRDATA 3190 2011
  SITEDATA 99999 2011
  PROFBASE 367.0 METERS
ME FINISHED
* *
**********
** AERMOD Output Pathway
***********
**
* *
OU STARTING
  RECTABLE ALLAVE 1ST
  RECTABLE 24 1ST
** Auto-Generated Plotfiles
  PLOTFILE 24 ALL 1ST DPM2026A.AD\24H1GALL.PLT 31
  PLOTFILE ANNUAL ALL DPM2026A.AD\AN00GALL.PLT 32
  SUMMFILE DPM2026A.sum
```

OU FINISHED

-9.28

-98.31

-38.91

-0.08

38.91

38.83

0.08

* *

** Project Parameters

** PROJCTN CoordinateSystemUTM

** DESCPTN UTM: Universal Transverse Mercator

** DATUM World Geodetic System 1984

** DTMRGN Global Definition

** UNITS m

** ZONE 11

** ZONEINX 0

* *

* AERMOD (22112): Slover / Alder Ave Industrial - 2026-2040 DPM \star AERMET (16216):

* MODELING OPTIONS USED: RegDFAULT CONC ELEV URBAN ADJ_U*

* PLOT FILE OF ANNUAL VALUES AVERAGED ACROSS 5 YEARS FOR SOURCE GROUP: ALL

* FOR A TOTAL OF 76 RECEPTORS.

* FORMAT: (3(1x,F13.5),3(1x,F8.2),2x,A6,2x,A8,2x,18.8,2x,A8)

* AVERAGE CONC ZELEV ZHILL ZFLAG AVE GRP

	ı																														
NET ID	NCART1	NCART1	NCART1	NCART1	NCART1	NCART1	NCART1	NCART1	NCART1	NCART1	NCART1	NCART1	NCART1	NCART1	NCART1	NCART1	NCART1	NCART1	NCART1	NCART1	NCART1	NCART1	NCART1	NCART1							
NUM YRS	00000	0	00000	000000	00000	000000	00	00000	000000	000000	00000	000000	00000	000000	000000	00000	000000	000000	000000	000	000000	0000	000000	00000	00000	000000	00000	00000	00000		000
GRP	ALL	ALL	ALL	ALL	ALL	ALL	ALL	ALL	ALL	ALL	ALL	ALL	ALL	ALL	ALL	ALL	ALL	ALL	ALL	ALL	ALL	ALL	ALL	ALL							
AVE	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAL	ANNUAL							
ZFLAG	9	0.	0.	0.	0.	0.	0.	00.00	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	•	0.	
ZHILL	5.0	3.0	0.6	0.6	0.6	0.6	0.6		0.6	9.0	9.0	0.6	0.6	9.0	9.0	0.6	9.0	9.0	0.6	9.0	9.0	9.0	9.0	9.0	9.0	9.0	0.6	9.0	9.0	9.0	0.
ZELEV	1.4	21	21.0	21.0	20.7	20.0	20.0	\sim	22.0	21.9	21.6	21.0	21.0	21.0	20.6	20.5	22.3	22.0	22.0	22.0	21.3	321.30	21.0	21.0	23.0	23.0	22.1	22.0	22.0	22.0	\sim
AVERAGE CONC	.0002	.0002	.0002	.0001	.0001	.0001	.0001	0.00011	.0002	.0002	.0002	.0002	.0001	.0001	.0001	.0001	.0003	.0003	.0002	.0002	.0002	000.	.0001	.0001	.0003	.0003	.0003	.0002	.0002	000.	000.
X	768525.5600	768525.5600	768525.5600	768525.5600	768525.5600	768525.5600	768525.5600	3768525.56000	768575.5600	768575.5600	768575.5600	768575.5600	768575.5600	768575.5600	768575.5600	768575.5600	768625.5600	768625.5600	768625.5600	768625.5600	768625.5600	768625.5600	768625.5600	768625.5600	768675.5600	768675.5600	768675.5600	768675.5600	768675.5600	768675.5600	768675.5600
* *	61426.8200	61476.8200	61526.8200	61576.8200	61626.8200	61676.8200	61726.8200	461776.82000	61426.8200	61476.8200	61526.8200	61576.8200	61626.8200	61676.8200	61726.8200	61776.8200	61426.8200	61476.8200	61526.8200	61576.8200	61626.8200	61676.8200	61726.8200	61776.8200	61426.8200	61476.8200	61526.8200	61576.8200	61626.8200	61676.8200	1726.8200

0005 NCART1 0005 NCART1	0005 NCART1	0005 NCART1	00	00	0005 NCART1	00	0005 NCART1	0005 NCART1	0005 NCART1	00	0005 NCART1	00	00	$\overline{}$	0005 NCART1	0005 NCART1	0005 NCART1	0005 NCART1	00	00	00	00	00	0005 NCART1	0005	0005	0005	00	0005	0005							
0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000
ANNUAL ALL ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALI
0.00	0 0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0 0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5	0.0	0.0
.30 57	.00 579	.00 57	.80 579.	.60 579.	.10 579.	.00	.00 57	.00 579	.80 57	.30 57	.10 573.	.00 573.	.00 562.	.00	.30 56	.40 573	.00	.00	.00 562.	.00 562.	.10 562.	.00 562.	00.	.00	.00 562	.70 562.	.60 562.	.00 562.	.00 56	.80 56	.50 56	.00 33	.36 32	00.	.85 327.	. 92	.52 561.
.00015 32	.00043	.00039 32	.00034 32	.00028 32	.00023 3	.00019	.00017	.00053 32	.00052 32	.00047	.00040 32	.00031 32	.00026 32	1022 32	.00019 3	1063 32	.00063 32	.00058 32	.00048 32	.00037 32	.00029 32	.00024 32	.00020 3	.00074 32	.00079 32	.00073 32	.00059 32	.00043 32	.00032 32	.00026 3	.00022 32	.00063	86000.	.00186 32	.00128 3	.00044 32	.00045 32
0 0000	000	000	000	000	000	000	000	000	000	000	000	000	000	000	000	000	000	000	000	000	000	000	000	000	000	000	000	000	000	000	000	000	000	000	000	000	000
0 3768675.56 0 3768725.56	3768725.5	3768725.5	3768725.5	3768725.5	3768725.5	3768725.5	3768725.5	3768775.5	3768775.5	3768775.5	3768775.5	3768775.5	3768775.5	3768775.5	3768775.5	3768825.5	3768825.5	3768825.5	3768825.5	3768825.5	3768825.5	3768825.5	3768825.5	3768875.5	3768875.5	3768875.5	3768875.5	3768875.5	3768875.5	3768875.5	3768875.5	3769256.0	3769257.0	3769204.0	3769203.0	3769062.0	3769022.0
461776.82000 461426.82000	61476.8200	61526.8200	61576.8200	61626.8200	61676.8200	61726.8200	61776.8200	61426.8200	61476.8200	61526.8200	61576.8200	61626.8200	61676.8200	61726.8200	61776.8200	61426.8200	61476.8200	61526.8200	61576.8200	61626.8200	61676.8200	61726.8200	61776.8200	61426.8200	61476.8200	61526.8200	61576.8200	61626.8200	61676.8200	61726.8200	61776.8200	61352.0000	61484.0000	61729.0000	61780.0000	61786.0000	61726.0000

461645.00000 3769015.00000	769015.00000	0.00049	326.00	562.00	00.00	ANNUAL	ALL	0000000
461568.00000 3768930.00000	768930.00000	0.00083	325.00	562.00	00.0	ANNUAL	ALL	0000000
461434.00000 3769023.00000	769023.00000	0.00113	327.00	562.00	0.00	ANNUAL	ALL	0000000
461372.00000 3769044.00000	769044.00000	0.00091	327.26	562.00	00.0	ANNUAL	ALL	0000000
461382.00000 3769140.00000	769140.00000	0.00072	328.46	561.00	00.00	ANNUAL	ALL	0000000
461286.00000 3769219.00000	769219.00000	0.00063	330.00	330.00	0.00	ANNUAL	ALL	0000000
** CONCUNIT ug/m^3	%							
** DEPUNIT g/m^2								

APPENDIX E

AERMOD Model Years 2041 – 2052 Operational PM10 Printouts

```
***********
** AERMOD Input Produced by:
** AERMOD View Ver. 11.0.1
** Lakes Environmental Software Inc.
** Date: 10/4/2022
** File: C:\Vista Env\2021\21060 SB Co\AERMOD\DPM2041A\DPM2041A.ADI
**********
* *
*********
** AERMOD Control Pathway
*********
**
* *
CO STARTING
  TITLEONE Slover / Alder Ave Industrial - 2041-2052 DPM
  TITLETWO PM10
  MODELOPT DFAULT CONC
  AVERTIME 24 ANNUAL
  URBANOPT 2035210 San Bernardino Co
  POLLUTID PM 10
  RUNORNOT RUN
  ERRORFIL DPM2041A.err
CO FINISHED
**********
** AERMOD Source Pathway
*********
* *
* *
SO STARTING
** Source Location **
** Source ID - Type - X Coord. - Y Coord. **
** -----
** Line Source Represented by Adjacent Volume Sources
** LINE VOLUME Source ID = DWY1
** DESCRSRC Project DWY 1 - Alder Ave
** PREFIX
** Length of Side = 3.66
** Configuration = Adjacent
** Emission Rate = 3.81E-07
** Vertical Dimension = 1.83
** SZINIT = 0.85
** Nodes = 3
** 461413.126, 3769172.571, 329.00, 0.00, 1.70
** 461470.310, 3769171.735, 328.44, 0.00, 1.70
** 461553.714, 3769149.977, 327.87, 0.00, 1.70
** -----
  LOCATION L0000769
                   VOLUME
                          461414.955 3769172.545 328.98
  LOCATION L0000770
                          461418.612 3769172.491 328.95
                   VOLUME
  LOCATION L0000771
                   VOLUME
                          461422.269 3769172.438 328.91
```

```
461425.926 3769172.384 328.87
  LOCATION L0000772
                       VOLUME
  LOCATION L0000773
                               461429.583 3769172.331 328.84
                       VOLUME
  LOCATION L0000774
                               461433.241 3769172.277 328.80
                       VOLUME
  LOCATION L0000775
                       VOLUME 461436.898 3769172.224 328.77
                               461440.555 3769172.170 328.73
  LOCATION L0000776
                       VOLUME
                              461444.212 3769172.117 328.70
  LOCATION L0000777
                       VOLUME
  LOCATION L0000778
                      VOLUME 461447.869 3769172.063 328.66
                       VOLUME 461451.527 3769172.009 328.62
  LOCATION L0000779
                       VOLUME 461455.184 3769171.956 328.59
  LOCATION L0000780
                               461458.841 3769171.902 328.55
  LOCATION L0000781
                       VOLUME
                               461462.498 3769171.849 328.52
  LOCATION L0000782
                       VOLUME
                               461466.156 3769171.795 328.48
  LOCATION L0000783
                       VOLUME
                               461469.813 3769171.742 328.44
  LOCATION L0000784
                       VOLUME
                              461473.368 3769170.937 328.42
  LOCATION L0000785
                       VOLUME
                      VOLUME 461476.907 3769170.014 328.39
  LOCATION L0000786
                      VOLUME 461480.446 3769169.090 328.37
  LOCATION L0000787
                              461483.985 3769168.167 328.35
  LOCATION L0000788
                      VOLUME
                               461487.525 3769167.244 328.32
  LOCATION L0000789
                       VOLUME
  LOCATION L0000790
                      VOLUME 461491.064 3769166.320 328.30
                      VOLUME 461494.603 3769165.397 328.27
  LOCATION L0000791
                              461498.142 3769164.474 328.25
  LOCATION L0000792
                      VOLUME
                      VOLUME 461501.681 3769163.551 328.23
  LOCATION L0000793
  LOCATION L0000794
                      VOLUME 461505.220 3769162.627 328.20
                      VOLUME 461508.759 3769161.704 328.18
  LOCATION L0000795
                              461512.299 3769160.781 328.15
  LOCATION L0000796
                      VOLUME
                      VOLUME 461515.838 3769159.858 328.13
  LOCATION L0000797
                      VOLUME 461519.377 3769158.934 328.10
  LOCATION L0000798
                      VOLUME 461522.916 3769158.011 328.08
  LOCATION L0000799
  LOCATION L0000800
                      VOLUME 461526.455 3769157.088 328.06
                      VOLUME 461529.994 3769156.165 328.03
  LOCATION L0000801
                      VOLUME 461533.534 3769155.241 328.01
  LOCATION L0000802
                      VOLUME 461537.073 3769154.318 327.98
  LOCATION L0000803
                      VOLUME 461540.612 3769153.395 327.96
  LOCATION L0000804
  LOCATION L0000805
                      VOLUME 461544.151 3769152.472 327.94
                      VOLUME 461547.690 3769151.548 327.91
  LOCATION L0000806
                      VOLUME 461551.229 3769150.625 327.89
  LOCATION L0000807
** End of LINE VOLUME Source ID = DWY1
** -----
** Line Source Represented by Adjacent Volume Sources
** LINE VOLUME Source ID = DWY2
** DESCRSRC Project Driveway 2 - Slover Ave West
** PREFIX
** Length of Side = 3.66
** Configuration = Adjacent
** Emission Rate = 2.11E-07
** Vertical Dimension = 1.83
** SZINIT = 0.85
** Nodes = 3
** 461531.677, 3769225.292, 328.91, 0.00, 1.70
** 461531.677, 3769168.387, 328.00, 0.00, 1.70
** 461552.877, 3769160.298, 327.96, 0.00, 1.70
** ______
                              461531.677 3769223.463 328.88
  LOCATION L0000808
                      VOLUME
  LOCATION L0000809 VOLUME 461531.677 3769219.806 328.82
```

```
461531.677 3769216.148 328.76
  LOCATION L0000810
                       VOLUME
  LOCATION L0000811
                               461531.677 3769212.490 328.71
                       VOLUME
  LOCATION L0000812
                       VOLUME
                               461531.677 3769208.833 328.65
  LOCATION L0000813
                       VOLUME 461531.677 3769205.175 328.59
  LOCATION L0000814
                               461531.677 3769201.518 328.53
                       VOLUME
                              461531.677 3769197.860 328.47
  LOCATION L0000815
                       VOLUME
                      VOLUME 461531.677 3769194.202 328.41
  LOCATION L0000816
                      VOLUME 461531.677 3769190.545 328.35
  LOCATION L0000817
                       VOLUME 461531.677 3769186.887 328.30
  LOCATION L0000818
                               461531.677 3769183.230 328.24
  LOCATION L0000819
                       VOLUME
                      VOLUME 461531.677 3769179.572 328.18
  LOCATION L0000820
                      VOLUME 461531.677 3769175.914 328.12
  LOCATION L0000821
                               461531.677 3769172.257 328.06
  LOCATION L0000822
                       VOLUME
                              461531.677 3769168.599 328.00
  LOCATION L0000823
                      VOLUME
                      VOLUME 461534.897 3769167.159 327.99
  LOCATION L0000824
                      VOLUME 461538.314 3769165.855 327.99
  LOCATION L0000825
                     VOLUME 461541.731 3769164.551 327.98
  LOCATION L0000826
                      VOLUME 461545.148 3769163.247 327.97
  LOCATION L0000827
  LOCATION L0000828
                      VOLUME 461548.566 3769161.943 327.97
  LOCATION L0000829
                      VOLUME 461551.983 3769160.639 327.96
** End of LINE VOLUME Source ID = DWY2
** ______
** Line Source Represented by Adjacent Volume Sources
** LINE VOLUME Source ID = DWY3
** DESCRSRC Project Driveway 3 - Slover Ave East
** PREFIX
** Length of Side = 3.66
** Configuration = Adjacent
** Emission Rate = 4.53E-07
** Vertical Dimension = 1.83
** SZINIT = 0.85
** Nodes = 3
** 461673.660, 3769226.129, 328.00, 0.00, 1.70
** 461673.102, 3769173.408, 327.64, 0.00, 1.70
** 461556.782, 3769154.719, 327.97, 0.00, 1.70
** ______
  LOCATION L0000830
                               461673.641 3769224.300 327.99
                       VOLUME
  LOCATION L0000831
                      VOLUME
                              461673.602 3769220.643 327.96
                      VOLUME 461673.563 3769216.985 327.94
  LOCATION L0000832
  LOCATION L0000833
                      VOLUME 461673.525 3769213.328 327.91
  LOCATION L0000834
                              461673.486 3769209.670 327.89
                      VOLUME
  LOCATION L0000835
                      VOLUME
                              461673.447 3769206.013 327.86
  LOCATION L0000836
                      VOLUME 461673.408 3769202.356 327.84
  LOCATION L0000837
                      VOLUME 461673.370 3769198.698 327.81
                               461673.331 3769195.041 327.79
  LOCATION L0000838
                       VOLUME
  LOCATION L0000839
                      VOLUME
                              461673.292 3769191.383 327.76
  LOCATION L0000840
                      VOLUME
                              461673.254 3769187.726 327.74
  LOCATION L0000841
                      VOLUME
                              461673.215 3769184.069 327.71
                               461673.176 3769180.411 327.69
  LOCATION L0000842
                      VOLUME
  LOCATION L0000843
                      VOLUME
                               461673.137 3769176.754 327.66
                               461672.794 3769173.359 327.64
  LOCATION L0000844
                      VOLUME
  LOCATION L0000845
                      VOLUME 461669.183 3769172.779 327.65
                              461665.572 3769172.198 327.66
  LOCATION L0000846
                      VOLUME
  LOCATION L0000847
                      VOLUME
                              461661.960 3769171.618 327.67
```

```
461658.349 3769171.038 327.68
  LOCATION L0000848
                       VOLUME
  LOCATION L0000849
                               461654.738 3769170.458 327.69
                       VOLUME
  LOCATION L0000850
                               461651.127 3769169.877 327.70
                       VOLUME
  LOCATION L0000851
                       VOLUME 461647.515 3769169.297 327.71
  LOCATION L0000852
                               461643.904 3769168.717 327.72
                       VOLUME
  LOCATION L0000853
                               461640.293 3769168.137 327.73
                       VOLUME
  LOCATION L0000854
                       VOLUME 461636.681 3769167.557 327.74
                       VOLUME 461633.070 3769166.976 327.75
  LOCATION L0000855
                       VOLUME 461629.459 3769166.396 327.76
  LOCATION L0000856
                       VOLUME
                               461625.848 3769165.816 327.77
  LOCATION L0000857
                               461622.236 3769165.236 327.78
  LOCATION L0000858
                       VOLUME
                       VOLUME 461618.625 3769164.655 327.79
  LOCATION L0000859
                                461615.014 3769164.075 327.80
  LOCATION L0000860
                       VOLUME
                               461611.402 3769163.495 327.82
  LOCATION L0000861
                       VOLUME
                       VOLUME 461607.791 3769162.915 327.83
  LOCATION L0000862
                       VOLUME 461604.180 3769162.334 327.84
  LOCATION L0000863
                              461600.569 3769161.754 327.85
  LOCATION L0000864
                       VOLUME
                               461596.957 3769161.174 327.86
  LOCATION L0000865
                       VOLUME
  LOCATION L0000866
                       VOLUME 461593.346 3769160.594 327.87
  LOCATION L0000867
                       VOLUME 461589.735 3769160.014 327.88
                              461586.123 3769159.433 327.89
  LOCATION L0000868
                       VOLUME
                       VOLUME 461582.512 3769158.853 327.90
  LOCATION L0000869
  LOCATION L0000870
                       VOLUME 461578.901 3769158.273 327.91
                      VOLUME 461575.290 3769157.693 327.92
  LOCATION L0000871
                              461571.678 3769157.112 327.93
  LOCATION L0000872
                       VOLUME
                       VOLUME 461568.067 3769156.532 327.94
  LOCATION L0000873
                       VOLUME 461564.456 3769155.952 327.95
  LOCATION L0000874
                       VOLUME 461560.844 3769155.372 327.96
  LOCATION L0000875
  LOCATION L0000876
                      VOLUME 461557.233 3769154.791 327.97
** End of LINE VOLUME Source ID = DWY3
** Line Source Represented by Adjacent Volume Sources
** LINE VOLUME Source ID = ALDER
** DESCRSRC Alder Ave - DWY 1 to Slover Ave
** PREFIX
** Length of Side = 3.66
** Configuration = Adjacent
** Emission Rate = 1.18E-07
** Vertical Dimension = 1.83
** SZINIT = 0.85
** Nodes = 2
** 461405.873, 3769224.734, 329.00, 0.00, 1.70
** 461405.873, 3769172.014, 329.00, 0.00, 1.70
** -----
                               461405.873 3769222.905 329.00
  LOCATION L0000877
                       VOLUME
  LOCATION L0000878
                       VOLUME
                              461405.873 3769219.248 329.00
  LOCATION L0000879
                       VOLUME 461405.873 3769215.590 329.00
  LOCATION L0000880
                      VOLUME 461405.873 3769211.932 329.00
                              461405.873 3769208.275 329.00
  LOCATION L0000881
                       VOLUME
  LOCATION L0000882
                       VOLUME 461405.873 3769204.617 329.00
                      VOLUME 461405.873 3769200.960 329.00
  LOCATION L0000883
  LOCATION L0000884
                       VOLUME 461405.873 3769197.302 329.00
                              461405.873 3769193.644 329.00
  LOCATION L0000885
                       VOLUME
  LOCATION L0000886
                      VOLUME 461405.873 3769189.987 329.00
```

```
461405.873 3769186.329 329.00
  LOCATION L0000887
                      VOLUME
  LOCATION L0000888
                      VOLUME 461405.873 3769182.672 329.00
  LOCATION L0000889
                      VOLUME 461405.873 3769179.014 329.00
  LOCATION L0000890
                      VOLUME 461405.873 3769175.356 329.00
** End of LINE VOLUME Source ID = ALDER
** -----
** Line Source Represented by Adjacent Volume Sources
** LINE VOLUME Source ID = SLOVER
** DESCRSRC Slover Ave
** PREFIX
** Length of Side = 12.19
** Configuration = Adjacent
** Emission Rate = 4.0E-06
** Vertical Dimension = 1.83
** SZINIT = 0.85
** Nodes = 5
** 460972.339, 3769234.573, 331.00, 0.00, 5.67
** 461117.706, 3769238.668, 330.83, 0.00, 5.67
** 461377.729, 3769233.550, 329.63, 0.00, 5.67
** 461809.736, 3769235.597, 328.00, 0.00, 5.67
** 462162.918, 3769234.573, 327.68, 0.00, 5.67
** -----
  LOCATION L0000891
                              460978.432 3769234.745 330.99
                      VOLUME
                              460990.619 3769235.088 330.98
  LOCATION L0000892
                      VOLUME
                              461002.807 3769235.432 330.96
  LOCATION L0000893
                      VOLUME
                              461014.994 3769235.775 330.95
  LOCATION L0000894
                       VOLUME
  LOCATION L0000895
                      VOLUME 461027.181 3769236.118 330.94
                      VOLUME 461039.368 3769236.462 330.92
  LOCATION L0000896
  LOCATION L0000897
                       VOLUME
                              461051.555 3769236.805 330.91
                              461063.742 3769237.148 330.89
  LOCATION L0000898
                       VOLUME
  LOCATION L0000899
                      VOLUME 461075.930 3769237.492 330.88
                      VOLUME
                              461088.117 3769237.835 330.86
  LOCATION L0000900
                              461100.304 3769238.178 330.85
  LOCATION L0000901
                       VOLUME
                               461112.491 3769238.521 330.84
  LOCATION L0000902
                       VOLUME
  LOCATION L0000903
                       VOLUME
                               461124.680 3769238.531 330.80
                       VOLUME 461136.869 3769238.291 330.74
  LOCATION L0000904
  LOCATION L0000905
                               461149.059 3769238.051 330.69
                       VOLUME
  LOCATION L0000906
                       VOLUME
                              461161.249 3769237.811 330.63
                              461173.438 3769237.571 330.57
  LOCATION L0000907
                       VOLUME
  LOCATION L0000908
                       VOLUME
                              461185.628 3769237.331 330.52
                               461197.817 3769237.091 330.46
  LOCATION L0000909
                       VOLUME
  LOCATION L0000910
                       VOLUME
                               461210.007 3769236.851 330.40
                               461222.197 3769236.611 330.35
  LOCATION L0000911
                       VOLUME
  LOCATION L0000912
                               461234.386 3769236.371 330.29
                       VOLUME
                               461246.576 3769236.132 330.24
  LOCATION L0000913
                       VOLUME
  LOCATION L0000914
                       VOLUME
                               461258.766 3769235.892 330.18
  LOCATION L0000915
                       VOLUME
                              461270.955 3769235.652 330.12
  LOCATION L0000916
                       VOLUME
                               461283.145 3769235.412 330.07
                               461295.335 3769235.172 330.01
  LOCATION L0000917
                       VOLUME
  LOCATION L0000918
                               461307.524 3769234.932 329.95
                       VOLUME
                               461319.714 3769234.692 329.90
  LOCATION L0000919
                      VOLUME
  LOCATION L0000920
                       VOLUME 461331.903 3769234.452 329.84
                              461344.093 3769234.212 329.79
  LOCATION L0000921
                       VOLUME
  LOCATION L0000922
                      VOLUME
                              461356.283 3769233.972 329.73
```

```
LOCATION L0000923
                                461368.472 3769233.732 329.67
                      VOLUME
LOCATION L0000924
                                461380.663 3769233.564 329.62
                      VOLUME
LOCATION L0000925
                                461392.854 3769233.621 329.57
                      VOLUME
LOCATION L0000926
                      VOLUME
                                461405.046 3769233.679 329.53
LOCATION L0000927
                                461417.238 3769233.737 329.48
                      VOLUME
LOCATION L0000928
                                461429.430 3769233.795 329.43
                      VOLUME
LOCATION L0000929
                      VOLUME
                                461441.622 3769233.853 329.39
LOCATION L0000930
                                461453.814 3769233.910 329.34
                      VOLUME
                                461466.006 3769233.968 329.30
LOCATION L0000931
                      VOLUME
                                461478.197 3769234.026 329.25
LOCATION L0000932
                      VOLUME
LOCATION L0000933
                                461490.389 3769234.084 329.20
                      VOLUME
                                461502.581 3769234.141 329.16
LOCATION L0000934
                      VOLUME
                                461514.773 3769234.199 329.11
LOCATION L0000935
                      VOLUME
LOCATION L0000936
                                461526.965 3769234.257 329.07
                      VOLUME
                                461539.157 3769234.315 329.02
LOCATION L0000937
                      VOLUME
                                461551.349 3769234.373 328.97
LOCATION L0000938
                      VOLUME
                                461563.540 3769234.430 328.93
LOCATION L0000939
                      VOLUME
LOCATION L0000940
                                461575.732 3769234.488 328.88
                      VOLUME
LOCATION L0000941
                                461587.924 3769234.546 328.84
                      VOLUME
LOCATION L0000942
                      VOLUME
                                461600.116 3769234.604 328.79
                                461612.308 3769234.662 328.74
LOCATION L0000943
                      VOLUME
                                461624.500 3769234.719 328.70
LOCATION L0000944
                      VOLUME
LOCATION L0000945
                      VOLUME
                                461636.692 3769234.777 328.65
                                461648.884 3769234.835 328.61
LOCATION L0000946
                      VOLUME
                                461661.075 3769234.893 328.56
LOCATION L0000947
                      VOLUME
                                461673.267 3769234.950 328.51
LOCATION L0000948
                      VOLUME
LOCATION L0000949
                                461685.459 3769235.008 328.47
                      VOLUME
                                461697.651 3769235.066 328.42
LOCATION L0000950
                      VOLUME
LOCATION L0000951
                                461709.843 3769235.124 328.38
                      VOLUME
                                461722.035 3769235.182 328.33
LOCATION L0000952
                      VOLUME
LOCATION L0000953
                      VOLUME
                                461734.227 3769235.239 328.28
                                461746.418 3769235.297 328.24
LOCATION L0000954
                      VOLUME
                                461758.610 3769235.355 328.19
LOCATION L0000955
                      VOLUME
LOCATION L0000956
                      VOLUME
                                461770.802 3769235.413 328.15
LOCATION L0000957
                      VOLUME
                                461782.994 3769235.470 328.10
LOCATION L0000958
                      VOLUME
                                461795.186 3769235.528 328.05
LOCATION L0000959
                                461807.378 3769235.586 328.01
                      VOLUME
LOCATION L0000960
                      VOLUME
                                461819.570 3769235.569 327.99
LOCATION L0000961
                                461831.762 3769235.533 327.98
                      VOLUME
LOCATION L0000962
                      VOLUME
                                461843.954 3769235.498 327.97
                                461856.146 3769235.463 327.96
LOCATION L0000963
                      VOLUME
LOCATION L0000964
                      VOLUME
                                461868.337 3769235.427 327.95
LOCATION L0000965
                                461880.529 3769235.392 327.94
                      VOLUME
LOCATION L0000966
                      VOLUME
                                461892.721 3769235.357 327.92
                                461904.913 3769235.321 327.91
LOCATION L0000967
                      VOLUME
LOCATION L0000968
                      VOLUME
                                461917.105 3769235.286 327.90
LOCATION L0000969
                      VOLUME
                                461929.297 3769235.251 327.89
                      VOLUME
LOCATION L0000970
                                461941.489 3769235.215 327.88
                                461953.681 3769235.180 327.87
LOCATION L0000971
                      VOLUME
LOCATION L0000972
                      VOLUME
                                461965.873 3769235.145 327.86
                                461978.065 3769235.109 327.85
LOCATION L0000973
                      VOLUME
LOCATION L0000974
                                461990.257 3769235.074 327.84
                      VOLUME
                                462002.449 3769235.039 327.83
LOCATION L0000975
                      VOLUME
LOCATION L0000976
                      VOLUME
                                462014.641 3769235.003 327.81
```

```
LOCATION L0000977
                                   462026.833 3769234.968 327.80
                         VOLUME
  LOCATION L0000978
                                   462039.025 3769234.933 327.79
                          VOLUME
  LOCATION L0000979
                                   462051.217 3769234.897 327.78
                         VOLUME
  LOCATION L0000980
                          VOLUME
                                   462063.409 3769234.862 327.77
  LOCATION L0000981
                                   462075.601 3769234.827 327.76
                          VOLUME
  LOCATION L0000982
                                   462087.793 3769234.791 327.75
                          VOLUME
                                   462099.985 3769234.756 327.74
  LOCATION L0000983
                         VOLUME
  LOCATION L0000984
                                   462112.176 3769234.721 327.73
                         VOLUME
                                   462124.368 3769234.685 327.71
  LOCATION L0000985
                         VOLUME
  LOCATION L0000986
                                   462136.560 3769234.650 327.70
                         VOLUME
  LOCATION L0000987
                                   462148.752 3769234.615 327.69
                         VOLUME
                                   462160.944 3769234.579 327.68
  LOCATION L0000988
                         VOLUME
** End of LINE VOLUME Source ID = SLOVER
  LOCATION IDLING
                                     461555.730 3769145.780
                                                                    327.690
                          POINT
** DESCRSRC Truck Idling
** Source Parameters **
** LINE VOLUME Source ID = DWY1
   SRCPARAM L0000769
                                               0.00
                                                         1.70
                                                                    0.85
                          0.00000009769
   SRCPARAM L0000770
                          0.00000009769
                                               0.00
                                                         1.70
                                                                    0.85
                                                         1.70
   SRCPARAM L0000771
                          0.00000009769
                                               0.00
                                                                    0.85
                                                         1.70
                                               0.00
   SRCPARAM L0000772
                          0.000000009769
                                                                    0.85
                          0.00000009769
                                               0.00
                                                         1.70
   SRCPARAM L0000773
                                                                    0.85
   SRCPARAM L0000774
                          0.000000009769
                                               0.00
                                                         1.70
                                                                    0.85
                                                         1.70
   SRCPARAM L0000775
                          0.00000009769
                                               0.00
                                                                    0.85
   SRCPARAM L0000776
                          0.00000009769
                                               0.00
                                                         1.70
                                                                    0.85
                                               0.00
   SRCPARAM L0000777
                          0.00000009769
                                                         1.70
                                                                    0.85
   SRCPARAM L0000778
                          0.00000009769
                                               0.00
                                                         1.70
                                                                    0.85
                                               0.00
                                                         1.70
   SRCPARAM L0000779
                          0.00000009769
                                                                    0.85
   SRCPARAM L0000780
                          0.00000009769
                                               0.00
                                                         1.70
                                                                    0.85
   SRCPARAM L0000781
                          0.00000009769
                                               0.00
                                                         1.70
                                                                    0.85
   SRCPARAM L0000782
                          0.00000009769
                                               0.00
                                                         1.70
                                                                    0.85
   SRCPARAM L0000783
                          0.00000009769
                                               0.00
                                                         1.70
                                                                    0.85
                                                         1.70
   SRCPARAM L0000784
                          0.00000009769
                                               0.00
                                                                    0.85
   SRCPARAM L0000785
                          0.000000009769
                                               0.00
                                                         1.70
                                                                    0.85
   SRCPARAM L0000786
                          0.000000009769
                                               0.00
                                                         1.70
                                                                    0.85
   SRCPARAM L0000787
                          0.00000009769
                                               0.00
                                                         1.70
                                                                    0.85
   SRCPARAM L0000788
                          0.00000009769
                                               0.00
                                                         1.70
                                                                    0.85
   SRCPARAM L0000789
                          0.00000009769
                                               0.00
                                                         1.70
                                                                    0.85
                          0.00000009769
                                               0.00
                                                         1.70
                                                                    0.85
   SRCPARAM L0000790
   SRCPARAM L0000791
                          0.000000009769
                                               0.00
                                                         1.70
                                                                    0.85
   SRCPARAM L0000792
                          0.00000009769
                                               0.00
                                                         1.70
                                                                    0.85
   SRCPARAM L0000793
                          0.00000009769
                                               0.00
                                                         1.70
                                                                    0.85
   SRCPARAM L0000794
                          0.00000009769
                                               0.00
                                                         1.70
                                                                    0.85
   SRCPARAM L0000795
                          0.00000009769
                                               0.00
                                                         1.70
                                                                    0.85
                                                         1.70
   SRCPARAM L0000796
                          0.00000009769
                                               0.00
                                                                    0.85
   SRCPARAM L0000797
                          0.000000009769
                                               0.00
                                                         1.70
                                                                    0.85
   SRCPARAM L0000798
                          0.00000009769
                                               0.00
                                                         1.70
                                                                    0.85
   SRCPARAM L0000799
                          0.00000009769
                                               0.00
                                                         1.70
                                                                    0.85
   SRCPARAM L0000800
                          0.00000009769
                                               0.00
                                                         1.70
                                                                    0.85
   SRCPARAM L0000801
                          0.00000009769
                                               0.00
                                                         1.70
                                                                    0.85
                                                         1.70
   SRCPARAM L0000802
                          0.000000009769
                                               0.00
                                                                    0.85
  SRCPARAM L0000803
                          0.00000009769
                                               0.00
                                                         1.70
                                                                    0.85
   SRCPARAM L0000804
                          0.000000009769
                                               0.00
                                                         1.70
                                                                    0.85
  SRCPARAM L0000805
                          0.000000009769
                                               0.00
                                                         1.70
                                                                    0.85
```

**	SRCPARAM L00008 SRCPARAM L00008				1.70 1.70	0.85 0.85
	LINE VOLUME SOU SRCPARAM L00008	08 09 00 10 00 11 00 11 10 12 13 14 15 16 17 18 19 20 21 22 22 23 24 25 26 27 0	DWY2 0.000000009591	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00	1.70 1.70 1.70 1.70 1.70 1.70 1.70 1.70	0.85 0.85 0.85 0.85 0.85 0.85 0.85 0.85
**	SRCPARAM L00008		.000000009591			
**	LINE VOLUME SOU SRCPARAM L00008	30 0 31 0 32 0 33 3 34 0 35 0 36 0 37 0 38 0 39 0 40 40 41 0 42 0 41 0 42 0 43 0 44 0 45 0 46 0 47 0 48 0 49 0 50 0	0.00000009638 0.000000009638 0.000000009638 0.000000009638 0.000000009638 0.000000009638	0.00 0.00 0.00 0.00 0.00	1.70 1.70 1.70 1.70	0.85 0.85 0.85 0.85 0.85 0.85

	SRCPARAM	L0000856	0.000000009638	0.00	1.70	0.85
		L0000857	0.000000009638	0.00	1.70	0.85
		L0000858	0.000000009638	0.00	1.70	0.85
		L0000859	0.000000009638	0.00	1.70	0.85
		L0000860	0.00000009638	0.00	1.70	0.85
		L0000861	0.000000009638	0.00	1.70	0.85
		L0000862	0.00000009638	0.00	1.70	0.85
	SRCPARAM	L0000863	0.00000009638	0.00	1.70	0.85
	SRCPARAM	L0000864	0.00000009638	0.00	1.70	0.85
	SRCPARAM	L0000865	0.000000009638	0.00	1.70	0.85
	SRCPARAM	L0000866	0.00000009638	0.00	1.70	0.85
		L0000867	0.00000009638	0.00	1.70	0.85
		L0000868	0.000000009638	0.00	1.70	0.85
		L0000869	0.000000009638	0.00	1.70	0.85
		L0000870	0.000000009638	0.00	1.70	0.85
		L0000870	0.000000009638	0.00	1.70	0.85
		L0000872	0.000000009638	0.00	1.70	0.85
		L0000873	0.00000009638	0.00	1.70	0.85
		L0000874	0.00000009638	0.00	1.70	0.85
			0.00000009638		1.70	0.85
	SRCPARAM	L0000876	0.000000009638	0.00	1.70	0.85
**		JME Source ID				
			0.000000008429			
			0.000000008429		1.70	
	SRCPARAM	L0000879	0.000000008429	0.00	1.70	0.85
	SRCPARAM	L0000880	0.000000008429	0.00	1.70	0.85
	SRCPARAM	L0000881	0.000000008429	0.00	1.70	0.85
	SRCPARAM	L0000882	0.000000008429	0.00	1.70	0.85
	SRCPARAM	L0000883	0.000000008429	0.00	1.70	0.85
		L0000884	0.000000008429	0.00	1.70	
		L0000885	0.000000008429	0.00	1.70	
		L0000886	0.000000008429	0.00	1.70	
		L0000887	0.000000008429	0.00	1.70	
		L0000888	0.000000008429	0.00	1.70	
		L0000889	0.000000008429	0.00	1.70	
ala ala	SRCPARAM	L0000890	0.00000008429	0.00	1.70	0.85
**		TATE CO	GI OVER			
~ ~		JME Source ID		0 00	- C	0.05
		L0000891	0.0000004082		5.67	0.85
		L0000892	0.00000004082	0.00	5.67	0.85
		L0000893	0.00000004082	0.00	5.67	0.85
	SRCPARAM		0.00000004082	0.00	5.67	0.85
	SRCPARAM	L0000895	0.00000004082	0.00	5.67	0.85
	SRCPARAM	L0000896	0.00000004082	0.00	5.67	0.85
	SRCPARAM	L0000897	0.00000004082	0.00	5.67	0.85
	SRCPARAM	L0000898	0.00000004082	0.00	5.67	0.85
	SRCPARAM	L0000899	0.00000004082	0.00	5.67	0.85
	SRCPARAM		0.00000004082	0.00	5.67	0.85
	SRCPARAM		0.00000004082	0.00	5.67	0.85
	SRCPARAM		0.00000004082	0.00	5.67	0.85
	SRCPARAM		0.00000004082	0.00	5.67	0.85
	SRCPARAM		0.00000004082	0.00	5.67	0.85
	SRCPARAM		0.00000004082	0.00	5.67	0.85
	DICLARAM	ПООООЭОЭ	0.0000004002	0.00	J. 0 /	0.00

SRCPARAM	L0000906	0.00000004082	0.00	5.67	0.85
SRCPARAM	L0000907	0.00000004082	0.00	5.67	0.85
	L0000908	0.00000004082	0.00	5.67	0.85
SRCPARAM	L0000909	0.00000004082	0.00	5.67	0.85
SRCPARAM	L0000910	0.00000004082	0.00	5.67	0.85
SRCPARAM	L0000911	0.00000004082	0.00	5.67	0.85
SRCPARAM	L0000912	0.00000004082	0.00	5.67	0.85
	L0000913	0.0000004082	0.00	5.67	0.85
	L0000914	0.00000004082	0.00	5.67	0.85
	L0000915	0.00000004082	0.00	5.67	0.85
	L0000916	0.00000004082	0.00	5.67	0.85
	L0000917	0.00000004082	0.00	5.67	0.85
	L0000917	0.00000004082	0.00	5.67	0.85
	L0000919	0.00000004082	0.00	5.67	0.85
	L0000919	0.00000004082	0.00	5.67	0.85
	L0000921	0.00000004082	0.00	5.67	0.85
	L0000922	0.00000004082	0.00	5.67	0.85
	L0000923	0.00000004082	0.00	5.67	0.85
	L0000924	0.00000004082	0.00	5.67	0.85
	L0000925	0.00000004082	0.00	5.67	0.85
	L0000926	0.00000004082	0.00	5.67	0.85
	L0000927	0.0000004082	0.00	5.67	0.85
	L0000928	0.0000004082	0.00	5.67	0.85
	L0000929	0.0000004082	0.00	5.67	0.85
	L0000930	0.0000004082	0.00	5.67	0.85
	L0000931	0.0000004082	0.00	5.67	0.85
	L0000932	0.0000004082	0.00	5.67	0.85
	L0000933	0.0000004082	0.00	5.67	0.85
	L0000934	0.00000004082	0.00	5.67	0.85
	L0000935	0.00000004082	0.00	5.67	0.85
	L0000936	0.00000004082	0.00	5.67	0.85
SRCPARAM	L0000937	0.00000004082	0.00	5.67	0.85
SRCPARAM	L0000938	0.00000004082	0.00	5.67	0.85
	L0000939	0.00000004082	0.00	5.67	0.85
SRCPARAM	L0000940	0.00000004082	0.00	5.67	0.85
SRCPARAM	L0000941	0.00000004082	0.00	5.67	0.85
SRCPARAM	L0000942	0.00000004082	0.00	5.67	0.85
SRCPARAM	L0000943	0.00000004082	0.00	5.67	0.85
SRCPARAM	L0000944	0.00000004082	0.00	5.67	0.85
SRCPARAM	L0000945	0.00000004082	0.00	5.67	0.85
SRCPARAM	L0000946	0.00000004082	0.00	5.67	0.85
SRCPARAM	L0000947	0.00000004082	0.00	5.67	0.85
SRCPARAM	L0000948	0.00000004082	0.00	5.67	0.85
SRCPARAM	L0000949	0.00000004082	0.00	5.67	0.85
SRCPARAM	L0000950	0.00000004082	0.00	5.67	0.85
SRCPARAM	L0000951	0.00000004082	0.00	5.67	0.85
	L0000952	0.00000004082	0.00	5.67	0.85
	L0000953	0.0000004082	0.00	5.67	0.85
	L0000954	0.0000004082	0.00	5.67	0.85
	L0000955	0.00000004082	0.00	5.67	0.85
	L0000956	0.0000004082	0.00	5.67	0.85
	L0000957	0.00000004082	0.00	5.67	0.85
	L0000958	0.00000004082	0.00	5.67	0.85
	L0000959	0.00000004082	0.00	5.67	0.85
				- -	

	SRCPARAM		0.00000004 0.00000004 0.00000004	1082	0.00	5.67	0.85	
	SRCPARAM	L0000963	0.0000004	1082	0.00	5.67	0.85	
		L0000964						
		L0000965						
		L0000966						
		L0000967						
		L0000968						
		L0000969						
		L0000970						
			0.0000004					
		L0000972						
		L0000973						
		L0000974						
		L0000975						
		L0000976						
		L0000977						
		L0000978 L0000979						
				1082	0.00	5.67	0.85 0.85	
		L0000982 L0000983	0.00000004					
		L0000983	0.00000004					
		L0000985	0.00000004	1082	0.00	5 67	0.05	
			0.00000004	1002	0.00	5 67	0.05	
	DICTIMA	П0000000	0.0000000	1002	0.00	3.07	0.05	
	SRCPARAM	T.0000987	0.00000004	1082	0.00	5 67	0.85	
	SRCPARAM SRCPARAM	L0000987 L0000988	0.0000004	1082	0.00	5.67 5.67	0.85 0.85	
**	SRCPARAM	L0000988 	0.00000004 0.00000004	1082 1082 	0.00	5.67 	0.85	 0.1
**	SRCPARAM	L0000988 	0.0000004	1082 1082 	0.00	5.67 	0.85	 0.1
	SRCPARAM SRCPARAM Building	L0000988 IDLING Downwash **	0.00000004 0.00000004 0.0000301	1082 1082 3.84	0.00	5.67 00	0.85 50	
	SRCPARAM SRCPARAM Building BUILDHGT	L0000988 IDLING Downwash ** IDLING	0.00000004 0.00000004 0.0000301	1082 1082 3.84	0.00	5.67 00	0.85 50	
	SRCPARAM SRCPARAM Building BUILDHGT BUILDHGT	L0000988 IDLING Downwash ** IDLING IDLING	0.00000004 0.00000004 0.0000301	1082 1082 3.84	0.00	5.67 00	0.85 50	
	SRCPARAM SRCPARAM Building BUILDHGT BUILDHGT BUILDHGT	L0000988 IDLING Downwash ** IDLING IDLING IDLING IDLING	0.00000004 0.00000004 0.0000301	1082 1082 3.84	0.00	5.67 00	0.85 50	
	SRCPARAM SRCPARAM Building BUILDHGT BUILDHGT BUILDHGT BUILDHGT	L0000988 IDLING Downwash ** IDLING IDLING IDLING IDLING IDLING	0.00000004 0.00000004 0.0000301 13.41 13.41 13.41 13.41 13.41	1082 1082 3.84 13.41 13.41 13.41 13.41	0.00 0 0 366.00 13.41 13.41 13.41 13.41	5.67 00 13.41 13.41 13.41 13.41	0.85 50 13.41 13.41 13.41 13.41	13.41 13.41 13.41 13.41
	SRCPARAM SRCPARAM Building BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT	L0000988 IDLING Downwash ** IDLING IDLING IDLING IDLING IDLING IDLING	0.00000004 0.00000004 0.0000301 13.41 13.41 13.41 13.41 13.41 13.41	13.41 13.41 13.41 13.41 13.41 13.41	0.00 0 0 366.00 13.41 13.41 13.41 13.41 13.41	5.67 00 13.41 13.41 13.41 13.41 13.41	0.85 50 13.41 13.41 13.41 13.41 13.41	13.41 13.41 13.41 13.41 13.41
	SRCPARAM SRCPARAM Building BUILDHGT BUILDHGT BUILDHGT BUILDHGT	L0000988 IDLING Downwash ** IDLING IDLING IDLING IDLING IDLING IDLING	0.00000004 0.00000004 0.0000301 13.41 13.41 13.41 13.41 13.41	13.41 13.41 13.41 13.41 13.41 13.41	0.00 0 0 366.00 13.41 13.41 13.41 13.41 13.41	5.67 00 13.41 13.41 13.41 13.41	0.85 50 13.41 13.41 13.41 13.41 13.41	13.41 13.41 13.41 13.41 13.41
	SRCPARAM SRCPARAM Building BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT	L0000988 IDLING Downwash ** IDLING IDLING IDLING IDLING IDLING IDLING IDLING IDLING	0.00000004 0.00000004 0.0000301 13.41 13.41 13.41 13.41 13.41 13.41	13.41 13.41 13.41 13.41 13.41 13.41	0.00 0 0 366.00 13.41 13.41 13.41 13.41 13.41	5.67 	0.85 	13.41 13.41 13.41 13.41 13.41
	SRCPARAM SRCPARAM Building BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT	L0000988 IDLING Downwash ** IDLING IDLING IDLING IDLING IDLING IDLING IDLING IDLING IDLING	0.00000004 0.00000004 0.0000301 13.41 13.41 13.41 13.41 13.41 13.41 13.41	13.41 13.41 13.41 13.41 13.41 13.41 13.41 13.41 14.41 14.41	0.00 0 366.00 13.41 13.41 13.41 13.41 13.41 274.58 107.59	5.67 	0.85 	13.41 13.41 13.41 13.41 13.41 220.16
	SRCPARAM SRCPARAM Building BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT	L0000988 IDLING Downwash ** IDLING	0.00000004 0.00000004 0.0000301 0.0000301 13.41 13.41 13.41 13.41 13.41 13.41 270.09	13.41 13.41 13.41 13.41 13.41 13.41 13.41 276.54	0.00 0 366.00 13.41 13.41 13.41 13.41 13.41 274.58 107.59	5.67 	0.85 	13.41 13.41 13.41 13.41 13.41 220.16
	SRCPARAM SRCPARAM Building BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT	L0000988 IDLING Downwash ** IDLING	0.00000004 0.00000004 0.0000301 0.0000301 13.41 13.41 13.41 13.41 13.41 13.41 13.41 13.67	13.41 13.41 13.41 13.41 13.41 13.41 13.41 13.41 14.41 14.41	0.00 0 366.00 13.41 13.41 13.41 13.41 13.41 13.41 274.58 107.59 274.93	5.67 	0.85 	13.41 13.41 13.41 13.41 13.41 220.16 220.57 255.74
	SRCPARAM SRCPARAM Building BUILDHGT	L0000988 IDLING Downwash ** IDLING	0.00000004 0.00000004 0.0000301 13.41 13.41 13.41 13.41 13.41 13.41 13.67 246.36	13.41 13.41 13.41 13.41 13.41 13.41 13.41 276.54 149.48 264.67 276.54	0.00 0 366.00 13.41 13.41 13.41 13.41 13.41 13.41 274.58 107.59 274.93 274.58	5.67 	0.85 	13.41 13.41 13.41 13.41 13.41 220.16 220.57 255.74 220.16
	SRCPARAM SRCPARAM Building BUILDHGT BUILDWID BUILDWID BUILDWID BUILDWID	L0000988 IDLING Downwash ** IDLING	0.00000004 0.00000004 0.0000301 13.41 13.41 13.41 13.41 13.41 13.41 270.09 187.67 246.36 270.09	13.41 13.41 13.41 13.41 13.41 13.41 13.41 276.54 149.48 264.67 276.54	0.00 0 366.00 13.41 13.41 13.41 13.41 13.41 13.41 13.41 274.58 107.59 274.93 274.58 107.59	5.67 	0.85 	13.41 13.41 13.41 13.41 13.41 220.16 220.57 255.74 220.16
	SRCPARAM SRCPARAM Building BUILDHGT BUILDWID BUILDWID BUILDWID BUILDWID BUILDWID	L0000988 IDLING Downwash ** IDLING	0.00000004 0.00000004 0.0000301 0.0000301 13.41 13.41 13.41 13.41 13.41 270.09 187.67 246.36 270.09 187.67 246.36	13.41 13.41 13.41 13.41 13.41 13.41 13.41 276.54 149.48 264.67 276.54 149.48	0.00 0 366.00 13.41 13.41 13.41 13.41 13.41 13.41 13.41 274.58 107.59 274.93 274.58 107.59	5.67 	0.85 	13.41 13.41 13.41 13.41 13.41 220.16 220.57 255.74 220.16 220.57 255.74
	SRCPARAM SRCPARAM Building BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDWID BUILDWID BUILDWID BUILDWID BUILDWID BUILDWID BUILDWID	L0000988 IDLING Downwash ** IDLING	0.00000004 0.00000004 0.0000301 13.41 13.41 13.41 13.41 13.41 13.41 270.09 187.67 246.36 270.09 187.67	13.41 13.41 13.41 13.41 13.41 13.41 276.54 149.48 264.67 276.54 149.48 264.67	0.00 0 366.00 13.41 13.41 13.41 13.41 13.41 274.58 107.59 274.93 274.58 107.59 274.93	5.67 	0.85 	13.41 13.41 13.41 13.41 13.41 220.16 220.57 255.74 220.16 220.57 255.74
	SRCPARAM SRCPARAM Building BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDWID BUILDWID BUILDWID BUILDWID BUILDWID BUILDWID BUILDWID BUILDWID BUILDWID	L0000988 IDLING Downwash ** IDLING	0.00000004 0.00000004 0.0000301 0.0000301 13.41 13.41 13.41 13.41 13.41 270.09 187.67 246.36 270.09 187.67 246.36	13.41 13.41 13.41 13.41 13.41 13.41 276.54 149.48 264.67 276.54 149.48 264.67	0.00 0 366.00 13.41 13.41 13.41 13.41 13.41 274.58 107.59 274.93 274.58 107.59 274.93	5.67 	0.85 50 13.41 13.41 13.41 13.41 13.41 245.96 188.07 270.34 245.96 188.07 270.34 245.96	13.41 13.41 13.41 13.41 13.41 220.16 220.57 255.74 220.16 220.57 255.74
	SRCPARAM SRCPARAM Building BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDWID	L0000988 IDLING Downwash ** IDLING	0.00000004 0.00000004 0.0000301 0.0000301 13.41 13.41 13.41 13.41 13.41 13.41 270.09 187.67 246.36 270.09 187.67 246.36 270.09 187.67 246.36	1082 1082 3.84 13.41 13.41 13.41 13.41 13.41 276.54 149.48 264.67 276.54 149.48 264.67 276.54	0.00 0 366.00 13.41 13.41 13.41 13.41 13.41 274.58 107.59 274.93 274.58 107.59 274.93 274.93 220.57 255.74 220.16	5.67 	0.85 50 13.41 13.41 13.41 13.41 13.41 13.41 245.96 188.07 270.34 245.96 188.07 270.34 245.96	13.41 13.41 13.41 13.41 13.41 220.16 220.57 255.74 220.16 220.57 255.74 274.93 274.58 107.59
	SRCPARAM SRCPARAM Building BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDHGT BUILDWID	L0000988 IDLING Downwash ** IDLING	0.00000004 0.00000004 0.0000301 13.41 13.41 13.41 13.41 13.41 13.41 13.67 246.36 270.09 187.67 246.36 270.09 187.67 246.36	13.41 13.41 13.41 13.41 13.41 13.41 13.41 276.54 149.48 264.67 276.54 149.48 264.67	0.00 0 366.00 13.41 13.41 13.41 13.41 13.41 274.58 107.59 274.93 274.58 107.59 274.93 274.93 220.57 255.74 220.16 220.57	5.67 	0.85 50 13.41 13.41 13.41 13.41 13.41 13.41 245.96 188.07 270.34 245.96 188.07 270.34 245.96 188.07 270.34 245.96	13.41 13.41 13.41 13.41 13.41 220.16 220.57 255.74 220.16 220.57 255.74 274.93 274.93 274.93

```
-119.03 -136.14 -149.11 -157.55 -161.21 -159.96
  XBADJ
       TDLING
  XBADJ
                     -153.86 -143.08 -127.95 -127.18 -122.85 -114.78
         IDLING
         IDLING
                     -103.24 -88.55 -71.17 -51.63 -30.53
  XBADJ
  XBADJ
         IDLING
                     -30.83 -51.93 -71.45 -88.80 -103.46 -114.97
                     -122.99 -127.27 -127.79 -142.91 -153.69 -159.80
  XBADJ
         IDLING
                     -161.05 -157.41 -148.99 -136.04 -118.96
  XBADJ
         IDLING
  YBADJ
                      -7.87 -15.42 -22.51 -28.91 -34.43
        IDLING
       IDLING
                     -42.20 -44.22 -44.52 -44.10 -42.11 -38.83
  YBADJ
                      -34.37
                            -28.87
                                   -22.50
                                           -15.44
                                                    -7.91
  YBADJ
         IDLING
                       7.87
                             15.42
                                    22.51 28.91
                                                    34.43
         IDLING
  YBADJ
                                                   42.11
                      42.20
                             44.22
                                    44.52
                                            44.10
  YBADJ
         IDLING
                      34.37 28.87 22.50 15.44
         IDLING
                                                   7.91
  YBADJ
  URBANSRC ALL
  SRCGROUP ALL
SO FINISHED
* *
*********
** AERMOD Receptor Pathway
********
* *
RE STARTING
  INCLUDED DPM2041A.rou
RE FINISHED
*********
** AERMOD Meteorology Pathway
*********
* *
ME STARTING
  SURFFILE ..\FontanaADJU\FONT V9 ADJU\FONT v9.SFC
  PROFFILE ..\FontanaADJU\FONT V9 ADJU\FONT v9.PFL
  SURFDATA 3102 2011 Fontana
  UAIRDATA 3190 2011
  SITEDATA 99999 2011
  PROFBASE 367.0 METERS
ME FINISHED
* *
**********
** AERMOD Output Pathway
***********
**
* *
OU STARTING
  RECTABLE ALLAVE 1ST
  RECTABLE 24 1ST
** Auto-Generated Plotfiles
  PLOTFILE 24 ALL 1ST DPM2041A.AD\24H1GALL.PLT 31
  PLOTFILE ANNUAL ALL DPM2041A.AD\AN00GALL.PLT 32
  SUMMFILE DPM2041A.sum
```

OU FINISHED

-9.28

-98.31

-38.91

-0.08

38.91

38.83

0.08

* *

** Project Parameters

** PROJCTN CoordinateSystemUTM

** DESCPTN UTM: Universal Transverse Mercator

** DATUM World Geodetic System 1984

** DTMRGN Global Definition

** UNITS m

** ZONE 11

** ZONEINX 0

* *

10/04/22 12:36:40					NUM YRS NET ID	
		GROUP: ALL			AVE GRP	
2 DPM	7 U*	AVERAGED ACROSS 5 YEARS FOR SOURCE GROUP: ALL		.8,2X,A8)		
Industrial - 2041-2052 DPM	CONC ELEV URBAN ADJ U*	ACROSS 5 YE.		16,2X,A8,2X,I8	ZELEV ZHILL ZFLAG	
ır Ave Industri			76 RECEPTORS.	FORMAT: (3(1X,F13.5),3(1X,F8.2),2X,A6,2X,A8,2X,18.8,2X,A8)	AVERAGE CONC	
Slover / Alder Ave	USED: RegDFAULT	PLOT FILE OF ANNUAL VALUES		(3(1X, F13.5), 3	Y AV	
AERMOD (22112): Slover AERMET (16216):	MODELING OPTIONS USED:	PLOT FIL	FOR A TOTAL OF	FORMAT:	\bowtie	
* * AE	* MC	*	*	*	*	*

T.1	T1	T1	T1	T1	T1	T1	T1	T1	T1	T1	T1	T1	T1	T1	T1	T1	T1	T1	T1	T1	T1	T1	T1	T1	T1	T1	T1	T1	T1	T1
NCAR	NCAR	NCAR	NCAR	NCAR	NCAR	NCAR	NCAR	NCAR	NCAR	NCAR	NCAR	NCART	NCAR																	
	00000		000	000	00000	000	00000	000	000	000		000	00000	0	000	00000	0	000	000	00000	000	00000	00	000	00000	00			00000	0
	000			0	000	00	0	000	00	00	000	00	00	00	00	000	00	00	00	000	00	00	000	0		000	0	0	000	
ı	ı	Г	L	ī	Г	ı	Γ	ī	I	L	L	ī	I	L	Г	I	T	ī	ī	I	T	ī	I	I	ī	ī	T	ī	ī	ı
AL	, AL	, AL	ALL	ALL	ALL	, ALL	ALL	_	_	_		_	_				_	_	_	, ALL	_	ALL	, ALL	_	ALL	ALL	, ALL	, ALL	, ALL	ALI
ANNUAI	ANNUAI	ANNUAI	ANNUAI	ANNUAI	ANNUAL	ANNUAL	ANNUAI	ANNUAL	ANNUAI	ANNUAI	ANNUAL	ANNUAI																		
•	00.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	•	0.	Ō		0
00	00.		0		0	0	00.		0		0		0	0	0		00.	0		0			00.		00.	00.		00	00	
75		Γ	79	79	79	79	79	79	79	79	79	79	79	79	79	79	79	79	79	79	79	79	79	79	79	79	79	\sim	579	_
-	H	1.0	1.0	0.7	00.03	0.0		2.0	1.9	1.6	1.00	1.0	1.0	0.6	0.5	2.3	2.0	2.0	2.0	1.30	1.3	1.0	1.00	3.0	3.0	2.10	2.0	2.0	2.00	2.0
	32																			32						32			32	
00	0022	00	001	001	00	001	00	002	002	002	002	001	001	001	001	003	003	002	002	00	001	001	001	003	003	003	002	0	0	0017
•	0.0	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	0.0	0.0	0.0
	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
009	.56000	600	009	5600	600	5600	5600	5600	5600	5600	5600	5600	009	5600	5600	5600	5600	5600	5600	5600	5600	5600	5600	5600	5600	5600	009	5600	009	009
8525	8525	8525	8525	852	8525	852	852	857	857	857	857	857	8575	857	857	862	862	862	862	862	862	862	862	867	867	867	8675	867	8675	867
37	376	37	37	37	37	37	37	37	37	37	37	37	37	37	37	37	37	37	37	37	37	37	37	37	37	37	37	37	37	37
200	82000	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200
42	1476.	52	57	62	67	72	77	42	47	52	57	62	67	72	77	42	47	52	57	\sim	67	72	77	42	47	52	57	62	67	72
9	46	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9

0005 NCART1 0005 NCART1	005	0005 NCART1	00	00	0005 NCART1	00	005	00	0005 NCART1	0005 NCART1	0005 NCART1	00	00	00	00	$\overline{}$	0005 NCART1	0005 NCART1	0005 NCART1	0005 NCART1	00	00	00	00	00	0005 NCART1	0005	0005	0005	0005	00	0005					
0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000
ANNUAL ALL ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALL	ANNUAL ALI
00.0	0.0 0.0	0.0 0.0	0.0 0.0	0.0 0.0	0.0 0.0	0.0 0.0	0 00	0.0 0.0	0.0 0.0	0.0 0.0	0.0 0.0	0.0 0.0	0.0	0.0 0.0	0.0 0.0	0.0 0.0	0.0 0.0	0.0 0.0	0.0	0.0	0.0 0.0	0.0 0.0	0.0 0.0	0.0	0.0	.0 00	0.0 0.0	0.0 0.0	0.0 0.0	0.0 0.0	0.0 0.0	0.0 0.0	36 0.0	0.0 0.0	85 0	0.0	0.0
21.00 579. 23.30 579.	.00 57	57	.80 57	2.60	2.10 57	57	.00 57	.00 57	3.80 57		3.10 57	3.00 57	00.	3.00 56	2.30 56	4.40 573	4.00 57	4.00 56	4.00 56	4.00 562	.10 56	3.00 56	3.00 56	5.00 56	5.00 562	0	4.60 56	4.00 56	.00 56	3.80 56	3.50 56	33	.36	8.00 32	7.85 32	. 92	5.52
0.00015 3.000045 3.000045	.00043	.00039	.00034 3	.00027 3	.00022 3	.00019 3	.00017 3	.00053 3	.00052 3	.00047 3	.00039 3	.00031 3	.00025 3	021 3	.00018 3	063 3	.00063 3	.00058 3	.00047 3	.00036 3	.00028 3	.00023 3	.00020 3	.00074 3	.00078 3	.00073 3	.00059 3	.00042 3	.00032 3	.00026 3	.00022 3	.00059 3	.00093 3	.00182 3	.00125 3	.00043 3	.00044 3
461776.82000 3768675.56000 461426.82000 3768725.56000	61476.82000 3768725.5600	61526.82000 3768725.5600	61576.82000 3768725.5600	61626.82000 3768725.5600	61676.82000 3768725.5600	61726.82000 3768725.5600	61776.82000 3768725.5600	61426.82000 3768775.5600	61476.82000 3768775.5600	61526.82000 3768775.5600	61576.82000 3768775.5600	61626.82000 3768775.5600	61676.82000 3768775.5600	61726.82000 3768775.5600	61776.82000 3768775.5600	61426.82000 3768825.5600	61476.82000 3768825.5600	61526.82000 3768825.5600	61576.82000 3768825.5600	61626.82000 3768825.5600	61676.82000 3768825.5600	61726.82000 3768825.5600	61776.82000 3768825.5600	61426.82000 3768875.5600	61476.82000 3768875.5600	61526.82000 3768875.5600	61576.82000 3768875.5600	61626.82000 3768875.5600	61676.82000 3768875.5600	61726.82000 3768875.5600	61776.82000 3768875.5600	61352.00000 3769256.0000	61484.00000 3769257.0000	61729.00000 3769204.0000	61780.00000 3769203.0000	61786.00000 3769062.0000	61726.00000 3769022.0000

461645.00000 3769015.00000	769015.00000	0.00048	326.00	562.00	0.00	ANNUAL	ALL	0000000
461568.00000 3768930.00000	768930.00000	0.00082	325.00	562.00	0.00	ANNUAL	ALL	0000000
461434.00000 3769023.00000	769023.00000	0.00112	327.00	562.00	0.00	ANNUAL	ALL	0000000
461372.00000 3769044.00000	769044.00000	06000.0	327.26	562.00	0.00	ANNUAL	ALL	0000000
461382.00000 3769140.00000	769140.00000	0.00070	328.46	561.00	00.0	ANNUAL	ALL	0000000
461286.00000 3769219.00000	769219.00000	09000.0	330.00	330.00	0.00	ANNUAL	ALL	0000000
** CONCUNIT ug/m^3	٣,							
** DEPUNIT g/m^2								

APPENDIX F

CalEEMod Model Annual Printouts

CalEEMod Version: CalEEMod.2020.4.0

Page 1 of 34

Date: 2/6/2022 6:44 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Slover-Alder Avenue Industrial

San Bernardino-South Coast County, Annual

1.0 Project Characteristics

1.1 Land Usage

Population	0	0
Floor Surface Area	259,481.00	230,432.40
Lot Acreage	7.94	5.29
Metric	1000sqft	Acre 5.29 230,432.40 0
Size		
Land Uses	Unrefrigerated Warehouse-No Rail	Parking Lot

1.2 Other Project Characteristics

Urbanization	Urban	Wind Speed (m/s)	2.2	Precipitation Freq (Days)	32
Climate Zone	10			Operational Year	2023
Utility Company	Southern California Edison	-			
CO2 Intensity (Ib/MWhr)	390.98	CH4 Intensity (Ib/MWhr)	0.033	N2O Intensity (Ib/MWhr)	0.004

1.3 User Entered Comments & Non-Default Data

Project Characteristics -

Land Use - Total Project Site = 13.23 acres

Construction Phase - Construction schedule provided by applicant

Off-road Equipment - Grading - 2 Excavators, 1 Grader, 1 Rubber Tired Dozer, 2 Scrapers, 2 Crawler Tractors

Off-road Equipment - Site Preparation - 3 Rubber Tired Dozers and 4 Crawler Tractors

Trips and VMT - 6 vendor trucks added to Demolition, Site Prep, and Grading Phases to account for water truck emissions

Demolition - 16,800 sq ft of building space = 773 tons + 117,000 sq ft of pavement = 2,828 tons

Grading -

Construction Off-road Equipment Mitigation - Water Exposed Area 3x per day selected to account for SCAQMD Rule 403 minimum requirements Vehicle Trips - Truck Trips analyzed under Parking Lot Land use and the Auto Trips analyzed under the Unrefrigerated Warehouse Land Use

Mobile Land Use Mitigation - Improve Pedestrian Network on Project Site and Connecting Offsite and 0.06 mile to nearest Transit Station

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Energy Mitigation

Water Mitigation - Install Low-Flow fixtures and use water-efficient Irrigation Systems selected to account for Title 24 Part 11 requirements

Waste Mitigation - 50% reduction in solid waste selected to account for AB 341

Operational Off-Road Equipment - 4 Forklifts 7 hours per day. Per PDF 1, analyzed as CNG fuel

Fleet Mix - Vehicle Mix set to match Trip Generation Memo

Water And Wastewater -

Architectural Coating -

Solid Waste -

New Value	129688	389064	130.00	130.00	09:0	0.00	0.00	0.58	0.00	0.06	00:00	0.19	00:00	0.00	0.22	0.00	0.00	0.03	0.00
Default Value	129741	389222	20.00	20.00	0.02	0.02	0.54	0.54	0.06	0.06	0.17	0.17	0.03	0.03	7.1960e-003	7.1960e-003	0.03	0.03	0.14
Column Name	Area_Nonresidential_Exterior	Area_Nonresidential_Interior	NumDays	NumDays	雅	OHH.	LDA	LDA	LDT1	LDT1	LDT2	LDT2	LHD1	LAD1	LHD2	LHD2	MCY	MCY	MDV
Table Name	tblAreaCoating	tblAreaCoating	tblConstructionPhase	tblConstructionPhase	tblFleetMix														

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Γ	-		<u> </u>	:	:	i	;	;	i	<u> </u>	;	•		;	;	;		:	i	;	:	i	i			:	:	i
0 7 7	cl.:0	0.00	0.00	0.18	0.00	0.00	0.00	0.00	0.00	0.00	0.00	259,481.00	7.94	CNG	7.00	4.00	6.00	6.00	0.09	40.00	100.00	100.00	21.36	0.97	21.36	76.0	21.36	0.97
	0.14	5.0710e-003	5.0710e-003	0.01	0.01	5.5900e-004	5.5900e-004	9.5400e-004	9.5400e-004	2.5400e-004	2.5400e-004	259,480.00	5.96	Diesel	8.00	0.00	0.00	0.00	0.00	8.40	0.00	0.00	0.00	1.74	0.00	1.74	0.00	1.74
XV	A CIM	HW	HW	QHW	QHW	OBUS	OBUS	SBUS	SBUS	UBUS	UBUS	LandUseSquareFeet	LotAcreage	OperFuelType	OperHoursPerDay	OperOffRoadEquipmentNumber	VendorTripNumber	VendorTripNumber	VendorTripNumber	CC_TL	CC_TTP	PR_TP	ST_TR	ST_TR	SU_TR	SU_TR	WD_TR	WD_TR
	XIIXIIXIIXI	tblFleetMix	tblLandUse	tblLandUse	tblOperationalOffRoadEquipment	tblOperationalOffRoadEquipment	tblOperationalOffRoadEquipment	tblTripsAndVMT	tblTripsAndVMT	tblTripsAndVMT	tblVehicleTrips	tblVehicleTrips	tblVehicleTrips	tbIVehicleTrips	tblVehicleTrips	tblVehicleTrips	tblVehicleTrips	tbIVehicleTrips	tbIVehicleTrips									

Page 4 of 34

Date: 2/6/2022 6:44 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

2.0 Emissions Summary

2.1 Overall Construction

Unmitigated Construction

	ROG	XON	00	S02	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	Bio- CO2 NBio- CO2 Total CO2	Total CO2	CH4	NZO	CO2e
Year					tons/yr	s/yr							MT/yr	'yr		
2022	0.3242	2.8403	2.7583	0.3242 2.8403 2.7583 6.8300e- 0.5312 003		0.1208	0.6520	0.1760	0.6520 0.1760 0.1128	0.2888	0.0000	615.3898	0.0000 615.3898 615.3898 0.1001 0.0235 624.8971	0.1001	0.0235	624.8971
2023	1.5018	2.0166	2.8861	2.8861 6.2600e- 0.2347 003	0.2347	0.0896	0.3243	0.0632	0.0839	0.1470	0.0000	564.0292	0.0000 564.0292 564.0292 0.0886	0.0886	0.0188 571.8309	571.8309
Maximum	1.5018	1.5018 2.8403	2.8861	2.8861 6.8300e- (.5312	0.1208	0.6520	0.1760	0.1128	0.2888	0.0000	615.3898 615.3898	615.3898	0.1001	0.0235	624.8971

Mitigated Construction

CO2e		624.8967	571.8305	624.8967
N20		0.0235 624.8967	0.0188	0.0235
CH4	yr	0.1001	0.0886	0.1001
Total CO2	MT/yr	615.3894	564.0288	615.3894
Bio- CO2 NBio- CO2 Total CO2		0.0000 615.3894 615.3894	0.0000 564.0288 564.0288	615.3894 615.3894
Bio- CO2		0.000.0	0.000.0	0.000
PM2.5 Total		0.2192	0.1470	0.2192
Exhaust PM2.5		0.1128	0.0839	0.1128
Fugitive PM2.5		0.1065	0.0632	0.1065
PM10 Total		0.4682	0.3243	0.4682
Exhaust PM10	ns/yr	0.1208	0.0896	0.1208
Fugitive PM10	tons	0.3473	0.2347	0.3473
SO2		2.7583 6.8300e- 0.3473 003	2.8861 6.2600e- 003	2.8861 6.8300e- 003
00		2.7583	2.8861	2.8861
NOx		2.8403	2.0166	1.5018 2.8403
ROG		0.3242	1.5018	1.5018
	Year	2022	2023	Maximum

Date: 2/6/2022 6:44 PM Page 5 of 34 CalEEMod Version: CalEEMod.2020.4.0

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

C02e	0.00								
N20	0.00								
CH4	0.00	arter)							
Total CO2	0.00	X (tons/qua							
Bio- CO2 NBio-CO2 Total CO2	0.00	d ROG + NC	1.4370	0.7357	0.7312	1.1714	1.7207	0.8783	1.7207
Bio- CO2	00:0	Maximum Mitigated ROG + NOX (tons/quarter)							
PM2.5 Total	15.96	Maxim							
Exhaust PM2.5	0.00	rarter)							
Fugitive PM2.5	29.07	Maximum Unmitigated ROG + NOX (tons/quarter)							
PM10 Total	18.83	ted ROG + N	1.4370	0.7357	0.7312	1.1714	1.7207	0.8783	1.7207
Exhaust PM10	0.00	m Unmitiga							
Fugitive PM10	24.00	Maximu							
S02	0.00	End Date	5-31-2022	8-31-2022	11-30-2022	2-28-2023	5-31-2023	8-31-2023	Highest
00	0.00	End	5-31	8-31	11-30	2-28	5-31	8-31	Hig
NOX	0.00	Start Date	3-1-2022	6-1-2022	9-1-2022	12-1-2022	3-1-2023	6-1-2023	
ROG	0.00	Sta	ઌ૽	9	9	12-	ج	9	
	Percent Reduction	Quarter	~	2	3	4	2	9	

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

2.2 Overall Operational **Unmitigated Operational**

CO2e		7.0000e- 003	149.6867	2,252.488 4	80.4607	122.6627	220.9549	2,826.260 4
N2O		0.0000	1.7500e- 003	0.2807	0.0000	0.0000	0.0476	0.3301
CH4	/yr	2.0000e- 005	0.0108	0.0781	0.0258	2.9261	1.9670	5.0077
Total CO2	MT/yr	6.5700e- 003	148.8967	2,166.877 7	79.8153	49.5115	157.6007	2,602.708 6
Bio- CO2 NBio- CO2 Total CO2		6.5700e- 003	148.8967	2,166.877 7	79.8153	0.0000	138.5640	2,534.160 3
Bio- CO2		0.0000	0.0000	0.0000	0.0000	49.5115	19.0367	68.5483
PM2.5 Total		1.0000e- 005	1.9400e- 003	0.3471	5.2100e- 003	0.0000	0.0000	0.3543
Exhaust PM2.5		1.0000e- 005	1.9400e- 003	0.0366	5.2100e- 003	0.000.0	0.000.0	0.0437
Fugitive PM2.5				0.3105				0.3105
PM10 Total		1.0000e- 005	1.9400e- 003	1.1626	5.2100e- 003	0.0000	0.0000	1.1698
Exhaust PM10	s/yr	1.0000e- 005	1.9400e- 003	0.0383	5.2100e- 003	0.0000	0.0000	0.0455
Fugitive PM10	tons/yr			1.1243				1.1243
S02			1.5000e- 004	0.0224	7.0000e- 004			0.0232
00		3.3800e- 003	0.0215	2.6689	4.2173			6.9110
XON		1.0763 3.0000e- 3.3800e- 005 003	0.0256		0.3228			4.0150
ROG		1.0763	2.8100e- 0 003	0.2295	6.6200e- 003			1.3152
	Category	Area		Mobile	Offroad	Waste	Water	Total

Page 7 of 34

Date: 2/6/2022 6:44 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

2.2 Overall Operational

Mitigated Operational

CO2e		7.0000e- 003	149.6867	1,719.699 6	80.4607	61.3314	186.4860	2,197.671 2
N20		0.0000	1.7500e- 003	0.2150	0.0000	0.0000	0.0402	0.2569
CH4	/yr	2.0000e- 005	0.0108	0.0609	0.0258	1.4630	1.6601	3.2206
Total CO2	MT/yr	6.5700e- 003	148.8967	1,654.103 0	79.8153	24.7558	133.0150	2,040.592 4
Bio- CO2 NBio- CO2 Total CO2		6.5700e- 003	148.8967	1,654.103 0	79.8153	0.0000	116.9480	1,999.769 6
Bio- CO2		0.0000	0.0000	0.0000	0.0000	24.7558	16.0670	40.8228
PM2.5 Total		1.0000e- 005	1.9400e- 003	0.2634	5.2100e- 003	0.0000	0.0000	0.2706
Exhaust PM2.5		1.0000e- 005	1.9400e- 003	0.0278	5.2100e- 003	0.000.0	0.000.0	0.0350
Fugitive PM2.5				0.2356				0.2356
PM10 Total		1.0000e- 005	1.9400e- 003	0.8822	5.2100e- 003	0.0000	0.0000	0.8894
Exhaust PM10	s/yr	1.0000e- 005	1.9400e- 003	0.0291	5.2100e- 003	0.0000	0.0000	0.0363
Fugitive PM10	tons/yr			0.8531	 			0.8531
SO2			1.5000e- 004	0.0171	7.0000e- 004			0.0179
00		3.3800e- 003	0.0215	2.1485	4.2173			6.3906
×ON		3.0000e- 005	0.0256	2.8546	0.3228			3.2029
ROG		1.0763	2.8100e- 003	0.1960	6.6200e- 003			1.2817
	Category	Area	:	Mobile	Offroad	Waste	Water	Total

CO2e	22.24
N20	22.16
CH4	35.69
Total CO2	21.60
Bio- CO2 NBio-CO2 Total CO2	21.09
Bio- CO2	40.45
PM2.5 Total	23.62
Exhaust PM2.5	20.03
Fugitive PM2.5	24.13
PM10 Total	23.97
Exhaust PM10	20.17
Fugitive PM10	24.13
805	22.80
00	7.53
NOx	20.23
ROG	2.54
	Percent Reduction

3.0 Construction Detail

Construction Phase

Phase Jumber	Phase Name	Phase Type	Start Date	End Date	Num Days Num Days Week	Num Days	Phase Description
		Demolition	3/1/2022	3/28/2022		5 20	
	Site Preparation	eparation	3/29/2022	4/11/2022		10	

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

Date: 2/6/2022 6:44 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3	Grading	Grading	4/12/2022	5/23/2022	5	30	
4	Building Construction	Building Construction 5/24/2022 7/17/2023	5/24/2022	7/17/2023		300	
5	Paving	Paving	1/17/2023 7/17/2023	+ 	5	5 130	
9	Architectural Coating	Architectural Coating 1/17/2023 7/17/2023 5 130	1/17/2023	7/17/2023	5	130	

Acres of Grading (Site Preparation Phase): 35

Acres of Grading (Grading Phase): 120

Acres of Paving: 5.29

Residential Indoor: 0; Residential Outdoor: 0; Non-Residential Indoor: 389,222; Non-Residential Outdoor: 129,741; Striped Parking Area: 13,826 (Architectural Coating – sqft)

OffRoad Equipment

Phase Name	Offroad Equipment Type	Amount	Usage Hours	Horse Power	Load Factor
Demolition	Concrete/Industrial Saws		8.00	81	0.73
Demolition	Excavators	ε • • • • • • • • • • • • • • • • • • •	8.00	158	0.38
Demolition	Rubber Tired Dozers	2	8.00	247	0.40
Site Preparation	Crawler Tractors	4	8.00	212	0.43
Site Preparation	Rubber Tired Dozers	E	8.00	247	0.40
Grading	Crawler Tractors	2	8.00	212	0.43
Grading	Excavators	2	8.00	158	0.38
1 1 1 1 1 1 1 1 1 1 1 1	Graders		8.00	187	0.41
	Rubber Tired Dozers		8.00	247	0.40
Grading	Scrapers	2	8.00	367	0.48
Building Construction	Cranes		7.00	231	0.29
Building Construction	Forklifts	E	8.00	68	0.20
Building Construction	Generator Sets		8.00	84	0.74
Building Construction	Tractors/Loaders/Backhoes	С	7.00	26	0.37
Building Construction	Welders		8.00	46	0.45
Paving	Pavers	2	8.00	130	0.42

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Paving	Paving Equipment	2	8.00	132	0.36
Paving	Rollers		8.00	8.00 80 0.38	0.38
Architectural Coating	Architectural Coating Air Compressors 0.48		00.9	78	0.48

Trips and VMT

Demolition	Count	Number	Number	Number	Voorker Lip Length	vendor Inp Length	Hauling Inp Length	VVOIKET VEINCIE Class	Vehicle Class	radiing Vehicle Class
• •	9	15.00	00.9	356.00	14.70	06.90	20.00			HHDT
Site Preparation		18.00	00.9				! ! !		:	HHDT
Grading	8	20.00	00.9			9.90			;	! ! !
Building Construction	ာ စ	206.00	80.00		14.70	9.90			:	HHDT
Paving	9	15.00				9.90	! ! !		:	HHDT
Architectural Coating	-	1 41.00	00:00	00.00	14.70			20.00 LD_Mix	HDT_Mix	HHDT

3.1 Mitigation Measures Construction

Water Exposed Area

Page 10 of 34

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

Date: 2/6/2022 6:44 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.2 Demolition - 2022

Unmitigated Construction On-Site

CO2e		0.0000	34.2289	34.2289						
NZO		0.000 0.0000 0.0000	0.0000	0.0000						
CH4	MT/yr	0.0000	9.5500e- 003	9.5500e- 003						
Total CO2	M	0.000.0	33.9902	33.9902						
Bio- CO2 NBio- CO2 Total CO2 CH4		0.0000 0.0000 0.0000	33.9902 33.9902 9.5500e- 003	33.9902						
Bio- CO2		0.0000	0.0000	0.0000						
PM2.5 Total		5.8300e- 003	0.0116	0.0174						
Exhaust PM2.5		0.0000	0.0116	0.0116						
Fugitive PM2.5		0.0385 5.8300e- 0.0000 5.8300e- 003 003		5.8300e- 003						
PM10 Total	tons/yr	tons/yr	ons/yr	ons/yr	ons/yr	ons/yr		0.0385	0.0124	0.0510
Exhaust PM10							0.000	0.0124	0.0124	
Fugitive PM10			0.0		0.0385					
SO2			3.9000e- 004	3.9000e- 004						
00			0.2059	0.2059						
×ON			0.0264 0.2572 0.2059 3.9000e- 004	0.0264 0.2572 0.2059 3.9000e- 0.0385 004						
ROG			0.0264	0.0264						
	Category	Fugitive Dust	Off-Road	Total						

e		20	83	5	49
CO2e		10.8450	1.1383	1.3315	13.3149
N2O		0.0000 10.3454 10.3454 4.4000e- 1.6400e- 003	1.6000e- 004	4.0000e- 005	1.8400e- 003
CH4	/yr	4.4000e- 004	3.0000e- 005	4.0000e- 005	5.1000e- 004
Total CO2	MT/yr	10.3454	1.0895	1.3193	12.7542
Bio- CO2 NBio- CO2 Total CO2		10.3454	1.0895	1.3193	12.7542
Bio- CO2			0.0000	0.0000	0.0000
PM2.5 Total		1.0900e- 003	1.4000e- 004	4.4000e- 004	1.6700e- 003
Exhaust PM2.5		e- 2.5000e- 3.3200e- 8.4000e- 2.4000e- 1.0900e- 004 003 004 004 003	0000e- 005	0000e- 005	2.8000e- 004
Fugitive PM2.5		8.4000e- 004	1.1000e- 004	4.4000e- 004	1.3900e- 003
PM10 Total		3.3200e- 003	9- 4.1000e- 004	1.6500e- 003	5.3800e- 003
Exhaust PM10	tons/yr	2.5000e- 004	0000	- 1.0000e- 005	2.9000e- 004
Fugitive PM10	ton	3.0700e- 003	3.8000e- 3	1.6400e 003	5.0900e- 003
S02		1.0000e- 004	1.0000e- 005	5.3200e- 1.0000e- 003 005	1.2000e- 004
00		6.3900e- 003	9.8000e- 004	5.3200e- 003	0.0127
NOx		0.0256	2.7600e- 003	4.4000e- 004	0.0288
ROG		6.6000e- 0.0256 6.3900e- 1.0000e- 3.0700e 004 003	1.0000e- 2.7600e- 9 004 003	5.7000e- 004	1.3300e- 003
	Category	Hauling	Vendor	Worker	Total

Page 11 of 34

Date: 2/6/2022 6:44 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.2 Demolition - 2022

Mitigated Construction On-Site

	ROG	NOX	00	S02	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	Bio- CO2 NBio- CO2 Total CO2	Total CO2	CH4	NZO	CO2e
Category					tons/yr								MT/yr	'yr		
Fugitive Dust					0.0150	0.0000	0.0150	0.0150 2.2700e- 003	0.0000	2.2700e- 0 003	0.0000	0.0000 0.0000 0.0000 0.0000 0.0000	0.0000	0.000.0	0.0000	0.0000
Off-Road	0.0264	0.0264 0.2572 0.2059 3.9000e- 004	0.2059	3.9000e- 004		0.0124	0.0124		0116	0.0116	0.0000	0.0000 33.9902	33.9902	9.5500e- 003	0.0000	34.2289
Total	0.0264	0.0264 0.2572 0.2059 3.9000e- 0.0150 0.0450	0.2059	3.9000e- 004	0.0150	0.0124	0.0275	2.2700e- 0. 003	0.0116	0.0138	0.0000	33.9902	33.9902	9.5500e- 003	0.000	34.2289

CO2e		10.8450	1.1383	1.3315	13.3149
NZO		1.6400e- 003	1.6000e- 004	4.0000e- 005	1.8400e- 003
CH4	'yr	4.4000e- 004	3.0000e- 005	4.0000e- 005	5.1000e- 004
Total CO2	MT/yr	10.3454	1.0895	1.3193	12.7542
Bio- CO2 NBio- CO2 Total CO2		0.0000 10.3454 10.3454 4.4000e-	1.0895	1.3193	12.7542
Bio- CO2		0.0000	0.0000	0.0000	0.000
PM2.5 Total		1.0900e- (1.4000e- 004	4.4000e- 004	1.6700e- 003
Exhaust PM2.5		2.4000e- 004	3.0000e- 005	э- 1.0000e- 005	3000e- 004
Fugitive PM2.5		3.3200e- 8.4000e- 003 004	1.1000e- 004	1.4000 004	1.3900e- 003
PM10 Total		3.3200e- 003	1000e- 004	1.6500e- 003	5.3800e- 003
Exhaust PM10	tons/yr	2.5000e- 004	3.0000e 005	1.0000e- 005	2.9000e- 004
Fugitive PM10	ton	3.0700e- 003	. 3.8000e- 004	1.6400e- 003	5.0900e- 003
805		1.0000e- 004	1.0000e- 005	1.0000e- 005	0.0127 1.2000e- 5.0900e-
00		6.3900e- 003	9.8000e- 004	5.3200e- 003	0.0127
×ON		0.0256	2.7600e- 003	4.4000e- 004	0.0288
ROG		6.6000e- 004	1.0000e- 2.7600e- 9.8000e- 1.0000e- 3.8000e- 3.0000e- 3.8000e- 3.8	5.7000e- 004	1.3300e- 003
	Category	Hauling	Vendor	Worker	Total

Page 12 of 34

age 12 of 34 Date: 2/6/2022 6:44 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

3.3 Site Preparation - 2022
Unmitigated Construction On-Site

	ROG	XON	00	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Bio- CO2 NBio- CO2 Total CO2	CH4	N20	CO2e
Category					tons/yr	s/yr							MT/yr	'yr		
Fugitive Dust					0.1089	0.0000	0.1089	0.0517	0.1089 0.0517 0.0000	0.0517	0.0000	0.0000	0.0000 0.0000 0.0000 0.0000 0.0000	0.000.0	0.0000	0.0000
Off-Road	0.0224	0.0224 0.2521 0.1000 2.8000e- 004	0.1000	2.8000e- 004		0.0108	0.0108		9.9300e- 003	- 9.9300e- (003	0.0000	0.0000 25.0258 25.0258	25.0258	8.0900e- 003	0.0000	25.2281
Total	0.0224	0.2521	0.1000	0.0224 0.2521 0.1000 2.8000e- 0.1089	0.1089	0.0108	0.1197	0.0517	9.9300e- 003	0.0616	0.0000	25.0258	25.0258	8.0900e- 003	0.000.0	25.2281

Φ		00	32	68	<u>~</u>
CO2e		0.0000	0.5692	0.7989	1.3681
NZO		0.0000 0.0000	8.0000e- 005	- 2.0000e- 005	1.0000e- 004
CH4	MT/yr		1.0000e- 005	2.0000e- 005	3.0000e- 005
Total CO2	LM	0.0000	0.5448	0.7916	1.3363
Bio- CO2 NBio- CO2 Total CO2		0.0000 0.0000 0.0000	0.5448	0.7916	1.3363
Bio- CO2		0.0000	0.0000	0.0000	0.000
PM2.5 Total		0.0000	7.0000e- 005	2.7000e- 004	3.4000e- 004
Exhaust PM2.5		0.000.0	1.0000e- 005	0.0000	1.0000e- 005
Fugitive PM2.5		0.0000 0.0000 0.0000	00000e- 005	2.6000e- 004	3.1000e- 004
PM10 Total		0.0000	2.0000e 004	9.9000e- 2. 004	1.1900e- 003
Exhaust PM10	tons/yr	0.0000	.0000e- 005	1.0000e- 005	3.0000e- 005
Fugitive PM10	ton	0.0000	- 1.9000e- 2 004	9.9000e- 004	1.1800e- 003
SO2		0.0000	- 1.0000e- 1.9 005	1.0000e- 005	3.6800e- 2.0000e- 003 005
00		0.0000	4.9000e- 004	3.1900e- 003	3.6800e- 003
XON		0.0000 0.0000 0.0000 0.0000	5.0000e- 1.3800e- 4.9000e- 005 003 004	2.7000e- 004	3.9000e- 004 003
ROG		0.0000	5.0000e- 005	3.4000e- 2.7000e- 3.1900e- 1.0000e- 004 003 005	3.9000e- 004
	Category	Hauling	Vendor	Worker	Total

Page 13 of 34

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

Date: 2/6/2022 6:44 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Mitigated Construction On-Site 3.3 Site Preparation - 2022

CO2e		0.0000	25.2281	25.2281					
N20		0.0000	0.0000	0.000					
CH4	/yr	0.0000 0.0000	8.0900e- 003	8.0900e- 003					
Total CO2	MT/yr	0.0000 0.0000.0	25.0257	25.0257					
Bio- CO2 NBio- CO2 Total CO2		0.0000	25.0257 25.0257 8.0900e- 003	25.0257					
Bio- CO2		0.0000	0.0000	0.000.0					
PM2.5 Total		0.0202	9.9300e- 003	0.0301					
Exhaust PM2.5		0.000.0	9.9300e- 9.9300e- 003 003	9.9300e- 003					
Fugitive PM2.5		0.0202		0.0202					
PM10 Total		0.0425	0.0108	0.0533					
Exhaust PM10	tons/yr	ns/yr	ns/yr	ıns/yr	ıns/yr	ns/yr	0.0000	0.0108	0.0108
Fugitive PM10		0.0425		0.0425					
SO2			2.8000e- 004	0.1000 2.8000e- 0.0425 004					
00			0.1000	0.1000					
×ON			0.0224 0.2521 0.1000 2.8000e-	0.2521					
ROG			0.0224	0.0224					
	Category	Fugitive Dust	Off-Road	Total					

Φ		0	72	0	Σ
CO2e		0.0000	0.5692	0.7989	1.3681
NZO			8.0000e- 005	2.0000e- 005	1.0000e- 004
CH4	/yr	0.000.0	1.0000e- 005	2.0000e- 005	3.0000e- 005
Total CO2	MT/yr	0.000 0.0000 0.0000	0.5448	0.7916	1.3363
Bio- CO2 NBio- CO2 Total CO2		0.0000 0.0000	0.5448	0.7916	1.3363
Bio- CO2		0.000.0	0.000.0	0.000.0	0.000
PM2.5 Total		0.0000	7.0000e- 005	2.7000e- 004	3.4000e- 004
Exhaust PM2.5		0.000.0	1.0000e- 005	0.000	1.0000e- 3 005
Fugitive PM2.5		0.0000 0.0000 0.0000	5.0000e- 005	. 2.6000e- (004	3.1000e- 004
PM10 Total		0.000.0	2.0000e- 004	9.9000e 004	1.1900e- 003
Exhaust PM10	ons/yr	0.000.0	2.0000e- 005	1.0000e- 005	3.0000e- 005
Fugitive PM10	ton	0.0000	1.9000e- 004	9.9000e- 004	1.1800e- 003
80 <i>z</i>		0.0000	1.0000e- 005	1.0000e- 005	2.0000e- 005
00		0.0000	4.9000e- 004	3.1900e- 003	3.6800e- 003
×ON		0.0000 0.0000 0.0000 0.0000	5.0000e- 1.3800e- 4.9000e- 1.0000e- 005 003 004 005	3.4000e- 2.7000e- 3.1900e- 1.0000e- 004 004 005	3.9000e- 1.6500e- 3.6800e- 004 003
ROG		0.0000	5.0000e- 005	3.4000e- 004	3.9000e- 004
	Category	Hauling	Vendor	Worker	Total

Page 14 of 34

Date: 2/6/2022 6:44 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.4 Grading - 2022

Unmitigated Construction On-Site

0		0	. . .	Σ
CO2e		0.000	95.0231	95.0231
NZO		0.0000	0.0305 0.0000	0.000
CH4	/yr	0.000.0	0.0305	0.0305
Total CO2	MT/yr	0.000.0	94.2610	94.2610
Bio- CO2 NBio- CO2 Total CO2		0.0000 0.0000 0.0000 0.0000 0.0000	0.0000 94.2610	94.2610
Bio- CO2				0.0000
PM2.5 Total		0.0565	0.0263	0.0829
Exhaust PM2.5		0.0000	0.0263	0.0263
Fugitive PM2.5		0.1540 0.0565		9950.0
PM10 Total		0.1540	0.0286	0.1826
Exhaust PM10	tons/yr	0.0000	0.0286	0.0286
Fugitive PM10	ton	0.1540		0.1540
805			1.0700e- 003	1.0700e- 003
00			0.4379	0.4379
×ON			0.0642 0.7126 0.4379 1.0700e- 003	0.7126 0.4379 1.0700e-
ROG			0.0642	0.0642
	Category	Fugitive Dust	Off-Road	Total

CO2e		0.0000	1.7075	2.6631	4.3705
N20		0.0000	2.4000e- 004	8.0000e- 005	3.2000e- 004
CH4	MT/yr	0.0000	4.0000e- 2. 005	8.0000e- 8 005	1.2000e- 004
Total CO2	M	0.000.0	1.6343	2.6386	4.2728
Bio- CO2 NBio- CO2 Total CO2		0.0000 0.0000 0.0000	1.6343	2.6386	4.2728
Bio- CO2			0.000.0	0.000.0	0.000
PM2.5 Total		0.0000	2.1000e- 004	8.9000e- 004	1.1000e- 003
Exhaust PM2.5			.0000e- 005	.0000e- 005	6.0000e- 005
Fugitive PM2.5		0.000 0.0000 0.0000	1.6000e- 4. 004	8.7000e- 2 004	1.0300e- 6 003
PM10 Total			1000e- 004	3100e- 003	3.9200e- 003
Exhaust PM10	ns/yr	0.0000	5.0000e- 005	2.0000e- 3. 005	7.0000e- 005
Fugitive PM10	ton	0.0000	5.7000e- 004	3.2900e- 003	3.8600e- 003
SO2		0.0000 0.0000 0.0000 0.0000	:.0000e- 005	3.0000e- 005	5.0000e- 005
00		0.0000	1.4700e- 003	0.0107	0.0121
×ON		0.0000	1.5000e- 4.1500e- 1.4700e- 2 004 003 003	8.9000e- 004	1.2800e- 5.0400e- 003 003
ROG		0.0000	1.5000e- 004	1.1300e- 003	1.2800e- 003
	Category	Hauling	Vendor	Worker	Total

Page 15 of 34

Date: 2/6/2022 6:44 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.4 Grading - 2022

Mitigated Construction On-Site

CO2e		0.0000	95.0230	95.0230
			00 95	
N20		0.000	0.0000	0.000
CH4	/yr	0.0000 0.0000	0.0305	0.0305
Total CO2	MT/yr	0.000.0	94.2609	94.2609
Bio- CO2 NBio- CO2 Total CO2		0.0000 0.0000 0.0000	94.2609	94.2609
Bio- CO2		0.000.0	0.0000	0.000.0
PM2.5 Total		0.0220	0.0263	0.0484
Exhaust PM2.5			0.0263	0.0263
Fugitive PM2.5		0.0600 0.0220 0.0000		0.0220
PM10 Total		0.0600	0.0286	0.0887
Exhaust PM10	tons/yr	0.0000	0.0286	0.0286
Fugitive PM10	tons	0.0600		0.090.0
S02			1.0700e- 003	1.0700e- 003
00			0.4379	0.4379
NOx			0.7126 0.4379 1.0700e- 003	0.7126 0.4379 1.0700e-
ROG			0.0642	0.0642
	Category	Fugitive Dust	Off-Road	Total

Total CO2 CH4 N2O CO2e	MT/yr	00000 00000 00000 00000 00000	1.6343 4.0000e- 2.4000e- 1.7075 005 004	2.6386 8.0000e- 8.0000e- 2.6631 005 005	4.2728 1.2000e- 3.2000e- 4.3705 004 004
Bio- CO2 NBio- CO2 Total CO2		0.0000 0.0000	0.0000 1.6343	0.0000 2.6386	0.0000 4.2728
PM2.5 Total		00000	2.1000e- 004	8.9000e- 004	1.1000e- 003
Exhaust PM2.5		0.0000	4.0000e- 2 005	2.0000e- 005	6.0000e- 005
Fugitive PM2.5		0.0000	1.6000e- 004	8.7000e- 004	1.0300e- 003
PM10 Total		0.0000	6.1000e- 004	3.3100e- 003	3.9200e- 003
Exhaust PM10	ons/yr	0.0000	5.0000e- 005	2.0000e- 005	7.0000e- 005
Fugitive PM10	to	0.0000 0.0000 0.0000 0.0000 0.0000	5.7000e- 004	3.2900e- 2 003	3.8600e- 003
SO2		0.0000	000e- 005	3.0000e- 005	5.0000e- 005
00		0.0000	1.4700e 003	0.0107	0.0121
×ON		0.0000	1500e 003	1.1300e- 8.9000e- 003 004	1.2800e- 5.0400e- 003 003
ROG		0.0000	1.5000e- 4. 004	1.1300e- 003	1.2800e- 003
	Category	Hauling	Vendor	Worker	Total

Page 16 of 34

Date: 2/6/2022 6:44 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.5 Building Construction - 2022 **Unmitigated Construction On-Site**

CO2e		185.3249	185.3249
N20		0.0000 184.2216 184.2216 0.0441 0.0000 185.3249	0.0000
CH4	yr	0.0441	0.0441
Total CO2	MT/yr	184.2216	184.2216
Bio- CO2 NBio- CO2 Total CO2 CH4		184.2216	0.0000 184.2216 184.2216
Bio- CO2		0.000.0	0.0000
PM2.5 Total		0.0605	0.0605
Exhaust PM2.5		0.0605 0.0605	0.0605
Fugitive PM2.5			
PM10 Total		0.0643	0.0643
Exhaust PM10	s/yr	0.0643 0.0643	0.0643
Fugitive PM10	tons/yr		
S02		2.1400e- 003	2.1400e- 003
00		1.3009	1.3009 2.1400e-
NOX		1.2414	1.2414
ROG		0.1357 1.2414 1.3009 2.1400e-	0.1357
	Category	Off-Road	Total

			_		
CO2e		0.0000	120.6619	145.3766	266.0385
N20		0.0000	0.0171	4.1400e- 003	0.0212
CH4	yr	0.000.0	3.1100e- 003	4.1000e- 003	7.2100e- 003
Total CO2	MT/yr	0.000.0	115.4873	144.0405	259.5279
Bio- CO2 NBio- CO2 Total CO2		0.0000 0.0000 0.0000	0.0000 115.4873 115.4873	0.0000 144.0405 144.0405	0.0000 259.5279 259.5279
Bio- CO2		0.000.0	0.000.0	0.0000	0.000
PM2.5 Total		0.0000	0.0148	0.0486	0.0633
Exhaust PM2.5		0.000.0	3.1700e- 003	8.8000e- 004	4.0500e- 003
Fugitive PM2.5		0.0000 0.0000	0.0116	0.0477	0.0593
PM10 Total		0.0000	0.0434	0.1805	0.2240
Exhaust PM10	tons/yr	0.0000	3.3200e- 003	9.6000e- 004	4.2800e- 003
Fugitive PM10	tons	0.0000	0.0401	0.1796	0.2197
SO2		0.0000	0.1039 1.1900e- 003	1.5600e- 003	2.7500e- 003
00		0.000.0	0.1039	0.5811	0.6850
XON		0.0000	0.2930	0.0485	0.3414 0.6850 2.7500e- 003
ROG		0.0000	0.0108	0.0617	0.0726
	Category	Hauling	Vendor	Worker	Total

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

Page 17 of 34

Date: 2/6/2022 6:44 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.5 Building Construction - 2022

Mitigated Construction On-Site

2e		3247	3247
CO2e		185.3	185.3
N20		0.0000	0.0000 185.3247
CH4	/yr	0.0441	0.0441
Total CO2	MT/yr	184.2214	184.2214
Bio- CO2 NBio- CO2 Total CO2		0.0000 184.2214 184.2214 0.0441 0.0000 185.3247	0.0000 184.2214 184.2214 0.0441
Bio- CO2		0.0000	0.000
PM2.5 Total			0.0605
Exhaust PM2.5		0.0605 0.0605	0.0605
Fugitive PM2.5			
PM10 Total		0.0643	0.0643
Exhaust PM10	ons/yr	0.0643 0.0643	0.0643
Fugitive PM10	t		
SO2		0.1357 1.2414 1.3009 2.1400e-	2.1400e- 003
00		1.3009	1.3009 2.1400e-
×ON		1.2414	1.2414
ROG		0.1357	0.1357
	Category	Off-Road	Total

			_		
CO2e		0.0000	120.6619	145.3766	266.0385
N20		0.0000	0.0171	4.1400e- 003	0.0212
CH4	yr	0.000.0	3.1100e- 003	4.1000e- 003	7.2100e- 003
Total CO2	MT/yr	0.000.0	115.4873	144.0405	259.5279
Bio- CO2 NBio- CO2 Total CO2		0.0000 0.0000 0.0000	0.0000 115.4873 115.4873	0.0000 144.0405 144.0405	0.0000 259.5279 259.5279
Bio- CO2		0.0000	0.0000	0.0000	0.000
PM2.5 Total		0.0000	0.0148	0.0486	0.0633
Exhaust PM2.5		0.000.0	3.1700e- 003	8.8000e- 004	4.0500e- 003
Fugitive PM2.5		0.0000 0.0000	0.0116	0.0477	0.0593
PM10 Total			0.0434	0.1805	0.2240
Exhaust PM10	tons/yr	0.0000	3.3200e- 003	9.6000e- 004	4.2800e- 003
Fugitive PM10	tons	0.000.0	0.0401	0.1796	0.2197
SO2		0.000.0	0.1039 1.1900e- 003	1.5600e- 003	2.7500e- 003
00		0.000.0	0.1039	0.5811	0.6850
XON		0.0000	0.2930	0.0485	0.3414 0.6850 2.7500e- 003
ROG		0.0000	0.0108	0.0617	0.0726
	Category	Hauling	Vendor	Worker	Total

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.5 Building Construction - 2023 **Unmitigated Construction On-Site**

CO2e		4.3942	164.3942
		00 164	
N20		0.000	0.0000
CH4	/yr	0.0389	0.0389
Total CO2	MT/yr	163.4224	163.4224
Bio- CO2 NBio- CO2 Total CO2		0.0000 163.4224 163.4224 0.0389 0.0000 164.3942	0.0000 163.4224 163.4224 0.0389
Bio- CO2			0.000
PM2.5 Total		0.0464 0.0464	0.0464
Exhaust PM2.5		0.0464	0.0464
Fugitive PM2.5			
PM10 Total		0.0493	0.0493
Exhaust PM10	tons/yr	0.0493 0.0493	0.0493
Fugitive PM10			
805		1.9000e- 003	1.9000e- 003
00		1.1452	1.1452
×ON		1.0141	0.1109 1.0141
ROG		0.1109 1.0141 1.1452 1.9000e-	0.1109
	Category	Off-Road	Total

		I	٠	01	"
CO2e		0.0000	102.6884	125.4562	228.1446
N2O		0.0000	0.0145	3.3700e- 003	0.0179
CH4	'yr	0.000 0.0000 0.0000	2.5600e- 003	3.2600e- 003	5.8200e- 003
Total CO2	MT/yr	0.000.0	98.2956	124.3690	222.6646
Bio- CO2 NBio- CO2 Total CO2		0.0000 0.0000 0.0000	98.2956	124.3690 124.3690 3.2600e- 003	0.0000 222.6646
Bio- CO2		0.0000	0.0000	0.0000	0.000.0
PM2.5 Total		0.0000	0.0117	0.0430	0.0547
Exhaust PM2.5		0.000.0	1.4200e- 003	7.4000e- 004	2.1600e- 003
Fugitive PM2.5		0.0000 0.0000 0.0000	0.0103	0.0423	0.0526
PM10 Total		0.000.0	0.0371	0.1600	0.1971
Exhaust PM10	tons/yr	0.0000	1.4900e- 003	8.0000e- 004	2.2900e- 003
Fugitive PM10	tons	0.0000	0.0356	0.1592	0.1948
802		0.0000	.0100e- 003	0.4726 1.3400e- C	2.3500e- 003
00		0.000.0	0.0842	0.4726	0.5568
×ON		0.0000 0.0000 0.0000 0.0000	0.2081	0.0378	0.2459
ROG		0.0000	6.3600e- 0.2081 003	0.0506	0.0570
	Category	Hauling	Vendor	Worker	Total

Page 19 of 34

Date: 2/6/2022 6:44 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.5 Building Construction - 2023

Mitigated Construction On-Site

CO2e		164.3940	0.0000 164.3940
N20		0.0464 0.0464 0.0000 163.4222 163.4222 0.0389 0.0000 164.3940	
CH4	/yr	0.0389	0.0389
Total CO2	MT/yr	163.4222	163.4222
Bio- CO2 NBio- CO2 Total CO2		163.4222	0.0000 163.4222 163.4222
Bio- CO2		0.0000	0.0000
PM2.5 Total		0.0464	0.0464
Exhaust PM2.5		0.0464	0.0464
Fugitive PM2.5			
PM10 Total		0.0493	0.0493
Exhaust PM10	s/yr	0.0493 0.0493	0.0493
Fugitive PM10	tons/yr		
S02		1.9000e- 003	1.9000e- 003
00		1.1452	1.1452 1.9000e-
NOx		1.0141	1.0141
ROG		0.1109 1.0141 1.1452 1.9000e- 003	0.1109
	Category	Off-Road	Total

D2 Fugitive Exhaust PM10 Fugitive Exhaust PM2.5 PM2.5 Total PM2.5 Total CO2 Total CO2 Total CO2 Total CO2 CO2 CO2 Total PM2.5 PM2.5 Total PM2.5 Total CO2 To	tons/yr	0.0000 0.0000 0.0000 0.0000 0.0000 0.0000 0.0000 0.0000 0.0000 0.0000 0.0000 0.0000 0.0000 0.0000 0.0000	0.0842 1.0100e- 0.0356 1.4900e- 0.0371 0.0103 1.4200e- 0.0117 0.0000 98.2956 98.2956 2.5600e- 0.0145 102.6884 003 003 003	00e- 0.1592 8.0000e- 0.1600 0.0423 7.4000e- 0.0430 0.0000 124.3690 124.3690 3.2600e- 3.3700e- 125.4562 03 003 003	2 2000 2 4074 0 0526 2 45002
			0.0000	0.0000	
		0.0000 0.00	! }	ļ 	2.1600e- 0.0547 003
Fugitive PM2.5		0.0000	ļ		0.0526
		0.0000	ļ	ļ	9- 0.1971
	tons/yr		 		2.2900e- 003
		0.0000	0.0356	0.1592	0.5568 2.3500e- 0.1948 003
802		0.0000	1.0100e 003	0.4726 1.3400e- C	2.3500e 003
8		0.0000	0.0842	0.4726	
× O Z		0.0000	0.2081	0.0378	0.0570 0.2459
ROG		0.0000	6.3600e- 0.2081 003	0.0506	0.0570
	Category	Hauling	Vendor	Worker	Total

CalEEMod Version: CalEEMod.2020.4.0

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

Page 20 of 34

Date: 2/6/2022 6:44 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.6 Paving - 2023

Unmitigated Construction On-Site

PM10 Fugitive Exhaust Total PM2.5 PM2.5 0.0332 0.0305	Fugitive Exhaust PM10 Fugitive Exhaust PM10 Total PM2.5 PM2.5 tons/yr 0.0332 0.0332 0.0305	Fugitive Exhaust PM10 Fugitive Exhaust PM10 Total PM2.5 PM2.5 tons/yr 0.0332 0.0332 0.0305	SO2 Fugitive Exhaust PM10 Fugitive Exhaust PM2.5 PM2.5 PM2.5 tons/yr tons/yr 0.0332 0.0332 0.0305
Total PM2.5	tons/yr	tons/yr	tons/yr
PM10 Total	Fugitive Exhaust PM10 PM10 Total tons/yr 0.0332 0.0332	Fugitive Exhaust PM10 PM10 Total tons/yr 0.0332 0.0332	Fugitive Exhaust PM10 PM10 Total tons/yr 0.0332 0.0332
	Fugitive PM10 tons	Fugitive PM10 tons	Fugitive PM10 tons

CO2e		0.0000	0.0000	8.4225	8.4225
N2O		0.0000	0.0000	- 2.3000e- 8 004	2.3000e- 004
CH4	MT/yr	0.0000 0.0000 0.0000	0.0000	2.2000e- 2.0 004	2.2000e- 004
Total CO2	M	0.000.0	0.0000	8.3495	8.3495
Bio- CO2 NBio- CO2 Total CO2		0.0000	0.0000	8.3495	8.3495
Bio- CO2		0.0000	0.0000	0.000.0	0.000.0
PM2.5 Total		0.0000	0.0000	2.8900e- 003	2.8900e- 003
Exhaust PM2.5			0000	0000e- 005	5.0000e- 005
Fugitive PM2.5		0.000 0.0000 0.0000	0.0000	2.8400e- 5. 003	2.8400e- 003
PM10 Total		0.0000	0.000.0	0.0107	0.0107
Exhaust PM10	tons/yr	0.000.0	0.0000	5.0000e- 005	5.0000e- 005
Fugitive PM10	ton	0.0000	0.0000	0.0107	0.0107
SO2		0.0000 0.0000 0.0000 0.0000	0.0000	0.0317 9.0000e- 005	0.0317 9.0000e- 005
00		0.0000	0.000.0	0.0317	0.0317
×ON		0.0000	0.0000	2.5400e- 003	3.4000e- 2.5400e- 003 003
ROG		0.0000	0.0000	3.4000e- 2.5400e- 003 003	3.4000e- 003
	Category	Hauling	Vendor	Worker	Total

CalEEMod Version: CalEEMod.2020.4.0

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

Page 21 of 34

Date: 2/6/2022 6:44 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.6 Paving - 2023

Mitigated Construction On-Site

	ROG	×ON	00	S02	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	Bio- CO2 NBio- CO2 Total CO2	Total CO2	CH4	N20	CO2e
Category					tons/yr	s/yr							MT/yr	yr		
Off-Road	0.0671	3625	0.9480	1.4800e- 003		0.0332	0.0332		0.0305	0.0305	0.0000	130.1745	0.0000 130.1745 130.1745 0.0421 0.0000 131.2270	0.0421	0.0000	131.2270
Paving	6.9300e- 003					0.0000	0.0000		0.0000	0.0000	0.0000	0.0000 0.0000	0.0000 0.0000	0.000.0	0.0000	0.0000
Total	0.0741	0.6625	0.9480	0.9480 1.4800e- 003		0.0332	0.0332		0.0305	0.0305	0.0000	0.0000 130.1745 130.1745	130.1745	0.0421	0.0000 131.2270	131.2270

Şe.		00	8	25	55
CO2e		0.0000	0.0000	8.4225	8.4225
N20		0.000.0 0.000.0	0.0000	2.3000e- 004	2.3000e- 004
CH4	MT/yr	0.0000	0.0000	2.2000e- 004	2.2000e- 004
Total CO2	M	0.0000	0.0000	8.3495	8.3495
Bio- CO2 NBio- CO2 Total CO2		0.0000 0.0000 0.0000	0.0000	8.3495	8.3495
Bio- CO2		0.0000	0.0000	0.0000	0.000
PM2.5 Total		0.0000	0.0000	2.8900e- 003	2.8900e- 003
Exhaust PM2.5		0.000.0	0.0000	0000e- 005	5.0000e- 005
Fugitive PM2.5		0.0000 0.0000 0.0000	0.0000	2.8400e- 5. 003	2.8400e- 003
PM10 Total		0.0000	0.0000	0.0107	0.0107
Exhaust PM10	tons/yr	0.0000	0.0000	5.0000e- 005	5.0000e- 005
Fugitive PM10	ton	0.0000	0.0000	0.0107	0.0107
805		0.0000	0.0000	9.0000e- 0.0 005	9.0000e- 005
00		0.0000	0.0000	0.0317	0.0317 9.0000e-
NOX		0.0000 0.0000 0.0000 0.0000	0.0000 0.0000	2.5400e- 003	3.4000e- 2.5400e- 003 003
ROG		0.0000	0.0000	3.4000e- 2.5400e- 003 003	3.4000e- 003
	Category	Hauling	Vendor	Worker	Total

Page 22 of 34

Date: 2/6/2022 6:44 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.7 Architectural Coating - 2023 Unmitigated Construction On-Site

CO2e		0.0000	16.6210	16.6210
N20		0.0000	0.0000	0.000
CH4	Уr	0000.0	9000e- 004	9.9000e- 004
Total CO2	MT/yr	0.000.0	16.5962 9.	16.5962
Bio- CO2 NBio- CO2 Total CO2		0.000 0.0000 0.0000	0.0000 16.5962	16.5962
Bio- CO2		0.0000	0.0000	0.000
PM2.5 Total		0.0000	- 4.6000e- 003	4.6000e- 003
Exhaust PM2.5		0.000.0	4.6000e- 4.	4.6000e- 003
Fugitive PM2.5				
PM10 Total		0.0000	- 4.6000e- 003	4.6000e- 003
Exhaust PM10	ons/yr	0.0000	4.6000e- 003	4.6000e- 003
Fugitive PM10	tons			
S02			1.9000e- 004	1.9000e- 004
00			0.1177	0.1177 1.9000e-
×ON			0.0125 0.0847 0.1177 1.9000e- 004	0.0847
ROG		1.2347	0.0125	1.2472
	Category	Archit. Coating 1.2347	Off-Road	Total

CO2e		0.0000	0.0000	23.0215	23.0215
N2O		0.0000	0.0000	6.2000e- 2: 004	6.2000e- 004
CH4	yr	0.000.0 0.000.0	0.0000	6.0000e- 004	6.0000e- 004
Total CO2	MT/yr	0.000.0	0.0000	22.8220	22.8220
Bio- CO2 NBio- CO2 Total CO2		0.0000 0.0000 0.0000	0.0000	22.8220	22.8220
Bio- CO2		0.0000	0.0000	0.0000	0.000.0
PM2.5 Total		0.0000	0.0000	1.4000e- 7.9000e- 004 003	600 -90006-
Exhaust PM2.5		0.0000	0.0000	1.4000e- 004	1.4000e- 004
Fugitive PM2.5		0.0000 0.0000 0.0000	0.0000	7.7600e- 003	7.7600e- 003
PM10 Total		0.000.0	0.000.0	0.0294	0.0294
Exhaust PM10	tons/yr	0.0000	0.0000	1.5000e- 004	1.5000e- 004
Fugitive PM10	tons	0.0000	0.0000	0.0292	0.0292
S02		0.0000	0.0000	0.0867 2.5000e- (0.0867 2.5000e-
00		0.0000	0.0000	0.0867	2980.0
XON		0.0000 0.0000 0.0000 0.0000	0.0000 0.0000	9.2900e- 6.9300e- 003 003	9.2900e- 003 6.9300e-
ROG		0.0000	0.0000	9.2900e- 003	9.2900e- 003
	Category	Hauling	Vendor	Worker	Total

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.7 Architectural Coating - 2023

Mitigated Construction On-Site

	ROG	×ON	00	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive Exhaust PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	Bio- CO2 NBio- CO2 Total CO2	Total CO2	CH4	N20	CO2e
Category					tons/yr	s/yr							MT/yr	ýr		
Archit. Coating 1.2347	1.2347					0.0000	0.0000		0.0000	0.0000 0.0000	0.0000	0.0000 0.0000 0.0000 0.0000 0.0000	0.0000	0.000.0	0.000.0	0.0000
Off-Road	0.0125	0.0847	0.1177	0.0125 0.0847 0.1177 1.9000e- 004		4.6000e- 4.6000e- 003 003	4.6000e- 003		4.6000e- 003	4.6000e- C	0.0000	0.0000 16.5961 16.5961 9.9000e- 004	16.5961	9.9000e- 004	0.0000	16.6210
Total	1.2472	1.2472 0.0847 0.1177 1.9000e-	0.1177	1.9000e- 004		4.6000e- 4.6 003 (4.6000e- 003		4.6000e- 003	4.6000e- 0	.0000	16.5961	16.5961	9.9000e- 004	0.0000	16.6210

CO2e		0.0000	0.0000	23.0215	23.0215
		000	000	6.2000e- 23 004	6.2000e- 23 004
NZO		0.00	0.0000	6.200	
CH4	MT/yr	0.0000 0.0000	0.0000	6.0000e- 004	6.0000e- 004
Total CO2	M	0.000.0	0.000.0	22.8220	22.8220
Bio- CO2 NBio- CO2 Total CO2		0.0000 0.0000 0.0000	0.0000	22.8220	22.8220
Bio- CO2		0.0000	0.0000	0.0000	0.000.0
PM2.5 Total		0.0000	0.0000	7.9000e- 003	7.9000e- 003
Exhaust PM2.5		0.0000	0.0000	1.4000e- 7.9000e- 004 003	1.4000e- 004
Fugitive PM2.5		0.0000 0.0000 0.0000	0.0000	7.7600e- 003	7.7600e- 003
PM10 Total		0.000.0	0.000.0	0.0294	0.0294
Exhaust PM10	tons/yr	0.0000	0.0000	1.5000e- 004	1.5000e- 004
Fugitive PM10	ton	0.0000	0.0000	0.0292	0.0292
S02		0.0000	0.0000	0.0867 2.5000e- (0.0867 2.5000e-
00		0.0000	0.0000	0.0867	2980.0
×ON		0.0000 0.0000 0.0000 0.0000	0.0000 0.0000	6.9300e- 003	9.2900e- 003 6.9300e-
ROG		0.0000	0.0000	9.2900e- 6.9300e- 003 003	9.2900e- 003
	Category	Hauling	Vendor	Worker	Total

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

4.0 Operational Detail - Mobile

4.1 Mitigation Measures Mobile

Increase Transit Accessibility

Improve Pedestrian Network

CO2e		1,719.699 6	2,252.488 4				
N20		0.2150	0.2807				
CH4	٧٢	6090.0	0.0781				
Total CO2	MT/yr	1,654.103 0	2,166.877 7				
NBio- CO2		0.0000 1,654.103 1,654.103 0.0609 0.2150 1,719.699 0 0	2,166.877 2,166.877 7				
Bio-CO2 NBio-CO2 Total CO2 CH4		0.0000	0.0000 2,166.877 2,166.877 0.0781 0.2807 2,252.488				
PM2.5 Total	Total PM2.5 PM2.5 Total Total 0.8822 0.2356 0.0278 0.2634 1.1626 0.3105 0.0366 0.3471						
Exhaust PM2.5	Total PM2.5 PM2.5 Total 0.8822 0.2356 0.0278 0.2634 1.1626 0.3105 0.0366 0.3471						
Fugitive PM2.5	Total PM2.5 PM2.5 Total 0.8822 0.2356 0.0278 0.2634 1.1626 0.3105 0.0366 0.3471						
PM10 Total	Total PM2.5 PM2.5 Total 0.8822 0.2356 0.0278 0.2634 1.1626 0.3105 0.0366 0.3471						
Exhaust PM10	/yr	0.0291	0.0383				
Fugitive PM10	tons/yr		1.1243				
802		0.0171	0.0224				
00		2.1485	2.6689				
XON		2.8546	3.6667				
ROG		0.1960 2.8546 2.1485 0.0171 0.8531	0.2295 3.6667 2.6689 0.0224 1.1243				
	Category		Unmitigated				

4.2 Trip Summary Information

	Aver	Average Daily Trip Rate	ıte	Unmitigated	Mitigated
Land Use	Weekday	Saturday	Sunday	Annual VMT	Annual VMT
Parking Lot	112.99	112.99	112.99	1,645,198	1,248,255
Unrefrigerated Warehouse-No Rail	251.70	251.70	251.70	1,078,696	
Total	364.69	364.69	364.69	2,723,895	2,066,689

4.3 Trip Type Information

		Miles			Trip %			Trip Purpose %	% ә
Land Use	H-W or C-W	H-S or C-C	H-W or C-W H-S or C-C H-O or C-NW H-W or C-W H-S or C-C H-O or C-NW	H-W or C-W	H-S or C-C	H-O or C-NW	Primary	Diverted	Pass-by
Parking Lot	16.60	40.00	9.90	00.0	100.00		100	0	0
Unrefrigerated Warehouse-No 16.60 8.40	16.60	8.40	6.90	59.00	0.00	41.00	92	5	3

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

4.4 Fleet Mix

Land Use	PDA	LDT1	LDT2	MDV	LHD1	LHD2	MHD	HHD	OBUS	NBUS	MCY	SBUS	MH
Parking Lot	0.000000	0.00000.0	0.000000 0.000000 0.000000 0.0000000	0.000000	0.00000.0	0.221000	0.221000 0.177000 0.602000 0.000000 0.000000 0.000000	0.602000	0.00000.0	0.00000.0	0.00000.0	0.00000	0.000000
Unrefrigerated Warehouse-No 0.579000 0.059000 0.185000 0.1500 Rail	0.579000	0.059000	0.185000	0.579000 0.059000 0.185000 0.150000 0.000000	0.000000	000 0.000000 0.000000 0.000000 0.000000 0.000000	0.000000 0.000000 0.000000 0.000000 0.000000	0.000000	0.000000	0.000000	0.027000	0.000000	0.000000

5.0 Energy Detail

Historical Energy Use: N

5.1 Mitigation Measures Energy

CO2e		121.6890	121.6890	27.9977	27.9977	
NZO		1.2400e- 121.6890 003	1.2400e- 003	. 5.1000e- 2 004	5.1000e- 2 004	
CH4	MT/yr	0.0102	0.0102	5.3000e- 004	5.3000e- 004	
Total CO2		121.0645	121.0645	27.8323	27.8323	
Bio- CO2 NBio- CO2 Total CO2		0.0000 121.0645 121.0645 0.0102	121.0645 121.0645	27.8323	27.8323	
Bio- CO2		0.000.0	0.000.0	0.000.0	0.000.0	
PM2.5 Total		0.0000 0.00000	0.0000	1.9400e- 003	1.9400e- 003	
Exhaust PM2.5	γλι	0.0000	0.0000		1.9400e- 003	
Fugitive PM2.5				 		} ! ! ! !
PM10 Total		0.000.0	0.0000	1.9400e- 003	٠,	
Exhaust PM10		0.0000 0.0000	0.0000	Ι,	1.9400e- 1 003	
Fugitive PM10	tons/yr		 	 		
SO2			 	1.5000e- 004	1.5000e- 004	
00				0.0215 1.5000e- 004	0.0215	
×ON				0.0256	0.0256	
ROG				2.8100e- 003	2.8100e- 003	
	Category	Electricity Mitigated	Electricity Unmitigated	NaturalGas 2.8100e 0.0256 0. Mitigated 003	NaturalGas Unmitigated	

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

5.2 Energy by Land Use - NaturalGas

Unmitigated

				_					
CO2e		0.0000	27.9977	27.9977					
NZO		0.0000	5.1000e- 2. 004	5.1000e- 004					
CH4	MT/yr	0.0000	23 5.3000e- (004	3 5.3000e- 004					
Total CO2	MT	0.0000	27.8323	27.8323					
Bio- CO2 NBio- CO2 Total CO2		0.0000 0.0000 0.0000	27.8323	27.8323					
Bio- CO2		0.000.0	0.0000	0.0000					
PM2.5 Total		0.0000	1.9400e- 003	1.9400e- 003					
Exhaust PM2.5							0.0000	1.9400e- 003	1.9400e- 003
Fugitive PM2.5									
PM10 Total		0.0000	1.9400e- 003	1.9400e- 003					
Exhaust PM10	tons/yr	ns/yr	0.0000	1.9400e- 003	1.9400e- 003				
Fugitive PM10									
805		0.0000	1.5000e- 004	1.5000e- 004					
00		0.0000	0.0215	0.0215					
NOx		0.0000	0.0256	0.0256					
ROG		0.0000 0.0000 0.0000	7 2.8100e- 0. 003	2.8100e- 003					
NaturalGa s Use	kBTU/yr	0	521557						
	Land Use	Parking Lot	Unrefrigerated Warehouse-No Rail	Total					

Mitigated

C02e		0.0000	27.9977	27.9977			
N2O		0.0000 0.0000 0.0000 0.0000 0.0000	- 5.1000e- 27 004	5.1000e- 27 004			
CH4	/yr	0.0000	23 5.3000e- 5 004	5.3000e- 004			
Total CO2	MT/yr	0.000.0	27.83	27.8323			
Bio- CO2 NBio- CO2 Total CO2		0.000.0	27.8323	27.8323			
Bio- CO2		0.000.0	0.000.0	0.0000			
PM2.5 Total	tons/yr	0.0000	1.9400e- 003	1.9400e- 003			
Exhaust PM2.5					0.0000	1.9400e- 003	1.9400e- 003
Fugitive PM2.5							
PM10 Total		0.000.0	1.9400e- 003	1.9400e- 003			
Exhaust PM10		ns/yr	0.000.0	1.9400e- 003	1.9400e- 003		
Fugitive PM10							
SO2		0.0000	1.5000e- 004	1.5000e- 004			
00		0.0000	0.0215	0.0215			
NOx			0.000.0	0.0256	0.0256		
ROG		0.0000	2.8100e- 0. 003	2.8100e- 003			
NaturalGa s Use	kBTU/yr	0	521557				
	Land Use	Parking Lot	Unrefrigerated Warehouse-No Rail	Total			

CalEEMod Version: CalEEMod.2020.4.0

Page 27 of 34

Date: 2/6/2022 6:44 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

5.3 Energy by Land Use - Electricity

Unmitigated

CO2e		14.3769	107.3121	121.6890
N20	MT/yr	1.5000e- 004	1.0900e- 003	1.2400e- 003
CH4	M	1.2100e- 003	9.0100e- 003	0.0102
Electricity Total CO2 Use		80651.3 1 14.3032	106.7613	121.0645
Electricity Use	kWh/yr	80651.3	601996	
	Land Use	Parking Lot	Unrefrigerated Warehouse-No Rail	Total

Mitigated

			. ,	
9700	kWh/yr	14.3769	107.3121	121.6890
NZO		1.5000e- 14.3769 004	1.0900e- 003	1.2400e- 003
5 4		1.2100e- 003	9.0100e- 003	121.0645 0.0102
Use I otal COZ		80651.3 1 14.3032 1.2100e-	106.7613	121.0645
Electricity Use		80651.3	601996	
	Land Use	Parking Lot	Unrefrigerated Warehouse-No Rail	Total

Land Use	Use	Use Use KWhýr	2	MT/yr	
Parking Lot	80651.3	80651.3 1 14.3032	1.2100e- 003	1.5000e- 004	14.376
Unrefrigerated Warehouse-No Rail	601996	106.7613	9.0100e- 003	1.0900e- 003	107.31;
Total		121.0645	0.0102	1.2400e- 003	121.68

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

6.1 Mitigation Measures Area

CO2e		. 0.0000 7.0000e-	7.0000e- 003
N20		0.000.0	0.0000
CH4		2.0000e- 005	2.0000e- 005
Bio- CO2 NBio- CO2 Total CO2	MT/yr	0.0000 6.5700e- 6.5700e- 2.0000e- 003 003 005	6.5700e- 2.0000e- 003 005
NBio- CO2		6.5700e- 003	0.0000 6.5700e- 6.
Bio- CO2		0.0000	0.0000
PM2.5 Total		1.0000e- 1.0000e- 005 005)e- 1.0000e- (
Exhaust PM2.5		1.0000e- 005	1.0000e- 005
Fugitive PM2.5			
PM10 Total		le- 1.0000e- 005	1.0000e- 005
Exhaust PM10	tons/yr	1.0000e- 1.0 005 (1.0000e- 1.0 005
Fugitive PM10	ton		
S02		0.0000	0.0000
00		3.3800e- 003	3.3800e- 003
×ON		1.0763 3.0000e- 3.3800e- 0.0000 005 003	1.0763 3.0000e- 3.3800e- 0.0000 005 003
ROG		1.0763	1.0763
	Category	Mitigated	Unmitigated

6.2 Area by SubCategory

Unmitigated

		_		4	۸.		
CO2e	MT/yr	0.0000	0.0000	7.0000e- 003	7.0000e- 003		
N20		0.0000	0.0000	0.0000	0.000		
CH4		MT/yr	MT/yr	0.000.0	0.000.0	2.0000e- 005	2.0000e- 005
Total CO2				M	M	0.0000	0.0000
NBio- CO2 Total CO2		0.0000 0.0000 0.0000 0.0000	0.0000	6.5700e- 003	6.5700e- 003		
Bio- CO2		0.0000	0.0000	0.0000	0.0000		
PM2.5 Total		0.0000 0.0000	0.0000	1.0000e- 005	1.0000e- 005		
Exhaust PM2.5	lyr		0.0000	0.0000	1.0000e- 005	1.0000e- 005	
Fugitive PM2.5							
PM10 Total		0.0000	0.0000	1.0000e- 005	1.0000e- 005		
Exhaust PM10		0.0000	0.0000	1.0000e- 005	1.0000e- 005		
Fugitive PM10	tons/yr						
S02				0.0000	0.000.0		
00				3.3800e- 003	3.3800e- 003		
×ON				3.0000e- 3.3800e- 005 003	1.0763 3.0000e- 3.3800e- 005 003		
ROG		0.1234	0.9525	3.1000e- 004	1.0763		
	SubCategory	Architectural Coating	Consumer Products	Landscaping	Total		

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

6.2 Area by SubCategory

Mitigated

CO2e		0.0000	0.0000	7.0000e- 003	7.0000e- 003	
NZO			0.0000	0.0000	0.000	
CH4	/yr	0.000 0.0000 0.0000	0.0000	2.0000e- (005	2.0000e- 005	
Total CO2	MT/yr	0.0000	0.0000	6.5700e 003	6.5700e- 003	
Bio- CO2 NBio- CO2 Total CO2		0.0000 0.0000	0.0000	6.5700e- 003	6.5700e- 003	
Bio- CO2		0.000.0	0.0000	0.0000	0.000.0	
PM2.5 Total		0.000.0	0.0000	1.0000e- 005	1.0000e- 005	
Exhaust PM2.5		0.0000	0.0000	1.0000e- 005	1.0000e- 005	
Fugitive PM2.5						
PM10 Total		0.0000	0.0000	1.0000e- 005	1.0000e- 005	
Exhaust PM10	/yr	ons/yr	0.0000	0.0000	1.0000e- 005	1.0000e- 005
Fugitive PM10	ton					
805				0.0000	0.000.0	
00				3.3800e- 003	3.3800e- 003	
XON			 	3.1000e- 3.0000e- 3.3800e- 004 005 003	3.0000e- 005 003	
ROG		0.1234	0.9525	3.1000e- 004	1.0763	
	SubCategory	Architectural Coating	Consumer Products	Landscaping	Total	

7.0 Water Detail

7.1 Mitigation Measures Water

Install Low Flow Bathroom Faucet

Install Low Flow Kitchen Faucet

Install Low Flow Toilet

Use Water Efficient Irrigation System

Page 30 of 34

Date: 2/6/2022 6:44 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

CO2e		186.4860	220.9549
N2O	/yr	0.0402	0.0476
CH4	MT/yr	1.6601	1.9670
Total CO2		133.0150 1.6601	157.6007
	Category	ō	Unmitigated

7.2 Water by Land Use

Unmitigated

C02e		0.0000	220.9549	220.9549
N2O	MT/yr	0.0000	0.0476	0.0476
CH4		0.0000	1.9670	1.9670
Indoor/Out Total CO2 door Use		0.0000	157.6007	157.6007
Indoor/Out door Use	Mgal	0/0	60.0048 / 0	
	Land Use	Parking Lot	Unrefrigerated Warehouse-No Rail	Total

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

7.2 Water by Land Use

Mitigated

				0
CO2e		0.0000 0.0000	186.4860	186.4860
NZO	MT/yr	0.0000	0.0402	0.0402
CH4	M	0.0000	1.6601	1.6601
Total CO2		0.0000	133.0150	133.0150
Indoor/Out Total CO2 door Use	Mgal	0/0	50.644 / 0 133.0150	
	Land Use	Parking Lot	Unrefrigerated Warehouse-No Rail	Total

8.0 Waste Detail

8.1 Mitigation Measures Waste

Institute Recycling and Composting Services

Page 32 of 34

Date: 2/6/2022 6:44 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Category/Year

CO2e		61.3314	122.6627
N2O	MT/yr	0.0000	0.0000
CH4	MT	_	2.9261
Total CO2		24.7558	49.5115
			Unmitigated

8.2 Waste by Land Use

Unmitigated

122.6627	0.0000	2.9261	49.5115		Total
122.6627	0.0000	2.9261	49.5115	243.91	Unrefrigerated Warehouse-No Rail
0.0000	0.0000	0.0000	0.0000	0	Parking Lot
	MT/yr	MT		tons	Land Use
CO2e	N2O	CH4	Total CO2	Waste Disposed	

Page 33 of 34

Date: 2/6/2022 6:44 PM

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

8.2 Waste by Land Use

Mitigated

CO2e		0.0000	61.3314	61.3314
NZO	MT/yr	0.0000	0.0000	0.0000
CH4	MT	0.0000	1.4630	1.4630
Total CO2		0.000.0	24.7558	24.7558
Waste Disposed	tons	0	121.955	
	Land Use	Parking Lot	Unrefrigerated Warehouse-No Rail	Total

9.0 Operational Offroad

Equipment Type	Number	Hours/Day	Days/Year	Horse Power	Load Factor	Fuel Type
orklifts	4	7.00	260	68	0.20	0.20 CNG

Slover-Alder Avenue Industrial - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

UnMitigated/Mitigated

ROG	XON	00	S02	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2 Total CO2	Total CO2	CH4	NZO	C02e
				tons	ıs/yr							MT/yr	yr		
	0.3228	6.6200e- 0.3228 4.2173 7.0000e- 003 004	7.0000e- 004		5.2100e- 5.2100e- 003 003	5.2100e- 003		5.2100e- 5.2100e- 003 003	5.2100e- 003	0.0000	0.0000 79.8153 79.8153 0.0258 0.0000 80.4607	79.8153	0.0258	0.0000	80.4607
	0.3228	6.6200e- 0.3228 4.2173 7.0000e- 003 004	7.0000e- 004		5.2100e- 003 5.2100e-	5.2100e- 003		5.2100e- 003	5.2100e- 003	0.0000	79.8153	79.8153	0.0258	0.0000	80.4607

10.0 Stationary Equipment

Fire Pumps and Emergency Generators

add i add i	
בסמת ו מכנסו	
10000	
ווסמוס/ ו פמו	
i louis/Day	
Equipment Type	Boilers

Fuel Type

Boiler Rating

Heat Input/Year

Heat Input/Day

Number

Equipment Type

User Defined Equipment

umber
Nun
уре
Equipment Type

11.0 Vegetation