

TRAFFIC IMPACT STUDY

LOS ANGELES

201 S. Figueroa St, Suite 240
Los Angeles, CA 90012
213.337.3680

ONTARIO

4141 E. Inland Empire Blvd, Suite 250
Ontario, CA 91764
909.481.5750

SAN DIEGO

600 B St, Suite 1600
San Diego, CA 92101
619.400.0600

SANTA CLARITA

25152 Springfield Ct, Suite 350
Santa Clarita, CA 91355
661.284.7400

TEMECULA

41951 Remington Ave, Suite 220
Temecula, CA 92590
951.294.9300

TUSTIN

17782 17th St, Suite 200
Tustin, CA 92780
714.665.4500

VICTORVILLE

14297 Cajon Ave, Suite 101
Victorville, CA 92395
760.524.9100

www.deainc

DEEP CREEK ROAD GAS STATION

UNINCORPORATED AREA OF APPLE VALLEY, CALIFORNIA

Prepared by:



DAVID EVANS
AND ASSOCIATES INC.

FINAL REPORT
May 22, 2019



May 22, 2019

Job No. MMAI0000-1001

Mr. Mark Maida
Deep Creek Road Gas Station
13302 Ranchero Road
Oak Hills, CA 92344

**RE: FINAL TRAFFIC IMPACT ANALYSIS – DEEP CREEK ROAD GAS STATION –
UNINCORPORATED AREA OF APPLE VALLEY, CALIFORNIA**

Dear Mr. Maida:

David Evans and Associates, Inc. is pleased to submit this Final Traffic Impact Analysis report for the proposed Deep Creek Road Gas Station development project in the unincorporated area of Apple Valley, California.

The report evaluates potential project-specific traffic impacts and recommends traffic improvements if any impacts are determined to be significant. The report also evaluates the impacts of overall growth in development to determine if the proposed project, cumulatively with other development, contributes to significant impacts. The report has been prepared in coordination with the San Bernardino County Engineering Department who approved the scope of work prior to preparation of this report. The analysis and methods employed in the report comply with California Environmental Quality Act (CEQA) requirements.

We are pleased to have been of assistance to you in processing and obtaining approval for the project. If you have any questions or comments, please feel free to contact me at 760-524-9115.

Respectfully submitted,

David Evans and Associates, Inc.


Robert A. Kilpatrick, P.E., T.E.
Senior Project Manager / Senior Associate





TABLE OF CONTENTS

1 INTRODUCTION	4
2 EXISTING CONDITIONS	7
Local and Major Roadways	7
Existing Traffic Volumes	7
Capacity Analysis Methodologies	7
Existing Traffic Analysis	9
3 BACKGROUND TRAFFIC CONDITIONS – YEAR 2019	12
Area Growth	12
Background Traffic Analysis	12
4 PROJECT CONDITIONS	14
Project Trip Generation	14
Project Trip Distribution and Assignment	14
Project Traffic Analysis	19
5 FUTURE YEAR 2040 CONDITIONS	22
Future Year 2040 Traffic Analysis	22
Future Year 2040 Plus Project Traffic Analysis	22
6 PROJECT MITIGATION AND SUMMARY	25
Project Specific Mitigations	25
7 APPENDICES	26

LIST OF FIGURES

Figure 1: Vicinity Map	5
Figure 2: Site Plan	6
Figure 3: Existing Traffic Volumes	10
Figure 4: Existing Geometrics	11
Figure 5: Background Traffic Volumes	13
Figure 6: Primary Project Trip Distribution	15
Figure 7: Primary Project Trips	16
Figure 8: Pass-by Project Trips	17
Figure 9: Total Project Trips	18
Figure 10: Project Traffic Volumes	20
Figure 11: Project Geometrics	21
Figure 12: Future Year 2040 Traffic Volumes	23
Figure 13: Future Year 2040 plus Project Traffic Volumes	24



LIST OF TABLES

Table 2-1: HCM 6 – LOS Criteria for Signalized Intersections	8
Table 2-2: HCM 6 – LOS Criteria for TWSC	8
Table 2-3: HCM 6 – LOS Criteria for AWSC	8
Table 2-4: Intersection Capacity Analysis – Existing Conditions	9
Table 3-1: Intersection Capacity Analysis – Background Conditions	12
Table 4-1: Estimated Project Trip Generation	14
Table 4-2: Intersection Capacity Analysis – Project Conditions	19
Table 5-1: Intersection Capacity Analysis – Future Year 2040 Conditions	22
Table 5-2: Intersection Capacity Analysis – Future Year 2040 plus Project Conditions	22

LIST OF APPENDICES

- Appendix A: SBTAM Plots
- Appendix B: Intersection Capacity Analysis Calculations

1 INTRODUCTION

This report identifies the traffic impacts and presents recommendations for access and traffic mitigation for the proposed Deep Creek Road Gas Station located on the southwest corner of Rock Springs Road and Deep Creek Road. The project, identified as Deep Creek Road Gas Station, consists of a Gas Station with twelve pumps and Convenience Store in the unincorporated area of Apple Valley, California. The site is accessed from a driveway along Rock Springs Road and another driveway along Deep Creek Road. *Figure 1* illustrates the vicinity map, and *Figure 2* illustrates the proposed project site plan.

The intent of this Traffic Impact Analysis (TIA) report is to identify and recommend mitigation for significant impacts caused by, or contributed to, by the proposed project under the following study scenarios:

- Existing Conditions
- Background (Cumulative) Conditions
- Project Conditions
- Future Year 2040 Conditions
- Future Year 2040 Plus Project Conditions

The Existing Condition analysis is based on traffic counts collected in February 2018 and reflects the current conditions in the study area.

The Background (Cumulative) Condition addresses impacts due to ambient growth in traffic up to the project buildout year of 2019 within the study area. Ambient growth is estimated at two percent of the existing traffic volumes annually.



The Project Condition analyzes the effects of project traffic added to the Background (Cumulative) Condition. This analysis identifies impacts that the proposed project contributes to, along with other cumulative development, and may be required to fund its fair share of the necessary mitigations.

The Future Year 2040 Conditions addresses impacts due to growth of the surrounding regional area up to the year 2040. The growth in traffic reflecting the year 2040 was derived from the San Bernardino County Transportation Authority (SBCTA) traffic forecast model.

The Future Year 2040 Plus Project Conditions addresses impacts due to growth of the surrounding regional area to the year 2040 plus the proposed project



FIGURE 1: VICINITY MAP
 DEEP CREEK GAS STATION
 APPLE VALLEY, CALIFORNIA



2 EXISTING CONDITIONS

Currently the project site is vacant and undeveloped land. The proposed project is bounded to the north by Rock Springs Road and BNSF Railroad right-of-way, to the east by Deep Creek Road and undeveloped land, to the south by residential housing, and to the west by undeveloped land.

Local and Major Roadways

Rock Springs Road is east-west primarily two-lane road (one in each direction, with turn pockets at key intersections). Rock Springs Road provides direct access to the project site. The road extends from the intersection with Main St/Arrowhead Lake Rd on the west to the intersection with Kiowa Rd on the east. The posted speed limit within the project area is 50 mph. The San Bernardino County Land Use Plan Circulation and Transportation General Plan dated March 13, 2012 identifies Rock Springs Road as a Major Highway.

Deep Creek Road is a local north-south roadway primarily two-lane (one in each direction). Deep Creek Road provides direct access to the project site. The road extends from the intersection with Bear Valley Road on the north to the intersection with Saddle Dike Embankment on the south. The San Bernardino County Land Use Plan Circulation and Transportation General Plan dated March 13, 2012 identifies Deep Creek Road as a Secondary Highway.

Primary access to the project is from one driveway along Rock Springs Road and one driveway along Deep Creek Road. The project would potentially impact the following one existing public street intersection and two future driveway intersections within the study area:

1. Rock Springs Road and Deep Creek Road
2. Rock Springs Road and Project Driveway "A" (future intersection)
3. Deep Creek Road and Project Driveway "B" (future intersection)

The intersection of Rock Springs Road and Deep Creek Road is signalized.

Existing Traffic Volumes

Figure 3 provides the existing intersection traffic volumes. Newport Traffic Studies (NTS) conducted AM (7:00-9:00 AM) and PM (4:00-6:00 PM) peak period turn movement counts in February 2018.

Capacity Analysis Methodologies

Intersection capacity analyses were conducted using Synchro software (1), which implements the methods of the Highway Capacity Manual, 6th Edition (HCM 6) used in this report. The intersection capacity analyses utilize existing intersection geometrics and existing and forecasted traffic volumes in analyzing AM and PM peak hour intersection operating conditions. The traffic analysis methodology concepts presented in Chapters 19, 20, and 21 of the Highway Capacity Manual (HCM 6) (2) were utilized to calculate intersection Level of Service (LOS) based on the average control delay (in seconds per vehicle) of vehicles utilizing intersections. *Table 2-1* provides the HCM 6 LOS thresholds for signalized intersections. *Table 2-2* provides the HCM 6 LOS thresholds for two way stop controlled (TWSC). *Table 2-3* for all way stop controlled (AWSC) intersections.

1 Trafficware Ltd, version 10.

2 Transportation Research Board, Washington D.C., 2010.

Signalized Intersections

The analysis determines a LOS that quantitatively describes the operating characteristics of signalized intersections. *Table 2-1* provides LOS thresholds for signalized intersections as provided in the HCM 6 Chapter 19.

Table 2-1: HCM 6 – LOS Criteria for Signalized Intersections

Control Delay (s/veh)	LOS by Volume-to-Capacity Ratio ^a	
	≤1.0	>1.0
≤ 10	A	F
> 10 - 20	B	F
> 20 - 35	C	F
> 35 - 55	D	F
> 55 - 80	E	F
> 80	F	F

Note: ^aFor approach-based and intersectionwide assessments, LOS is defined solely by control delay.
Source: Highway Capacity Manual 6th Edition, Exhibit 19-8.

Unsignalized Intersections

The LOS for a Two-Way-Stop-Controlled (TWSC) intersection is determined by the computed or measured control delay. The LOS is determined for each minor-street movement (or shared movement), as major-street left turns, by using the criteria provided in *Table 2-2* referenced from HCM 6 LOS thresholds for TWSC as provided in the HCM 6 Chapter 20.

Table 2-2: HCM 6 – LOS Criteria for TWSC

Control Delay (s/veh)	LOS by Volume-to-Capacity Ratio	
	v/c ≤1.0	v/c >1.0
0 - 10	A	F
> 10 -15	B	F
> 15 - 25	C	F
> 25 - 35	D	F
> 35 - 50	E	F
> 50	F	F

Note: The LOS criteria apply to each lane on a given approach and to each approach on the minor street. LOS is not calculated for major-street approaches or for the intersection as a whole.
Source: Highway Capacity Manual 6th Edition, Exhibit 20-2.

The analysis determines a LOS that quantitatively describes the operating characteristics of All-Way-Stop-Controlled (AWSC) intersections. *Table 2-3* provides LOS thresholds for AWSC intersections as provided in the HCM 6 Chapter 21.

Table 2-3: HCM 6 – LOS Criteria for AWSC

Control Delay (s/veh)	LOS by Volume-to-Capacity Ratio ^a	
	v/c ≤1.0	v/c >1.0
0 - 10	A	F
> 10 -15	B	F
> 15 - 25	C	F
> 25 - 35	D	F
> 35 - 50	E	F
> 50	F	F

Note: ^aFor approach-based and intersectionwide assessments, LOS is defined solely by control delay.
Source: Highway Capacity Manual 6th Edition, Exhibit 21-8.

Existing Traffic Analysis

The existing intersection capacity analysis uses existing intersection geometrics and existing AM and PM peak hour traffic counts to determine level of service. *Table 2-4* and *Appendix B* provide the results of the analysis. *Figure 4* illustrates the existing geometrics utilized in the capacity analysis.

Table 2-4: Intersection Capacity Analysis – Existing Conditions

Intersection	AM Peak Hour		PM Peak Hour	
	Delay(1)	LOS(2)	Delay(1)	LOS(2)
1 Rock Springs Road and Deep Creek Road	16.1	B	16.1	B



(1) Delay – In seconds per vehicle

(2) LOS – Level of Service

(3) Stop controlled intersection



Source: David Evans and Associates, Inc.

As presented in *Table 2-4*, under Existing Conditions, the study intersection operates at an acceptable LOS.



LEGEND

- XX/XX - AM/PM PROJECT TRIP
- ① - STUDY INTERSECTIONS
- SIGNALIZED INTERSECTION
- ◻ - STOP CONTROLLED APPROACH



1 ROCK SPRINGS RD/ DEEP CREEK RD	

LEGEND



- EXISTING GEOMETRICS



- STUDY INTERSECTIONS



- SIGNALIZED INTERSECTION



- STOP CONTROLLED APPROACH

3 BACKGROUND TRAFFIC CONDITIONS – YEAR 2019

The Background Conditions scenario evaluates impacts due to ambient growth in traffic within the study area up to the project opening year of 2019. Typically, ambient growth in traffic ranges from 1% to 2% annually— the ambient growth in traffic in this report uses a 2% annual rate of growth applied to existing traffic volumes.

Area Growth

To analyze the project impacts, the inclusion of traffic generated by other projects within the study area is necessary. The Other Area projects include approved projects that were recently constructed or to be constructed by project opening year of 2019.

Background Traffic Analysis

The Background Conditions intersection capacity analysis utilized existing intersection geometrics and the projected AM and PM peak hour traffic volumes shown in *Figure 5. Table 3-1* and *Appendix B* provides the results of the analysis.

Table 3-1: Intersection Capacity Analysis – Background Conditions

Intersection	AM Peak Hour		PM Peak Hour	
	Delay(1)	LOS(2)	Delay(1)	LOS(2)
1 Rock Springs Road and Deep Creek Road	16.8	B	16.7	B

(1) Delay – In seconds per vehicle

(2) LOS – Level of Service

(3) Stop controlled intersection

Source: David Evans and Associates, Inc.

As presented in *Table 3-1*, the study intersection under Background Conditions continues to operate at an acceptable LOS.

4 PROJECT CONDITIONS

The proposed project is anticipated to open in the year 2019. The estimated project trips are added to the Background Condition traffic volumes to represent Project Conditions.

Project Trip Generation

To identify potential traffic impacts, trip generation factors are applied to the proposed land uses to estimate project vehicle trips. Trip generation factors for the Super Convenience Market/Gas Station (ITE 960) were obtained from the Institute of Transportation Engineers (ITE) Trip Generation manual, 10th Edition.

Commuter oriented land uses such as gas stations attract trips (known as “pass-by” trips) from traffic passing the site on the way from an origin to an ultimate destination. The Gas Station with Convenience Market (ITE Land Use Category 945) pass-by trip factors were referenced in approximating the pass-by parameters utilized in this study. These pass-by trip factors were referenced for the Super Convenience Market/Gas Station (ITE 960), since such parameters are not available in the ITE Trip Generation Manual, 10th Edition.

Table 4-1 summarizes the estimated daily, AM peak hour, and PM peak hour trip generation for the project site.

Table 4-1: Estimated Project Trip Generation


Land Use	Daily	AM Peak Hour			PM Peak Hour		
		In	Out	Total	In	Out	Total
1 Super Convenience Market/Gas Station							
(ITE 960) Vehicle Fueling Positions	230.52	14.04	14.04	28.08	11.48	11.48	22.96
12 Gasoline Fueling Pump Position	2,766	169	169	338	138	138	276
Breakdown of Project Trips							
Pass-By Trips (AM = 62% / PM = 56%)	1,632	105	105	210	77	77	154
Primary Trips (AM = 38% / PM = 44%)	1,134	64	64	128	61	61	122

Source: “Trip Generation Manual, Institute of Transportation Engineers”, 10th Edition

As presented in *Table 4-1*, the total trips at the project driveways is estimated to be 338 and 276 trips in the AM and PM peak hours respectively. The majority of these trips are pass-by trips, trips that are already passing by the site on adjacent streets and that stop at the site as an interim stop between their origin and primary destination. The project would generate 128 primary trips during the AM peak and 122 primary trips during the PM peak hours—primary trips are new trips added to the surrounding street network.



Project Trip Distribution and Assignment

The project trips are distributed by direction and assigned to the local network of streets. *Figure 6* illustrates the distribution of the primary project trips. *Figure 7*, *Figure 8* and *Figure 9* illustrate the primary, pass-by, and total project trips respectively.



LEGEND

- XX% — GENERAL PROJECT TRIP DISTRIBUTION
- XX% — SPECIFIC PROJECT TRIP PERCENTAGE
- # — STUDY INTERSECTIONS
- SIGNALIZED INTERSECTION
- STOP CONTROLLED APPROACH



① ROCK SPRINGS RD/ DEEP CREEK RD			
10/10	10/10	10/10	10/10
10/10	10/10		10/10

② ROCK SPRINGS RD/ DWY "A"			
		20/20	
25/25		25/25	20/20



③ DEEP CREEK RD/ DWY "B"			
20/20			
20/20	10/10		

PROJECT TRIPS

AM PEAK PERIOD - 64 IN / 64 OUT
PM PEAK PERIOD - 61 IN / 61 OUT

LEGEND

- XX/XX - AM/PM PROJECT TRIP
- ① - STUDY INTERSECTIONS
- SIGNALIZED INTERSECTION
- STOP CONTROLLED APPROACH



① ROCK SPRINGS RD/ DEEP CREEK RD	
-15/5 -15/5	-55/-5 55/5
-10/-40 -10/-20	65/10 10/40 10/20

② ROCK SPRINGS RD/ DWY "A"	
	-30/-10 30/10
-20/-65 20/65	30/10 10/10



③ DEEP CREEK RD/ DWY "B"	
65/10	
75/65	

PROJECT TRIPS

AM PEAK PERIOD - 105 IN / 105 OUT
PM PEAK PERIOD - 77 IN / 77 OUT

LEGEND

- XX/XX - AM/PM PROJECT TRIP
 ① - STUDY INTERSECTIONS
 - SIGNALIZED INTERSECTION
 - STOP CONTROLLED APPROACH



① ROCK SPRINGS RD/ DEEP CREEK RD	
-5/5 25/15	-45/5 65/15
0/-30 0/-10	65/10 20/50 20/30

② ROCK SPRINGS RD/ DWY "A"	
	-30/-10 50/30
-20/-65 45/90	55/35 30/30

③ DEEP CREEK RD/ DWY "B"	
85/30	
95/85 10/10	10/10

PROJECT TRIPS

AM PEAK PERIOD - 169 IN / 169 OUT
PM PEAK PERIOD - 138 IN / 138 OUT

LEGEND

- XX/XX - AM/PM PROJECT TRIP
 ① - STUDY INTERSECTIONS
 - SIGNALIZED INTERSECTION
 - STOP CONTROLLED APPROACH

Project Traffic Analysis

The intersection capacity analysis of Project Conditions utilized existing intersection geometrics and the AM and PM peak hour traffic volumes shown in *Figure 10*. *Figure 11* illustrates the project condition geometrics. *Table 4-2* and *Appendix B* provide the results of the analysis.

Table 4-2: Intersection Capacity Analysis – Project Conditions

Intersection		AM Peak Hour		PM Peak Hour	
		Delay(1)	LOS(2)	Delay(1)	LOS(2)
1	Rock Springs Road and Deep Creek Road	19.0	B	17.6	B
2	Rock Springs Road and Project Driveway "A" (3)	26.6	D	23.7	C
3	Deep Creek Road and Project Driveway "B" (3)	10.3	B	10.5	B



(1) Delay – In seconds per vehicle

(2) LOS – Level of Service

(3) Stop controlled intersection

Source: David Evans and Associates, Inc.

As presented in *Table 4-2*, all study intersections under Project Conditions would operate at an acceptable level of service.



- - EXISTING GEOMETRICS
- - PROPOSED GEOMETRICS
- - STUDY INTERSECTIONS
- - SIGNALIZED INTERSECTION
- - STOP CONTROLLED APPROACH



Drawing Name: P:\MIMA\I00001001\0400CAD\T\T\EXHIBITS\Traffic Study\Figure 11.dwg
Last Opened: May 20, 2019 - 12:43pm by: Tnm

5 FUTURE YEAR 2040 CONDITIONS

The Future Year 2040 Condition evaluates impacts of forecasted regional growth to the year 2040. Future year 2040 traffic projections were developed from the San Bernardino Transportation Analysis Model (SBTAM). Intersection turn movements were derived from existing traffic counts and the model's forecasted approach volumes for each study intersection (3). The SBTAM traffic model plots are provided in *Appendix A*.

Future Year 2040 Traffic Analysis

The intersection capacity analysis under Future Year 2040 Conditions utilizes existing intersection geometrics and the projected AM and PM peak hour traffic volumes shown in *Figure 12*. *Table 5-1* and *Appendix B* provide the results of the analysis.

Table 5-1: Intersection Capacity Analysis – Future Year 2040 Conditions

Intersection	AM Peak Hour		PM Peak Hour	
	Delay(1)	LOS(2)	Delay(1)	LOS(2)
1 Rock Springs Road and Deep Creek Road	16.7	B	24.9	C

(1) Delay – In seconds per vehicle

(2) LOS – Level of Service

(3) Stop controlled intersection

Source: David Evans and Associates, Inc.

As presented in *Table 5-1* under the Future Year 2040 Conditions without the project, the study intersection would operate at an acceptable level of service (LOS C or better).

Future Year 2040 Plus Project Traffic Analysis

The intersection capacity analysis under Future Year 2040 plus Project Conditions utilizes existing intersection geometrics and the projected AM and PM peak hour traffic volumes shown in *Figure 13*. *Table 5-2* and *Appendix B* provide the results of the analysis.

Table 5-2: Intersection Capacity Analysis – Future Year 2040 plus Project Conditions

Intersection	AM Peak Hour		PM Peak Hour	
	Delay(1)	LOS(2)	Delay(1)	LOS(2)
1 Rock Springs Road and Deep Creek Road	25.2	C	24.3	C
2 Rock Springs Road and Project Driveway "A" (3)	40.7	E	41.2	E
3 Deep Creek Road and Project Driveway "B" (3)	12.4	B	10.0	B

(1) Delay – In seconds per vehicle

(2) LOS – Level of Service

(3) Stop controlled intersection

Source: David Evans and Associates, Inc.

As presented in *Table 5-2* under Future Year 2040 plus Project Conditions, the public street intersection operates at an acceptable LOS C in the AM and PM peak hour. Project driveway "A" on Rock Springs Road operates at a LOS E in the AM and PM peak hours. This is an acceptable level of service for private driveways with the delay occurring on the driveway approach of the intersection.

3 Methodology from NCHRP Report 765: Analytical Travel Forecasting Approaches for Project-Level Planning and Design. National Cooperative Highway Research Program (NCHRP). Washington, D.C. 2014.

6 PROJECT MITIGATION AND SUMMARY

In summary, the project as presented will not cause significant impacts to the study intersections.

Project Specific Mitigations

In summary, the addition of traffic from the proposed project does not cause any of the public street study intersections to exceed the County of San Bernardino's level of service standard, individually or cumulatively, and therefore does not result in any significant traffic impacts requiring mitigation. The following are project-specific improvements to facilitate access to the site.

1. Construct frontage improvements (curb, gutter, and sidewalk) to County standards along Rock Springs Road and Deep Creek Road.
2. Construct a full access driveway on Rock Springs Road at the location identified as Project Driveway "A" on the site plan.
3. Construct a full access driveway on Deep Creek Road at the location identified as Project Driveway "B" on the site plan.

7 APPENDICES


Appendix A: SBTAM Plots

Appendix B: Intersection Capacity Analysis Calculations



Appendix A: SBTAM Plots

SBTAM 2040
Rock Springs Road and Deep Creek Road
AM Peak Period Flow



Map layers

Node

SBTAM 2040

Node selection sets

Centroids

Connectors

0


.33

.67

1

Miles

SBTAM 2040
Rock Springs Road and Deep Creek Road
PM Peak Period Flow



Map layers

Node

SBTAM 2040

Node selection sets


Centroids

Connectors

0 .33 .67 1

Miles

SBTAM 2040
Rock Springs Road and Deep Creek Road
Daily Traffic Flow





Appendix B: Intersection Capacity Analysis Calculations



DAVID EVANS
AND ASSOCIATES INC.

SUBJECT	BY	DATE	JOB NO.	SHEET OF
TURN MOVEMENTS	TNM	5-Mar-19	MMAI0000-1001	1 OF 2

E/W STREET : ROCKSPRINGS RD

N/S STREET : DEEP CREEK RD


CONDITION : AM PEAK HOUR

INTERSECTION : 1

PROJECTED GROWTH : 2%

PER YEAR :

CONDITION DIAGRAMS



EXISTING GEOMETRICS

TURN MOVEMENTS

Condition	Existing Condition Traffic	Ambient Growth	Background Condition Traffic	Project Trips	Project Condition Traffic	Future Year 2040 Condition Traffic	Future +Project Year 2040 Condition Traffic
Scenario #	1		3		5	7	9

ROCKSPRINGS RD

EB LEFT	120	5	125	0	125	130	130
EB THRU	245	5	250	0	250	300	300
EB RIGHT	15	5	20	0	20	40	40
WB LEFT	10	5	15	65	80	10	75
WB THRU	325	10	335	-45	290	360	315
WB RIGHT	20	5	25	0	25	10	10

DEEP CREEK RD

NB LEFT	20	5	25	65	90	140	205
NB THRU	25	5	30	20	50	60	80
NB RIGHT	15	5	20	20	40	40	60
SB LEFT	15	5	20	0	20	10	10
SB THRU	15	5	20	25	45	10	35
SB RIGHT	180	5	185	-5	180	150	145
TOTALS	1005	65	1070	145	1215	1260	1405

Los Angeles Office: 213.785.7887 ~ Ontario Office: 909.481.5750 ~ San Diego Office: 619.400.0600

Santa Barbara Office: 805.962.8590 ~ Santa Clarita Office: 661.284.7400 ~ Temecula Office: 951.294.9300

Tustin Office: 714.665.4500 ~ Victorville Office: 760.524.9100



DAVID EVANS
AND ASSOCIATES INC.

SUBJECT	BY	DATE	JOB NO.	SHEET OF
TURN VOLUME SUMMARY	TNM	5-Mar-19	MMAI0000-1001	2 OF 2

E/W STREET : ROCKSPRINGS RD

N/S STREET : DEEP CREEK RD

CONDITION : AM PEAK HOUR

PHF : 0.88

NORTH LEG								
LARGE 2 AXLE			LARGE 3 AXLE			LARGE 4(+) AXLE		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	0	0	0	0	0	1	0	0
0	2	0	1	0	0	0	0	0
1	0	0	1	0	1	2	0	0
0	0	0	1	2	0	0	0	0

SOUTH LEG								
LARGE 2 AXLE			LARGE 3 AXLE			LARGE 4(+) AXLE		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
1	0	0	0	0	0	0	0	0
1	1	1	0	1	0	0	0	0
2	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	0	0

EAST LEG								
LARGE 2 AXLE			LARGE 3 AXLE			LARGE 4(+) AXLE		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
1	0	1	0	1	0	0	1	0
0	0	0	0	2	0	0	0	0
0	3	0	0	0	0	0	1	0
0	0	0	0	0	0	0	0	0

WEST LEG								
LARGE 2 AXLE			LARGE 3 AXLE			LARGE 4(+) AXLE		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	0	0	0	0	1	0	2	0
0	0	0	0	0	0	0	0	0
0	1	1	0	0	1	0	0	0
0	0	0	1	0	0	1	2	0

NORTH LEG			SOUTH LEG			EAST LEG			WEST LEG		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
33	1	0	4	4	3	4	77	0	0	55	24
46	6	2	2	6	8	5	75	2	3	71	36
45	2	4	3	6	4	5	88	3	1	75	27
46	2	5	1	2	3	4	73	1	6	39	29

TRUCK TOTAL	AUTO VOLUMES	TOTALS	ROUNDED TOTALS	TRUCK PERCENTAGE
-------------	--------------	--------	----------------	------------------

ROCKSPRINGS RD

EB LEFT	3	116	119	120	5%
EB THRU	5	240	245	245	5%
EB RIGHT	2	10	12	15	15%
WB LEFT	1	6	7	10	15%
WB THRU	8	313	321	325	5%
WB RIGHT	1	18	19	20	5%

DEEP CREEK RD

NB LEFT	1	18	19	20	5%
NB THRU	3	18	21	25	15%
NB RIGHT	4	10	14	15	30%
SB LEFT	1	11	12	15	10%
SB THRU	4	11	15	15	25%
SB RIGHT	7	170	177	180	5%

INTERSECTION TURN COUNT

PEAK HOUR

NORTH-SOUTH STREET: DEEP CREEK
EAST-WEST STREET: ROCK SPRINGS
JURISDICTION: APPLE VALLEY

DATE: 02-20-18

PEAK HOUR: 07:15AM

NORTH LEG

TOTAL: 204

177	15	12
34	1	0
47	8	2
49	2	5
47	4	5

Total

1st

2nd

3rd

4th

Rt Thru Lt

EAST LEG TOTAL: 347

Rt	5	5	5	4	19
Thru	79	77	92	73	321
Lt	1	2	3	1	7

1st 2nd 3rd 4th Total

Total 1st 2nd 3rd 4th

119	25	36	29	29
245	57	71	76	41
12	0	3	1	8

Lt

Thru

Rt

WEST LEG TOTAL: 376

PEAK HOUR FACTORS

NORTH LEG = 0.89

SOUTH LEG = 0.68

EAST LEG = 0.87

WEST LEG = 0.85

ALL LEGS = 0.88

	Lt	Thru	Rt
1st	3	4	5
2nd	9	8	3
3rd	4	7	5
4th	3	2	1
Total	19	21	14

TOTAL: 54

SOUTH LEG

HOOR TOTAL: 981

Prepared by NEWPORT TRAFFIC STUDIES

SANBAG CLASSIFICATION SUMMARY
NORTH-SOUTH STREET : DEEP CREEK
EAST-WEST STREET : ROCK SPRINGS
BEGINNING TIME : 07:00AM

APPLE VALLEY
02-20-18

AUTOS			LARGE 2 AXLE			3 AXLE			4(+) AXLE			TOTALS
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT	RT	THRU	LT	
NORTH LEG												
29	3	0	0	0	0	0	0	0	0	0	0	32
33	1	0	0	0	0	0	0	0	1	0	0	35
46	6	2	0	2	0	1	0	0	0	0	0	57
45	2	4	1	0	0	1	0	1	2	0	0	56
46	2	5	0	0	0	1	2	0	0	0	0	56
33	3	3	0	0	1	0	0	0	1	1	0	42
34	3	1	0	0	0	1	0	0	0	0	0	39
30	2	4	2	0	0	0	0	0	1	1	0	40
296	22	19	3	2	1	4	2	1	5	2	0	357
SOUTH LEG												
2	3	2	0	1	0	0	1	0	0	0	0	9
4	4	3	1	0	0	0	0	0	0	0	0	12
2	6	8	1	1	1	0	1	0	0	0	0	20
3	6	4	2	0	0	0	0	0	0	1	0	16
1	2	3	0	0	0	0	0	0	0	0	0	6
2	2	5	0	0	0	0	0	0	0	0	0	9
2	3	4	0	0	0	0	0	0	0	2	0	11
2	5	5	0	0	1	0	0	0	0	1	0	14
18	31	34	4	2	2	0	2	0	0	4	0	97
EAST LEG												
7	69	1	0	2	0	0	0	0	0	0	0	79
4	77	0	1	0	1	0	1	0	0	1	0	85
5	75	2	0	0	0	0	2	0	0	0	0	84
5	88	3	0	3	0	0	0	0	0	1	0	100
4	73	1	0	0	0	0	0	0	0	0	0	78
3	67	4	0	1	0	0	2	0	0	0	0	77
2	73	2	0	2	0	0	1	0	0	1	0	81
2	82	0	0	1	0	0	0	0	0	0	0	85
32	604	13	1	9	1	0	6	0	0	3	0	669
WEST LEG												
1	48	20	0	0	0	0	0	0	0	0	0	69
0	55	24	0	0	0	0	0	1	0	2	0	82
3	71	36	0	0	0	0	0	0	0	0	0	110
1	75	27	0	1	1	0	0	1	0	0	0	106
6	39	29	0	0	0	1	0	0	1	2	0	78
4	35	32	0	0	0	1	0	0	0	0	0	72
3	40	28	0	1	1	0	0	0	0	1	1	75
0	51	24	0	1	0	0	1	2	0	0	0	79
18	414	220	0	3	2	2	1	4	1	5	1	671

INTERSECTION TURNING COUNT

NORTH-SOUTH STREET: DEEP CREEK

EAST-WEST STREET: ROCK SPRINGS

TIME: 07:00AM-08:00AM

DATE: 02-20-18

NORTH LEG

159	14	7	Total
29	3	0	1st
34	1	0	2nd
47	8	2	3rd
49	2	5	4th
Rt	Thru	Lt	

Total 1st 2nd 3rd 4th

110	20	25	36	29	Lt
252	48	57	71	76	Thru
5	1	0	3	1	Rt

Rt	7	5	5	5	22
Thru	71	79	77	92	319
Lt	1	1	2	3	7
	1st	2nd	3rd	4th	Total

Lt Thru Rt

1st	2	5	2
2nd	3	4	5
3rd	9	8	3
4th	4	7	5
Total	18	24	15

Prepared by NEWPORT TRAFFIC STUDIES

INTERSECTION TURNING COUNT

NORTH-SOUTH STREET: DEEP CREEK

EAST-WEST STREET: ROCK SPRINGS

TIME: 08:00AM-09:00AM

DATE: 02-20-18

NORTH LEG

149	14	14	Total
47	4	5	1st
34	4	4	2nd
35	3	1	3rd
33	3	4	4th
Rt	Thru	Lt	

Total 1st 2nd 3rd 4th

117	29	32	30	26
171	41	35	42	53
16	8	5	3	0

Lt

Thru

Rt

Rt	4	3	2	2	11
Thru	73	70	77	83	303
Lt	1	4	2	0	7
	1st	2nd	3rd	4th	Total

Lt Thru Rt

1st	3	2	1
2nd	5	2	2
3rd	4	5	2
4th	6	6	2
Total	18	15	7

Prepared by NEWPORT TRAFFIC STUDIES

HCM 6th Signalized Intersection Summary

1: Deep Creek Rd & Rocksprings Rd

Synchro 10 Report

03/05/2019

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	120	245	15	10	325	20	20	25	15	15	15	180
Future Volume (veh/h)	120	245	15	10	325	20	20	25	15	15	15	180
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1826	1826	1826	1678	1826	1826	1678	1678	1678	1530	1530	1530
Adj Flow Rate, veh/h	136	278	17	11	369	23	23	28	17	17	17	205
Peak Hour Factor	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
Percent Heavy Veh, %	5	5	5	15	5	5	15	15	15	25	25	25
Cap, veh/h	173	661	40	18	510	32	194	190	88	106	32	253
Arrive On Green	0.10	0.39	0.39	0.01	0.30	0.30	0.23	0.23	0.23	0.23	0.23	0.23
Sat Flow, veh/h	1739	1703	104	1598	1701	106	329	842	390	44	142	1124
Grp Volume(v), veh/h	136	0	295	11	0	392	68	0	0	239	0	0
Grp Sat Flow(s),veh/h/ln	1739	0	1807	1598	0	1807	1560	0	0	1311	0	0
Q Serve(g_s), s	3.1	0.0	4.8	0.3	0.0	7.8	0.0	0.0	0.0	2.2	0.0	0.0
Cycle Q Clear(g_c), s	3.1	0.0	4.8	0.3	0.0	7.8	1.4	0.0	0.0	6.9	0.0	0.0
Prop In Lane	1.00		0.06	1.00		0.06	0.34		0.25	0.07		0.86
Lane Grp Cap(c), veh/h	173	0	701	18	0	542	472	0	0	391	0	0
V/C Ratio(X)	0.79	0.00	0.42	0.60	0.00	0.72	0.14	0.00	0.00	0.61	0.00	0.00
Avail Cap(c_a), veh/h	304	0	995	160	0	859	472	0	0	391	0	0
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	0.00	1.00	0.00	0.00
Uniform Delay (d), s/veh	17.6	0.0	8.9	19.7	0.0	12.5	12.5	0.0	0.0	14.7	0.0	0.0
Incr Delay (d2), s/veh	7.6	0.0	0.4	27.4	0.0	1.8	0.6	0.0	0.0	6.9	0.0	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	1.3	0.0	1.3	0.2	0.0	2.5	0.4	0.0	0.0	2.1	0.0	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	25.2	0.0	9.3	47.0	0.0	14.4	13.2	0.0	0.0	21.6	0.0	0.0
LnGrp LOS	C	A	A	D	A	B	B	A	A	C	A	A
Approach Vol, veh/h	431			403			68			239		
Approach Delay, s/veh	14.3			15.2			13.2			21.6		
Approach LOS	B			B			B			C		
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	5.5	20.5		14.0	9.0	17.0		14.0				
Change Period (Y+Rc), s	5.0	5.0		5.0	5.0	5.0		5.0				
Max Green Setting (Gmax), s	4.0	22.0		9.0	7.0	19.0		9.0				
Max Q Clear Time (g_c+I1), s	2.3	6.8		8.9	5.1	9.8		3.4				
Green Ext Time (p_c), s	0.0	1.4		0.0	0.1	1.5		0.1				

Intersection Summary

HCM 6th Ctrl Delay **16.1**
 HCM 6th LOS **B**

HCM 6th Signalized Intersection Summary

1: Deep Creek Rd & Rocksprings Rd

Synchro 10 Report

03/05/2019

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	125	250	20	15	335	25	25	30	20	20	20	185
Future Volume (veh/h)	125	250	20	15	335	25	25	30	20	20	20	185
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1826	1826	1826	1678	1826	1826	1678	1678	1678	1530	1530	1530
Adj Flow Rate, veh/h	142	284	23	17	381	28	28	34	23	23	23	210
Peak Hour Factor	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
Percent Heavy Veh, %	5	5	5	15	5	5	15	15	15	25	25	25
Cap, veh/h	181	642	52	27	502	37	190	184	94	111	39	241
Arrive On Green	0.10	0.39	0.39	0.02	0.30	0.30	0.22	0.22	0.22	0.22	0.22	0.22
Sat Flow, veh/h	1739	1667	135	1598	1680	123	314	822	422	61	174	1076
Grp Volume(v), veh/h	142	0	307	17	0	409	85	0	0	256	0	0
Grp Sat Flow(s),veh/h/ln	1739	0	1802	1598	0	1804	1558	0	0	1312	0	0
Q Serve(g_s), s	3.2	0.0	5.1	0.4	0.0	8.3	0.0	0.0	0.0	3.3	0.0	0.0
Cycle Q Clear(g_c), s	3.2	0.0	5.1	0.4	0.0	8.3	1.7	0.0	0.0	7.5	0.0	0.0
Prop In Lane	1.00		0.07	1.00		0.07	0.33		0.27	0.09		0.82
Lane Grp Cap(c), veh/h	181	0	694	27	0	539	468	0	0	392	0	0
V/C Ratio(X)	0.78	0.00	0.44	0.62	0.00	0.76	0.18	0.00	0.00	0.65	0.00	0.00
Avail Cap(c_a), veh/h	303	0	987	159	0	853	468	0	0	392	0	0
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	0.00	1.00	0.00	0.00
Uniform Delay (d), s/veh	17.6	0.0	9.1	19.6	0.0	12.8	12.8	0.0	0.0	15.0	0.0	0.0
Incr Delay (d2), s/veh	7.3	0.0	0.4	20.5	0.0	2.2	0.9	0.0	0.0	8.2	0.0	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	1.4	0.0	1.4	0.3	0.0	2.7	0.5	0.0	0.0	2.4	0.0	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	24.9	0.0	9.6	40.1	0.0	15.0	13.6	0.0	0.0	23.2	0.0	0.0
LnGrp LOS	C	A	A	D	A	B	B	A	A	C	A	A
Approach Vol, veh/h	449				426				85			
Approach Delay, s/veh	14.4				16.0				13.6			
Approach LOS	B				B				B			
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	5.7	20.5		14.0	9.2	17.0		14.0				
Change Period (Y+Rc), s	5.0	5.0		5.0	5.0	5.0		5.0				
Max Green Setting (Gmax), s	4.0	22.0		9.0	7.0	19.0		9.0				
Max Q Clear Time (g_c+I1), s	2.4	7.1		9.5	5.2	10.3		3.7				
Green Ext Time (p_c), s	0.0	1.4		0.0	0.1	1.5		0.1				
Intersection Summary												
HCM 6th Ctrl Delay	16.8											
HCM 6th LOS	B											

HCM 6th Signalized Intersection Summary

1: Deep Creek Rd & Rocksprings Rd

Synchro 10 Report

03/05/2019

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	125	250	20	80	290	25	90	50	40	20	45	180
Future Volume (veh/h)	125	250	20	80	290	25	90	50	40	20	45	180
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1826	1826	1826	1678	1826	1826	1678	1678	1678	1530	1530	1530
Adj Flow Rate, veh/h	142	284	23	91	330	28	102	57	45	23	51	205
Peak Hour Factor	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
Percent Heavy Veh, %	5	5	5	15	5	5	15	15	15	25	25	25
Cap, veh/h	181	558	45	108	496	42	248	112	64	110	68	224
Arrive On Green	0.10	0.33	0.33	0.07	0.30	0.30	0.22	0.22	0.22	0.22	0.22	0.22
Sat Flow, veh/h	1739	1667	135	1598	1660	141	509	500	285	60	301	1000
Grp Volume(v), veh/h	142	0	307	91	0	358	204	0	0	279	0	0
Grp Sat Flow(s),veh/h/ln	1739	0	1802	1598	0	1801	1294	0	0	1361	0	0
Q Serve(g_s), s	3.2	0.0	5.5	2.3	0.0	7.0	0.0	0.0	0.0	2.4	0.0	0.0
Cycle Q Clear(g_c), s	3.2	0.0	5.5	2.3	0.0	7.0	5.6	0.0	0.0	8.0	0.0	0.0
Prop In Lane	1.00		0.07	1.00		0.08	0.50		0.22	0.08		0.73
Lane Grp Cap(c), veh/h	181	0	604	108	0	538	424	0	0	402	0	0
V/C Ratio(X)	0.78	0.00	0.51	0.84	0.00	0.67	0.48	0.00	0.00	0.69	0.00	0.00
Avail Cap(c_a), veh/h	303	0	987	159	0	851	424	0	0	402	0	0
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	0.00	1.00	0.00	0.00
Uniform Delay (d), s/veh	17.6	0.0	10.7	18.5	0.0	12.3	14.1	0.0	0.0	15.2	0.0	0.0
Incr Delay (d2), s/veh	7.3	0.0	0.7	22.2	0.0	1.4	3.9	0.0	0.0	9.5	0.0	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	1.4	0.0	1.6	1.3	0.0	2.2	1.6	0.0	0.0	2.7	0.0	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	24.9	0.0	11.4	40.7	0.0	13.8	18.0	0.0	0.0	24.7	0.0	0.0
LnGrp LOS	C	A	B	D	A	B	B	A	A	C	A	A
Approach Vol, veh/h	449			449			204			279		
Approach Delay, s/veh	15.6			19.2			18.0			24.7		
Approach LOS	B			B			B			C		
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	7.7	18.5		14.0	9.2	17.0		14.0				
Change Period (Y+Rc), s	5.0	5.0		5.0	5.0	5.0		5.0				
Max Green Setting (Gmax), s	4.0	22.0		9.0	7.0	19.0		9.0				
Max Q Clear Time (g_c+I1), s	4.3	7.5		10.0	5.2	9.0		7.6				
Green Ext Time (p_c), s	0.0	1.4		0.0	0.1	1.4		0.1				

Intersection Summary

HCM 6th Ctrl Delay **19.0**
 HCM 6th LOS **B**

HCM 6th Signalized Intersection Summary

1: Deep Creek Rd & Rocksprings Rd

Synchro 10 Report

03/05/2019

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	130	300	40	10	360	10	140	60	40	10	10	150
Future Volume (veh/h)	130	300	40	10	360	10	140	60	40	10	10	150
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1826	1826	1826	1678	1826	1826	1678	1678	1678	1530	1530	1530
Adj Flow Rate, veh/h	148	341	45	11	409	11	159	68	45	11	11	170
Peak Hour Factor	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
Percent Heavy Veh, %	5	5	5	15	5	5	15	15	15	25	25	25
Cap, veh/h	189	624	82	18	528	14	304	90	50	102	27	270
Arrive On Green	0.11	0.40	0.40	0.01	0.30	0.30	0.22	0.22	0.22	0.22	0.22	0.22
Sat Flow, veh/h	1739	1580	208	1598	1770	48	733	405	226	35	122	1216
Grp Volume(v), veh/h	148	0	386	11	0	420	272	0	0	192	0	0
Grp Sat Flow(s),veh/h/ln	1739	0	1788	1598	0	1817	1365	0	0	1373	0	0
Q Serve(g_s), s	3.4	0.0	6.7	0.3	0.0	8.5	2.4	0.0	0.0	0.0	0.0	0.0
Cycle Q Clear(g_c), s	3.4	0.0	6.7	0.3	0.0	8.5	7.7	0.0	0.0	5.3	0.0	0.0
Prop In Lane	1.00		0.12	1.00		0.03	0.58		0.17	0.06		0.89
Lane Grp Cap(c), veh/h	189	0	707	18	0	542	445	0	0	400	0	0
V/C Ratio(X)	0.79	0.00	0.55	0.60	0.00	0.77	0.61	0.00	0.00	0.48	0.00	0.00
Avail Cap(c_a), veh/h	301	0	973	158	0	854	445	0	0	400	0	0
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	0.00	1.00	0.00	0.00
Uniform Delay (d), s/veh	17.6	0.0	9.4	19.9	0.0	13.0	15.1	0.0	0.0	14.3	0.0	0.0
Incr Delay (d2), s/veh	7.0	0.0	0.7	27.4	0.0	2.4	6.2	0.0	0.0	4.1	0.0	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	1.4	0.0	1.8	0.2	0.0	2.8	2.3	0.0	0.0	1.5	0.0	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	24.6	0.0	10.1	47.3	0.0	15.4	21.2	0.0	0.0	18.4	0.0	0.0
LnGrp LOS	C	A	B	D	A	B	C	A	A	B	A	A
Approach Vol, veh/h	534			431			272			192		
Approach Delay, s/veh	14.1			16.2			21.2			18.4		
Approach LOS	B			B			C			B		
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	5.5	21.0		14.0	9.4	17.1		14.0				
Change Period (Y+Rc), s	5.0	5.0		5.0	5.0	5.0		5.0				
Max Green Setting (Gmax), s	4.0	22.0		9.0	7.0	19.0		9.0				
Max Q Clear Time (g_c+I1), s	2.3	8.7		7.3	5.4	10.5		9.7				
Green Ext Time (p_c), s	0.0	1.8		0.1	0.1	1.5		0.0				

Intersection Summary

HCM 6th Ctrl Delay **16.7**
 HCM 6th LOS **B**

HCM 6th Signalized Intersection Summary

1: Deep Creek Rd & Rocksprings Rd

Synchro 10 Report

03/05/2019

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	130	300	40	75	315	10	205	80	60	10	35	145
Future Volume (veh/h)	130	300	40	75	315	10	205	80	60	10	35	145
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1826	1826	1826	1678	1826	1826	1678	1678	1678	1530	1530	1530
Adj Flow Rate, veh/h	148	341	45	85	358	11	233	91	68	11	40	165
Peak Hour Factor	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
Percent Heavy Veh, %	5	5	5	15	5	5	15	15	15	25	25	25
Cap, veh/h	189	542	71	100	524	16	305	63	47	101	67	242
Arrive On Green	0.11	0.34	0.34	0.06	0.30	0.30	0.22	0.22	0.22	0.22	0.22	0.22
Sat Flow, veh/h	1739	1580	208	1598	1762	54	729	285	213	33	303	1086
Grp Volume(v), veh/h	148	0	386	85	0	369	392	0	0	216	0	0
Grp Sat Flow(s),veh/h/ln	1739	0	1788	1598	0	1816	1226	0	0	1422	0	0
Q Serve(g_s), s	3.3	0.0	7.3	2.1	0.0	7.2	3.1	0.0	0.0	0.0	0.0	0.0
Cycle Q Clear(g_c), s	3.3	0.0	7.3	2.1	0.0	7.2	9.0	0.0	0.0	5.9	0.0	0.0
Prop In Lane	1.00		0.12	1.00		0.03	0.59		0.17	0.05		0.76
Lane Grp Cap(c), veh/h	189	0	613	100	0	540	415	0	0	411	0	0
V/C Ratio(X)	0.79	0.00	0.63	0.85	0.00	0.68	0.94	0.00	0.00	0.53	0.00	0.00
Avail Cap(c_a), veh/h	301	0	974	158	0	855	415	0	0	411	0	0
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	0.00	1.00	0.00	0.00
Uniform Delay (d), s/veh	17.5	0.0	11.1	18.7	0.0	12.5	17.0	0.0	0.0	14.5	0.0	0.0
Incr Delay (d2), s/veh	7.0	0.0	1.1	20.9	0.0	1.5	32.0	0.0	0.0	4.8	0.0	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	1.4	0.0	2.2	1.2	0.0	2.3	6.4	0.0	0.0	1.7	0.0	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	24.6	0.0	12.2	39.6	0.0	14.1	49.1	0.0	0.0	19.3	0.0	0.0
LnGrp LOS	C	A	B	D	A	B	D	A	A	B	A	A
Approach Vol, veh/h	534			454			392			216		
Approach Delay, s/veh	15.6			18.8			49.1			19.3		
Approach LOS	B			B			D			B		
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	7.5	18.8		14.0	9.4	17.0		14.0				
Change Period (Y+Rc), s	5.0	5.0		5.0	5.0	5.0		5.0				
Max Green Setting (Gmax), s	4.0	22.0		9.0	7.0	19.0		9.0				
Max Q Clear Time (g_c+I1), s	4.1	9.3		7.9	5.3	9.2		11.0				
Green Ext Time (p_c), s	0.0	1.8		0.1	0.1	1.4		0.0				
Intersection Summary												
HCM 6th Ctrl Delay	25.2											
HCM 6th LOS	C											



DAVID EVANS
AND ASSOCIATES INC.

SUBJECT	BY	DATE	JOB NO.	SHEET	OF
TURN MOVEMENTS	TNM	5-Mar-19	MMAI0000-1001	1	OF 2

E/W STREET : ROCKSPRINGS RD

INTERSECTION : 1

N/S STREET : DEEP CREEK RD

PROJECTED GROWTH : 2%

CONDITION : PM PEAK HOUR

PER YEAR :

TURN MOVEMENTS

	Existing Condition Traffic	Ambient Growth	Background Condition Traffic	Project Trips	Project Condition Traffic	Future Year 2040 Condition Traffic	Future +Project Year 2040 Condition Traffic
Scenario #	2		4		6	8	10

ROCKSPRINGS RD

EB LEFT	190	5	195	-30	165	180	150
EB THRU	360	10	370	-10	360	490	480
EB RIGHT	40	5	45	0	45	40	40
WB LEFT	25	5	30	15	45	40	55
WB THRU	280	10	290	5	295	420	425
WB RIGHT	25	5	30	0	30	30	30

DEEP CREEK RD

NB LEFT	30	5	35	10	45	40	50
NB THRU	40	5	45	50	95	40	90
NB RIGHT	15	5	20	30	50	20	50
SB LEFT	25	5	30	0	30	50	50
SB THRU	25	5	30	15	45	40	55
SB RIGHT	155	5	160	5	165	230	235
TOTALS	1210	70	1280	90	1370	1620	1710

Los Angeles Office: 213.785.7887 ~ Ontario Office: 909.481.5750 ~ San Diego Office: 619.400.0600

Santa Barbara Office: 805.962.8590 ~ Santa Clarita Office: 661.284.7400 ~ Temecula Office: 951.294.9300

Tustin Office: 714.665.4500 ~ Victorville Office: 760.524.9100



DAVID EVANS
AND ASSOCIATES INC.

SUBJECT	BY	DATE	JOB NO.	SHEET OF
TURN VOLUME SUMMARY	TNM	5-Mar-19	MMAI0000-1001	2 OF 2

E/W STREET : ROCKSPRINGS RD

N/S STREET : DEEP CREEK RD

CONDITION : PM PEAK HOUR

PHF : 0.92

NORTH LEG

LARGE 2 AXLE			LARGE 3 AXLE			LARGE 4(+) AXLE		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	1	0	0	0	0	0	0	0
0	0	0	0	1	0	1	0	0
0	2	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SOUTH LEG

LARGE 2 AXLE			LARGE 3 AXLE			LARGE 4(+) AXLE		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
1	0	0	0	0	0	0	0	0
0	0	0	0	2	0	0	0	0
0	1	0	0	0	0	0	1	0
2	1	0	0	0	0	0	0	0

EAST LEG

LARGE 2 AXLE			LARGE 3 AXLE			LARGE 4(+) AXLE		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	0	1	0	1	0	0	0	0
1	0	0	0	1	0	0	1	0
0	3	0	0	0	0	0	0	0
0	1	0	0	1	0	0	0	0

WEST LEG

LARGE 2 AXLE			LARGE 3 AXLE			LARGE 4(+) AXLE		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	1	0	0	1	0	1	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	2	3	0
0	0	0	0	0	0	0	0	0

NORTH LEG			SOUTH LEG			EAST LEG			WEST LEG		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
31	3	5	1	9	10	5	57	4	4	86	47
37	7	7	5	7	7	5	71	5	11	96	55
42	3	6	3	10	6	5	74	6	10	83	50
40	6	3	1	9	5	5	66	5	8	88	36

TRUCK TOTAL	AUTO VOLUMES	TOTALS	ROUNDED TOTALS	TRUCK PERCENTAGE
-------------	--------------	--------	----------------	------------------

ROCKSPRINGS RD

EB LEFT	0	188	188	190	5%
EB THRU	5	353	358	360	5%
EB RIGHT	3	33	36	40	10%
WB LEFT	1	20	21	25	5%
WB THRU	8	268	276	280	5%
WB RIGHT	1	20	21	25	5%

DEEP CREEK RD

NB LEFT	0	28	28	30	5%
NB THRU	5	35	40	40	15%
NB RIGHT	3	10	13	15	25%
SB LEFT	0	21	21	25	5%
SB THRU	4	19	23	25	15%
SB RIGHT	1	150	151	155	5%

INTERSECTION TURN COUNT

PEAK HOUR

NORTH-SOUTH STREET: DEEP CREEK
EAST-WEST STREET: ROCK SPRINGS
JURISDICTION: APPLE VALLEY

DATE: 02-20-18

PEAK HOUR: 04:30PM

NORTH LEG

TOTAL: 195

151	23	21
31	4	5
38	8	7
42	5	6
40	6	3

Total

1st

2nd

3rd

4th

Rt Thru Lt

EAST LEG TOTAL: 318

Rt	5	6	5	5	21
Thru	58	73	77	68	276
Lt	5	5	6	5	21

1st 2nd 3rd 4th Total

Total 1st 2nd 3rd 4th

188	47	55	50	36
358	88	96	86	88
36	5	11	12	8

Lt

Thru

Rt

WEST LEG TOTAL: 582

PEAK HOUR FACTORS

NORTH LEG = 0.92

SOUTH LEG = 0.96

EAST LEG = 0.90

WEST LEG = 0.90

ALL LEGS = 0.92

	Lt	Thru	Rt
1st	10	9	2
2nd	7	9	5
3rd	6	12	3
4th	5	10	3
Total	28	40	13

TOTAL: 81

SOUTH LEG

HOOR TOTAL: 1,176

Prepared by NEWPORT TRAFFIC STUDIES

SANBAG CLASSIFICATION SUMMARY
 NORTH-SOUTH STREET : DEEP CREEK
 EAST-WEST STREET : ROCK SPRINGS
 BEGINNING TIME : 04:00PM

APPLE VALLEY
 02-20-18

AUTOS			LARGE 2 AXLE			3 AXLE			4 (+) AXLE			TOTALS
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT	RT	THRU	LT	
NORTH LEG												
26	2	3	0	0	0	0	0	0	0	0	0	31
23	0	4	0	0	1	0	0	0	0	0	0	28
31	3	5	0	1	0	0	0	0	0	0	0	40
37	7	7	0	0	0	0	1	0	1	0	0	53
42	3	6	0	2	0	0	0	0	0	0	0	53
40	6	3	0	0	0	0	0	0	0	0	0	49
43	1	2	0	0	0	1	2	0	0	0	0	49
39	5	2	0	0	0	0	0	0	0	1	0	47
281	27	32	0	3	1	1	3	0	1	1	0	350
SOUTH LEG												
2	2	3	0	1	0	0	0	0	0	0	0	8
1	4	3	0	0	0	0	0	0	0	1	0	9
1	9	10	1	0	0	0	0	0	0	0	0	21
5	7	7	0	0	0	0	2	0	0	0	0	21
3	10	6	0	1	0	0	0	0	0	1	0	21
1	9	5	2	1	0	0	0	0	0	0	0	18
5	8	3	0	0	0	0	0	0	0	0	0	16
2	3	3	0	0	0	0	1	0	0	0	0	9
20	52	40	3	3	0	0	3	0	0	2	0	123
EAST LEG												
6	41	3	0	1	0	0	1	0	0	1	0	53
9	59	7	0	2	0	0	0	0	0	0	0	77
5	57	4	0	0	1	0	1	0	0	0	0	68
5	71	5	1	0	0	0	1	0	0	1	0	84
5	74	6	0	3	0	0	0	0	0	0	0	88
5	66	5	0	1	0	0	1	0	0	0	0	78
2	66	7	0	0	0	0	0	0	0	0	0	75
1	55	3	0	2	1	0	0	0	0	2	0	64
38	489	40	1	9	2	0	4	0	0	4	0	587
WEST LEG												
5	59	32	0	0	1	0	0	0	0	0	0	97
7	71	58	0	0	0	0	0	0	0	1	0	137
4	86	47	0	1	0	0	1	0	1	0	0	140
11	96	55	0	0	0	0	0	0	0	0	0	162
10	83	50	0	0	0	0	0	0	2	3	0	148
8	88	36	0	0	0	0	0	0	0	0	0	132
7	68	27	0	1	0	0	0	0	0	0	0	103
5	62	28	0	0	2	0	0	0	0	0	0	97
57	613	333	0	2	3	0	1	0	3	4	0	1016

INTERSECTION TURNING COUNT

NORTH-SOUTH STREET: DEEP CREEK

EAST-WEST STREET: ROCK SPRINGS

TIME: 04:00PM-05:00PM

DATE: 02-20-18

NORTH LEG

118	14	20	Total
26	2	3	1st
23	0	5	2nd
31	4	5	3rd
38	8	7	4th
Rt	Thru	Lt	

Total 1st 2nd 3rd 4th

193	33	58	47	55	Lt
315	59	72	88	96	Thru
28	5	7	5	11	Rt

Rt	6	9	5	6	26
Thru	44	61	58	73	236
Lt	3	7	5	5	20
	1st	2nd	3rd	4th	Total

Lt Thru Rt

1st	3	3	2
2nd	3	5	1
3rd	10	9	2
4th	7	9	5
Total	23	26	10

Prepared by NEWPORT TRAFFIC STUDIES

INTERSECTION TURNING COUNT

NORTH-SOUTH STREET: DEEP CREEK

EAST-WEST STREET: ROCK SPRINGS

TIME: 05:00PM-06:00PM

DATE: 02-20-18

NORTH LEG

165	20	13	Total
42	5	6	1st
40	6	3	2nd
44	3	2	3rd
39	6	2	4th
Rt	Thru	Lt	

Rt	5	5	2	1	13
Thru	77	68	66	59	270
Lt	6	5	7	4	22
	1st	2nd	3rd	4th	Total

Total 1st 2nd 3rd 4th

143	50	36	27	30	Lt
305	86	88	69	62	Thru
32	12	8	7	5	Rt

	Lt	Thru	Rt
1st	6	12	3
2nd	5	10	3
3rd	3	8	5
4th	3	4	2
Total	17	34	13

HCM 6th Signalized Intersection Summary

1: Deep Creek Rd & Rocksprings Rd

Synchro 10 Report

03/05/2019

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	190	360	40	25	280	25	30	40	15	25	25	155
Future Volume (veh/h)	190	360	40	25	280	25	30	40	15	25	25	155
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1826	1826	1826	1826	1826	1826	1678	1678	1678	1678	1678	1678
Adj Flow Rate, veh/h	207	391	43	27	304	27	33	43	16	27	27	168
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	5	5	5	5	5	5	15	15	15	15	15	15
Cap, veh/h	263	660	73	45	468	42	190	196	57	116	54	232
Arrive On Green	0.15	0.41	0.41	0.03	0.28	0.28	0.21	0.21	0.21	0.21	0.21	0.21
Sat Flow, veh/h	1739	1616	178	1739	1653	147	353	922	268	97	254	1092
Grp Volume(v), veh/h	207	0	434	27	0	331	92	0	0	222	0	0
Grp Sat Flow(s),veh/h/ln	1739	0	1794	1739	0	1799	1544	0	0	1443	0	0
Q Serve(g_s), s	4.9	0.0	8.0	0.7	0.0	6.9	0.0	0.0	0.0	2.1	0.0	0.0
Cycle Q Clear(g_c), s	4.9	0.0	8.0	0.7	0.0	6.9	2.0	0.0	0.0	6.0	0.0	0.0
Prop In Lane	1.00		0.10	1.00		0.08	0.36		0.17	0.12		0.76
Lane Grp Cap(c), veh/h	263	0	733	45	0	509	443	0	0	401	0	0
V/C Ratio(X)	0.79	0.00	0.59	0.60	0.00	0.65	0.21	0.00	0.00	0.55	0.00	0.00
Avail Cap(c_a), veh/h	410	0	930	164	0	679	443	0	0	401	0	0
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	0.00	1.00	0.00	0.00
Uniform Delay (d), s/veh	17.3	0.0	9.8	20.4	0.0	13.4	14.0	0.0	0.0	15.5	0.0	0.0
Incr Delay (d2), s/veh	5.4	0.0	0.8	12.4	0.0	1.4	1.1	0.0	0.0	5.4	0.0	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	1.9	0.0	2.2	0.4	0.0	2.3	0.6	0.0	0.0	2.0	0.0	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	22.7	0.0	10.6	32.9	0.0	14.8	15.0	0.0	0.0	20.9	0.0	0.0
LnGrp LOS	C	A	B	C	A	B	B	A	A	C	A	A
Approach Vol, veh/h	641			358			92			222		
Approach Delay, s/veh	14.5			16.1			15.0			20.9		
Approach LOS	B			B			B			C		
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	6.1	22.3		14.0	11.4	17.0		14.0				
Change Period (Y+Rc), s	5.0	5.0		5.0	5.0	5.0		5.0				
Max Green Setting (Gmax), s	4.0	22.0		9.0	10.0	16.0		9.0				
Max Q Clear Time (g_c+I1), s	2.7	10.0		8.0	6.9	8.9		4.0				
Green Ext Time (p_c), s	0.0	2.0		0.1	0.2	1.0		0.1				

Intersection Summary

HCM 6th Ctrl Delay **16.1**
 HCM 6th LOS **B**

HCM 6th Signalized Intersection Summary

1: Deep Creek Rd & Rocksprings Rd

Synchro 10 Report

03/05/2019

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	195	370	45	30	290	30	35	45	20	30	30	160
Future Volume (veh/h)	195	370	45	30	290	30	35	45	20	30	30	160
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1826	1826	1826	1826	1826	1826	1678	1678	1678	1678	1678	1678
Adj Flow Rate, veh/h	212	402	49	33	315	33	38	49	22	33	33	174
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	5	5	5	5	5	5	15	15	15	15	15	15
Cap, veh/h	269	648	79	53	458	48	187	191	67	121	59	221
Arrive On Green	0.15	0.41	0.41	0.03	0.28	0.28	0.21	0.21	0.21	0.21	0.21	0.21
Sat Flow, veh/h	1739	1596	195	1739	1625	170	344	902	315	117	280	1045
Grp Volume(v), veh/h	212	0	451	33	0	348	109	0	0	240	0	0
Grp Sat Flow(s),veh/h/ln	1739	0	1791	1739	0	1795	1560	0	0	1442	0	0
Q Serve(g_s), s	5.0	0.0	8.5	0.8	0.0	7.4	0.0	0.0	0.0	3.1	0.0	0.0
Cycle Q Clear(g_c), s	5.0	0.0	8.5	0.8	0.0	7.4	2.4	0.0	0.0	6.6	0.0	0.0
Prop In Lane	1.00		0.11	1.00		0.09	0.35		0.20	0.14		0.72
Lane Grp Cap(c), veh/h	269	0	727	53	0	506	444	0	0	401	0	0
V/C Ratio(X)	0.79	0.00	0.62	0.63	0.00	0.69	0.25	0.00	0.00	0.60	0.00	0.00
Avail Cap(c_a), veh/h	408	0	925	163	0	675	444	0	0	401	0	0
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	0.00	1.00	0.00	0.00
Uniform Delay (d), s/veh	17.3	0.0	10.0	20.4	0.0	13.6	14.2	0.0	0.0	15.8	0.0	0.0
Incr Delay (d2), s/veh	5.8	0.0	0.9	11.5	0.0	1.9	1.3	0.0	0.0	6.5	0.0	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	2.0	0.0	2.4	0.4	0.0	2.5	0.8	0.0	0.0	2.2	0.0	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	23.1	0.0	10.9	31.9	0.0	15.5	15.5	0.0	0.0	22.3	0.0	0.0
LnGrp LOS	C	A	B	C	A	B	B	A	A	C	A	A
Approach Vol, veh/h	663			381			109			240		
Approach Delay, s/veh	14.8			16.9			15.5			22.3		
Approach LOS	B			B			B			C		
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	6.3	22.3		14.0	11.6	17.0		14.0				
Change Period (Y+Rc), s	5.0	5.0		5.0	5.0	5.0		5.0				
Max Green Setting (Gmax), s	4.0	22.0		9.0	10.0	16.0		9.0				
Max Q Clear Time (g_c+I1), s	2.8	10.5		8.6	7.0	9.4		4.4				
Green Ext Time (p_c), s	0.0	2.0		0.0	0.2	1.0		0.2				
Intersection Summary												
HCM 6th Ctrl Delay	16.7											
HCM 6th LOS	B											

HCM 6th Signalized Intersection Summary

1: Deep Creek Rd & Rocksprings Rd

Synchro 10 Report

03/05/2019

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	165	360	45	45	295	30	45	95	50	30	45	165
Future Volume (veh/h)	165	360	45	45	295	30	45	95	50	30	45	165
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1826	1826	1826	1826	1826	1826	1678	1678	1678	1678	1678	1678
Adj Flow Rate, veh/h	179	391	49	49	321	33	49	103	54	33	49	179
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	5	5	5	5	5	5	15	15	15	15	15	15
Cap, veh/h	226	602	75	72	472	49	162	198	90	122	77	220
Arrive On Green	0.13	0.38	0.38	0.04	0.29	0.29	0.22	0.22	0.22	0.22	0.22	0.22
Sat Flow, veh/h	1739	1591	199	1739	1628	167	250	912	413	110	353	1012
Grp Volume(v), veh/h	179	0	440	49	0	354	206	0	0	261	0	0
Grp Sat Flow(s),veh/h/ln	1739	0	1790	1739	0	1796	1574	0	0	1475	0	0
Q Serve(g_s), s	4.1	0.0	8.4	1.1	0.0	7.2	0.0	0.0	0.0	2.1	0.0	0.0
Cycle Q Clear(g_c), s	4.1	0.0	8.4	1.1	0.0	7.2	4.7	0.0	0.0	6.8	0.0	0.0
Prop In Lane	1.00		0.11	1.00		0.09	0.24		0.26	0.13		0.69
Lane Grp Cap(c), veh/h	226	0	677	72	0	521	450	0	0	419	0	0
V/C Ratio(X)	0.79	0.00	0.65	0.68	0.00	0.68	0.46	0.00	0.00	0.62	0.00	0.00
Avail Cap(c_a), veh/h	294	0	952	168	0	824	450	0	0	419	0	0
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	0.00	1.00	0.00	0.00
Uniform Delay (d), s/veh	17.5	0.0	10.6	19.6	0.0	13.0	14.5	0.0	0.0	15.3	0.0	0.0
Incr Delay (d2), s/veh	10.5	0.0	1.1	10.5	0.0	1.6	3.3	0.0	0.0	6.8	0.0	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	2.0	0.0	2.4	0.6	0.0	2.3	1.6	0.0	0.0	2.4	0.0	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	27.9	0.0	11.7	30.1	0.0	14.6	17.9	0.0	0.0	22.2	0.0	0.0
LnGrp LOS	C	A	B	C	A	B	B	A	A	C	A	A
Approach Vol, veh/h	619			403			206			261		
Approach Delay, s/veh	16.4			16.4			17.9			22.2		
Approach LOS	B			B			B			C		
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	6.7	20.7		14.0	10.4	17.0		14.0				
Change Period (Y+Rc), s	5.0	5.0		5.0	5.0	5.0		5.0				
Max Green Setting (Gmax), s	4.0	22.0		9.0	7.0	19.0		9.0				
Max Q Clear Time (g_c+I1), s	3.1	10.4		8.8	6.1	9.2		6.7				
Green Ext Time (p_c), s	0.0	2.0		0.0	0.0	1.4		0.2				

Intersection Summary

HCM 6th Ctrl Delay **17.6**
 HCM 6th LOS **B**

HCM 6th Signalized Intersection Summary

1: Deep Creek Rd & Rocksprings Rd

Synchro 10 Report

03/05/2019

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	180	490	40	40	420	30	40	40	20	50	40	230
Future Volume (veh/h)	180	490	40	40	420	30	40	40	20	50	40	230
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1826	1826	1826	1826	1826	1826	1678	1678	1678	1678	1678	1678
Adj Flow Rate, veh/h	196	533	43	43	457	33	43	43	22	54	43	250
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	5	5	5	5	5	5	15	15	15	15	15	15
Cap, veh/h	249	706	57	64	533	39	188	154	59	125	49	209
Arrive On Green	0.14	0.42	0.42	0.04	0.32	0.32	0.20	0.20	0.20	0.20	0.20	0.20
Sat Flow, veh/h	1739	1667	135	1739	1683	121	371	760	289	155	245	1030
Grp Volume(v), veh/h	196	0	576	43	0	490	108	0	0	347	0	0
Grp Sat Flow(s),veh/h/ln	1739	0	1802	1739	0	1804	1421	0	0	1430	0	0
Q Serve(g_s), s	4.8	0.0	12.1	1.1	0.0	11.3	0.0	0.0	0.0	6.4	0.0	0.0
Cycle Q Clear(g_c), s	4.8	0.0	12.1	1.1	0.0	11.3	2.5	0.0	0.0	9.0	0.0	0.0
Prop In Lane	1.00		0.07	1.00		0.07	0.40		0.20	0.16		0.72
Lane Grp Cap(c), veh/h	249	0	762	64	0	572	401	0	0	383	0	0
V/C Ratio(X)	0.79	0.00	0.76	0.67	0.00	0.86	0.27	0.00	0.00	0.91	0.00	0.00
Avail Cap(c_a), veh/h	391	0	891	156	0	649	401	0	0	383	0	0
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	0.00	1.00	0.00	0.00
Uniform Delay (d), s/veh	18.4	0.0	10.9	21.1	0.0	14.2	15.2	0.0	0.0	18.4	0.0	0.0
Incr Delay (d2), s/veh	5.5	0.0	3.2	11.2	0.0	10.0	1.6	0.0	0.0	27.4	0.0	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	2.0	0.0	3.9	0.6	0.0	5.0	0.9	0.0	0.0	5.6	0.0	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	23.9	0.0	14.0	32.4	0.0	24.3	16.8	0.0	0.0	45.9	0.0	0.0
LnGrp LOS	C	A	B	C	A	C	B	A	A	D	A	A
Approach Vol, veh/h	772			533			108			347		
Approach Delay, s/veh	16.5			24.9			16.8			45.9		
Approach LOS	B			C			B			D		
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	6.6	23.8		14.0	11.4	19.1		14.0				
Change Period (Y+Rc), s	5.0	5.0		5.0	5.0	5.0		5.0				
Max Green Setting (Gmax), s	4.0	22.0		9.0	10.0	16.0		9.0				
Max Q Clear Time (g_c+I1), s	3.1	14.1		11.0	6.8	13.3		4.5				
Green Ext Time (p_c), s	0.0	2.2		0.0	0.2	0.8		0.2				
Intersection Summary												
HCM 6th Ctrl Delay	24.9											
HCM 6th LOS	C											

HCM 6th Signalized Intersection Summary

1: Deep Creek Rd & Rocksprings Rd

Synchro 10 Report

03/05/2019

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	150	480	40	55	425	30	50	90	50	50	55	235
Future Volume (veh/h)	150	480	40	55	425	30	50	90	50	50	55	235
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1826	1826	1826	1826	1826	1826	1678	1678	1678	1678	1678	1678
Adj Flow Rate, veh/h	163	522	43	60	462	33	54	98	54	54	60	255
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	5	5	5	5	5	5	15	15	15	15	15	15
Cap, veh/h	207	672	55	82	560	40	158	170	80	127	64	215
Arrive On Green	0.12	0.40	0.40	0.05	0.33	0.33	0.21	0.21	0.21	0.21	0.21	0.21
Sat Flow, veh/h	1739	1664	137	1739	1684	120	264	828	388	157	310	1043
Grp Volume(v), veh/h	163	0	565	60	0	495	206	0	0	369	0	0
Grp Sat Flow(s),veh/h/ln	1739	0	1801	1739	0	1804	1480	0	0	1510	0	0
Q Serve(g_s), s	4.0	0.0	11.9	1.5	0.0	11.0	0.0	0.0	0.0	3.5	0.0	0.0
Cycle Q Clear(g_c), s	4.0	0.0	11.9	1.5	0.0	11.0	5.5	0.0	0.0	9.0	0.0	0.0
Prop In Lane	1.00		0.08	1.00		0.07	0.26		0.26	0.15		0.69
Lane Grp Cap(c), veh/h	207	0	727	82	0	600	409	0	0	405	0	0
V/C Ratio(X)	0.79	0.00	0.78	0.73	0.00	0.83	0.50	0.00	0.00	0.91	0.00	0.00
Avail Cap(c_a), veh/h	278	0	906	159	0	784	409	0	0	405	0	0
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	0.00	1.00	0.00	0.00
Uniform Delay (d), s/veh	18.7	0.0	11.3	20.5	0.0	13.4	15.9	0.0	0.0	18.0	0.0	0.0
Incr Delay (d2), s/veh	10.3	0.0	3.4	11.6	0.0	5.6	4.4	0.0	0.0	27.1	0.0	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	1.9	0.0	3.9	0.8	0.0	4.2	1.8	0.0	0.0	5.8	0.0	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	29.0	0.0	14.7	32.1	0.0	19.0	20.3	0.0	0.0	45.1	0.0	0.0
LnGrp LOS	C	A	B	C	A	B	C	A	A	D	A	A
Approach Vol, veh/h	728			555			206			369		
Approach Delay, s/veh	17.9			20.4			20.3			45.1		
Approach LOS	B			C			C			D		
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	7.1	22.7		14.0	10.2	19.5		14.0				
Change Period (Y+Rc), s	5.0	5.0		5.0	5.0	5.0		5.0				
Max Green Setting (Gmax), s	4.0	22.0		9.0	7.0	19.0		9.0				
Max Q Clear Time (g_c+I1), s	3.5	13.9		11.0	6.0	13.0		7.5				
Green Ext Time (p_c), s	0.0	2.2		0.0	0.0	1.5		0.1				

Intersection Summary

HCM 6th Ctrl Delay **24.3**
 HCM 6th LOS **C**

**CALCULATION OF FUTURE DIRECTIONAL TURN VOLUMES FROM
FUTURE DIRECTIONAL LINK VOLUMES (NCHRP 255)**

Intersection No.: 1
North/South Street: DEEP CREEK RD
East/West Street: ROCKSPRINGS RD

Analysis Condition: YEAR 2040 FUTURE TRAFFIC

A.M. Peak Hour

Approach Direction		Base Year Count	Forecast Future Year			
			Link Volume	Turn Volume	Rounded Volume	
South leg NB	Left	20	Approach	104	Left	137
	Through	25	Departure	63	Through	64
	Right	15			Right	44
North leg SB	Left	15	Approach	187	Left	5
	Through	15	Departure	197	Through	12
	Right	180			Right	148
West leg EB	Left	120	Approach	537	Left	125
	Through	245	Departure	641	Through	296
	Right	15			Right	41
East leg WB	Left	10	Approach	421	Left	11
	Through	325	Departure	345	Through	355
	Right	20			Right	8

P.M. Peak Hour

Approach Direction		Base Year Count	Forecast Future Year			
			Link Volume	Turn Volume	Rounded Volume	
South leg NB	Left	30	Approach	90	Left	37
	Through	40	Departure	119	Through	45
	Right	15			Right	24
North leg SB	Left	25	Approach	269	Left	49
	Through	25	Departure	259	Through	38
	Right	155			Right	231
West leg EB	Left	190	Approach	605	Left	180
	Through	360	Departure	691	Through	493
	Right	40			Right	43
East leg WB	Left	25	Approach	420	Left	38
	Through	280	Departure	566	Through	422
	Right	25			Right	34




DAVID EVANS
AND ASSOCIATES INC.

SUBJECT	BY	DATE	JOB NO.	SHEET	OF
TURN MOVEMENTS	TM	5-Mar-19	MMAI0000-1001	1	OF 2

E/W STREET : ROCKSPRINGS RD
N/S STREET : PROJECT DRIVEWAY A
CONDITION : AM PEAK HOUR

INTERSECTION : 2
PROJECTED GROWTH : 2%
PER YEAR :

CONDITION DIAGRAMS



PROJECT GEOMETRICS

TURN MOVEMENTS

Condition	Existing Condition Traffic	Ambient Growth	Background Condition Traffic	Project Trips	Project Condition Traffic	Future Year 2040 Condition Traffic	Future +Project Year 2040 Condition Traffic
Scenario #	1		3		5	7	9

ROCKSPRINGS RD

EB LEFT	0	0	0	0	0	0	0
EB THRU	380	10	390	-20	370	470	450
EB RIGHT	0	0	0	45	45	0	45
WB LEFT	0	0	0	50	50	0	50
WB THRU	520	15	535	-30	505	650	620
WB RIGHT	0	0	0	0	0	0	0

PROJECT DRIVEWAY A

NB LEFT	0	0	0	55	55	0	55
NB THRU	0	0	0	0	0	0	0
NB RIGHT	0	0	0	30	30	0	30
SB LEFT	0	0	0	0	0	0	0
SB THRU	0	0	0	0	0	0	0
SB RIGHT	0	0	0	0	0	0	0
TOTALS	900	25	925	130	1055	1120	1250

Los Angeles Office: 213.785.7887 ~ Ontario Office: 909.481.5750 ~ San Diego Office: 619.400.0600
Santa Barbara Office: 805.962.8590 ~ Santa Clarita Office: 661.284.7400 ~ Temecula Office: 951.294.9300
Tustin Office: 714.665.4500 ~ Victorville Office: 760.524.9100



DAVID EVANS
AND ASSOCIATES INC.

SUBJECT	BY	DATE	JOB NO.	SHEET OF
TURN VOLUME SUMMARY	TM	5-Mar-19	MMAI0000-1001	2 OF 2

E/W STREET : ROCKSPRINGS RD

N/S STREET : PROJECT DRIVEWAY A

CONDITION : AM PEAK HOUR

PHF : 0.89

NORTH LEG

LARGE 2 AXLE			LARGE 3 AXLE			LARGE 4(+) AXLE		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SOUTH LEG

LARGE 2 AXLE			LARGE 3 AXLE			LARGE 4(+) AXLE		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

EAST LEG

LARGE 2 AXLE			LARGE 3 AXLE			LARGE 4(+) AXLE		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	0	0	0	1	0	0	2	0
0	1	0	0	3	0	0	0	0
0	4	0	0	1	0	0	3	0
0	0	0	0	1	0	0	0	0

WEST LEG

LARGE 2 AXLE			LARGE 3 AXLE			LARGE 4(+) AXLE		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	0	0	0	1	0	0	2	0
0	0	0	0	0	0	0	0	0
0	2	0	0	1	0	0	0	0
0	0	0	0	1	0	0	3	0

NORTH LEG			SOUTH LEG			EAST LEG			WEST LEG		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	0	0	0	0	0	0	113	0	0	79	0
0	0	0	0	0	0	0	129	0	0	110	0
0	0	0	0	0	0	0	137	0	0	103	0
0	0	0	0	0	0	0	122	0	0	74	0

TRUCK TOTAL	AUTO VOLUMES	TOTALS	ROUNDED TOTALS	TRUCK PERCENTAGE
-------------	--------------	--------	----------------	------------------

ROCKSPRINGS RD

EB LEFT	0	0	0	0	0%
EB THRU	10	366	376	380	5%
EB RIGHT	0	0	0	0	0%
WB LEFT	0	0	0	0	0%
WB THRU	16	501	517	520	5%
WB RIGHT	0	0	0	0	0%

PROJECT DRIVEWAY A

NB LEFT	0	0	0	0	0%
NB THRU	0	0	0	0	0%
NB RIGHT	0	0	0	0	0%
SB LEFT	0	0	0	0	0%
SB THRU	0	0	0	0	0%
SB RIGHT	0	0	0	0	0%

Los Angeles Office: 213.785.7887 ~ Ontario Office: 909.481.5750 ~ San Diego Office: 619.400.0600

Santa Barbara Office: 805.962.8590 ~ Santa Clarita Office: 661.284.7400 ~ Temecula Office: 951.294.9300

Tustin Office: 714.665.4500 ~ Victorville Office: 760.524.9100

Intersection

Int Delay, s/veh 2.6

Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Vol, veh/h	370	45	50	505	55	30
Future Vol, veh/h	370	45	50	505	55	30
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	88	88	88	88	88	88
Heavy Vehicles, %	5	15	15	5	5	30
Mvmt Flow	420	51	57	574	63	34

Major/Minor	Major1	Major2	Minor1
Conflicting Flow All	0	0	471
Stage 1	-	-	-
Stage 2	-	-	-
Critical Hdwy	-	-	4.25
Critical Hdwy Stg 1	-	-	-
Critical Hdwy Stg 2	-	-	-
Follow-up Hdwy	-	-	2.335
Pot Cap-1 Maneuver	-	-	1026
Stage 1	-	-	-
Stage 2	-	-	-
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	-	-	1026
Mov Cap-2 Maneuver	-	-	-
Stage 1	-	-	-
Stage 2	-	-	-

Approach	EB	WB	NB
HCM Control Delay, s	0	0.8	26.6
HCM LOS			D

Minor Lane/Major Mvmt	NBLn1	EBT	EBR	WBL	WBT
Capacity (veh/h)	262	-	-	1026	-
HCM Lane V/C Ratio	0.369	-	-	0.055	-
HCM Control Delay (s)	26.6	-	-	8.7	0
HCM Lane LOS	D	-	-	A	A
HCM 95th %tile Q(veh)	1.6	-	-	0.2	-

Intersection						
Int Delay, s/veh	3.1					
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Vol, veh/h	450	45	50	620	55	30
Future Vol, veh/h	450	45	50	620	55	30
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	88	88	88	88	88	88
Heavy Vehicles, %	5	15	15	5	5	30
Mvmt Flow	511	51	57	705	63	34
Major/Minor	Major1		Major2		Minor1	
Conflicting Flow All	0	0	562	0	1356	537
Stage 1	-	-	-	-	537	-
Stage 2	-	-	-	-	819	-
Critical Hdwy	-	-	4.25	-	6.45	6.5
Critical Hdwy Stg 1	-	-	-	-	5.45	-
Critical Hdwy Stg 2	-	-	-	-	5.45	-
Follow-up Hdwy	-	-	2.335	-	3.545	3.57
Pot Cap-1 Maneuver	-	-	948	-	162	493
Stage 1	-	-	-	-	580	-
Stage 2	-	-	-	-	428	-
Platoon blocked, %	-	-		-		
Mov Cap-1 Maneuver	-	-	948	-	146	493
Mov Cap-2 Maneuver	-	-	-	-	146	-
Stage 1	-	-	-	-	523	-
Stage 2	-	-	-	-	428	-
Approach	EB		WB		NB	
HCM Control Delay, s	0		0.7		40.7	
HCM LOS					E	
Minor Lane/Major Mvmt	NBLn1	EBT	EBR	WBL	WBT	
Capacity (veh/h)	194	-	-	948	-	
HCM Lane V/C Ratio	0.498	-	-	0.06	-	
HCM Control Delay (s)	40.7	-	-	9	0	
HCM Lane LOS	E	-	-	A	A	
HCM 95th %tile Q(veh)	2.5	-	-	0.2	-	



DAVID EVANS
AND ASSOCIATES INC.

SUBJECT	BY	DATE	JOB NO.	SHEET	OF
TURN MOVEMENTS	TM	5-Mar-19	MMAI0000-1001	1	OF 2

E/W STREET : ROCKSPRINGS RD
N/S STREET : PROJECT DRIVEWAY A
CONDITION : PM PEAK HOUR

INTERSECTION : 2
PROJECTED GROWTH : 2%
PER YEAR :

TURN MOVEMENTS

	Existing Condition Traffic	Ambient Growth	Background Condition Traffic	Project Trips	Project Condition Traffic	Future Year 2040 Condition Traffic	Future +Project Year 2040 Condition Traffic
Scenario #	2		4		6	8	10

ROCKSPRINGS RD

EB LEFT	0	0	0	0	0	0	0
EB THRU	585	15	600	-65	535	710	645
EB RIGHT	0	0	0	90	90	0	90
WB LEFT	0	0	0	30	30	0	30
WB THRU	455	10	465	-10	455	690	680
WB RIGHT	0	0	0	0	0	0	0

PROJECT DRIVEWAY A

NB LEFT	0	0	0	35	35	0	35
NB THRU	0	0	0	0	0	0	0
NB RIGHT	0	0	0	30	30	0	30
SB LEFT	0	0	0	0	0	0	0
SB THRU	0	0	0	0	0	0	0
SB RIGHT	0	0	0	0	0	0	0
TOTALS	1040	25	1065	110	1175	1400	1510

Los Angeles Office: 213.785.7887 ~ Ontario Office: 909.481.5750 ~ San Diego Office: 619.400.0600
Santa Barbara Office: 805.962.8590 ~ Santa Clarita Office: 661.284.7400 ~ Temecula Office: 951.294.9300
Tustin Office: 714.665.4500 ~ Victorville Office: 760.524.9100



DAVID EVANS
AND ASSOCIATES INC.

SUBJECT	BY	DATE	JOB NO.	SHEET OF
TURN VOLUME SUMMARY	TM	5-Mar-19	MMAI0000-1001	2 OF 2

E/W STREET : ROCKSPRINGS RD

N/S STREET : PROJECT DRIVEWAY A

CONDITION : PM PEAK HOUR

PHF : 0.93

NORTH LEG								
LARGE 2 AXLE			LARGE 3 AXLE			LARGE 4(+) AXLE		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SOUTH LEG								
LARGE 2 AXLE			LARGE 3 AXLE			LARGE 4(+) AXLE		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

EAST LEG								
LARGE 2 AXLE			LARGE 3 AXLE			LARGE 4(+) AXLE		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	0	0	0	1	0	0	0	0
0	0	0	0	1	0	0	2	0
0	3	0	0	0	0	0	0	0
0	1	0	0	1	0	0	0	0

WEST LEG								
LARGE 2 AXLE			LARGE 3 AXLE			LARGE 4(+) AXLE		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	1	0	0	1	0	0	1	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	5	0
0	0	0	0	0	0	0	0	0

NORTH LEG			SOUTH LEG			EAST LEG			WEST LEG		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	0	0	0	0	0	0	98	0	0	137	0
0	0	0	0	0	0	0	115	0	0	162	0
0	0	0	0	0	0	0	122	0	0	143	0
0	0	0	0	0	0	0	111	0	0	132	0

TRUCK TOTAL	AUTO VOLUMES	TOTALS	ROUNDED TOTALS	TRUCK PERCENTAGE
-------------	--------------	--------	----------------	------------------

ROCKSPRINGS RD

EB LEFT	0	0	0	0	0%
EB THRU	8	574	582	585	5%
EB RIGHT	0	0	0	0	0%
WB LEFT	0	0	0	0	0%
WB THRU	9	446	455	455	5%
WB RIGHT	0	0	0	0	0%

PROJECT DRIVEWAY A

NB LEFT	0	0	0	0	0%
NB THRU	0	0	0	0	0%
NB RIGHT	0	0	0	0	0%
SB LEFT	0	0	0	0	0%
SB THRU	0	0	0	0	0%
SB RIGHT	0	0	0	0	0%

Intersection

Int Delay, s/veh 1.6

Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Vol, veh/h	535	90	30	455	35	30
Future Vol, veh/h	535	90	30	455	35	30
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	5	10	5	5	5	25
Mvmt Flow	582	98	33	495	38	33

Major/Minor	Major1	Major2	Minor1
Conflicting Flow All	0	0	680
Stage 1	-	-	-
Stage 2	-	-	-
Critical Hdwy	-	-	4.15
Critical Hdwy Stg 1	-	-	-
Critical Hdwy Stg 2	-	-	-
Follow-up Hdwy	-	-	2.245
Pot Cap-1 Maneuver	-	-	898
Stage 1	-	-	-
Stage 2	-	-	-
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	-	-	898
Mov Cap-2 Maneuver	-	-	-
Stage 1	-	-	-
Stage 2	-	-	-

Approach	EB	WB	NB
HCM Control Delay, s	0	0.6	23.7
HCM LOS			C

Minor Lane/Major Mvmt	NBLn1	EBT	EBR	WBL	WBT
Capacity (veh/h)	262	-	-	898	-
HCM Lane V/C Ratio	0.27	-	-	0.036	-
HCM Control Delay (s)	23.7	-	-	9.2	0
HCM Lane LOS	C	-	-	A	A
HCM 95th %tile Q(veh)	1.1	-	-	0.1	-

Intersection						
Int Delay, s/veh	2					
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Vol, veh/h	645	90	30	680	35	30
Future Vol, veh/h	645	90	30	680	35	30
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	5	10	5	5	5	25
Mvmt Flow	701	98	33	739	38	33
Major/Minor	Major1		Major2		Minor1	
Conflicting Flow All	0	0	799	0	1555	750
Stage 1	-	-	-	-	750	-
Stage 2	-	-	-	-	805	-
Critical Hdwy	-	-	4.15	-	6.45	6.45
Critical Hdwy Stg 1	-	-	-	-	5.45	-
Critical Hdwy Stg 2	-	-	-	-	5.45	-
Follow-up Hdwy	-	-	2.245	-	3.545	3.525
Pot Cap-1 Maneuver	-	-	811	-	122	376
Stage 1	-	-	-	-	461	-
Stage 2	-	-	-	-	435	-
Platoon blocked, %	-	-		-		
Mov Cap-1 Maneuver	-	-	811	-	114	376
Mov Cap-2 Maneuver	-	-	-	-	114	-
Stage 1	-	-	-	-	429	-
Stage 2	-	-	-	-	435	-
Approach	EB		WB		NB	
HCM Control Delay, s	0		0.4		41.2	
HCM LOS					E	
Minor Lane/Major Mvmt	NBLn1	EBT	EBR	WBL	WBT	
Capacity (veh/h)	168	-	-	811	-	
HCM Lane V/C Ratio	0.421	-	-	0.04	-	
HCM Control Delay (s)	41.2	-	-	9.6	0	
HCM Lane LOS	E	-	-	A	A	
HCM 95th %tile Q(veh)	1.9	-	-	0.1	-	



DAVID EVANS
AND ASSOCIATES INC.

SUBJECT	BY	DATE	JOB NO.	SHEET	OF
TURN MOVEMENTS	TM	5-Mar-19	MMAI0000-1001	1	OF 2

E/W STREET : PROJECT DRIVEWAY B

N/S STREET : DEEP CREEK RD


CONDITION : AM PEAK HOUR

INTERSECTION : 3

PROJECTED GROWTH : 2%

PER YEAR :

CONDITION DIAGRAMS



PROJECT GEOMETRICS

TURN MOVEMENTS

	Existing Condition Traffic	Ambient Growth	Background Condition Traffic	Project Trips	Project Condition Traffic	Future Year 2040 Condition Traffic	Future +Project Year 2040 Condition Traffic
Condition							
Scenario #	1		3		5	7	9

PROJECT DRIVEWAY B

EB LEFT	0	0	0	95	95	0	95
EB THRU	0	0	0	0	0	0	0
EB RIGHT	0	0	0	10	10	0	10
WB LEFT	0	0	0	0	0	0	0
WB THRU	0	0	0	0	0	0	0
WB RIGHT	0	0	0	0	0	0	0

DEEP CREEK RD

NB LEFT	0	0	0	10	10	0	10
NB THRU	55	5	60	0	60	240	240
NB RIGHT	0	0	0	0	0	0	0
SB LEFT	0	0	0	0	0	0	0
SB THRU	35	5	40	0	40	60	60
SB RIGHT	0	0	0	85	85	0	85
TOTALS	90	10	100	200	300	300	500

Los Angeles Office: 213.785.7887 ~ Ontario Office: 909.481.5750 ~ San Diego Office: 619.400.0600

Santa Barbara Office: 805.962.8590 ~ Santa Clarita Office: 661.284.7400 ~ Temecula Office: 951.294.9300

Tustin Office: 714.665.4500 ~ Victorville Office: 760.524.9100



DAVID EVANS
AND ASSOCIATES INC.

SUBJECT	BY	DATE	JOB NO.	SHEET OF
TURN VOLUME SUMMARY	TM	5-Mar-19	MMAI0000-1001	2 OF 2

E/W STREET : PROJECT DRIVEWAY B

N/S STREET : DEEP CREEK RD

CONDITION : AM PEAK HOUR

PHF : 0.67

NORTH LEG

LARGE 2 AXLE			LARGE 3 AXLE			LARGE 4(+) AXLE		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	1	0	0	0	0	0	0	0
0	2	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	3	0	0	1	0

SOUTH LEG

LARGE 2 AXLE			LARGE 3 AXLE			LARGE 4(+) AXLE		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	1	0	0	0	0	0	0	0
0	3	0	0	1	0	0	0	0
0	2	0	0	0	0	0	1	0
0	0	0	0	0	0	0	0	0

EAST LEG

LARGE 2 AXLE			LARGE 3 AXLE			LARGE 4(+) AXLE		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

WEST LEG

LARGE 2 AXLE			LARGE 3 AXLE			LARGE 4(+) AXLE		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

NORTH LEG			SOUTH LEG			EAST LEG			WEST LEG		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	1	0	0	11	0	0	0	0	0	0	0
0	11	0	0	16	0	0	0	0	0	0	0
0	6	0	0	13	0	0	0	0	0	0	0
0	9	0	0	6	0	0	0	0	0	0	0

TRUCK TOTAL	AUTO VOLUMES	TOTALS	ROUNDED TOTALS	TRUCK PERCENTAGE
-------------	--------------	--------	----------------	------------------

PROJECT DRIVEWAY B

EB LEFT	0	0	0	0	0%
EB THRU	0	0	0	0	0%
EB RIGHT	0	0	0	0	0%
WB LEFT	0	0	0	0	0%
WB THRU	0	0	0	0	0%
WB RIGHT	0	0	0	0	0%

DEEP CREEK RD

NB LEFT	0	0	0	0	0%
NB THRU	8	46	54	55	15%
NB RIGHT	0	0	0	0	0%
SB LEFT	0	0	0	0	0%
SB THRU	7	27	34	35	20%
SB RIGHT	0	0	0	0	0%

Intersection						
Int Delay, s/veh	3.9					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Vol, veh/h	95	10	10	60	40	85
Future Vol, veh/h	95	10	10	60	40	85
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	88	88	88	88	88	88
Heavy Vehicles, %	5	15	5	15	25	5
Mvmt Flow	108	11	11	68	45	97

Major/Minor	Minor2	Major1	Major2
Conflicting Flow All	184	94	142
Stage 1	94	-	-
Stage 2	90	-	-
Critical Hdwy	6.45	6.35	4.15
Critical Hdwy Stg 1	5.45	-	-
Critical Hdwy Stg 2	5.45	-	-
Follow-up Hdwy	3.545	3.435	2.245
Pot Cap-1 Maneuver	798	928	1423
Stage 1	922	-	-
Stage 2	926	-	-
Platoon blocked, %			
Mov Cap-1 Maneuver	792	928	1423
Mov Cap-2 Maneuver	792	-	-
Stage 1	915	-	-
Stage 2	926	-	-

Approach	EB	NB	SB
HCM Control Delay, s	10.3	1.1	0
HCM LOS	B		

Minor Lane/Major Mvmt	NBL	NBT	EBLn1	SBT	SBR
Capacity (veh/h)	1423	-	803	-	-
HCM Lane V/C Ratio	0.008	-	0.149	-	-
HCM Control Delay (s)	7.5	0	10.3	-	-
HCM Lane LOS	A	A	B	-	-
HCM 95th %tile Q(veh)	0	-	0.5	-	-

Intersection						
Int Delay, s/veh	2.8					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Vol, veh/h	95	10	10	240	60	85
Future Vol, veh/h	95	10	10	240	60	85
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	88	88	88	88	88	88
Heavy Vehicles, %	5	15	5	15	25	5
Mvmt Flow	108	11	11	273	68	97
Major/Minor	Minor2	Major1		Major2		
Conflicting Flow All	412	117	165	0	-	0
Stage 1	117	-	-	-	-	-
Stage 2	295	-	-	-	-	-
Critical Hdwy	6.45	6.35	4.15	-	-	-
Critical Hdwy Stg 1	5.45	-	-	-	-	-
Critical Hdwy Stg 2	5.45	-	-	-	-	-
Follow-up Hdwy	3.545	3.435	2.245	-	-	-
Pot Cap-1 Maneuver	591	901	1395	-	-	-
Stage 1	901	-	-	-	-	-
Stage 2	749	-	-	-	-	-
Platoon blocked, %				-	-	-
Mov Cap-1 Maneuver	586	901	1395	-	-	-
Mov Cap-2 Maneuver	586	-	-	-	-	-
Stage 1	893	-	-	-	-	-
Stage 2	749	-	-	-	-	-
Approach	EB	NB		SB		
HCM Control Delay, s	12.4	0.3		0		
HCM LOS	B					
Minor Lane/Major Mvmt	NBL	NBT	EBLn1	SBT	SBR	
Capacity (veh/h)	1395	-	606	-	-	
HCM Lane V/C Ratio	0.008	-	0.197	-	-	
HCM Control Delay (s)	7.6	0	12.4	-	-	
HCM Lane LOS	A	A	B	-	-	
HCM 95th %tile Q(veh)	0	-	0.7	-	-	



DAVID EVANS
AND ASSOCIATES INC.

SUBJECT	BY	DATE	JOB NO.	SHEET	OF
TURN MOVEMENTS	TM	5-Mar-19	MMAI0000-1001	1	OF 2

E/W STREET : PROJECT DRIVEWAY B

INTERSECTION : 3

N/S STREET : DEEP CREEK RD

PROJECTED GROWTH : 2%

CONDITION : PM PEAK HOUR

PER YEAR :

TURN MOVEMENTS

	Existing Condition Traffic	Ambient Growth	Background Condition Traffic	Project Trips	Project Condition Traffic	Future Year 2040 Condition Traffic	Future +Project Year 2040 Condition Traffic
Condition							
Scenario #	2		4		6	8	10

PROJECT DRIVEWAY B

EB LEFT	0	0	0	85	85	0	85
EB THRU	0	0	0	0	0	0	0
EB RIGHT	0	0	0	10	10	0	10
WB LEFT	0	0	0	0	0	0	0
WB THRU	0	0	0	0	0	0	0
WB RIGHT	0	0	0	0	0	0	0

DEEP CREEK RD

NB LEFT	0	0	0	10	10	0	10
NB THRU	85	5	90	0	90	100	100
NB RIGHT	0	0	0	0	0	0	0
SB LEFT	0	0	0	0	0	0	0
SB THRU	80	5	85	0	85	120	120
SB RIGHT	0	0	0	30	30	0	30
TOTALS	165	10	175	135	310	220	355



DAVID EVANS
AND ASSOCIATES INC.

SUBJECT	BY	DATE	JOB NO.	SHEET OF
TURN VOLUME SUMMARY	TM	5-Mar-19	MMAI0000-1001	2 OF 2

E/W STREET : PROJECT DRIVEWAY B

N/S STREET : DEEP CREEK RD

CONDITION : PM PEAK HOUR

PHF : 0.89

NORTH LEG

LARGE 2 AXLE			LARGE 3 AXLE			LARGE 4(+) AXLE		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	2	0	0	0	0	0	1	0
0	0	0	0	1	0	0	0	0
0	2	0	0	0	0	0	2	0
0	0	0	0	0	0	0	0	0

SOUTH LEG

LARGE 2 AXLE			LARGE 3 AXLE			LARGE 4(+) AXLE		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	1	0	0	0	0	0	0	0
0	0	0	0	2	0	0	0	0
0	1	0	0	0	0	0	1	0
0	3	0	0	0	0	0	0	0

EAST LEG

LARGE 2 AXLE			LARGE 3 AXLE			LARGE 4(+) AXLE		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

WEST LEG

LARGE 2 AXLE			LARGE 3 AXLE			LARGE 4(+) AXLE		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

NORTH LEG			SOUTH LEG			EAST LEG			WEST LEG		
RT	THRU	LT	RT	THRU	LT	RT	THRU	LT	RT	THRU	LT
0	11	0	0	20	0	0	0	0	0	0	0
0	23	0	0	19	0	0	0	0	0	0	0
0	19	0	0	19	0	0	0	0	0	0	0
0	19	0	0	15	0	0	0	0	0	0	0

TRUCK TOTAL	AUTO VOLUMES	TOTALS	ROUNDED TOTALS	TRUCK PERCENTAGE
-------------	--------------	--------	----------------	------------------

PROJECT DRIVEWAY B

EB LEFT	0	0	0	0	0%
EB THRU	0	0	0	0	0%
EB RIGHT	0	0	0	0	0%
WB LEFT	0	0	0	0	0%
WB THRU	0	0	0	0	0%
WB RIGHT	0	0	0	0	0%

DEEP CREEK RD

NB LEFT	0	0	0	0	0%
NB THRU	8	73	81	85	10%
NB RIGHT	0	0	0	0	0%
SB LEFT	0	0	0	0	0%
SB THRU	8	72	80	80	10%
SB RIGHT	0	0	0	0	0%

Los Angeles Office: 213.785.7887 ~ Ontario Office: 909.481.5750 ~ San Diego Office: 619.400.0600

Santa Barbara Office: 805.962.8590 ~ Santa Clarita Office: 661.284.7400 ~ Temecula Office: 951.294.9300

Tustin Office: 714.665.4500 ~ Victorville Office: 760.524.9100

Intersection						
Int Delay, s/veh	3.5					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Vol, veh/h	85	10	10	90	85	30
Future Vol, veh/h	85	10	10	90	85	30
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	5	10	5	15	15	5
Mvmt Flow	92	11	11	98	92	33

Major/Minor	Minor2	Major1	Major2
Conflicting Flow All	229	109	125
Stage 1	109	-	-
Stage 2	120	-	-
Critical Hdwy	6.45	6.3	4.15
Critical Hdwy Stg 1	5.45	-	-
Critical Hdwy Stg 2	5.45	-	-
Follow-up Hdwy	3.545	3.39	2.245
Pot Cap-1 Maneuver	753	923	1443
Stage 1	908	-	-
Stage 2	898	-	-
Platoon blocked, %			
Mov Cap-1 Maneuver	747	923	1443
Mov Cap-2 Maneuver	747	-	-
Stage 1	901	-	-
Stage 2	898	-	-

Approach	EB	NB	SB
HCM Control Delay, s	10.5	0.8	0
HCM LOS	B		

Minor Lane/Major Mvmt	NBL	NBT	EBLn1	SBT	SBR
Capacity (veh/h)	1443	-	762	-	-
HCM Lane V/C Ratio	0.008	-	0.136	-	-
HCM Control Delay (s)	7.5	0	10.5	-	-
HCM Lane LOS	A	A	B	-	-
HCM 95th %tile Q(veh)	0	-	0.5	-	-

Intersection						
Int Delay, s/veh	3.1					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Vol, veh/h	85	10	10	100	120	30
Future Vol, veh/h	85	10	10	100	120	30
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	5	10	5	15	15	5
Mvmt Flow	92	11	11	109	130	33

Major/Minor	Minor2	Major1	Major2
Conflicting Flow All	278	147	163
Stage 1	147	-	-
Stage 2	131	-	-
Critical Hdwy	6.45	6.3	4.15
Critical Hdwy Stg 1	5.45	-	-
Critical Hdwy Stg 2	5.45	-	-
Follow-up Hdwy	3.545	3.39	2.245
Pot Cap-1 Maneuver	705	879	1398
Stage 1	873	-	-
Stage 2	888	-	-
Platoon blocked, %			
Mov Cap-1 Maneuver	699	879	1398
Mov Cap-2 Maneuver	699	-	-
Stage 1	866	-	-
Stage 2	888	-	-

Approach	EB	NB	SB
HCM Control Delay, s	10.9	0.7	0
HCM LOS	B		

Minor Lane/Major Mvmt	NBL	NBT	EBLn1	SBT	SBR
Capacity (veh/h)	1398	-	714	-	-
HCM Lane V/C Ratio	0.008	-	0.145	-	-
HCM Control Delay (s)	7.6	0	10.9	-	-
HCM Lane LOS	A	A	B	-	-
HCM 95th %tile Q(veh)	0	-	0.5	-	-