

Appendix A

Valley Communications Center Project, Air Quality, Greenhouse Gas, and Energy Impact Study

MD Acoustics

December 6, 2022

Valley Communications Center Project

Air Quality, Greenhouse Gas, and Energy Impact Study

County of San Bernardino

Prepared for:

Ms. Julie Gilbert

Compass Consulting Enterprises, Inc.
PO Box 2627

Avalon, CA 90704

Prepared by:

MD Acoustics, LLC

Tyler Klassen, EIT 1197 Los Angeles Ave, Ste C-256 Simi Valley, CA 93065

Date: 12/6/2022



Noise Study Reports | Vibration Studies | Air Quality | Greenhouse Gas | Health Risk Assessments

TABLE OF CONTENTS

1.0	Introduction 1				
	1.1	Purpose of Analysis and Study Objectives	1		
	1.2	Project Summary	1		
		1.2.1 Site Location	1		
		1.2.2 Project Description	1		
		1.2.3 Sensitive Receptors	2		
	1.3	Executive Summary of Findings and Mitigation Measures	2		
2.0	Regu	latory Framework and Background	6		
	3.3	Air Quality Regulatory Setting	6		
		3.3.1 National and State	6		
		2.1.2 South Coast Air Quality Management District	8		
	2.2	2.2 Greenhouse Gas Regulatory Setting			
		2.2.1 International	11		
		2.2.2 National	11		
		2.2.3 California	13		
		2.2.4 South Coast Air Quality Management District	20		
		2.2.5 County of San Bernardino	22		
	2.3	Energy Regulatory Setting	22		
		2.3.1 Federal Regulations	23		
		2.3.2 State Regulations	24		
3.0	Setting 30				
	3.3	Existing Physical Setting	30		
		3.3.1 Local Climate and Meteorology	30		
		3.1.2 Local Air Quality	31		
		3.1.3 Attainment Status	34		
	3.2	Greenhouse Gases	35		
	3.3	Energy	37		
		3.3.1 Overview	37		
		3.3.2 Electricity and Natural Gas	39		
		3.3.3 Transportation Energy Resources	40		
4.0	Modeling Parameters and Assumptions				
	4.1	Construction	42		
	4.2	Operations	43		
	4.3	Localized Construction Analysis	43		
	4.4	Localized Operational Analysis	44		
5.0	Thres	sholds of Significance	45		
3.0	5.1	Air Quality Thresholds of Significance	45		
		5.1.1 CEQA Guidelines for Air Quality	45		
		5.1.2 Regional Significance Thresholds for Construction Emissions	45		

		5.1.3 Regional Significance Thresholds for Operational Emissions	46		
		5.1.4 Thresholds for Localized Significance	46		
	5.2	Greenhouse Gas Thresholds of Significance	46		
		5.2.1 CEQA Guidelines for Greenhouse Gas	46		
	5.3	Toxic Air Contaminants	47		
6.0	Air Q	Air Quality Emissions Impact			
	6.1	Construction Air Quality Emissions Impact	48		
		6.1.1 Regional Construction Emissions	48		
		6.1.2 Localized Construction Emissions	49		
		6.1.3 Construction-Related Human Health Impacts	49		
		6.1.4 Construction-Related Toxic Air Contaminant Impact	49		
	6.2	Operational Air Quality Emissions Impact	50		
		6.2.1 Regional Operational Emissions	50		
		6.2.2 Localized Operational Emissions	50		
		6.2.3 Operations-Related Human Health Impacts	51		
	6.3	CO Hot Spot Emissions	51		
	6.4	Odors	52 53		
	6.5	Cumulative Regional Air Quality Impacts			
	6.6	Air Quality Compliance	53		
7.0	Gree	Greenhouse Gas Impact Analysis			
	7.1	Construction Greenhouse Gas Emissions Impact			
	7.2	Operational Greenhouse Gas Emissions Impact			
	7.3	Greenhouse Gas Plan Consistency	56		
	7.4	Cumulative Regional Greenhouse Gas Impacts	58		
8.0	Ener	gy Analysis	59		
	8.1	Construction Energy Demand	59		
		8.1.1 Construction Equipment Electricity Usage Estimates	59		
		8.1.2 Construction Equipment Fuel Estimates	59		
		8.1.3 Construction Worker Fuel Estimates	60		
		8.1.4 Construction Vendor/Hauling Fuel Estimates	61		
		8.1.5 Construction Energy Efficiency/Conservation Measures	62		
	8.2	Operational Energy Demand	62		
		8.2.1 Transportation Fuel Consumption	62		
		8.2.2 Facility Energy Demands (Electricity and Natural Gas)	63		
	8.3	Renewable Energy and Energy Efficiency Plan Consistency	64		
	8.4	Cumulative Regional Energy Impacts	65		
9.0	Refe	rences	66		

LIST OF APPENDICES

Appendix A: CalEEMod Daily Emission Output	
Appendix B: CalEEMod Annual Emission Output	
Appendix C: EMFAC2017 Output	
LIST OF EXHIBITS	
Exhibit A Location Map	4 4
Exhibit B	5 5
LIST OF TABLES	
Table 1: Land Use Summary	2
Table 2: Ambient Air Quality Standards	7
Table 3: Meteorological Summary	31
Table 4: Local Area Air Quality Levels from the San Bernardino 4 th Street Monitoring Station	32
Table 5: South Coast Air Basin Attainment Status	34
Table 6: Description of Greenhouse Gases	36
Table 7: Total Electricity System Power (California 2019)	38
Table 8: SCE 2019 Power Content Mix	39
Table 9: Construction Equipment Assumptions ¹	44
Table 10: Regional Significance - Construction Emissions (pounds/day)	48
Table 11: Localized Significance – Construction	49
Table 12: Regional Significance - Unmitigated Operational Emissions (lbs/day)	50
Table 13: Localized Significance - Unmitigated Operational Emissions	51
Table 14: Construction Greenhouse Gas Emissions	55
Table 15: Opening Year Unmitigated Project-Related Greenhouse Gas Emissions	55
Table 16: Project Consistency with the City of Chula Vista Climate Action Plan	56
Table 16: Project Construction Power Cost and Electricity Usage	59

Valley Communications Center Project Air Quality, Greenhouse Gas, and Energy Impact Study County of San Bernardino

Table 18: Construction Worker Fuel Consumption Estimates	. 61
Table 19: Construction Vendor Fuel Consumption Estimates (MHD Trucks) ¹	. 61
Table 20: Construction Hauling Fuel Consumption Estimates (HHD Trucks) ¹	. 62
Table 21: Estimated Vehicle Operations Fuel Consumption	. 63
Table 22: Project Unmitigated Annual Operational Energy Demand Summary ¹	. 64

GLOSSARY OF TERMS

AQMP Air Quality Management Plan

CAAQS California Ambient Air Quality Standards

CARB California Air Resources Board

CEQA California Environmental Quality Act

CFCs Chlorofluorocarbons

CH₄ Methane

CNG Compressed natural gas

CO Carbon monoxide CO₂ Carbon dioxide

CO₂e Carbon dioxide equivalent DPM Diesel particulate matter

GHG Greenhouse gas HFCs Hydrofluorocarbons

LST Localized Significant Thresholds

MTCO₂e Metric tons of carbon dioxide equivalent

MMTCO₂e Million metric tons of carbon dioxide equivalent

NAAQS National Ambient Air Quality Standards

NOx Nitrogen Oxides NO₂ Nitrogen dioxide N₂O Nitrous oxide

O₃ Ozone

PFCs Perfluorocarbons
PM Particle matter

PM10 Particles that are less than 10 micrometers in diameter PM2.5 Particles that are less than 2.5 micrometers in diameter

PMI Point of maximum impact

PPM Parts per million
PPB Parts per billion

RTIP Regional Transportation Improvement Plan

RTP Regional Transportation Plan

SCAB South Coast Air Basin

SCAQMD South Coast Air Quality Management District

SF₆ Sulfur hexafluoride

SIP State Implementation Plan

SOx Sulfur Oxides

SRA Source/Receptor Area
TAC Toxic air contaminants
VOC Volatile organic compounds
WRCC Western Regional Climate Center

MD Acoustics, LLC JN: 08052211_Report

vi

1.0 Introduction

1.1 Purpose of Analysis and Study Objectives

This air quality and greenhouse gas (GHG) analysis was prepared to evaluate whether the estimated criteria pollutants and GHG emissions generated from the Project would cause a significant impact to the air resources in the Project area as well as evaluate whether the estimated energy usage by the project would cause a significant impact to the local energy resources. This assessment was conducted within the context of the California Environmental Quality Act (CEQA, California Public Resources Code Sections 21000, et seq.). The assessment is consistent with the methodology and emission factors endorsed by South Coast Air Quality Management District (SCAQMD), California Air Resource Board (CARB), and the United States Environmental Protection Agency (US EPA).

1.2 Project Summary

1.2.1 Site Location

The Proposed Project is situated on the southeast corner of E Rialto Avenue and S Lena Road, in the City of San Bernardino, as shown in Exhibit A. The proposed use is a self-support and self-sufficient 75,062-square foot emergency communication center that will be occupied by the Sheriff Coroner (SBCSD), Office of Emergency management (OES), County Fire (SBCFD), Consolidated Fire Agency (CONFIRE), Inland Counties Emergency Medical Agency (ICEMA), Radio Manage Facility (ISD), and Building Services. Other San Bernardino County offices are situated west of S Lean Road and south of the Project Site. The Site is bounded on the north by E Rialto Avenue with residences on the north side of E Rialto Avenue, on the south by vacant land and the San Bernardino County Coroner's office, on the east by an industrial building and on the west by S Lena Road and the San Bernardino Regional Parks and General Services offices.

The City of San Bernardino designates zoning for APN 0279-261-17 as "Public Facilities" and the remainder of the Project Site parcels are zoned Industrial Light (Figure 4 – Site Zoning). The City of San Bernardino's Industrial Light (IL) designation is intended to retain, enhance, and intensify existing and provide for the new development of lighter industrial uses along major vehicular, rail, and air transportation routes serving the City. The Proposed Project is similar to Offices/Services which are permitted in the IL zone.

The City's Public Facilities Zone (PF) provides for the continuation of existing and development of new schools, government administrative, police, fire, libraries, social service, and other public facilities.

1.2.2 Project Description

The Proposed Project would build a 3-story 75,062-square foot office building, 190' communications tower, trash enclosure, support building/non-essential storage, transformer and generator, service yard, and covered oversized vehicle parking on 6.49 acres. Exhibit B demonstrates the site plan for the Project.

Construction activities within the Project area will consist of, site preparation, on-site grading, building, paving, and architectural coating. Table 1 summarizes the land use description for the Project Site.

Table 1: Land Use Summary

Land Use	Unit Amount	Size Metric
General Office Building	75.062	TSF ¹
Other Asphalt Surfaces	1.82	Acre
Other Non-Asphalt Surfaces	0.70	Acre
Parking Lot	250	Spaces

Notes:

1.2.3 Sensitive Receptors

Sensitive receptors are considered land uses or other types of population groups that are more sensitive to air pollution than others due to their exposure. Sensitive population groups include children, the elderly, the acutely and chronically ill, and those with cardio-respiratory diseases. For CEQA purposes, a sensitive receptor would be a location where a sensitive individual could remain for 24-hours or longer, such as residencies, hospitals, and schools (etc).

The closest existing sensitive receptors (to the site area) are residential land uses located 85 feet to the north of the Project site.

1.3 Executive Summary of Findings and Mitigation Measures

The following is a summary of the analysis results:

Construction-Source Emissions

Project construction-source emissions would not exceed applicable regional thresholds of significance established by the SCAQMD. For localized emissions, the Project will not exceed applicable Localized Significance Thresholds (LSTs) established by the SCAQMD.

Project construction-source emissions would not conflict with the Basin Air Quality Management Plan (AQMP). As discussed herein, the Project will comply with all applicable SCAQMD construction-source emission reduction rules and guidelines. Project construction source emissions would not cause or substantively contribute to violation of the California Ambient Air Quality Standards (CAAQS) or National Ambient Air Quality Standards (NAAQS).

Established requirements addressing construction equipment operations, and construction material use, storage, and disposal requirements act to minimize odor impacts that may result from construction activities. Moreover, construction-source odor emissions would be temporary, short-term, and intermittent in nature and would not result in persistent impacts that would affect substantial numbers of people. Potential construction-source odor impacts are therefore considered less-than-significant.

Operational-Source Emissions

¹ TSF = Thousand square feet.

The Project operational-sourced emissions would not exceed applicable regional thresholds of significance established by the SCAQMD. Project operational-source emissions would not result in or cause a significant localized air quality impact as discussed in the Operations-Related Local Air Quality Impacts section of this report. Additionally, Project-related traffic will not cause or result in carbon dioxide (CO) concentrations exceeding applicable state and/or federal standards (CO "hotspots). Project operational-source emissions would therefore not adversely affect sensitive receptors within the vicinity of the Project.

Project operational-source emissions would not conflict with the Basin Air Quality Management Plan (AQMP). The Project's emissions meet SCAQMD regional thresholds and will not result in a significant cumulative impact. The Project does not propose any such uses or activities that would result in potentially significant operational-source odor impacts. Potential operational-source odor impacts are therefore considered less-than-significant.

Project-related GHG emissions meet the San Bernardino County and SCAQMD draft threshold. Therefore, Project emissions are considered to be less than significant. The Project also complies with the goals of the CARB Scoping Plan, Assembly Bill (AB) 32, Senate Bill (SB) 32, County of San Bernardino Greenhouse Gas Emissions Reduction Plan, and the County of San Bernardino Climate Action Plan.

Neither construction nor operation of the project would result in wasteful, inefficient, or unnecessary consumption of energy, or wasteful use of energy resources. The proposed project does not include any unusual project characteristics or construction processes that would require the use of equipment that would be more energy intensive than is used for comparable activities and is an industrial project that is not proposing any additional features that would require a larger energy demand than other industrial projects of similar scale and configuration

Mitigation Measures

A. Construction Measures

No construction mitigation required.

B. Operational Measures

No operational mitigation required.

Exhibit A

Location Map



RIALTO AVENUE L1.01 L1.01.A L6.01 L6.01.A L7.01 L7.01.A L6.02 L6.02.A L7.02 OVERALL SITE PLAN #9300 05

Exhibit B **Site Plan**



2.0 Regulatory Framework and Background

3.3 Air Quality Regulatory Setting

Air pollutants are regulated at the national, state, and air basin level; each agency has a different level of regulatory responsibility. The United States EPA regulates at the national level. CARB regulates at the state level. SCAQMD regulates at the air basin level.

3.3.1 National and State

The EPA is responsible for global, international, and interstate air pollution issues and policies. The EPA sets national vehicle and stationary source emission standards, oversees approval of all State Implementation Plans, provides research and guidance for air pollution programs, and sets National Air Quality Standards, also known as federal standards. There are six common air pollutants, called criteria pollutants, which were identified from the provisions of the Clean Air Act of 1970.

- Ozone
- Nitrogen Dioxide
- Lead
- Particulate Matter (PM10 and PM2.5)
- Carbon Monoxide
- Particulate Matter
- Sulfur Dioxide

The federal standards were set to protect public health, including that of sensitive individuals; thus, the standards continue to change as more medical research is available regarding the health effects of the criteria pollutants. Primary federal standards are the levels of air quality necessary, with an adequate margin of safety, to protect the public health.

A State Implementation Plan is a document prepared by each state describing existing air quality conditions and measures that will be followed to attain and maintain federal standards. The State Implementation Plan for the State of California is administered by CARB, which has overall responsibility for statewide air quality maintenance and air pollution prevention. California's State Implementation Plan incorporates individual federal attainment plans for regional air districts—air district prepares their federal attainment plan, which sent to CARB to be approved and incorporated into the California State Implementation Plan. Federal attainment plans include the technical foundation for understanding air quality (e.g., emission inventories and air quality monitoring), control measures and strategies, and enforcement mechanisms. See http://www.arb.ca.gov/research/aaqs/aaqs.htm for additional information on criteria pollutants and air quality standards.

The federal and state ambient air quality standards are summarized in Table 2 and can also be found at http://www.arb.ca.gov/research/aaqs/aaqs2.pdf.

Table 2: Ambient Air Quality Standards

Pollutant	Averaging Time	California Standards ¹		National Standards ²		
Pollutant	Averaging Time	Concentrations ³	Method⁴	Primary ^{3,5}	Secondary ^{3,6}	Method ⁷
	1-Hour	0.09 ppm	Ultraviolet Photometry		Same as	Ultraviolet
Ozone (O3)	8-Hour	0.070 ppm		0.070 ppm (147 μg/m³)	Primary Standard	Photometry
Respirable	24-Hour	50 μg/m³	Gravimetric or Beta Attenuation	150 μ/m³	Same as	Inertial Separation and Gravimetric Analysis
Particulate Matter (PM10) ⁸	Annual Arithmetic Mean	20 μg/m³			Primary Standard	
Fine Particulate Matter (PM2.5)8	24-Hour			35 μg/m³	Same as Primary Standard	Inertial Separation and Gravimetric
Matter (1 M2.5)	Annual Arithmetic Mean	12 μg/m³	Gravimetric or Beta Attenuation	12 μg/m³	15 μg/m³	Analysis
Carbon Monoxide	1-Hour	20 ppm (23 μg/m³)	Non-Dispersive	35 ppm (40 μg/m³)		Non-Dispersive
(co)	8-Hour	9.0 ppm (10 μg/m³)	Infrared Photometry (NDIR)	9 ppm (10 μg/m³)		Infrared Photometry (NDIR)
	1-Hour	0.18 ppm (339 μg/m ³)		100 ppb (188 μg/m³)		Gas Phase Chemiluminescence
Nitrogen Dioxide (NO₂) ⁹	Annual Arithmetic Mean	0.030 ppm (357 μg/m³)	Gas Phase Chemiluminescence	0.053 ppm (100 μg/m³)	Same as Primary Standard	
	1-Hour	0.25 ppm (655 μg/m ³)	Ultraviolet Fluorescence	75 ppb (196 μg/m³)		Ultraviolet Fluorescence; Spectrophotometry (Pararosaniline Method)
Sulfur Dioxide	3-Hour				0.5 ppm (1300 mg/m³)	
(SO ₂) ¹⁰	24-Hour	0.04 ppm (105 μg/m³)		0.14 ppm (for certain areas) ¹⁰		
	Annual Arithmetic Mean			0.130ppm (for certain areas) ¹⁰		
	30 Day Average	1.5 μg/m³	Atomic Absorption			
Lead ^{11,12}	Calendar Qrtr			1.5 μg/m³ (for certain areas) ¹²	Same as Primary Standard	High Volume Sampler and Atomic Absorption
	Rolling 3-Month Average			0.15 μg/m³		
Visibility Reducing Particles ¹³	8-Hour	See footnote 13	Beta Attenuation and Transmittance through Filter Tape		No	
Sulfates	24-Hour	25 μg/m³	Ion Chromatography	National Standards		
Hydrogen Sulfide	1-Hour	0.03 ppm (42 μg/m³)	Ultraviolet Fluorescence			
Vinyl Chloride ¹¹	24-Hour	0.01 ppm (26 μg/m ³)	Gas Chromatography			

Notes:

- California standards for ozone, carbon monoxide, sulfur dioxide (1 and 24 hour), nitrogen dioxide, and particulate matter (PM10, PM2.5, and visibility reducing particles), are values that are not to be exceeded. All others are not to be equaled or exceeded. California ambient air quality standards are listed in the Table of Standards in Section 70200 of Title 17 of the California Code of Regulations.
- 2. National standards (other than ozone, particulate matter, and those based on annual arithmetic mean) are not to be exceeded more than once a year. The ozone standard is attained when the fourth highest 8-hour concentration measured at each site in a year, averaged over three years, is equal to or less than the standard. For PM10, the 24-hour standard is attained when the expected number of days per calendar year with a 24-hour average concentration above 150 µg/m³ is equal to or less than one. For PM2.5, the 24-hour standard is attained when 98 percent of the daily concentrations, averaged over three years, are equal to or less than the standard. Contact the U.S. EPA for further clarification and current national policies.
- 3. Concentration expressed first in units in which it was promulgated. Equivalent units given in parentheses are based upon a reference temperature of 25°C and a reference pressure of 760 torr. Most measurements of air quality are to be corrected to a reference temperature of 25°C and a reference pressure of 760 torr; ppm in this table refers to ppm by volume, or micromoles of pollutant per mole of gas.
- 4. Any equivalent measurement method which can be shown to the satisfaction of CARB to give equivalent results at or near the level of the air quality standard may be used.
- 5. National Primary Standards: The levels of air quality necessary, with an adequate margin of safety to protect the public health.

- 6. National Secondary Standards: The levels of air quality necessary to protect the public welfare from any known or anticipated adverse effects of a pollutant.
- 7. Reference method as described by the U.S. EPA. An "equivalent method" of measurement may be used but must have a "consistent relationship to the reference method" and must be approved by the U.S. EPA.
- 8. On December 14, 2012, the national annual PM2.5 primary standard was lowered from 15 μg/m³ to 12.0 μg/m³. The existing national 24-hour PM2.5 standards (primary and secondary) were retained at 35 μg/m³, as was the annual secondary standard of 15 μg/m³. The existing 24-hour PM10 standards (primary and secondary) of 150 μg/m³ also were retained. The form of the annual primary and secondary standards is the annual mean, averaged over 3 years.
- 9. To attain the 1-hour national standard, the 3-year average of the annual 98th percentile of the 1-hour daily maximum concentrations at each site must not exceed 100 ppb. Note that the national 1-hour standard is in units of parts per billion (ppb). California standards are in units of parts per million (ppm). To directly compare the national 1-hour standard to the California standards the units can be converted from ppb to ppm. In this case, the national standard of 100 ppb is identical to 0.100 ppm.
- 10. On June 2, 2010, a new 1-hour SO2 standard was established and the existing 24-hour and annual primary standards were revoked. To attain the 1-hour national standard, the 3-year average of the annual 99th percentile of the 1-hour daily maximum concentrations at each site must not exceed 75 ppb. The 1971 SO2 national standards (24-hour and annual) remain in effect until one year after an area is designated for the 2010 standard, except that in areas designated nonattainment for the 1971 standards, the 1971 standards remain in effect until implementation plans to attain or maintain the 2010 standards are approved.
 - Note that the 1-hour national standard is in units of parts per billion (ppb). California standards are in units of parts per million (ppm). To directly compare the 1-hour national standard to the California standard the units can be converted to ppm. In this case, the national standard of 75 ppb is identical to 0.075 ppm.
- 11. CARB has identified lead and vinyl chloride as 'toxic air contaminants' with no threshold level of exposure for adverse health effects determined. These actions allow for the implementation of control measures at levels below the ambient concentrations specified for these pollutants.
- 12. The national standard for lead was revised on October 15, 2008, to a rolling 3-month average. The 1978 lead standard (1.5 μg/m³ as a quarterly average) remains in effect until one year after an area is designated for the 2008 standard, except that in areas designated nonattainment for the 1978 standard, the 1978 standard remains in effect until implementation plans to attain or maintain the 2008 standard are approved.
- 13. In 1989, CARB converted the general statewide 10-mile visibility standard to an instrumental equivalent of "extinction of 0.23 per kilometer."

Several pollutants listed in Table 2 are not addressed in this analysis. Analysis of lead is not included in this report because the Project is not anticipated to emit lead. Visibility-reducing particles are not explicitly addressed in this analysis because particulate matter is addressed. The Project is not expected to generate or be exposed to vinyl chloride because proposed Project uses do not utilize the chemical processes that create this pollutant and there are no such uses in the Project vicinity. The proposed Project is not expected to cause exposure to hydrogen sulfide because it would not generate hydrogen sulfide in any substantial quantity.

2.1.2 South Coast Air Quality Management District

The agency for air pollution control for the South Coast Air Basin (basin) is SCAQMD. SCAQMD is responsible for controlling emissions primarily from stationary sources. SCAQMD maintains air quality monitoring stations throughout the basin. SCAQMD, in coordination with the Southern California Association of Governments, is also responsible for developing, updating, and implementing the Air Quality Management Plan (AQMP) for the basin. An AQMP is a plan prepared and implemented by an air pollution district for a county or region designated as nonattainment of the federal and/or California

ambient air quality standards. The term nonattainment area is used to refer to an air basin where one or more ambient air quality standards are exceeded.

Every three (3) years the SCAQMD prepares a new AQMP, updating the previous plan and having a 20-year horizon.

On March 23, 2017, CARB approved the 2016 AQMP. The 2016 AQMP is a regional blueprint for achieving the federal air quality standards and healthful air.

The 2016 AQMP includes both stationary and mobile source strategies to ensure that rapidly approaching attainment deadlines are met, that public health is protected to the maximum extent feasible, and that the region is not faced with burdensome sanctions if the Plan is not approved or if the NAAQS are not met on time. As with every AQMP, a comprehensive analysis of emissions, meteorology, atmospheric chemistry, regional growth projections, and the impact of existing control measures is updated with the latest data and methods. The most significant air quality challenge in the Basin is to reduce nitrogen oxide (NOx) emissions sufficiently to meet the upcoming ozone standard deadlines. The primary goal of the 2016 AQMP is to meet clean air standards and protect public health, including ensuring benefits to environmental justice and disadvantaged communities. Now that the plan has been approved by CARB, it has been forwarded to the U.S. Environmental Protection Agency for its review. If approved by EPA, the plan becomes federally enforceable.

South Coast AQMD has initiated the development of the 2022 AQMP to address the attainment of the 2015 8-hour ozone standard (70 ppb) for South Coast Air Basin and Coachella Valley. To support the development of mobile source strategies for the 2022 AQMP, South Coast AQMD, in conjunction with California Air Resources Board, has established Mobile Source Working Groups which are open to all interested parties.

South Coast Air Quality Management District Rules

The AQMP for the basin establishes a program of rules and regulations administered by SCAQMD to obtain attainment of the state and federal standards. Some of the rules and regulations that apply to this Project include, but are not limited to, the following:

SCAQMD Rule 402 prohibits a person from discharging from any source whatsoever such quantities of air contaminants or other material which cause injury, detriment, nuisance, or annoyance to any considerable number of persons or to the public, or which endanger the comfort, repose, health or safety of any such persons or the public, or which cause, or have a natural tendency to cause, injury or damage to business or property.

SCAQMD Rule 403 governs emissions of fugitive dust during construction and operation activities. Compliance with this rule is achieved through application of standard Best Management Practices, such as application of water or chemical stabilizers to disturbed soils, covering haul vehicles, restricting vehicle speeds on unpaved roads to 15 miles per hour, sweeping loose dirt from paved site access roadways, cessation of construction activity when winds exceed 25 mph, and establishing a permanent ground cover on finished sites.

Rule 403 requires that fugitive dust be controlled with best available control measures so that the presence of such dust does not remain visible in the atmosphere beyond the property line of the emission source. In addition, Rule 403 requires implementation of dust suppression techniques to prevent fugitive dust from creating a nuisance off site. Applicable suppression techniques are indicated below and include but are not limited to the following:

- Apply nontoxic chemical soil stabilizers according to manufacturers' specifications to all inactive construction areas (previously graded areas in active for 10 days or more).
- Water active sites at least three times daily.
- Cover all trucks hauling dirt, sand, soil, or other loose materials, or maintain at least 2 feet of freeboard in accordance with the requirements of California Vehicle Code (CVC) section 23114.
- Pave construction access roads at least 100 feet onto the site from the main road.
- Reduce traffic speeds on all unpaved roads to 15 mph or less.
- Suspension of all grading activities when wind speeds (including instantaneous wind gusts) exceed 25 mph.
- Bumper strips or similar best management practices shall be provided where vehicles enter and
 exit the construction site onto paved roads or wash off trucks and any equipment leaving the site
 each trip.
- Replanting disturbed areas as soon as practical.
- During all construction activities, construction contractors shall sweep on-site and off-site streets if silt is carried to adjacent public thoroughfares, to reduce the amount of particulate matter on public streets.

SCAQMD Rule 1113 governs the sale, use, and manufacturing of architectural coating and limits the VOC content in paints and paint solvents. This rule regulates the VOC content of paints available during construction. Therefore, all paints and solvents used during construction and operation of Project must comply with Rule 1113.

Idling Diesel Vehicle Trucks – Idling for more than 5 minutes in any one location is prohibited within California borders.

Rule 2702. The SCAQMD adopted Rule 2702 on February 6, 2009, which establishes a voluntary air quality investment program from which SCAQMD can collect funds from parties that desire certified GHG emission reductions, pool those funds, and use them to purchase or fund GHG emission reduction projects within two years, unless extended by the Governing Board. Priority will be given to projects that result in co-benefit emission reductions of GHG emissions and criteria or toxic air pollutants within environmental justice areas. Further, this voluntary program may compete with the cap-and-trade program identified for implementation in CARB's Scoping Plan, or a Federal cap and trade program.

2.2 Greenhouse Gas Regulatory Setting

2.2.1 International

Many countries around the globe have made an effort to reduce GHGs since climate change is a global issue.

Intergovernmental Panel on Climate Change. In 1988, the United Nations and the World Meteorological Organization established the Intergovernmental Panel on Climate Change to assess the scientific, technical and socio-economic information relevant to understanding the scientific basis of risk of human-induced climate change, its potential impacts, and options for adaptation and mitigation.

United Nations. The United States participates in the United Nations Framework Convention on Climate Change (UNFCCC) (signed on March 21, 1994). Under the Convention, governments gather and share information on greenhouse gas emissions, national policies, and best practices; launch national strategies for addressing greenhouse gas emissions and adapting to expected impacts, including the provision of financial and technological support to developing countries; and cooperate in preparing for adaptation to the impacts of climate change.

The 2014 UN Climate Change Conference in Lima Peru provided a unique opportunity to engage all countries to assess how developed countries are implementing actions to reduce emissions.

Kyoto Protocol. The Kyoto Protocol is a treaty made under the UNFCCC and was the first international agreement to regulate GHG emissions. It has been estimated that if the commitments outlined in the Kyoto Protocol are met, global GHG emissions could be reduced by an estimated 5 percent from 1990 levels during the first commitment period of 2008 – 2012 (UNFCCC 1997). On December 8, 2012, the Doha Amendment to the Kyoto Protocol was adopted. The amendment includes: New commitments for Annex I Parties to the Kyoto Protocol who agreed to take on commitments in a second commitment period from 2013 – 2020; a revised list of greenhouse gases (GHG) to be reported on by Parties in the second commitment period; and Amendments to several articles of the Kyoto Protocol which specifically referenced issues pertaining to the first commitment period and which needed to be updated for the second commitment period.

2.2.2 National

Greenhouse Gas Endangerment. On December 2, 2009, the EPA announced that GHGs threaten the public health and welfare of the American people. The EPA also states that GHG emissions from on-road vehicles contribute to that threat. The decision was based on *Massachusetts v. EPA* (Supreme Court Case 05-1120) which argued that GHGs are air pollutants covered by the Clean Air Act and that the EPA has authority to regulate those emissions.

Clean Vehicles. Congress first passed the Corporate Average Fuel Economy law in 1975 to increase the fuel economy of cars and light duty trucks. The law has become more stringent over time. On May 19, 2009, President Obama put in motion a new national policy to increase fuel economy for all new cars and trucks sold in the United States. On April 1, 2010, the EPA and the Department of Transportation's

National Highway Safety Administration announced a joint final rule establishing a national program that would reduce greenhouse gas emissions and improve fuel economy for new cars and trucks sold in the United States.

The first phase of the national program would apply to passenger cars, light-duty trucks, and medium-duty passenger vehicles, covering model years 2012 through 2016. They require these vehicles to meet an estimated combined average emissions level of 250 grams of carbon dioxide per mile, equivalent to 35.5 miles per gallon if the automobile industry were to meet this carbon dioxide level solely through fuel economy improvements. Together, these standards would cut carbon dioxide emissions by an estimated 960 million metric tons and 1.8 billion barrels of oil over the lifetime of the vehicles sold under the program (model years 2012-2016). The second phase of the national program would involve proposing new fuel economy and greenhouse gas standards for model years 2017 – 2025 by September 1, 2011.

On October 25, 2010, the EPA and the U.S. Department of Transportation proposed the first national standards to reduce greenhouse gas emissions and improve fuel efficiency of heavy-duty trucks and buses. For combination tractors, the agencies are proposing engine and vehicle standards that begin in the 2014 model year and achieve up to a 20 percent reduction in carbon dioxide emissions and fuel consumption by the 2018 model year. For heavy-duty pickup trucks and vans, the agencies are proposing separate gasoline and diesel truck standards, which phase in starting in the 2014 model year and achieve up to a 10 percent reduction for gasoline vehicles and 15 percent reduction for diesel vehicles by 2018 model year (12 and 17 percent respectively if accounting for air conditioning leakage). Lastly, for vocational vehicles, the agencies are proposing engine and vehicle standards starting in the 2014 model year which would achieve up to a 10 percent reduction in fuel consumption and carbon dioxide emissions by 2018 model year.

Issued by the National Highway Traffic Safety Administration (NHTSA) and EPA in March 2020 (published on April 30, 2020, and effective after June 29, 2020), the Safer Affordable Fuel-Efficient Vehicles Rule would maintain the Corporate Average Fuel Economy (CAFÉ) and CO2 standards applicable in model year 2020 for model years 2021 through 2026. The estimated CAFÉ and CO2 standards for model year 2020 are 43.7 mpg and 204 grams of CO2 per mile for passenger cars and 31.3 mpg and 284 grams of CO2 per mile for light trucks, projecting an overall industry average of 37 mpg, as compared to 46.7 mpg under the standards issued in 2012. This Rule also excludes CO2- equivalent emission improvements associated with air conditioning refrigerants and leakage (and, optionally, offsets for nitrous oxide and methane emissions) after model year 2020.¹

Mandatory Reporting of Greenhouse Gases. On January 1, 2010, the EPA started requiring large emitters of heat-trapping emissions to begin collecting GHG data under a new reporting system. Under

National Highway Traffic Safety Administration (NHTSA) and U.S. Environmental Protection Agency (USEPA), 2018. Federal Register / Vol. 83, No. 165 / Friday, August 24, 2018 / Proposed Rules, The Safer Affordable Fuel-Efficient (SAFE) Vehicles Rule for Model Years 2021–2026 Passenger Cars and Light Trucks 2018. Available at: https://www.gpo.gov/fdsys/pkg/FR-2018-08-24/pdf/2018-16820.pdf.

the rule, suppliers of fossil fuels or industrial greenhouse gases, manufacturers of vehicles and engines, and facilities that emit 25,000 metric tons or more per year of greenhouse gas emissions are required to submit annual reports to the EPA.

Climate Adaption Plan. The EPA Plan identifies priority actions the Agency will take to incorporate considerations of climate change into its programs, policies, rules and operations to ensure they are effective under future climatic conditions. The following link provides more information on the EPA Plan: https://www.epa.gov/arc-x/planning-climate-change-adaptation

2.2.3 California

California Code of Regulations (CCR) Title 24, Part 6. CCR Title 24, Part 6: California's Energy Efficiency Standards for Residential and Nonresidential Buildings (Title 24) were first established in 1978 in response to a legislative mandate to reduce California's energy consumption. The standards are updated periodically to allow consideration and possible incorporation of new energy efficiency technologies and methods. Although it was not originally intended to reduce GHG emissions, electricity production by fossil fuels results in GHG emissions and energy efficient buildings require less electricity. Therefore, increased energy efficiency results in decreased GHG emissions.

The Energy Commission adopted 2008 Standards on April 23, 2008, and Building Standards Commission approved them for publication on September 11, 2008. These updates became effective on August 1, 2009. 2013, 2016, and 2019 standards have been approved and became effective July 1, 2014, January 1, 2016, and January 1, 2020, respectively.

California Code of Regulations (CCR) Title 24, Part 11.

All buildings for which an application for a building permit is submitted on or after January 1, 2020, must follow the 2019 standards. Energy efficient buildings require less electricity; therefore, increased energy efficiency reduces fossil fuel consumption and decreases greenhouse gas emissions. The following links provide more information on Title 24, Part 11:

https://www.dgs.ca.gov/BSC/Codeshttps://www.energy.ca.gov/sites/default/files/2020-03/Title 24 2019 Building Standards FAQ ada.pdf

California Green Building Standards.

On January 12, 2010, the State Building Standards Commission unanimously adopted updates to the California Green Building Standards Code, which went into effect on January 1, 2011. The Housing and Community Development (HCD) updated CALGreen through the 2015 Triennial Code Adoption Cycle, during the 2016 to 2017 fiscal year. During the 2019-2020 fiscal year, the Department of Housing and Community Development (HCD) updated CALGreen through the 2019 Triennial Code Adoption Cycle.

The Code is a comprehensive and uniform regulatory code for all residential, commercial and school buildings. CCR Title 24, Part 11: California Green Building Standards (Title 24) became effective in 2001 in response to continued efforts to reduce GHG emissions associated with energy consumption. CCR Title 24, Part 11 now require that new buildings reduce water consumption, employ building

commissioning to increase building system efficiencies, divert construction waste from landfills, and install low pollutant-emitting finish materials. One focus of CCR Title 24, Part 11 is water conservation measures, which reduce GHG emissions by reducing electrical consumption associated with pumping and treating water. CCR Title 24, Part 11 has approximately 52 nonresidential mandatory measures and an additional 130 provisions for optional use. Some key mandatory measures for commercial occupancies include specified parking for clean air vehicles, a 20 percent reduction of potable water use within buildings, a 50 percent construction waste diversion from landfills, use of building finish materials that emit low levels of volatile organic compounds, and commissioning for new, nonresidential buildings over 10,000 square feet.

The 2019 CalGreen Code includes the following changes and/or additional regulations:

Single-family homes built with the 2019 standards will use about 7 percent less energy due to energy efficiency measures versus those built under the 2016 standards. Once rooftop solar electricity generation is factored in, homes built under the 2019 standards will use about 53 percent less energy than those under the 2016 standards. Nonresidential buildings will use about 30 percent less energy due mainly to lighting upgrades².

HCD modified the best management practices for stormwater pollution prevention adding Section 5.106.2 for projects that disturb one or more acres of land. This section requires projects that disturb one acre or more of land or less than one acre of land but are part of a larger common plan of development or sale must comply with the post-construction requirement detailed in the applicable National Pollutant Discharge Elimination System (NPDES) General Permit for Stormwater Discharges Associated with Construction and Land Disturbance Activities issued by the State Water Resources Control Board. The NPDES permits require post-construction runoff (post-project hydrology) to match the preconstruction runoff (pre-project hydrology) with installation of post-construction stormwater management measures.

HCD added sections 5.106.4.1.3 and 5.106.4.1.5 in regard to bicycle parking. Section 5.106.4.1.3 requires new buildings with tenant spaces that have 10 or more tenant-occupants, provide secure bicycle parking for 5 percent of the tenant-occupant vehicular parking spaces with a minimum of one bicycle parking facility. In addition, Section 5.106.4.1.5 states that acceptable bicycle parking facility for Sections 5.106.4.1.2 through 5.106.4.1.4 shall be convenient from the street and shall meeting one of the following: (1) covered, lockable enclosures with permanently anchored racks for bicycles; (2) lockable bicycle rooms with permanently anchored racks; or (3) lockable, permanently anchored bicycle lockers.

HCD amended section 5.106.5.3.5 allowing future charging spaces to qualify as designated parking for clean air vehicles.

14

² https://ww2.energy.ca.gov/title24/2019standards/documents/2018_Title_24_2019_Building_Standards_FAQ.pdf

HCD updated section 5.303.3.3 in regard to showerhead flow rates. This update reduced the flow rate to 1.8 GPM.

HCD amended section 5.304.1 for outdoor potable water use in landscape areas and repealed sections 5.304.2 and 5.304.3. The update requires nonresidential developments to comply with a local water efficient landscape ordinance or the current California Department of Water Resource's' Model Water Efficient Landscape Ordinance (MWELO), whichever is more stringent. Some updates were also made in regard to the outdoor potable water use in landscape areas for public schools and community colleges.

HCD updated Section 5.504.5.3 in regard to the use of MERV filters in mechanically ventilated buildings. This update changed the filter use from MERV 8 to MERV 13.

The California Green Building Standards Code does not prevent a local jurisdiction from adopting a more stringent code as state law provides methods for local enhancements. The Code recognizes that many jurisdictions have developed existing construction and demolition ordinances, and defers to them as the ruling guidance provided, they provide a minimum 50-percent diversion requirement. The code also provides exemptions for areas not served by construction and demolition recycling infrastructure. State building code provides the minimum standard that buildings need to meet in order to be certified for occupancy. Enforcement is generally through the local building official. The following link provides more on CalGreen Building Standards:

http://www.bsc.ca.gov/Home/CALGreen.aspx

The 2022 CalGreen Code will be effective January 1, 2023.

Executive Order S-3-05. California Governor issued Executive Order S-3-05, GHG Emission, in June 2005, which established the following targets:

- By 2010, California shall reduce greenhouse gas emissions to 2000 levels;
- By 2020, California shall reduce greenhouse gas emissions to 1990 levels; and
- By 2050, California shall reduce greenhouse gas emissions to 80 percent below 1990 levels.

The executive order directed the secretary of the California Environmental Protection Agency (CalEPA) to coordinate a multi-agency effort to reduce GHG emissions to the target levels. To comply with the Executive Order, the secretary of CalEPA created the California Climate Action Team (CAT), made up of members from various state agencies and commissions. The team released its first report in March 2006. The report proposed to achieve the targets by building on the voluntary actions of businesses, local governments, and communities and through State incentive and regulatory programs.

Executive Order S-01-07. Executive Order S-1-07 was issued in 2007 and proclaims that the transportation sector is the main source of GHG emissions in the State, since it generates more than 40 percent of the State's GHG emissions. It establishes a goal to reduce the carbon intensity of transportation fuels sold in the State by at least ten percent by 2020. This Order also directs CARB to

determine whether this Low Carbon Fuel Standard (LCFS) could be adopted as a discrete early-action measure as part of the effort to meet the mandates in AB 32.

On April 23, 2009 CARB approved the proposed regulation to implement the low carbon fuel standard and began implementation on January 1, 2011. The low carbon fuel standard is anticipated to reduce GHG emissions by about 16 MMT per year by 2020. CARB approved some amendments to the LCFS in December 2011, which were implemented on January 1, 2013. In September 2015, the Board approved the re-adoption of the LCFS, which became effective on January 1, 2016, to address procedural deficiencies in the way the original regulation was adopted. In 2018, the Board approved amendments to the regulation, which included strengthening and smoothing the carbon intensity benchmarks through 2030 in-line with California's 2030 GHG emission reduction target enacted through SB 32, adding new crediting opportunities to promote zero emission vehicle adoption, alternative jet fuel, carbon capture and sequestration, and advanced technologies to achieve deep decarbonization in the transportation sector.

The LCFS is designed to encourage the use of cleaner low-carbon transportation fuels in California, encourage the production of those fuels, and therefore, reduce GHG emissions and decrease petroleum dependence in the transportation sector. Separate standards are established for gasoline and diesel fuels and the alternative fuels that can replace each. The standards are "back-loaded", with more reductions required in the last five years, than the first five years. This schedule allows for the development of advanced fuels that are lower in carbon than today's fuels and the market penetration of plug-in hybrid electric vehicles, battery electric vehicles, fuel cell vehicles, and flexible fuel vehicles. It is anticipated that compliance with the low carbon fuel standard will be based on a combination of both lower carbon fuels and more efficient vehicles.

Reformulated gasoline mixed with corn-derived ethanol at ten percent by volume and low sulfur diesel fuel represent the baseline fuels. Lower carbon fuels may be ethanol, biodiesel, renewable diesel, or blends of these fuels with gasoline or diesel as appropriate. Compressed natural gas and liquefied natural gas also may be low carbon fuels. Hydrogen and electricity, when used in fuel cells or electric vehicles are also considered as low carbon fuels for the low carbon fuel standard.

SB 97. Senate Bill 97 (SB 97) was adopted August 2007 and acknowledges that climate change is a prominent environmental issue that requires analysis under CEQA. SB 97 directed the Governor's Office of Planning and Research (OPR), which is part of the State Resource Agency, to prepare, develop, and transmit to CARB guidelines for the feasible mitigation of GHG emissions or the effects of GHG emissions, as required by CEQA, by July 1, 2009. The Resources Agency was required to certify and adopt those guidelines by January 1, 2010.

Pursuant to the requirements of SB 97 as stated above, on December 30, 2009, the Natural Resources Agency adopted amendments to the state CEQA guidelines that address GHG emissions. The CEQA Guidelines Amendments changed 14 sections of the CEQA Guidelines and incorporate GHG language throughout the Guidelines. However, no GHG emissions thresholds of significance are provided and no

specific mitigation measures are identified. The GHG emission reduction amendments went into effect on March 18, 2010, and are summarized below:

- Climate action plans and other greenhouse gas reduction plans can be used to determine whether a project has significant impacts, based upon its compliance with the plan.
- Local governments are encouraged to quantify the greenhouse gas emissions of proposed projects, noting that they have the freedom to select the models and methodologies that best meet their needs and circumstances. The section also recommends consideration of several qualitative factors that may be used in the determination of significance, such as the extent to which the given Project complies with state, regional, or local GHG reduction plans and policies. OPR does not set or dictate specific thresholds of significance. Consistent with existing CEQA Guidelines, OPR encourages local governments to develop and publish their own thresholds of significance for GHG impacts assessment.
- When creating their own thresholds of significance, local governments may consider the thresholds
 of significance adopted or recommended by other public agencies, or recommended by experts.
- New amendments include guidelines for determining methods to mitigate the effects of greenhouse gas emissions in Appendix F of the CEQA Guidelines.
- OPR is clear to state that "to qualify as mitigation, specific measures from an existing plan must be identified and incorporated into the Project; general compliance with a plan, by itself, is not mitigation."
- OPR's emphasizes the advantages of analyzing GHG impacts on an institutional, programmatic level.
 OPR therefore approves tiering of environmental analyses and highlights some benefits of such an approach.
- Environmental impact reports (EIRs) must specifically consider a project's energy use and energy efficiency potential.

AB 32. The California State Legislature enacted AB 32, the California Global Warming Solutions Act of 2006. AB 32 requires that greenhouse gases emitted in California be reduced to 1990 levels by the year 2020. "Greenhouse gases" as defined under AB 32 include carbon dioxide, methane, nitrous oxide, hydrofluorocarbons, perfluorocarbons, and sulfur hexafluoride. CARB is the state agency charged with monitoring and regulating sources of greenhouse gases. AB 32 states the following:

Global warming poses a serious threat to the economic well-being, public health, natural resources, and the environment of California. The potential adverse impacts of global warming include the exacerbation of air quality problems, a reduction in the quality and supply of water to the state from the Sierra snowpack, a rise in sea levels resulting in the displacement of thousands of coastal businesses and residences, damage to marine ecosystems and the natural environment, and an increase in the incidences of infectious diseases, asthma, and other human health-related problems.

The CARB Board approved the 1990 greenhouse gas emissions level of 427 million metric tons of carbon dioxide equivalent (MMTCO2e) on December 6, 2007 (California Air Resources Board 2007). Therefore, emissions generated in California in 2020 are required to be equal to or less than 427 MMTCO2e. Emissions in 2020 in a "business as usual" scenario are estimated to be 596 MMTCO2e.

Under AB 32, CARB published its Final Expanded List of Early Action Measures to Reduce Greenhouse Gas Emissions in California. Discrete early action measures are currently underway or are enforceable by January 1, 2010. CARB has 44 early action measures that apply to the transportation, commercial, forestry, agriculture, cement, oil and gas, fire suppression, fuels, education, energy efficiency, electricity, and waste sectors. Of these early action measures, nine are considered discrete early action measures, as they are regulatory and enforceable by January 1, 2010. CARB estimates that the 44 recommendations are expected to result in reductions of at least 42 MMTCO2e by 2020, representing approximately 25 percent of the 2020 target.

CARB's Climate Change Scoping Plan (Scoping Plan) contains measures designed to reduce the State's emissions to 1990 levels by the year 2020 (California Air Resources Board 2008). The Scoping Plan identifies recommended measures for multiple greenhouse gas emission sectors and the associated emission reductions needed to achieve the year 2020 emissions target—each sector has a different emission reduction target. Most of the measures target the transportation and electricity sectors. As stated in the Scoping Plan, the key elements of the strategy for achieving the 2020 greenhouse gas target include:

- Expanding and strengthening existing energy efficiency programs as well as building and appliance standards;
- Achieving a statewide renewables energy mix of 33 percent;
- Developing a California cap-and-trade program that links with other Western Climate Initiative partner programs to create a regional market system;
- Establishing targets for transportation-related greenhouse gas emissions for regions throughout
 California and pursuing policies and incentives to achieve those targets;
- Adopting and implementing measures pursuant to existing State laws and policies, Including California's clean car standards, goods movement measures, and the Low Carbon Fuel Standard; and
- Creating targeted fees, including a public goods charge on water use, fees on high global warming
 potential gases, and a fee to fund the administrative costs of the State's long-term commitment to
 AB 32 implementation.

In addition, the Scoping Plan differentiates between "capped" and "uncapped" strategies. "Capped" strategies are subject to the proposed cap-and-trade program. The Scoping Plan states that the inclusion of these emissions within the cap-and trade program will help ensure that the year 2020 emission targets are met despite some degree of uncertainty in the emission reduction estimates for any individual measure. Implementation of the capped strategies is calculated to achieve a sufficient amount of reductions by 2020 to achieve the emission target contained in AB 32. "Uncapped" strategies that will not be subject to the cap-and-trade emissions caps and requirements are provided as a margin of safety by accounting for additional greenhouse gas emission reductions.⁴

Senate Bill 100. Senate Bill 100 (SB 100) requires 100 percent of total retail sales of electricity in California to come from eligible renewable energy resources and zero-carbon resources by December 31, 2045. SB 100 was adopted September 2018.

The interim thresholds from prior Senate Bills and Executive Orders would also remain in effect. These include Senate Bill 1078 (SB 1078), which requires retail sellers of electricity, including investor-owned utilities and community choice aggregators, to provide at least 20 percent of their supply from renewable sources by 2017. Senate Bill 107 (SB 107) which changed the target date to 2010. Executive Order S-14-08, which was signed on November 2008 and expanded the State's Renewable Energy Standard to 33 percent renewable energy by 2020. Executive Order S-21-09 directed CARB to adopt regulations by July 31, 2010 to enforce S-14-08. Senate Bill X1-2 codifies the 33 percent renewable energy requirement by 2020.

SB 375. Senate Bill 375 (SB 375) was adopted September 2008 and aligns regional transportation planning efforts, regional GHG emission reduction targets, and land use and housing allocation. SB 375 requires Metropolitan Planning Organizations (MPO) to adopt a sustainable communities strategy (SCS) or alternate planning strategy (APS) that will prescribe land use allocation in that MPOs Regional Transportation Plan (RTP). CARB, in consultation with each MPO, will provide each affected region with reduction targets for GHGs emitted by passenger cars and light trucks in the region for the years 2020 and 2035. These reduction targets will be updated every eight years but can be updated every four years if advancements in emissions technologies affect the reduction strategies to achieve the targets. CARB is also charged with reviewing each MPO's sustainable communities strategy or alternate planning strategy for consistency with its assigned targets.

The proposed Project is located within the Southern California Association of Governments (SCAG), which has authority to develop the SCS or APS. For the SCAG region, the targets set by CARB are at eight percent below 2005 per capita GHG emissions levels by 2020 and 13 percent below 2005 per capita GHG emissions levels by 2035. On April 4, 2012, SCAG adopted the 2012-2035 Regional Transportation Plan / Sustainable Communities Strategy (RTP/SCS), which meets the CARB emission reduction requirements.

On September 3, 2020, SCAG's Regional Council approved and fully adopted the Connect SoCal (2020–2045 Regional Transportation Plan/Sustainable Communities Strategy), and the addendum to the Connect SoCal Program Environmental Impact Report. Connect SoCal is a long-range visioning plan that builds upon and expands land use and transportation strategies established over several planning cycles to increase mobility options and achieve a more sustainable growth pattern. Connect SoCal outlines more than \$638 billion in transportation system investments through 2045. Connect SoCal is supported by a combination of transportation and land use strategies that help the region achieve state greenhouse gas emission reduction goals and federal Clean Air Act requirements, preserve open space areas, improve public health and roadway safety, support our vital goods movement industry and utilize resources more efficiently. By integrating the Forecasted Development Pattern with a suite of financially constrained transportation investments, Connect SoCal can reach the regional target of reducing greenhouse gases, or GHGs, from autos and light-duty trucks by 8 percent per capita by 2020, and 19 percent by 2035 (compared to 2005 levels).

City and County land use policies, including General Plans, are not required to be consistent with the RTP and associated SCS or APS. However, new provisions of CEQA would incentivize, through streamlining

and other provisions, qualified projects that are consistent with an approved SCS or APS and categorized as "transit priority projects."

Assembly Bill 939, Assembly Bill, and Senate Bill 1374. Assembly Bill 939 (AB 939) requires that each jurisdiction in California to divert at least 50 percent of its waste away from landfills, whether through waste reduction, recycling or other means. AB 341 requires at least 75 percent of generated waste be source reduced, recycled, or composted by the year 2020. Senate Bill 1374 (SB 1374) requires the California Integrated Waste Management Board to adopt a model ordinance by March 1, 2004 suitable for adoption by any local agency to require 50 to 75 percent diversion of construction and demolition of waste materials from landfills.

Executive Order S-13-08. Executive Order S-13-08 indicates that "climate change in California during the next century is expected to shift precipitation patterns, accelerate sea level rise and increase temperatures, thereby posing a serious threat to California's economy, to the health and welfare of its population and to its natural resources." Pursuant to the requirements in the order, the 2009 California Climate Adaptation Strategy (California Natural Resource Agency 2009) was adopted, which is the "... first statewide, multi-sector, region-specific, and information-based climate change in California, identifying and exploring strategies to adapt to climate change, and specifying a direction for future research.

Executive Order B-30-15. Executive Order B-30-15, establishing a new interim statewide greenhouse gas emission reduction target to reduce greenhouse gas emissions to 40 percent below 1990 levels by 2030, was signed by Governor Brown in April 2015.

Executive Order B-29-15. Executive Order B-29-15, mandates a statewide 25% reduction in potable water usage and was signed into law on April 1, 2015.

Executive Order B-37-16. Executive Order B-37-16, continuing the State's adopted water reduction, was signed into law on May 9, 2016. The water reduction builds off the mandatory 25% reduction called for in EO B-29-15.

Executive Order N-79-20. Executive Order N-79-20 was signed into law on September 23, 2020 and mandates 100 percent of in-state sales of new passenger cars and trucks be zero-emission by 2035; 100 percent of medium- and heavy-duty vehicles in the state be zero-emission vehicles by 2045 for all operations where feasible and by 2035 for drayage trucks; and to transition to 100 percent zero-emission off-road vehicles and equipment by 2035 where feasible.

2.2.4 South Coast Air Quality Management District

The Project is within the South Coast Air Basin, which is under the jurisdiction of SCAQMD. SCAQMD Regulation XXVII currently includes three rules:

• The purpose of Rule 2700 is to define terms and post global warming potentials.

- The purpose of Rule 2701, SoCal Climate Solutions Exchange, is to establish a voluntary program to
 encourage, quantify, and certify voluntary, high quality certified greenhouse gas emission reductions
 in the SCAQMD.
- Rule 2702, Greenhouse Gas Reduction Program, was adopted on February 6, 2009. The purpose of
 this rule is to create a Greenhouse Gas Reduction Program for greenhouse gas emission reductions
 in the SCAQMD. The SCAQMD will fund projects through contracts in response to requests for
 proposals or purchase reductions from other parties.

SCAQMD Threshold Development

The SCAQMD has established recommended significance thresholds for greenhouse gases for local lead agency consideration ("SCAQMD draft local agency threshold"). SCAQMD has published a five-tiered draft GHG threshold which includes a 10,000 metric ton of CO₂e per year for stationary/industrial sources and 3,000 metric tons of CO₂e per year significance threshold for residential/commercial projects (South Coast Air Quality Management District 2010c). Tier 3 is anticipated to be the primary tier by which the SCAQMD will determine significance for projects. The Tier 3 screening level for stationary sources is based on an emission capture rate of 90 percent for all new or modified projects. A 90-precent emission capture rate means that 90 percent of total emissions from all new or modified stationary source projects would be subject to CEQA analysis. The 90-percent capture rate GHG significance screening level in Tier 3 for stationary sources was derived using the SCAQMD's annual Emissions Reporting Program.

The current draft thresholds consist of the following tiered approach:

- Tier 1 consists of evaluating whether or not the Project qualifies for any applicable exemption under CEQA.
- Tier 2 consists of determining whether or not the Project is consistent with a greenhouse gas reduction plan. If a project is consistent with a qualifying local greenhouse gas reduction plan, it does not have significant greenhouse gas emissions.
- Tier 3 consists of screening values, which the lead agency can choose but must be consistent. A
 project's construction emissions are averaged over 30 years and are added to a project's operational
 emissions. If a project's emissions are under one of the following screening thresholds, then the
 project is less than significant:
 - All land use types: 3,000 MTCO2e per year; and
 - Based on land use types: residential is 3,500 MTCO2e per year; commercial is 1,400 MTCO2e per year; and mixed use is 3,000 MTCO2e per year
- Tier 4 has the following options:
 - Option 1: Reduce emissions from business as usual by a certain percentage; this percentage is currently undefined;
 - Option 2: Early implementation of applicable AB 32 Scoping Plan measures;
 - Option 3: Year 2020 target for service populations (SP), which includes residents and employees:
 4.8 MTCO2e/SP/year for projects and 6.6 MTCO2e/SP/year for plans; or
 - Option 3, 2035 target: 3.0 MTCO2e/SP/year for projects and 4.1 MTCO2e/SP/year for plans

Tier 5 involves mitigation offsets to achieve target significance threshold.

In addition, SCAQMD methodology for project construction is to average GHG emissions over 30-years and then add them to the Project's operational emissions to determine if the Project would exceed the screening values listed above.

2.2.5 County of San Bernardino

County of San Bernardino Climate Action Plan

The County of San Bernardino adopted its "Greenhouse Gas Emissions Reduction Plan" in December in 2011. An update to the GHG Emissions Development Review Process was made in 2015. The purpose of the GHG Plan is to reduce the County's internal and external GHG emissions by 15 percent below current (2011) levels by year 2020. The GHG Plan includes a two-tiered development review procedure to determine if a project could result in a significant impact related greenhouse gas emissions or otherwise comply with the Plan pursuant to Section 15183.5 of the state CEQA Guidelines. The City of San Bernardino is a participant in the Plan.

The initial screening procedure is to determine if a project will emit 3,000 metric tons of carbon dioxide equivalent (MTCO2e) per year or more. Projects that do not exceed this threshold require no further climate change analysis. Projects exceeding this threshold must meet a minimum 31 percent emissions reduction in order to garner a less than significant determination. This can be met by either (1) achieving 100 points from a menu of mitigation options provided in the GHG Plan or (2) quantifying proposed reduction measures. Projects failing to meet the 31 percent reduction threshold would have a potentially significant impact related to climate change and greenhouse gas emissions. An update to the GHG Emissions Development Review Process was made in March 2015 to both improve upon the menu of options available in the screening tables and to bring performance standards up to current code.

Therefore, to determine whether the Project's GHG emissions are significant, this analysis uses the County of San Bernardino and SCAQMD draft local agency tier 3 threshold screening threshold of 3,000 MTCO2e per year for all land use types.

The Project will be subject to the latest requirements of the California Green Building and Title 24 Energy Efficiency Standards (currently 2022) which would reduce Project-related greenhouse gas emissions.

2.3 Energy Regulatory Setting

Federal and state agencies regulate energy use and consumption through various means and programs. On the federal level, the United States Department of Transportation, the United States Department of Energy, and the United States Environmental Protection Agency are three federal agencies with substantial influence over energy policies and programs. On the state level, the PUC and the California Energy Commissions (CEC) are two agencies with authority over different aspects of energy. Relevant federal and state energy-related laws and plans are summarized below.

2.3.1 Federal Regulations

Corporate Average Fuel Economy (CAFÉ) Standards

First established by the U.S. Congress in 1975, the Corporate Average Fuel Economy (CAFÉ) standards reduce energy consumption by increasing the fuel economy of cars and light trucks. The National Highway Traffic Safety Administration (NHTSA) and U.S. Environmental Protection Agency (USEPA) jointly administer the CAFÉ standards. The U.S. Congress has specified that CAFÉ standards must be set at the "maximum feasible level" with consideration given for: (1) technological feasibility; (2) economic practicality; (3) effect of other standards on fuel economy; and (4) need for the nation to conserve energy.³

Issued by NHTSA and EPA in March 2020 (published on April 30, 2020 and effective after June 29, 2020), the Safer Affordable Fuel-Efficient Vehicles Rule would maintain the CAFÉ and CO2 standards applicable in model year 2020 for model years 2021 through 2026. The estimated CAFÉ and CO2 standards for model year 2020 are 43.7 mpg and 204 grams of CO2 per mile for passenger cars and 31.3 mpg and 284 grams of CO2 per mile for light trucks, projecting an overall industry average of 37 mpg, as compared to 46.7 mpg under the standards issued in 2012.⁴

Intermodal Surface transportation Efficiency Act of 1991 (ISTEA)

The Intermodal Surface Transportation Efficiency Act of 1991 (ISTEA) promoted the development of inter-modal transportation systems to maximize mobility as well as address national and local interests in air quality and energy. ISTEA contained factors that Metropolitan Planning Organizations (MPOs) were to address in developing transportation plans and programs, including some energy-related factors. To meet the new ISTEA requirements, MPOs adopted explicit policies defining the social, economic, energy, and environmental values guiding transportation decisions.

The Transportation Equity Act of the 21st Century (TEA-21)

The Transportation Equity Act for the 21st Century (TEA-21) was signed into law in 1998 and builds upon the initiatives established in the ISTEA legislation, discussed above. TEA-21 authorizes highway, highway safety, transit, and other efficient surface transportation programs. TEA-21 continues the program structure established for highways and transit under ISTEA, such as flexibility in the use of funds, emphasis on measures to improve the environment, and focus on a strong planning process as the foundation of good transportation decisions. TEA-21 also provides for investment in research and its application to maximize the performance of the transportation system through, for example,

³ https://www.nhtsa.gov/lawsregulations/corporate-average-fuel-economy.

⁴ National Highway Traffic Safety Administration (NHTSA) and U.S. Environmental Protection Agency (USEPA), 2018. Federal Register / Vol. 83, No. 165 / Friday, August 24, 2018 / Proposed Rules, The Safer Affordable Fuel-Efficient (SAFE) Vehicles Rule for Model Years 2021–2026 Passenger Cars and Light Trucks 2018. Available at: https://www.epa.gov/regulations-emissions-vehicles-and-engines/safer-affordable-fuel-efficient-safe-vehicles-final-rule.

deployment of Intelligent Transportation Systems, to help improve operations and management of transportation systems and vehicle safety.

2.3.2 State Regulations

Integrated Energy Policy Report (IEPR)

Senate Bill 1389 requires the California Energy Commission (CEC) to prepare a biennial integrated energy policy report that assesses major energy trends and issues facing the State's electricity, natural gas, and transportation fuel sectors and provides policy recommendations to conserve resources; protect the environment; ensure reliable, secure, and diverse energy supplies; enhance the state's economy; and protect public health and safety. The Energy Commission prepares these assessments and associated policy recommendations every two years, with updates in alternate years, as part of the Integrated Energy Policy Report.

The 2019 Integrated Energy Policy Report (2019 IEPR) was adopted February 20, 2020, and continues to work towards improving electricity, natural gas, and transportation fuel energy use in California. The 2019 IEPR focuses on a variety of topics such as decarbonizing buildings, integrating renewables, energy efficiency, energy equity, integrating renewable energy, updates on Southern California electricity reliability, climate adaptation activities for the energy sector, natural gas assessment, transportation energy demand forecast, and the California Energy Demand Forecast.⁵

The 2020 IEPR was adopted March 23, 2021 and identifies actions the state and others can take to ensure a clean. Affordable, and reliable energy system. In 2020, the IEPR focuses on California's transportation future and the transition to zero-emission vehicles, examines microgrids, lessons learned form a decade of state-supported research, and stakeholder feedback on the potential of microgrids to contribute to a lean and resilient energy system; and reports on California's energy demand outlook, updated to reflect the global pandemic and help plan for a growth in zero-emission plug in electric vehicles.⁶

State of California Energy Plan

The CEC is responsible for preparing the State Energy Plan, which identifies emerging trends related to energy supply, demand, conservation, public health and safety, and the maintenance of a healthy economy. The Plan calls for the state to assist in the transformation of the transportation system to improve air quality, reduce congestion, and increase the efficient use of fuel supplies with the least environmental and energy costs. To further this policy, the plan identifies a number of strategies,

⁵ California Energy Commission. Final 2019 Integrated Energy Policy Report. February 20, 2020. https://www.energy.ca.gov/data-reports/reports/integrated-energy-policy-report/2019-integrated-energy-policy-report

⁶ California Energy Commission. Final 2020 Integrated Energy Policy Report. March 23, 2020. https://www.energy.ca.gov/data-reports/reports/integrated-energy-policy-report/2020-integrated-energy-policy-report-update

including assistance to public agencies and fleet operators and encouragement of urban designs that reduce vehicle miles traveled and accommodate pedestrian and bicycle access.

California Building Standards Code (Title 24)

<u>California Building Energy Efficiency Standards (Title 24, Part 6)</u>

The California Building Energy Efficiency Standards for Residential and Nonresidential Buildings (California Code of Regulations, Title 24, Part 6) were adopted to ensure that building construction and system design and installation achieve energy efficiency and preserve outdoor and indoor environmental quality. The newest California Building Energy Efficiency Standards (Title 24 standards) are the 2022 Title 24 standards, which become effective on January 1, 2023. The 2019 Title 24 standards, which are currently in place, include efficiency improvements to the lighting and efficiency improvements to the non-residential standards include alignment with the American Society of Heating and Air-Conditioning Engineers.

All buildings for which an application for a building permit is submitted on or after January 1, 2020 must follow the 2019 standards. The 2016 residential standards were estimated to be approximately 28 percent more efficient than the 2013 standards, whereas the 2019 residential standards are estimated to be approximately 7 percent more efficient than the 2016 standards. Furthermore, once rooftop solar electricity generation is factored in, 2019 residential standards are estimated to be approximately 53 percent more efficient than the 2016 standards. Under the 2019 standards, nonresidential buildings are estimated to be approximately 30 percent more efficient than the 2016 standards. Energy efficient buildings require less electricity; therefore, increased energy efficiency reduces fossil fuel consumption and decreases greenhouse gas emissions.

California Building Energy Efficiency Standards (Title 24, Part 11)

The 2022 California Green Building Standards Code (California Code of Regulations, Title 24, Part 11), commonly referred to as the CALGreen Code, goes into effect on January 1, 2023. The 2022 CALGreen Code includes mandatory measures for non-residential development related to site development; energy efficiency; water efficiency and conservation; material conservation and resource efficiency; and environmental quality.

The Department of Housing and Community Development (HCD) updated CALGreen through the 2022 Triennial Code Adoption Cycle. HCD added sections 5.106.5.2, 5.106.5.3, and 5. 106.5.4 in regards to parking and readiness for clean air and electric vehicles; relocated thermal insulation and acoustical ceilings and wall panels from voluntary to mandatory in section 5.504.4.7 and 5.504.4.8; and amended shade tree requirements in section 5.106.12.

Senate Bill 100

Senate Bill 100 (SB 100) requires 100 percent of total retail sales of electricity in California to come from eligible renewable energy resources and zero-carbon resources by December 31, 2045. SB 100 was adopted September 2018.

The interim thresholds from prior Senate Bills and Executive Orders would also remain in effect. These include Senate Bill 1078 (SB 1078), which requires retail sellers of electricity, including investor-owned utilities and community choice aggregators, to provide at least 20 percent of their supply from renewable sources by 2017. Senate Bill 107 (SB 107) which changed the target date to 2010. Executive Order S-14-08, which was signed on November 2008 and expanded the State's Renewable Energy Standard to 33 percent renewable energy by 2020. Executive Order S-21-09 directed the CARB to adopt regulations by July 31, 2010 to enforce S-14-08. Senate Bill X1-2 codifies the 33 percent renewable energy requirement by 2020.

Senate Bill 350

Senate Bill 350 (SB 350) was signed into law October 7, 2015, SB 350 increases California's renewable electricity procurement goal from 33 percent by 2020 to 50 percent by 2030. This will increase the use of Renewables Portfolio Standard (RPS) eligible resources, including solar, wind, biomass, geothermal, and others. In addition, SB 350 requires the state to double statewide energy efficiency savings in electricity and natural gas end uses by 2030. To help ensure these goals are met and the greenhouse gas emission reductions are realized, large utilities will be required to develop and submit Integrated Resource Plans (IRPs). These IRPs will detail how each entity will meet their customers resource needs, reduce greenhouse gas emissions and ramp up the deployment of clean energy resources.

Assembly Bill 32

In 2006 the California State Legislature adopted Assembly Bill 32 (AB 32), the California Global Warming Solutions Act of 2006. AB 32 requires CARB, to adopt rules and regulations that would achieve GHG emissions equivalent to statewide levels in 1990 by 2020 through an enforceable statewide emission cap which will be phased in starting in 2012. Emission reductions shall include carbon sequestration projects that would remove carbon from the atmosphere and best management practices that are technologically feasible and cost effective.

Assembly Bill 1493/Pavley Regulations

California Assembly Bill 1493 enacted on July 22, 2002, required CARB to develop and adopt regulations that reduce GHGs emitted by passenger vehicles and light duty trucks. In 2005, the CARB submitted a "waiver" request to the EPA from a portion of the federal Clean Air Act in order to allow the State to set more stringent tailpipe emission standards for CO₂ and other GHG emissions from passenger vehicles and light duty trucks. On December 19, 2007 the EPA announced that it denied the "waiver" request. On January 21, 2009, CARB submitted a letter to the EPA administrator regarding the State's request to reconsider the waiver denial. The EPA approved the waiver on June 30, 2009.

Executive Order S-1-07/Low Carbon Fuel Standard

Executive Order S-1-07 was issued in 2007 and proclaims that the transportation sector is the main source of GHG emissions in the State, since it generates more than 40 percent of the State's GHG emissions. It establishes a goal to reduce the carbon intensity of transportation fuels sold in the State by at least ten percent by 2020. This Order also directs CARB to determine whether this Low Carbon Fuel

Standard (LCFS) could be adopted as a discrete early-action measure as part of the effort to meet the mandates in AB 32.

On April 23, 2009 CARB approved the proposed regulation to implement the low carbon fuel standard and began implementation on January 1, 2011. The low carbon fuel standard is anticipated to reduce GHG emissions by about 16 MMT per year by 2020. CARB approved some amendments to the LCFS in December 2011, which were implemented on January 1, 2013. In September 2015, the Board approved the re-adoption of the LCFS, which became effective on January 1, 2016, to address procedural deficiencies in the way the original regulation was adopted. In 2018, the Board approved amendments to the regulation, which included strengthening and smoothing the carbon intensity benchmarks through 2030 in-line with California's 2030 GHG emission reduction target enacted through SB 32, adding new crediting opportunities to promote zero emission vehicle adoption, alternative jet fuel, carbon capture and sequestration, and advanced technologies to achieve deep decarbonization in the transportation sector.

The LCFS is designed to encourage the use of cleaner low-carbon transportation fuels in California, encourage the production of those fuels, and therefore, reduce GHG emissions and decrease petroleum dependence in the transportation sector. Separate standards are established for gasoline and diesel fuels and the alternative fuels that can replace each. The standards are "back-loaded", with more reductions required in the last five years, than during the first five years. This schedule allows for the development of advanced fuels that are lower in carbon than today's fuels and the market penetration of plug-in hybrid electric vehicles, battery electric vehicles, fuel cell vehicles, and flexible fuel vehicles. It is anticipated that compliance with the low carbon fuel standard will be based on a combination of both lower carbon fuels and more efficient vehicles.

Reformulated gasoline mixed with corn-derived ethanol at ten percent by volume and low sulfur diesel fuel represent the baseline fuels. Lower carbon fuels may be ethanol, biodiesel, renewable diesel, or blends of these fuels with gasoline or diesel as appropriate. Compressed natural gas and liquefied natural gas also may be low carbon fuels. Hydrogen and electricity, when used in fuel cells or electric vehicles are also considered as low carbon fuels for the low carbon fuel standard.

Executive Order N-79-20.

Executive Order N-79-20 was signed into law on September 23, 2020 and mandates 100 percent of instate sales of new passenger cars and trucks be zero-emission by 2035; 100 percent of medium- and heavy-duty vehicles in the state be zero-emission vehicles by 2045 for all operations where feasible and by 2035 for drayage trucks; and to transition to 100 percent zero-emission off-road vehicles and equipment by 2035 where feasible.

California Air Resources Board

CARB's Advanced Clean Cars Program

Closely associated with the Pavley regulations, the Advanced Clean Cars emissions control program was approved by CARB in 2012. The program combines the control of smog, soot, and GHGs with

requirements for greater numbers of zero-emission vehicles for model years 2015–2025. The components of the Advanced Clean Cars program include the Low-Emission Vehicle (LEV) regulations that reduce criteria pollutants and GHG emissions from light- and medium-duty vehicles, and the Zero-Emission Vehicle (ZEV) regulation, which requires manufacturers to produce an increasing number of pure ZEVs (meaning battery electric and fuel cell electric vehicles), with provisions to also produce plug-in hybrid electric vehicles (PHEV) in the 2018 through 2025 model years.⁷

Airborne Toxic Control Measure to Limit Diesel-Fueled Commercial Motor Vehicle Idling

The Airborne Toxic Control Measure to Limit Diesel-Fueled Commercial Motor Vehicle Idling (Title 13, California Code of Regulations, Division 3, Chapter 10, Section 2435) was adopted to reduce public exposure to diesel particulate matter and other air contaminants by limiting the idling of diesel-fueled commercial motor vehicles. This section applies to diesel-fueled commercial motor vehicles with gross vehicular weight ratings of greater than 10,000 pounds that are or must be licensed for operation on highways. Reducing idling of diesel-fueled commercial motor vehicles reduces the amount of petroleum-based fuel used by the vehicle.

Regulation to Reduce Emissions of Diesel Particulate Matter, Oxides of Nitrogen, and other Criteria Pollutants, form In-Use Heavy-Duty Diesel-Fueled Vehicles

The Regulation to Reduce Emissions of Diesel Particulate Matter, Oxides of Nitrogen and other Criteria Pollutants, from In-Use Heavy-Duty Diesel-Fueled Vehicles (Title 13, California Code of Regulations, Division 3, Chapter 1, Section 2025) was adopted to reduce emissions of diesel particulate matter, oxides of nitrogen (NO_X) and other criteria pollutants from in-use diesel-fueled vehicles. This regulation is phased, with full implementation by 2023. The regulation aims to reduce emissions by requiring the installation of diesel soot filters and encouraging the retirement, replacement, or repower of older, dirtier engines with newer emission-controlled models. The newer emission controlled models would use petroleum-based fuel in a more efficient manner.

Sustainable Communities Strategy

The Sustainable Communities and Climate Protection Act of 2008, or Senate Bill 375 (SB 375), coordinates land use planning, regional transportation plans, and funding priorities to help California meet the GHG reduction mandates established in AB 32.

Senate Bill 375 (SB 375) was adopted September 2008 and aligns regional transportation planning efforts, regional GHG emission reduction targets, and land use and housing allocation. SB 375 requires Metropolitan Planning Organizations (MPO) to adopt a sustainable communities strategy (SCS) or alternate planning strategy (APS) that will prescribe land use allocation in that MPOs Regional Transportation Plan (RTP). CARB, in consultation with each MPO, will provide each affected region with

⁷ California Air Resources Board, California's Advanced Clean Cars Program, January 18, 2017. www.arb.ca.gov/msprog/acc/acc.htm.

reduction targets for GHGs emitted by passenger cars and light trucks in the region for the years 2020 and 2035. These reduction targets will be updated every eight years but can be updated every four years if advancements in emissions technologies affect the reduction strategies to achieve the targets. CARB is also charged with reviewing each MPO's sustainable communities strategy or alternate planning strategy for consistency with its assigned targets.

3.0 Setting

3.3 Existing Physical Setting

The Project site is located within the County of San Bernardino, which is part of the South Coast Air Basin (SCAB) that includes all of Orange County as well as the non-desert portions of Los Angeles, Riverside, and San Bernardino Counties. The South Coast Air Basin is located on a coastal plain with connecting broad valleys and low hills to the east. Regionally, the South Coast Air Basin is bounded by the Pacific Ocean to the southwest and high mountains to the east forming the inland perimeter.

3.3.1 Local Climate and Meteorology

Dominant airflows provide the driving mechanism for transport and dispersion of air pollution. The mountains surrounding the region form natural horizontal barriers to the dispersion of air contaminants. Air pollution created in the coastal areas and around the Los Angeles area is transported inland until it reaches the mountains where the combination of mountains and inversion layers generally prevent further dispersion. This poor ventilation results in a gradual degradation of air quality from the coastal areas to inland areas. Air stagnation may occur during the early evening and early morning periods of transition between day and nighttime flows. The region also experiences periods of hot, dry winds from the desert, known as Santa Ana winds. If the Santa Ana winds are strong, they can surpass the sea breeze, which blows from the ocean to the land, and carry the suspended dust and pollutants out to the ocean. If the winds are weak, they are opposed by the sea breeze and cause stagnation, resulting in high pollution events.

The annual average temperature varies little throughout much of the basin, ranging from the low to middle 60s, measured in degrees Fahrenheit (°F). With more pronounced oceanic influence, coastal areas show less variability in annual minimum and maximum temperatures than inland areas where the Project site is located. The majority of the annual rainfall in the basin occurs between November and April. Summer rainfall is minimal and is generally limited to scattered thunderstorms in the coastal regions and slightly heavier showers in the eastern portion of the basin along the coastal side of the mountains. Year-to-year patterns in rainfall are unpredictable because of fluctuations in the weather.

Temperature inversions limit the vertical depth through which pollution can be mixed. Among the most common temperature inversions in the basin are radiation inversions, which form on clear winter nights when cold air off mountains sink to the valley floor while the air aloft over the valley remains warm. These inversions, in conjunction with calm winds, trap pollutants near the source. Other types of temperature inversions that affect the basin include marine, subsidence, and high-pressure inversions.

Summers are often periods of hazy visibility and occasionally unhealthful air. Strong temperature inversions may occur that limit the vertical depth through which air pollution can be dispersed. Air pollutants concentrate because they cannot rise through the inversion layer and disperse. These inversions are more common and persistent during the summer months. Over time, sunlight produces photochemical reactions within this inversion layer that creates ozone, a particularly harmful air pollutant. Occasionally, strong thermal convections occur which allows the air pollutants to rise high

enough to pass over the mountains and ultimately dilute the smog cloudtrap pollutants such as automobile exhaust near their source. While these inversions may lead to air pollution "hot spots" in heavily developed coastal areas of the basin, there is not enough traffic in inland valleys to cause any winter air pollution problems. Despite light wind conditions, especially at night and in the early morning, winter is generally a period of good air quality in the Project vicinity.

In the winter, light nocturnal winds result mainly from the drainage of cool air off of the mountains toward the valley floor while the air aloft over the valley remains warm. This forms a type of inversion known as a radiation inversion. Such winds are characterized by stagnation and poor local mixing and trap pollutants such as automobile exhaust near their source. While these inversions may lead to air pollution "hot spots" in heavily developed coastal areas of the basin, there is not enough traffic to cause any winter air pollution problems. Despite light wind conditions, especially at night and in the early morning, winter is generally a period of good air quality in the Project vicinity.

The temperature and precipitation levels for the City of San Bernardino, the closest monitoring station to the Project site with available meteorological data, are in Table 3. Table 3 shows that August is typically the warmest month and January is typically the coolest month. Rainfall in the Project area varies considerably in both time and space. Almost all the annual rainfall comes from the fringes of mid-latitude storms from late November to early April, with summers being almost completely dry.

Table 3: Meteorological Summary

0.4 a malla	Temper	Temperature (°F)			
Month	Average High	Average Low	(inches)		
January	66.2	39.4	3.10		
February	68.1	41.6	3.45		
March	70.5	43.7	2.72		
April	75.9	47.2	1.28		
May	81.1	51.6	0.38		
June	88.6	55.5	0.09		
July	96.6	60.4	0.04		
August	96.5	61.0	0.16		
September	92.4	57.7	0.34		
October	83.4	51.3	0.64		
November	74.4	43.4	1.39		
December	67.7	39.4	2.49		
Annual Average	80.1	49.3	16.1		

Notes:

¹ Source: https://wrcc.dri.edu/cgi-bin/cliMAIN.pl?ca9847

3.1.2 Local Air Quality

The SCAQMD is divided into 38 air-monitoring areas with a designated ambient air monitoring station representative of each area. The Project site is located in the East San Bernardino Valley (Area 35). The nearest air monitoring station to the Project site with available air quality data is the San Bernardino 4th Street Station located approximately 1 mile northwest of the Project site; however, this location does

not provide all ambient weather data. Therefore, additional data was pulled from the SCAQMD historical data for the East San Bernardino Valley (Area 35) for both sulfur dioxide and carbon monoxide to provide the existing levels. Table 4 presents the monitored pollutant levels within the vicinity. However, it should be noted that due to the air monitoring station distance from the Project site, recorded air pollution levels at the air monitoring station reflect with varying degrees of accuracy, local air quality conditions at the Project site.

Table 4: Local Area Air Quality Levels from the San Bernardino 4th Street Monitoring Station

	Year				
Pollutant (Standard) ²	2018	2019	2020		
Ozone:					
Maximum 1-Hour Concentration (ppm)	0.138	0.127	0.162		
Days > CAAQS (0.09 ppm)	63	63	89		
Maximum 8-Hour Concentration (ppm)	0.116	0.114	0.128		
Days > NAAQS (0.07 ppm)	102	96	130		
Days > CAAQS (0.070 ppm)	107	96	132		
Carbon Monoxide:					
Maximum 1-Hour Concentration (ppm)	1.9	2.7	1.7		
Days > NAAQS (20 ppm)	0	0	0		
Maximum 8-Hour Concentration (ppm)	1.1	1.0	1.2		
Days > NAAQS (9 ppm)	0	0	0		
Nitrogen Dioxide:					
Maximum 1-Hour Concentration (ppm)	0.057	0.059	0.054		
Days > NAAQS (0.25 ppm)	0	0	0		
Sulfur Dioxide:					
Maximum 1-Hour Concentration (ppm) ³	0.003	0.002	0.003		
Days > CAAQS (0.04 ppm) ³	0	0	0		
Inhalable Particulates (PM10):					
Maximum 24-Hour Concentration (ug/m³)	130.2	112.7	174.8		
Days > NAAQS (150 ug/m³)	0	0	1		
Days > CAAQS (50 ug/m ³) ³	5	4	8		
Annual Average (ug/m³)	30.7	30.4	41.1		
Annual > NAAQS (50 ug/m³)	No	No	No		
Annual > CAAQS (20 ug/m³)	Yes	Yes	Yes		
Ultra-Fine Particulates (PM2.5):					
Maximum 24-Hour Concentration (ug/m³)	30.1	60.5	56.6		
Days > NAAQS (35 ug/m ³) ³	0	1	2		
Annual Average (ug/m³) ³	11.1	*	12.2		
Annual > NAAQS (15 ug/m ³) ³	No	*	No		
Annual > CAAQS (12 ug/m ³) ³	No	*	Yes		

¹ Source: obtained from https://www.aqmd.gov/home/air-quality/air-quality-data-studies/historical-data-by-year and /or https://www.arb.ca.gov/adam/topfour/topfour1.php

The monitoring data presented in Table 4 shows that ozone and particulate matter (PM10 and PM2.5) are the air pollutants of primary concern in the Project area, which are detailed below.

² CAAQS = California Ambient Air Quality Standard; NAAQS = National Ambient Air Quality Standard; ppm = parts per million

³ No data available.

Setting

Ozone

During the 2018 to 2020 monitoring period, the State 1-hour concentration standard for ozone has been exceeded between 63 and 89 days each year at the 4th Street Station. The State 8-hour concentration standard for ozone has been exceeded between 96 and 132 days each year over the past three years at the 4th Station. The Federal 8-hour concentration standard for ozone has been exceeded between 96 and 130 days each year over the past three years at the 4th Street Station.

Ozone is a secondary pollutant as it is not directly emitted. Ozone is the result of chemical reactions between other pollutants, most importantly hydrocarbons and NO₂, which occur only in the presence of bright sunlight. Pollutants emitted from upwind cities react during transport downwind to produce the oxidant concentrations experienced in the area. Many areas of the SCAQMD contribute to the ozone levels experienced at the monitoring station, with the more significant areas being those directly upwind.

Carbon Monoxide

CO is another important pollutant that is due mainly to motor vehicles. The East San Bernardino Valley Area did not record an exceedance of the state or federal 1-hour or 8-hour CO standards for the last three years.

Nitrogen Dioxide

The 4th Street Station did not record an exceedance of the State or Federal NO₂ standards for the last three years.

Sulfur Dioxide

The East San Bernardino Valley area did not record an exceedance of the State SO₂ standards for the last three years.

Particulate Matter

During the 2018 to 2020 monitoring period, State 24-hour concentration standard for PM10 was exceeded between 4 and 8 days each year at the 4th Street Station. Over the same time period the Federal 24-hour standard for PM10 was exceeded one day each in 2020 at the 4th Street Station.

During the 2018 to 2020 monitoring period, the Federal 24-hour standard for PM2.5 was exceeded 1 day in 2019 and 2 days in 2020 at the 4^{th} Street Station.

According to the EPA, some people are much more sensitive than others to breathing fine particles (PM10 and PM2.5). People with influenza, chronic respiratory and cardiovascular diseases, and the elderly may suffer worsening illness and premature death due to breathing these fine particles. People with bronchitis can expect aggravated symptoms from breathing in fine particles. Children may experience decline in lung function due to breathing in PM10 and PM2.5. Other groups considered sensitive are smokers and people who cannot breathe well through their noses. Exercising athletes are also considered sensitive because many breathe through their mouths during exercise.

3.1.3 Attainment Status

The EPA and CARB designate air basins where ambient air quality standards are exceeded as "nonattainment" areas. If standards are met, the area is designated as an "attainment" area. If there is inadequate or inconclusive data to make a definitive attainment designation, they are considered "unclassified." National nonattainment areas are further designated as marginal, moderate, serious, severe, or extreme as a function of deviation from standards. Each standard has a different definition, or 'form' of what constitutes attainment, based on specific air quality statistics. For example, the Federal 8-hour CO standard is not to be exceeded more than once per year; therefore, an area is in attainment of the CO standard if no more than one 8-hour ambient air monitoring values exceeds the threshold per year. In contrast, the federal annual PM2.5 standard is met if the three-year average of the annual average PM2.5 concentration is less than or equal to the standard. Table 5 lists the attainment status for the criteria pollutants in the basin.

Table 5: South Coast Air Basin Attainment Status

Pollutant	Standard ¹	Averaging Time	Designation ²	Attainment Date ³
1-Hour Ozone	NAAQS	1979 1-Hour (0.12 ppm)	Nonattainment (Extreme)	2/6/2023 (not attained) ⁴
1-Hour Ozone	CAAQS	1-Hour (0.09 ppm)	Nonattainment	N/A
	NAAQS	1997 8-Hour (0.08 ppm)	Nonattainment (Extreme)	6/15/2024
8-Hour Ozone ⁵	NAAQS	2008 8-Hour (0.075 ppm)	Nonattainment (Extreme)	7/20/2032
8-11001 O2011e	NAAQS	2015 8-Hour (0.070 ppm)	Nonattainment (Extreme)	8/3/2038
	CAAQS	8-Hour (0.070 ppm)	Nonattainment	Beyond 2032
со	NAAQS	1-Hour (35 ppm)	Attainment (Maintenance)	6/11/2007 (attained)
CO	CAAQS	8-Hour (9 ppm)	Attainment	6/11/2007 (attained)
	NAAQS	1-Hour (0.1 ppm)	Unclassifiable/Attainment	N/A (attained)
NO ₂ ⁶	NAAQS	Annual (0.053 ppm)	Attainment (Maintenance)	9/22/1998 (attained)
NO ₂ ·	CAAQS	1-hour (0.18 ppm) Annual (0.030 ppm)	Attainment	-
SO ₂ ⁷	NAAQS	1-Hour (75 ppb)	Designations Pending (expect Uncl./Attainment)	N/A (attained)
302	NAAQS	24-Hour (0.14 ppm) Annual (0.03 ppm)	Unclassifiable/Attainment	3/19/1979 (attained)
PM10	NAAQS	1987 24-Hour (150 μg/m³)	Attainment (Maintenance) ⁸	7/26/2013 (attained)
PIVITO	CAAQS	24-Hour (50 μg/m³) Annual (20 μg/m³)	Nonattainment	N/A
	NAAQS	2006 24-Hour (35 µg/m³)	Nonattainment (Serious)	12/31/2019
PM2.5 ⁹	NAAQS	1997 Annual (15.0 μg/m³)	Attainment	8/24/2016
	NAAQS	2021 Annual (12.0 μg/m³)	Nonattainment (Serious)	12/31/2025

Setting

	CAAQS	Annual (12.0 μg/m³)	Nonattainment	N/A
Lead	NAAQS	3-Months Rolling (0.15 μg/m³)	Nonattainment (Partial) ¹⁰	12/31/2015

Notes:

Source: http://www.aqmd.gov/docs/default-source/clean-air-plans/air-quality-management-plans/naaqs-caaqs-feb2016.pdf

- ¹ NAAQS = National Ambient Air Quality Standards, CAAQS = California Ambient Air Quality Standards
- 2 U.S. EPA often only declares Nonattainment areas; everywhere else is listed as Unclassifiable/Attainment or Unclassifiable.
- ³ A design value below the NAAQS for data through the full year or smog season prior to the attainment date is typically required for attainment demonstration.
- ⁴ 1-hour O3 standard (0.12 ppm) was revoked, effective June 15, 2005; however, the Basin has not attained this standard based on 2008-2010 data and is still subject to anti-backsliding requirements.
- ⁵ 1997 8-hour O3 standard (0.08 ppm) was reduced (0.075 ppm), effective May 27, 2008; the revoked 1997 O3 standard is still subject to anti-backsliding requirements.
- ⁶ New NO2 1-hour standard, effective August 2, 2010; attainment designations January 20, 2012; annual NO2 standard retained.
- ⁷ The 1971 annual and 24-hour SO2 standards were revoked, effective August 23, 2010; however, these 1971 standards will remain in effect until one year after U.S. EPA promulgates area designations for the 2010 SO2 1-hour standard. Area designations are still pending, with Basin expected to be designated Unclassifiable /Attainment.
- ⁸ Annual PM10 standard was revoked, effective December 18, 2006; 24-hour PM10 NAAQS deadline was 12/31/2006; SCAQMD request for attainment redesignation and PM10 maintenance plan was approved by U.S. EPA on June 26, 2013, effective July 26, 2013.
- 9 Attainment deadline for the 2006 24-Hour PM2.5 NAAQS (designation effective December 14, 2009) is December 31, 2019 (end of the 10^{th} calendar year after effective date of designations for Serious nonattainment areas). Annual PM2.5 standard was revised on January 15, 2013, effective March 18, 2013, from 15 to 12 μ g/m3. Designations effective April 15, 2015, so Serious area attainment deadline is December 31, 2025.
- ¹⁰ Partial Nonattainment designation Los Angeles County portion of Basin only for near-source monitors. Expect redesignation to attainment based on current monitoring data.

3.2 Greenhouse Gases

Constituent gases of the Earth's atmosphere, called atmospheric greenhouse gases (GHG), play a critical role in the Earth's radiation amount by trapping infrared radiation emitted from the Earth's surface, which otherwise would have escaped to space. Prominent greenhouse gases contributing to this process include carbon dioxide (CO_2), methane (CH_4), ozone, water vapor, nitrous oxide (N_2O), and chlorofluorocarbons (CFCs). This phenomenon, known as the Greenhouse Effect, is responsible for maintaining a habitable climate. Anthropogenic (caused or produced by humans) emissions of these greenhouse gases in excess of natural ambient concentrations are responsible for the enhancement of the Greenhouse Effect and have led to a trend of unnatural warming of the Earth's natural climate, known as global warming or climate change. Emissions of gases that induce global warming are attributable to human activities associated with industrial/manufacturing, agriculture, utilities, transportation, and residential land uses. Transportation is responsible for 41 percent of the State's greenhouse gas emissions, followed by electricity generation. Emissions of CO₂ and nitrous oxide (NO₂) are byproducts of fossil fuel combustion. Methane, a potent greenhouse gas, results from off-gassing associated with agricultural practices and landfills. Sinks of CO2, where CO2 is stored outside of the atmosphere, include uptake by vegetation and dissolution into the ocean. Table 6 provides a description of each of the greenhouse gases and their global warming potential.

Additional information is available: https://www.arb.ca.gov/cc/inventory/data/data.htm

Table 6: Description of Greenhouse Gases

Greenhouse Gas	Description and Physical Properties	Sources
Nitrous oxide	Nitrous oxide (N_20),also known as laughing gas is a colorless gas. It has a lifetime of 114 years. Its global warming potential is 298.	Microbial processes in soil and water, fuel combustion, and industrial processes. In addition to agricultural sources, some industrial processes (nylon production, nitric acid production) also emit N ₂ O.
Methane	Methane (CH ₄) is a flammable gas and is the main component of natural gas. It has a lifetime of 12 years. Its global warming potential is 25.	A natural source of CH ₄ is from the decay of organic matter. Methane is extracted from geological deposits (natural gas fields). Other sources are from the decay of organic material in landfills, fermentation of manure, and cattle farming.
Carbon dioxide	Carbon dioxide (CO ₂) is an odorless, colorless, natural greenhouse gas. Carbon dioxide's global warming potential is 1. The concentration in 2005 was 379 parts per million (ppm), which is an increase of about 1.4 ppm per year since 1960.	Natural sources include decomposition of dead organic matter; respiration of bacteria, plants, animals, and fungus; evaporation from oceans; and volcanic outgassing. Anthropogenic sources are from burning coal, oil, natural gas, and wood.
Chlorofluorocarbons	CFCs are nontoxic, nonflammable, insoluble, and chemically unreactive in the troposphere (the level of air at the earth's surface). They are gases formed synthetically by replacing all hydrogen atoms in methane or methane with chlorine and/or fluorine atoms. Global warming potentials range from 3,800 to 8,100.	Chlorofluorocarbons were synthesized in 1928 for use as refrigerants, aerosol propellants, and cleaning solvents. They destroy stratospheric ozone, therefore their production was stopped as required by the Montreal Protocol.
Hydrofluorocarbons	Hydrofluorocarbons (HFCs) are a group of greenhouse gases containing carbon, chlorine, and at least one hydrogen atom. Global warming potentials range from 140 to 11,700.	Hydrofluorocarbons are synthetic manmade chemicals used as a substitute for chlorofluorocarbons in applications such as automobile air conditioners and refrigerants.
Perfluorocarbons	Perfluorocarbons (PFCs) have stable molecular structures and only break down by ultraviolet rays about 60 kilometers above the Earth's surface. They have a lifetime 10,000 to 50,000 years. They have a global warming potential range of 6,200 to 9,500.	Two main sources of perfluorocarbons are primary aluminum production and semiconductor manufacturing.
Sulfur hexafluoride	Sulfur hexafluoride (SF ₆) is an inorganic, odorless, colorless, and nontoxic, nonflammable gas. It has a lifetime of 3,200 years. It has a high global warming potential, 23,900.	This gas is manmade and used for insulation in electric power transmission equipment, in the magnesium industry, in semiconductor manufacturing, and as a tracer gas for leak detection.

Notes:

^{1.} Sources: Intergovernmental Panel on Climate Change 2014a and Intergovernmental Panel on Climate Change 2014b. https://www.ipcc.ch/publications_and_data/ar4/wg1/en/ch2s2-10-2.html

3.3 Energy

3.3.1 Overview

California's estimated annual energy use as of 2019 included:

- Approximately 277,704 gigawatt hours of electricity;⁸
- Approximately 2,136,907 million cubic feet of natural gas per year (for the year 2018)⁹; and
- Approximately 23.2 billion gallons of transportation fuel (for the year 2015)¹⁰.

As of 2019, the year of most recent data currently available by the United States Energy Information Administration (EIA), energy use in California by demand sector was:

- Approximately 39.3 percent transportation;
- Approximately 23.2 percent industrial;
- Approximately 18.7 percent residential; and
- Approximately 18.9 percent commercial.¹¹

California's electricity in-state generation system generates approximately 200,475 gigawatt-hours each year. In 2019, California produced approximately 72 percent of the electricity it uses; the rest was imported from the Pacific Northwest (approximately 9 percent) and the U.S. Southwest (approximately 19 percent). Natural gas is the main source for electricity generation at approximately 42.97 percent of the total in-state electric generation system power as shown in Table 7.

<Table 7, next page>

⁸California Energy Commission. Energy Almanac. Total Electric Generation. [Online] 2020.

https://www.energy.ca.gov/data-reports/energy-almanac/california-electricity-data/2019-total-system-electric-generation.

⁹Natural Gas Consumption by End Use. U.S. Energy Information Administration. [Online] August 31, 20020.https://www.eia.gov/dnav/ng/ng_cons_sum_dcu_SCA_a.htm.

^oCalifornia Energy Commission. Revised Transportation Energy Demand Forecast 2018-2030. [Online] April 19, 2018. https://www.energy.ca.gov/assessments/

¹¹U.S. Energy Information Administration. California Energy Consumption by by End-Use Sector.
California State Profile and Energy Estimates.[Online] January 16, 2020 https://www.eia.gov/state/?sid=CA#tabs-2

Table 7: Total Electricity System Power (California 2019)

	California In-State	Percent of California	Northwest	Southwest	Total	Percent	California Power	Percent California
	Generation	In-State	Imports	Imports	Imports	of	Mix	Power
Fuel Type	(GWh)	Generation	(GWh)	(GWh)	(GWh)	Imports	(GWh)	Mix
Coal	248	0.12%	219	7,765	7,985	10.34%	8,233	2.96%
Natural Gas	86,136	42.97%	62	8,859	8,921	11.55%	95,057	34.23%
Nuclear	16,163	8.06%	39	8,743	8,782	11.37%	24,945	8.98%
Oil	36	0.02%	0	0	0	0.00%	36	0.01%
Other (Petroleum Coke/Waste Heat)	411	0.20%	0	11	11	0.01%	422	0.15%
Large Hydro	33,145	16.53%	6,387	1,071	7,458	9.66%	40,603	14.62%
Unspecified Sources of Power	0	0.00%	6,609	13,767	20,376	26.38%	20,376	7.34%
Renewables	64,336	32.09%	10,615	13,081	23,696	30.68%	88,032	31.70%
Biomass	5,851	2.92%	903	33	936	1.21%	6,787	2.44%
Geothermal	10,943	5.46%	99	2,218	2,318	3.00%	13,260	4.77%
Somall Hydro	5,349	2.67%	292	4	296	0.38%	5,646	2.03%
Solar	28,513	14.22%	282	5,295	5,577	7.22%	34,090	12.28%
Wind	13,680	6.82%	9,038	5,531	14,569	18.87%	28,249	10.17%
Total	200,475	100.00%	23,930	53,299	77,229	100.00%	277,704	100.00%

Notes:

A summary of and context for energy consumption and energy demands within the State is presented in "U.S. Energy Information Administration, California State Profile and Energy Estimates, Quick Facts" excerpted below:

- California was the seventh-largest producer of crude oil among the 50 states in 2018, and, as of January 2019, it ranked third in oil refining capacity.
- California is the largest consumer of jet fuel among the 50 states and accounted for one-fifth of the nation's jet fuel consumption in 2018.
- California's total energy consumption is the second-highest in the nation, but, in 2018, the State's
 per capita energy consumption ranked the fourth-lowest, due in part to its mild climate and its
 energy efficiency programs.
- In 2018, California ranked first in the nation as a producer of electricity from solar, geothermal, and biomass resources and fourth in the nation in conventional hydroelectric power generation.
- In 2018, large- and small-scale solar PV and solar thermal installations provided 19% of California's net electricity generation¹².

¹ Source: California Energy Commission. 2019 Total System electric Generation. https://www.energy.ca.gov/data-reports/energy-almanac/california-electricity-data/2019-total-system-electric-generation

¹² State Profile and Energy Estimates. Independent Statistics and Analysis. [Online] [Cited: January 16, 2020.] http://www.eia.gov/state/?sid=CA#tabs2.

As indicated above, California is one of the nation's leading energy-producing states, and California per capita energy use is among the nation's most efficient. Given the nature of the proposed project, the remainder of this discussion will focus on the three sources of energy that are most relevant to the project—namely, electricity and natural gas for building uses, and transportation fuel for vehicle trips associated with the proposed project.

3.3.2 Electricity and Natural Gas

Electricity would be provided to the project by Southern California Edison (SCE). SCE provides electric power to more than 15 million persons, within a service area encompassing approximately 50,000 square miles. SCE derives electricity from varied energy resources including: fossil fuels, hydroelectric generators, nuclear power plants, geothermal power plants, solar power generation, and wind farms. SCE also purchases from independent power producers and utilities, including out-of-state suppliers. Table 2 identifies SCE's specific proportional shares of electricity sources in 2019.

Table 8: SCE 2019 Power Content Mix

Energy Resources	2019 SDG&E Power Mix
Eligible Renewable ¹	31.7%
Biomass & Biowaste	2.4%
Geothermal	4.8%
Eligible Hydroelectric	2.0%
Solar	12.3%
Wind	10.2%
Coal	3.0%
Large Hydroelectric	14.6%
Natural Gas	34.2%
Nuclear	9.0%
Other	0.2%
Unspecified Sources of power ²	7.3%
Total	100%

Notes:

Source: 'https://www.energy.ca.gov/filebrowser/download/3265

(1) The eligible renewable percentage above does not reflect RPS compliance, which is determined using a different methodology.

¹³ https://www.sce.com/about-us/who-we-are/leadership/our-service-territory

¹⁴ California Energy Commission. Utility Energy Supply plans from 2015. https://www.energy.ca.gov/almanac/electricity_data/supply_forms.html

Setting

(2) Unspecified sources of power means electricity from transactions that are not traceable to specific generation sources.

Natural gas would be provided to the project by Southern California Gas (SoCalGas). The following summary of natural gas resources and service providers, delivery systems, and associated regulation is excerpted from information provided by the California Public Utilities Commission (CPUC).

The CPUC regulates natural gas utility service for approximately 11 million customers that receive natural gas from Pacific Gas and Electric (PG&E), Southern California Gas (SoCalGas), San Diego Gas & Electric (SDG&E), Southwest Gas, and several smaller investor-owned natural gas utilities. The CPUC also regulates independent storage operators Lodi Gas Storage, Wild Goose Storage, Central Valley Storage and Gill Ranch Storage.

The vast majority of California's natural gas customers are residential and small commercial customers, referred to as "core" customers. Larger volume gas customers, like electric generators and industrial customers, are called "noncore" customers. Although very small in number relative to core customers, noncore customers consume about 65% of the natural gas delivered by the state's natural gas utilities, while core customers consume about 35%.

The PUC regulates the California utilities' natural gas rates and natural gas services, including in-state transportation over the utilities' transmission and distribution pipeline systems, storage, procurement, metering and billing.

Most of the natural gas used in California comes from out-of-state natural gas basins. In 2017, for example, California utility customers received 38% of their natural gas supply from basins located in the U.S. Southwest, 27% from Canada, 27% from the U.S. Rocky Mountain area, and 8% from production located in California."¹⁵

3.3.3 Transportation Energy Resources

The project would attract additional vehicle trips with resulting consumption of energy resources, predominantly gasoline and diesel fuel. Gasoline (and other vehicle fuels) are commercially-provided commodities and would be available to the project patrons and employees via commercial outlets.

The most recent data available shows the transportation sector emits 40 percent of the total greenhouse gases in the state and about 84 percent of smog-forming oxides of nitrogen (NOx). About 28 percent of total United States energy consumption in 2019 was for transporting people and goods from one place to another. In 2019, petroleum comprised about 91 percent of all transportation energy use, excluding

¹⁵California Public Utilities Commission. Natural Gas and California. http://www.cpuc.ca.gov/natural_gas/

¹⁶ CARB. California Greenhouse Gas Emissions Inventory – 2020 Edition. https://www.arb.ca.gov/cc/inventory/data/data.htm

¹⁷ CARB. 2016 SIP Emission Projection Data. https://www.arb.ca.gov/app/emsinv/2017/emseic1_query.php?F_DIV=-4&F_YR=2012&F_SEASON=A&SP=SIP105ADJ&F_AREA=CA

Setting

fuel consumed for aviation and most marine vessels.¹⁸ In 2020, about 123.49 billion gallons (or about 2.94 billion barrels) of finished motor gasoline were consumed in the United States, an average of about 337 million gallons (or about 8.03 million barrels) per day.¹⁹

_

US Energy Information Administration. Use of Energy in the United States Explained: Energy Use for Transportation. https://www.eia.gov/energyexplained/?page=us_energy_transportation

¹⁹ https://www.eia.gov/tools/faqs/faq.php?id=23&t=10

4.0 Modeling Parameters and Assumptions

4.1 Construction

Typical emission rates from construction activities were obtained from CalEEMod Version 2020.4.0 CalEEMod is a computer model published by the SCAQMD for estimating air pollutant emissions. The CalEEMod program uses the EMFAC2017 computer program to calculate the emission rates specific for the southwestern portion of San Bernardino County for construction-related employee vehicle trips and the OFFROAD2011 computer program to calculate emission rates for heavy truck operations. EMFAC2017 and OFFROAD2011 are computer programs generated by CARB that calculates composite emission rates for vehicles. Emission rates are reported by the program in grams per trip and grams per mile or grams per running hour. Using CalEEMod, the peak daily air pollutant emissions were calculated and presented below. These emissions represent the highest level of emissions for each of the construction phases in terms of air pollutant emissions.

The analysis assesses the emissions associated with the construction of the proposed Project as indicated in Table 1. Per the Project owner, construction is anticipated to begin early 2023 and early 2024. The phases of the construction activities which have been analyzed below are: 1) site preparation, 2) grading, 3) building, 4) paving, and 5) architectural coating. For details on construction modeling and construction equipment for each phase, please see Appendix A.

The Project will be required to comply with existing SCAQMD rules for the reduction of fugitive dust emissions. SCAQMD Rule 403 establishes these procedures. Compliance with this rule is achieved through application of standard best management practices in construction and operation activities, such as application of water or chemical stabilizers to disturbed soils, managing haul road dust by application of water, covering haul vehicles, restricting vehicle speeds on unpaved roads to 15 mph, sweeping loose dirt from paved site access roadways, cessation of construction activity when winds exceed 25 mph and establishing a permanent, stabilizing ground cover on finished sites. In addition, projects that disturb 50 acres or more of soil or move 5,000 cubic yards of materials per day are required to submit a Fugitive Dust Control Plan or a Large Operation Notification Form to SCAQMD. Based on the size of the Project area (approximately 6.49 acres) and the fact that the Project won't export more than 5,000 cubic yards of material a day a Fugitive Dust Control Plan or Large Operation Notification would not be required.

SCAQMD's Rule 403 minimum requirements require that the application of the best available dust control measures are used for all grading operations and include the application of water or other soil stabilizers in sufficient quantity to prevent the generation of visible dust plumes. Compliance with Rule 403 would require the use of water trucks during all phases where earth moving operations would occur. Compliance with Rule 403 is required. Compliance is shown in the CalEEMod model as application of water three times daily, which is included in the model as a mitigation measure.

4.2 Operations

Operational or long-term emissions occur over the life of the Project. Both mobile and area sources generate operational emissions. Area source emissions arise from consumer product usage, heaters that consume natural gas, gasoline-powered landscape equipment, and architectural coatings (painting). Mobile source emissions from motor vehicles are the largest single long-term source of air pollutants from the operation of the Project. Small amounts of emissions would also occur from area sources such as the consumption of natural gas for heating, from landscaping emissions, and consumer product usage. The operational emissions were estimated using the latest version of CalEEMod.

Mobile Sources

Mobile sources include emissions from the additional vehicle miles generated from the proposed Project. The vehicle trips associated with the proposed Project are based upon the trip generation rates give in the Project-specific trip generation analysis (Integrated Engineering Group) which uses the ITE Trip Generation Manual 11th Edition. The trip generation analysis shows a net trip generation rate of 440 trips per day for the proposed Project.

The program then applies the emission factors for each trip which is provided by the EMFAC2017 model to determine the vehicular traffic pollutant emissions. The CalEEMod default trip lengths were used in this analysis. Please see CalEEMod output comments sections in Appendix A and B for details.

Area Sources

Area sources include emissions from consumer products, landscape equipment and architectural coatings. Landscape maintenance includes fuel combustion emissions from equipment such as lawn mowers, rototillers, shredders/grinders, blowers, trimmers, chain saws, and hedge trimmers, as well as air compressors, generators, and pumps. As specifics were not known about the landscaping equipment fleet, CalEEMod defaults were used to estimate emissions from landscaping equipment.

Per SCAQMD Rule 1113 as amended on June 3, 2011, the architectural coatings that would be applied after January 1, 2014 will be limited to an average of 50 grams per liter or less for buildings and 100 grams per liter or less for parking lot striping. No changes were made to the CalEEMod architectural coating default values.

Per AB 341, at least 75 percent of generated waste will be source reduced, recycled, or composted. This is shown in the CalEEMod model as a mitigation measure; however, it is required.

Energy Usage

2020.4.0 CalEEMod defaults were utilized.

4.3 Localized Construction Analysis

The SCAQMD has published a "Fact Sheet for Applying CalEEMod to Localized Significance Thresholds" (South Coast Air Quality Management District 2011b). CalEEMod calculates construction emissions based on the number of equipment hours and the maximum daily disturbance activity possible for each

piece of equipment. In order to compare CalEEMod reported emissions against the localized significance threshold lookup tables, the CEQA document should contain in its project design features or its mitigation measures the following parameters:

- 1. The off-road equipment list (including type of equipment, horsepower, and hours of operation) assumed for the day of construction activity with maximum emissions.
- 2. The maximum number of acres disturbed on the peak day.
- 3. Any emission control devices added onto off-road equipment.
- 4. Specific dust suppression techniques used on the day of construction activity with maximum emissions.

The construction equipment showing the equipment associated with the maximum area of disturbance is shown in Table 9.

Activity Equipment Number Acres/8hr-day **Total Acres Rubber Tired Dozers** 1 0.5 0.5 **Site Preparation** Tractors/Loaders/Backhoes 1 0.5 0.5 **Total Per Phase** 1.0 **Excavators** 1 0.5 0.5 1 0.5 0.5 Graders Grading **Rubber Tired Dozers** 1 0.5 0.5 Tractors/Loaders/Backhoes 3 0.5 1.5 **Total Per Phase** 3.0

Table 9: Construction Equipment Assumptions¹

As shown in Table 9, the maximum number of acres disturbed in a day would be 3 acres during grading.

The local air quality emissions from construction were analyzed using the SCAQMD's Mass Rate Localized Significant Threshold Look-up Tables and the methodology described in Localized Significance Threshold Methodology, prepared by SCAQMD, revised July 2008. The Look-up Tables were developed by the SCAQMD in order to readily determine if the daily emissions of CO, NOx, PM10, and PM2.5 from the proposed Project could result in a significant impact to the local air quality. The emission thresholds were based on the East San Bernardino Valley source receptor area (SRA 35) and a disturbance of 2 acres per day at a distance of 25 meters (82 feet) as the nearest sensitive receptor is located 85 feet to the north.

4.4 Localized Operational Analysis

For operational emissions, the screening tables for a disturbance area of 2 acres per day and a distance of 25 meters were used to determine significance. The tables were compared to the Project's onsite operational emissions.

Notes:

^{1.} Source: South Coast AQMD, Fact Sheet for Applying CalEEMod to Localized Significance Thresholds. http://www.aqmd.gov/docs/default-source/ceqa/handbook/localized-significance-thresholds/caleemod-guidance.pdf?sfvrsn=2

5.0 Thresholds of Significance

5.1 Air Quality Thresholds of Significance

5.1.1 CEQA Guidelines for Air Quality

The CEQA Guidelines define a significant effect on the environment as "a substantial, or potentially substantial, adverse change in the environment." To determine if a project would have a significant impact on air quality, the type, level, and impact of emissions generated by the project must be evaluated.

The following air quality significance thresholds are contained in Appendix G of the CEQA Guidelines. A significant impact would occur if the project would:

- a) Conflict with or obstruct implementation of the applicable air quality plan;
- b) Result in a cumulatively considerable net increase of any criteria pollutant for which the project region is nonattainment under an applicable national or state ambient air quality standard;
- c) Expose sensitive receptors to substantial pollutant concentrations; or
- d) Result in other emissions (such as those leading to odors) adversely affecting a substantial number of people.

While the final determination of whether a project is significant is within the purview of the Lead Agency pursuant to Section 15064(b) of the CEQA Guidelines, SCAQMD recommends that its quantitative air pollution thresholds be used to determine the significance of project emissions. If the Lead Agency finds that the project has the potential to exceed these air pollution thresholds, the project should be considered to have significant air quality impacts. There are daily emission thresholds for construction and operation of a proposed project in the basin.

5.1.2 Regional Significance Thresholds for Construction Emissions

The following CEQA significance thresholds for construction emissions are established for the Basin:

- 75 pounds per day (lbs/day) of VOC
- 100 lbs/day of NO_x
- 550 lbs/day of CO

- 150 lbs/day of PM10
- 55 lbs/day of PM2.5
- 150 lbs/day of SO₂

Projects in the basin with construction-related emissions that exceed any of the emission thresholds are considered to be significant under SCAQMD guidelines.

5.1.3 Regional Significance Thresholds for Operational Emissions

The daily operational emissions significance thresholds for the basin are as follows:

- 55 pounds per day (lbs/day) of VOC
- 55 lbs/day of NO_x
- 550 lbs/day of CO

- 150 lbs/day of PM10
- 55 lbs/day of PM2.5
- 150 lbs/day of SO₂

Local Microscale Concentration Standards The significance of localized project impacts under CEQA depends on whether ambient CO levels in the vicinity of the project are above or below State and federal CO standards. If ambient levels are below the standards, a project is considered to have a significant impact if project emissions result in an exceedance of one or more of these standards. If ambient levels already exceed a State or federal standard, project emissions are considered significant if they increase 1-hour CO concentrations by 1.0 ppm or more or 8-hour CO concentrations by 0.45 ppm or more. The following are applicable local emission concentration standards for CO:

- California State 1-hour CO standard of 20.0 ppm
- California State 8-hour CO standard of 9.0 ppm

5.1.4 Thresholds for Localized Significance

Project-related construction air emissions may have the potential to exceed the State and Federal air quality standards in the project vicinity, even though these pollutant emissions may not be significant enough to create a regional impact to the South Coast Air Basin. In order to assess local air quality impacts the SCAQMD has developed Localized Significant Thresholds (LSTs) to assess the project-related air emissions in the project vicinity. The SCAQMD has also provided Final Localized Significant Threshold Methodology (LST Methodology), June 2003, which details the methodology to analyze local air emission impacts. The Localized Significant Threshold Methodology found that the primary emissions of concern are NO2, CO, PM10, and PM2.5.

The emission thresholds were calculated based on the East San Bernardino Valley source receptor area (SRA 35) and a disturbance of 2 acres per day at a distance of 25 meters (82 feet), for construction.

5.2 Greenhouse Gas Thresholds of Significance

5.2.1 CEQA Guidelines for Greenhouse Gas

CEQA Guidelines define a significant effect on the environment as "a substantial, or potentially substantial, adverse change in the environment." To determine if a project would have a significant impact on greenhouse gases, the type, level, and impact of emissions generated by the project must be evaluated.

The following greenhouse gas significance thresholds are contained in Appendix G of the CEQA Guidelines, which were amendments adopted into the Guidelines on March 18, 2010, pursuant to SB 97. A significant impact would occur if the project would:

- (a) Generate greenhouse gas emissions, either directly or indirectly, that may have a significant impact on the environment; or
- (b) Conflict with any applicable plan, policy or regulation of an agency adopted for the purpose of reducing the emissions of greenhouse gases.

However, despite this, currently neither the CEQA statutes, OPR guidelines, nor the draft proposed changes to the CEQA Guidelines prescribe thresholds of significance or a particular methodology for performing an impact analysis; as with most environmental topics, significance criteria are left to the judgment and discretion of the Lead Agency. As previously discussed (Section 2.2.4 of this report), SCAQMD has drafted interim thresholds. The screening threshold of 3,000 MTCO2e per year for all land uses was used in this analysis.

5.3 Toxic Air Contaminants

The threshold for toxic air contaminants (TACs) has a maximum incremental cancer risk of 10 per million and a non-cancer (acute and chronic) hazard index of 1.0 or greater. An exceedance to these values would be considered a significant impact.

6.0 Air Quality Emissions Impact

6.1 Construction Air Quality Emissions Impact

The latest version of CalEEMod was used to estimate the onsite and offsite construction emissions. The emissions incorporate Rule 402 and 403. Rule 402 and 403 (fugitive dust) are not considered mitigation measures as the Project by default is required to incorporate these rules during construction.

6.1.1 Regional Construction Emissions

The construction emissions for the Project would not exceed the SCAQMD's daily emission thresholds at the regional level as demonstrated in Table 10, and therefore would be considered less than significant.

Table 10: Regional Significance - Construction Emissions (pounds/day)

		5.1		, ,	/ 1 \	
			lutant Emissi	1		1
Activity	VOC	NOx	со	SO ₂	PM10	PM2.5
Site Preparation						
On-Site ²	1.00	10.47	5.82	0.01	3.06	1.78
Off-Site ³	0.02	0.01	0.21	0.00	0.06	0.02
Total	1.02	10.48	6.03	0.01	3.12	1.80
Grading						
On-Site ²	1.95	20.86	15.27	0.03	3.73	2.21
Off-Site ³	0.34	10.69	3.26	0.05	1.58	0.50
Total	2.29	31.54	18.54	0.08	5.31	2.71
Building Construction						
On-Site ²	1.71	15.62	16.36	0.03	0.81	0.76
Off-Site ³	0.56	2.48	5.37	0.02	1.58	0.45
Total	2.26	18.09	21.73	0.05	2.39	1.21
Paving						
On-Site ²	1.57	10.19	14.58	0.02	0.51	0.47
Off-Site ³	0.06	0.04	0.57	0.00	0.17	0.05
Total	1.62	10.23	15.15	0.02	0.68	0.51
Architectural Coating						
On-Site ²	37.90	1.30	1.81	0.00	0.07	0.07
Off-Site ³	0.09	0.05	0.83	0.00	0.25	0.07
Total	37.99	1.36	2.64	0.01	0.32	0.14
Total of overlapping phases ⁴	41.87	29.68	39.52	0.08	3.39	1.86
SCAQMD Thresholds	75	100	550	150	150	55
Exceeds Thresholds	No	No	No	No	No	No

Notes:

¹ Source: CalEEMod Version 2020.4.0

² On-site emissions from equipment operated on-site that is not operated on public roads

³ Off-site emissions from equipment operated on public roads.

⁴ Construction, architectural coatings and paving phases may overlap.

² On-site emissions from equipment operated on-site that is not operated on public roads

6.1.2 Localized Construction Emissions

The data provided in Table 11 shows that none of the analyzed criteria pollutants would exceed the local emissions thresholds at the nearest sensitive receptors. Therefore, a less than significant local air quality impact would occur from construction of the proposed Project.

Table 11: Localized Significance – Construction

	On-Si	On-Site Pollutant Emissions (pounds/day) ¹				
Phase	NOx	СО	PM10	PM2.5		
Site Preparation	10.48	6.03	3.12	1.80		
Grading	20.86	15.27	3.73	2.21		
Building Construction	15.62	16.36	0.81	0.76		
Paving	10.19	14.58	0.51	0.47		
Architectural Coating	1.30	1.81	0.07	0.07		
Total of overlapping phases	27.11	32.76	1.39	1.30		
SCAQMD Threshold for 25 meters (82 feet) or less ²	170	1,174	7	5		
Exceeds Threshold?	No	No	No	No		

Notes:

6.1.3 Construction-Related Human Health Impacts

Regarding health effects related to criteria pollutant emissions, the applicable significance thresholds are established for regional compliance with the state and federal ambient air quality standards, which are intended to protect public health from both acute and long-term health impacts, depending on the potential effects of the pollutant. Because regional and local emissions of criteria pollutants during construction of the Project would be below the applicable thresholds, it would not contribute to long-term health impacts related to nonattainment of the ambient air quality standards. Therefore, significant adverse acute health impacts as a result of Project construction are not anticipated.

6.1.4 Construction-Related Toxic Air Contaminant Impact

The greatest potential for toxic air contaminant emissions would be related to diesel particulate emissions associated with heavy equipment operations during construction of the proposed Project. The Office of Environmental Health Hazard Assessment (OEHHA) has issued the Air Toxic Hot Spots Program Risk Assessment Guidelines and Guidance Manual for the Preparation of Health Risk Assessments, February 2015 to provide a description of the algorithms, recommended exposure variates, cancer and noncancer health values, and the air modeling protocols needed to perform a health risk assessment (HRA) under the Air Toxics Hot Spots Information and Assessment Act of 1987. Hazard identification includes identifying all substances that are evaluated for cancer risk and/or non-cancer acute, 8-hour, and chronic health impacts. In addition, identifying any multi-pathway substances that present a cancer risk or chronic non-cancer hazard via non-inhalation routes of exposure.

¹ Source: Calculated from CalEEMod and SCAQMD's Mass Rate Look-up Tables for two acres, to be conservative, in East San Bernardino Valley Source Receptor Area (SRA 35). Project will disturb a maximum of 3.0 acres per day (see Table 9).

²The nearest sensitive receptor is located 85 feet to the north of the property line; therefore, the 25-meter threshold has been used.

Given the relatively limited number of heavy-duty construction equipment and construction schedule, the proposed Project would not result in a long-term substantial source of toxic air containment emissions and corresponding individual cancer risk. Furthermore, construction-based particulate matter (PM) emissions (including diesel exhaust emissions) do not exceed any local or regional thresholds. Therefore, no significant short-term toxic air contaminant impacts would occur during construction of the proposed Project.

6.2 Operational Air Quality Emissions Impact

6.2.1 Regional Operational Emissions

The operations-related criteria air quality impacts created by the proposed Project have been analyzed through the use of CalEEMod model. The operating emissions were based on year 2024, which is the anticipated opening year for the Project per the trip generation analysis (Integrated Engineering Group). The summer and winter emissions created by the proposed Project's long-term operations were calculated and the highest emissions from either summer or winter are summarized in Table 12.

Table 12: Regional Significance - Unmitigated Operational Emissions (lbs/day)

	Pollutant Emissions (pounds/day) ¹					
Activity	VOC	NOx	СО	SO2	PM10	PM2.5
Area Sources ²	0.70	0.02	1.82	0.00	0.10	0.01
Energy Usage ³	0.01	0.12	0.05	0.00	0.01	0.01
Mobile Sources ⁴	0.49	0.67	4.79	0.01	1.08	0.29
Total Emissions	1.21	0.81	6.66	0.01	1.19	0.31
SCAQMD Thresholds	55	55	550	150	150	55
Exceeds Threshold?	No	No	No	No	No	No

Notes:

Table 12 provides the Project's unmitigated operational emissions. Table 12 shows that the Project does not exceed the SCAQMD daily emission threshold and regional operational emissions are considered to be less than significant.

6.2.2 Localized Operational Emissions

Table 13 shows the calculated emissions for the proposed operational activities compared with appropriate LSTs. The LST analysis only includes on-site sources; however, the CalEEMod software outputs do not separate on-site and off-site emissions for mobile sources. For a worst-case scenario assessment, the emissions shown in Table 13 include all on-site Project-related stationary sources and

¹ Source: CalEEMod Version 2020.4.0

² Area sources consist of emissions from consumer products, architectural coatings, and landscaping equipment.

³ Energy usage consists of emissions from on-site natural gas usage.

⁴ Mobile sources consist of emissions from vehicles and road dust.

10% of the Project-related new mobile sources.²⁰ This percentage is an estimate of the amount of Project-related new vehicle traffic that will occur on-site.

Table 13: Localized Significance - Unmitigated Operational Emissions

	On-	On-Site Pollutant Emissions (pounds/day) ¹			
On-Site Emission Source	NOx	СО	PM10	PM2.5	
Area Sources ²	0.02	1.82	0.10	0.01	
Energy Usage ³	0.12	0.05	0.01	0.01	
On-Site Vehicle Emissions ⁴	0.07	0.48	0.11	0.03	
Total Emissions	0.20	2.35	0.22	0.05	
SCAQMD Threshold for 25 meters (82 feet) ⁵	170	1,174	2	2	
Exceeds Threshold?	No	No	No	No	

Notes:

6.2.3 Operations-Related Human Health Impacts

As stated previously, regarding health effects related to criteria pollutant emissions, the applicable significance thresholds are established for regional compliance with the state and federal ambient air quality standards, which are intended to protect public health from both acute and long-term health impacts, depending on the potential effects of the pollutant. Because regional and local emissions of criteria pollutants during operation of the Project would be below the applicable thresholds, it would not contribute to long-term health impacts related to nonattainment of the ambient air quality standards. Therefore, significant adverse acute health impacts as a result of Project operation are not anticipated.

6.3 CO Hot Spot Emissions

CO is the pollutant of major concern along roadways because the most notable source of CO is motor vehicles. For this reason, CO concentrations are usually indicative of the local air quality generated by a roadway network and are used as an indicator of potential local air quality impacts. Local air quality impacts can be assessed by comparing future without and with Project CO levels to the State and Federal CO standards which were presented in above in Section 5.0.

¹ Source: Calculated from CalEEMod and SCAQMD's Mass Rate Look-up Tables for two acres in East San Bernardino Valley Source Receptor Area (SRA 35). Project will disturb a maximum of 3.0 acres per day (see Table 9).

² Area sources consist of emissions from consumer products, architectural coatings, and landscaping equipment.

³ Energy usage consists of emissions from generation of electricity and on-site natural gas usage.

⁴ On-site vehicular emissions based on 1/10 of the gross vehicular emissions and road dust.

⁵The nearest sensitive receptor is located approximately 85 feet to the north of the property line; therefore, the 25-meter threshold has been used.

²⁰ The project site is approximately 0.45 miles in length at its longest point; therefore the on-site mobile source emissions represent approximately 1/15th of the shortest CalEEMod default distance of 6.9 miles. Therefore, to be conservative, 1/10th the distance (dividing the mobile source emissions by 10) was used to represent the portion of the overall mobile source emissions that would occur on-site.

To determine if the proposed Project could cause emission levels in excess of the CO standards discussed above in Section 5.0, a sensitivity analysis is typically conducted to determine the potential for CO "hot spots" at a number of intersections in the general Project vicinity. Because of reduced speeds and vehicle queuing, "hot spots" potentially can occur at high traffic volume intersections with a Level of Service E or worse.

Micro-scale air quality emissions have traditionally been analyzed in environmental documents where the air basin was a non-attainment area for CO. However, the SCAQMD has demonstrated in the CO attainment redesignation request to EPA that there are no "hot spots" anywhere in the air basin, even at intersections with much higher volumes, much worse congestion, and much higher background CO levels than anywhere in San Bernardino County. If the worst-case intersections in the air basin have no "hot spot" potential, any local impacts will be below thresholds.

The Project-specific trip generation analysis showed that the Project is only anticipated to generate 440 daily vehicle trips (Integrated Engineering Group). The 1992 Federal Attainment Plan for Carbon Monoxide (1992 CO Plan) showed that an intersection which has a daily traffic volume of approximately 100,000 vehicles per day would not violate the CO standard. The volume of traffic at Project buildout would be well below 100,000 vehicles and below the necessary volume to even get close to causing a violation of the CO standard. Therefore, no CO "hot spot" modeling was performed and no significant long-term air quality impact is anticipated to local air quality with the on-going use of the proposed Project.

6.4 Odors

Potential sources that may emit odors during construction activities include the application of materials such as asphalt pavement. The objectionable odors that may be produced during the construction process are of short-term in nature and the odor emissions are expected cease upon the drying or hardening of the odor producing materials. Diesel exhaust and VOCs would be emitted during construction of the Project, which are objectionable to some; however, emissions would disperse rapidly from the Project site and therefore should not reach an objectionable level at the nearest sensitive receptors. Due to the short-term nature and limited amounts of odor producing materials being utilized, no significant impact related to odors would occur during construction of the proposed Project.

The SCAQMD recommends that odor impacts be addressed in a qualitative manner. Such an analysis shall determine whether the Project would result in excessive nuisance odors, as defined under the California Code of Regulations and Section 41700 of the California Health and Safety Code, and thus would constitute a public nuisance related to air quality.

Potential sources that may emit odors during the on-going operations of the proposed Project would include odor emissions from trash storage areas. Due to the distance of the nearest receptors from the Project site and through compliance with SCAQMD's Rule 402 no significant impact related to odors would occur during the on-going operations of the proposed Project.

6.5 Cumulative Regional Air Quality Impacts

Cumulative projects include local development as well as general growth within the project area. However, as with most development, the greatest source of emissions is from mobile sources, which travel well out of the local area. Therefore, from an air quality standpoint, the cumulative analysis would extend beyond any local projects and when wind patterns are considered, would cover an even larger area. Accordingly, the cumulative analysis for the Project's air quality must be generic by nature.

The Project area is out of attainment for both ozone and PM10 particulate matter. Construction and operation of cumulative projects will further degrade the local air quality, as well as the air quality of the South Coast Air Basin. The greatest cumulative impact on the quality of regional air cell will be the incremental addition of pollutants mainly from increased traffic from residential, commercial, and industrial development and the use of heavy equipment and trucks associated with the construction of these projects. Air quality will be temporarily degraded during construction activities that occur separately or simultaneously. However, in accordance with the SCAQMD methodology, projects that do not exceed the SCAQMD criteria or can be mitigated to less than criteria levels are not significant and do not add to the overall cumulative impact. The Project does not exceed any of the thresholds of significance and therefore is considered less than significant.

6.6 Air Quality Compliance

The California Environmental Quality Act (CEQA) requires a discussion of any inconsistencies between a proposed project and applicable General Plans and Regional Plans (CEQA Guidelines Section 15125). The regional plan that applies to the proposed Project includes the SCAQMD Air Quality Management Plan (AQMP). Therefore, this section discusses any potential inconsistencies of the proposed Project with the AQMP.

The purpose of this discussion is to set forth the issues regarding consistency with the assumptions and objectives of the AQMP and discuss whether the proposed Project would interfere with the region's ability to comply with Federal and State air quality standards. If the decision-makers determine that the proposed Project is inconsistent, the lead agency may consider Project modifications or inclusion of mitigation to eliminate the inconsistency.

The SCAQMD CEQA Handbook states that "New or amended General Plan Elements (including land use zoning and density amendments), Specific Plans, and significant projects must be analyzed for consistency with the AQMP." Strict consistency with all aspects of the plan is usually not required. A proposed Project should be considered to be consistent with the AQMP if it furthers one or more policies and does not obstruct other policies. The SCAQMD CEQA Handbook identifies two key indicators of consistency:

(1) Whether the Project will result in an increase in the frequency or severity of existing air quality violations or cause or contribute to new violations or delay timely attainment of air quality standards or the interim emission reductions specified in the AQMP.

(2) Whether the Project will exceed the assumptions in the AQMP in 2016 or increments based on the year of Project buildout and phase.

Both of these criteria are evaluated in the following sections.

A. Criterion 1 - Increase in the Frequency or Severity of Violations?

Based on the air quality modeling analysis contained in this Air Analysis in Section 6, neither short-term construction impacts, nor long-term operations will result in significant impacts based on the SCAQMD regional and local thresholds of significance.

Therefore, the proposed Project is not projected to contribute to the exceedance of any air pollutant concentration standards and is found to be consistent with the AQMP for the first criterion.

B. Criterion 2 - Exceed Assumptions in the AQMP?

Consistency with the AQMP assumptions is determined by performing an analysis of the proposed Project with the assumptions in the AQMP. The emphasis of this criterion is to ensure that the analyses conducted for the proposed Project are based on the same forecasts as the AQMP. The 2016-2040 Regional Transportation/Sustainable Communities Strategy, prepared by SCAG, 2016, includes chapters on: the challenges in a changing region, creating a plan for our future, and the road to greater mobility and sustainable growth. These chapters currently respond directly to federal and state requirements placed on SCAG. Local governments are required to use these as the basis of their plans for purposes of consistency with applicable regional plans under CEQA. For this Project, the County of San Bernardino Land Use Plan defines the assumptions that are represented in the AQMP.

The Project site is currently designated by the City of San Bernardino as partially Industrial Light and Public Facilities. The proposed Project is consistent with the City of San Bernardino current land use designation. Therefore, it is not anticipated that the Project would exceed the AQMP assumptions for the Project site and is found to be consistent with the AQMP for the second criterion.

Based on the above, the proposed Project will not result in an inconsistency with the SCAQMD AQMP. Therefore, a less than significant impact will occur.

7.0 Greenhouse Gas Impact Analysis

7.1 Construction Greenhouse Gas Emissions Impact

The greenhouse gas emissions from Project construction equipment and worker vehicles are shown in Table 14. The emissions are from all phases of construction. The total construction emissions amortized over a period of 30 years are estimated at 19.46 metric tons of CO₂e per year. Annual CalEEMod output calculations are provided in Appendix B.

Table 14: Construction Greenhouse Gas Emissions

A attivity.	Emissions (MTCO₂e)¹					
Activity	Onsite	Offsite	Total			
Site Preparation	5.16	0.22	5.38			
Grading	26.27	46.66	72.93			
Building Construction	268.14	211.46	479.60			
Paving	20.19	1.30	21.48			
Coating	2.56	1.90	4.46			
Total	322.31	261.54	583.85			
Averaged over 30 years ²	10.74	8.72	19.46			

Notes:

7.2 Operational Greenhouse Gas Emissions Impact

Operational emissions occur over the life of the Project. The operational emissions for the Project are 742.60 metric tons of CO₂e per year (see Table 15). Furthermore, as shown in Table 15, the Project's total emissions (with incorporation of construction related GHG emissions) would be 762.06 metric tons of CO₂e per year. These emissions do not exceed the County of San Bernardino CAP and SCAQMD screening threshold of 3,000 metric tons of CO₂e per year. Therefore, the Project's GHG emissions are considered to be less than significant.

Table 15: Opening Year Unmitigated Project-Related Greenhouse Gas Emissions

		Greenhouse Gas Emissions (Metric Tons/Year) ¹						
Category	Bio-CO2	NonBio-CO ₂	CO ₂	CH ₄	N₂O	CO₂e		
Area Sources ²	0.00	0.01	0.01	0.00	0.00	0.01		
Energy Usage ³	0.00	142.28	142.28	0.01	0.00	143.03		
Mobile Sources ⁴	0.00	490.96	490.96	0.03	0.03	499.14		
Solid Waste ⁵	14.14	0.00	14.14	0.84	0.00	35.11		
Water ⁶	4.23	46.92	51.15	0.44	0.01	65.32		
Construction ⁷	0.00	19.15	19.15	0.00	0.00	19.46		
Total Emissions	18.37	699.32	717.69	1.32	0.04	762.06		
SCAQMD Draft and San Bernardino County Screening Threshold						3,000		
Exceeds Threshold?						No		

Notes:

^{1.} MTCO₂e=metric tons of carbon dioxide equivalents (includes carbon dioxide, methane and nitrous oxide).

^{2.} The emissions are averaged over 30 years because the average is added to the operational emissions, pursuant to SCAQMD.

^{*} CalEEMod output (Appendix B)

¹ Source: CalEEMod Version 2020.4.0

- ² Area sources consist of GHG emissions from consumer products, architectural coatings, and landscape equipment.
- ³ Energy usage consist of GHG emissions from electricity and natural gas usage.
- ⁴ Mobile sources consist of GHG emissions from vehicles.
- ⁵ Solid waste includes the CO₂ and CH₄ emissions created from the solid waste placed in landfills.
- ⁶ Water includes GHG emissions from electricity used for transport of water and processing of wastewater.
- ⁷ Construction GHG emissions based on a 30-year amortization rate.

7.3 Greenhouse Gas Plan Consistency

The proposed Project would have the potential to conflict with any applicable plan, policy or regulation of an agency adopted for the purpose of reducing the emissions of greenhouse gases.

According to the *County of San Bernardino Greenhouse Gas Emissions Reduction Plan*, "all development projects, including those otherwise determined to be exempt from CEQA will be subject to applicable Development Code provisions, including the GHG performance standards, and state requirements, such as the California Building Code requirements for energy efficiency. With the application of the GHG performance standards, projects that are exempt from CEQA and small projects that do not exceed 3,000 MTCO2e per year will be considered to be consistent with the Plan and determined to have a less than significant individual and cumulative impact for GHG emissions." The Project's operational GHG emissions do not exceed the County's screening threshold of 3,000 MTCO2e per year. Therefore, the proposed Project is consistent with the GHG Plan pursuant to Section 15183.5 of the State CEQA Guidelines. The Project will not result in substantial emissions of greenhouse gases and will not conflict with the County of San Bernardino CAP or the goals of AB-32 or SB-32.

As discussed above, the City of San Bernardino was a participant in the San Bernardino County Regional Greenhouse Gas Reduction Plan, which identifies the County's vision and goals on reducing GHG emissions in the different cities, local government facilities, and communities. Table 16 below presents the proposed project's compliance with each reduction measure evaluated for the City of San Bernardino, as identified in the San Bernardino County Regional Greenhouse Gas Reduction Plan.

Table 16: Project Consistency with the City of San Bernardino GHG Reduction Measures

Measure	Description	Project Consistency
Building Energy		
Energy-1. Building Energy Efficiency	 Conserve scarce energy resources 13.1.1: Reduce the City's ongoing electricity use by 10% and set an example for residents and businesses to follow. Conserve scarce energy resources 13.1.3: Consider enrollment in the Community Energy Efficiency Program (CEEP), which provides incentives for builders who attain energy savings 30% above the National Model Energy Code, the Energy Star Program, which is sponsored by the United States Department of Energy and the Environmental Protection Agency and encourages superior energy efficiency by residents and businesses, or the State's Energy Efficiency and Demand Reduction Program, which offer rebates and incentives to agencies and developers who reduce energy consumption and use energy efficient fixtures and energy-saving design elements. 	Not Applicable. This measure is not applicable as the City would be responsible for implementing this measure. However, the proposed project would comply with CALGreen, regarding building energy efficiency and other green building standards.

		ı
	 Conserve scarce energy resources 13.1.4: Require energy audits of existing public structures and encourage audits of private structures, identifying levels of existing energy use and potential conservation measures. Conserve scarce energy resources 13.1.5: Encourage energy-efficient retrofitting of existing buildings throughout the City. Conserve scarce energy resources 13.1.6: Consider program that awards incentives to projects that install energy conservation measures, including technical assistance and possible low-interest loans. Conserve scarce energy resources 13.1.8: Educate the public regarding the need for energy conservation, environmental stewardship, and sustainability techniques and about systems and standards that are currently available for achieving greater energy and resource efficiency, such as the U.S. Green Building Council's LEED standards for buildings. 	
Energy-2. Lighting Efficiency	 Electricity 9.6.5: Encourage and promote the use of energy-efficient (U.S. Department of Energy "Energy Star®" or equivalent) lighting fixtures, light bulbs, and compact fluorescent bulbs in residences, commercial, and public buildings, as well as in traffic signals and signs where feasible. 	Consistent. The proposed project would comply with CALGreen, regarding energy conservation and green building standards.
Energy-3. All Electric Buildings	 Conserve scarce energy resources 13.1.5: Encourage energy- efficient retrofitting of existing buildings throughout the City. 	Not applicable. This measure is not applicable as the proposed project would not retrofit an existing building.
Energy-5. Renewable Energy – New Commercial/Industrial	 Conserve scarce energy resources 13.1.9: Encourage increased use of passive and active solar and wind design in existing and new development (e.g., orienting buildings to maximize exposure to cooling effects of prevailing winds, day lighting design, natural ventilation, space planning, thermal massing and locating landscaping and landscape structures to shade buildings). 	Consistent. The proposed project would comply with CALGreen, regarding energy conservation and green building standards.
Energy-10. Urban Tree Planting for Shading and Energy Savings	 Conserve scarce energy resources 13.1.9: Encourage increased use of passive and active solar and wind design in existing and new development (e.g., orienting buildings to maximize exposure to cooling effects of prevailing winds, day lighting design, natural ventilation, space planning, thermal massing and locating landscaping and landscape structures to shade buildings). 	Consistent. The proposed project would include landscaping, which would help with shading.
On-Road OnRoad-3. Transportation Demand Management and Signal Synchronization	 Distinct Character and Identity 2.3.2: Promote development that is compact, pedestrian-friendly, and served by a variety of transportation options along major corridors and in key activity areas. 	Not Applicable. The proposed project would generate 440 daily trips. The project would not be required

	 Distinct Character and Identity 2.3.1: Commercial centers, open spaces, educational facilities, and recreational facilities should be linked to residential neighborhoods. GOAL CI 4: The County will coordinate land use and transportation planning to ensure adequate transportation facilities to support planned land uses and ease congestion. Redevelopment and Revitalization 2.4.1 Specific Areas 5.5.3 and 5.5.5 	to implement transportation demand management strategies or signal synchronization.
	• 10. Downtown Strategic Area, Strategies 1,3,7, and 13	
Renewable & Energy Eff	icient	
Waste-2 . Waste Diversion	 Solid Waste 9.5.3: Continue to reduce the amount of solid waste that must be disposed of in area landfills, to conserve energy resources, and be consistent with the County Solid Waste Management Plan and State law. Solid Waste 9.5.4 through 9.5.6 	Consistent. The proposed project would be consistent with County Solid Waste and State requirements for waste reduction.

7.4 Cumulative Regional Greenhouse Gas Impacts

Cumulative projects include local development as well as general growth within the project area. However, as with most development, the greatest source of emissions is from mobile sources, which travel well out of the local area. Therefore, from a greenhouse gas standpoint, the cumulative analysis would extend beyond any local projects and when wind patterns are considered, would cover an even larger area. Accordingly, the cumulative analysis for the Project's greenhouse gas impacts must be generic by nature.

Construction and operation of cumulative projects will add to greenhouse gas emissions. The greatest cumulative impact will be the incremental addition of pollutants mainly from increased traffic from residential, commercial, and industrial development and the use of heavy equipment and trucks associated with the construction of these projects. Greenhouse gas emissions will temporarily increase during construction activities that occur separately or simultaneously. However, in accordance with the SCAQMD methodology, projects that do not exceed the SCAQMD criteria or can be mitigated to less than criteria levels are not significant and do not add to the overall cumulative impact. The Project does not exceed any of the thresholds of significance and therefore is considered less than significant.

8.0 Energy Analysis

Information from the CalEEMod 2020.4.0 Daily and Annual Outputs contained in the air quality and greenhouse gas analyses above was utilized for this analysis. The CalEEMod outputs detail Project related construction equipment, transportation energy demands, and facility energy demands.

8.1 Construction Energy Demand

8.1.1 Construction Equipment Electricity Usage Estimates

Electrical service will be provided by Southern California Edison (SCE). Based on the 2017 National Construction Estimator, Richard Pray (2017)²¹, the typical power cost per 1,000 square feet of building construction per month is estimated to be \$2.32. The Project plans to develop the site with 75,062 square feet of new single-family houses over the course of approximately 14 months. Based on Table 16, the total power cost of the on-site electricity usage during the construction of the proposed Project is estimated to be approximately \$2,438.01. As shown in Table 16, the total electricity usage from Project construction related activities is estimated to be approximately 44,328 kWh.²²

Table 16: Project Construction Power Cost and Electricity Usage

Power Cost (per 1,000 square foot of building per month of construction)	Total Building Size (1,000 Square Foot) ¹	Construction Duration (months)	Total Project Construction Power Cost
\$2.32	75.062	14	\$2,438.01

Cost per kWh	Total Project Construction Electricity Usage (kWh)
\$0.06	44,328

^{*} Assumes the Project will be under the GS-1 General Service rate under SCE.

8.1.2 Construction Equipment Fuel Estimates

Using the CalEEMod data input, the Project's construction phase would consume electricity and fossil fuels as a single energy demand, that is, once construction is completed their use would cease. CARB's 2017 Emissions Factors Tables show that on average aggregate fuel consumption (gasoline and diesel

²¹ Pray, Richard. 2017 National Construction Estimator. Carlsbad: Craftsman Book Company, 2017.

²² LADWP's Small Commercial & Multi-Family Service (A-1) is approximately \$0.06 per kWh of electricity Southern California Edison (SCE). Rates & Pricing Choices: General Service/Industrial Rates. https://library.sce.com/content/dam/sce-doclib/public/regulatory/historical/electric/2020/schedules/general-service-&-industrial-rates/ELECTRIC_SCHEDULES_GS-1_2020.pdf

fuel) would be approximately 18.5 hp-hr-gal.²³ As presented in Table 17 below, Project construction activities would consume an estimated 30,939 gallons of diesel fuel.

Table 17: Construction Equipment Fuel Consumption Estimates

Phase	Number of Days	Offroad Equipment Type	Amount	Usage Hours	Horse Power	Load Factor	HP hrs/ day	Total Fuel Consumption (gal diesel fuel) ¹
Site	10	Rubber Tired Dozers	1	8	247	0.4	790	427
Preparation	10	Tractors/Loaders/Backhoes	1	8	97	0.37	287	155
	20	Excavators	1	8	158	0.38	480	519
Constitute	20	Graders	1	8	187	0.41	613	663
Grading	20	Rubber Tired Dozers	1	8	247	0.4	790	854
	20	Tractors/Loaders/Backhoes	3	8	97	0.37	861	931
	230	Cranes	1	7	231	0.29	469	5,830
D :1.1:	230	Forklifts	2	8	89	0.2	285	3,541
Building	230	Generator Sets	1	8	84	0.74	497	6,182
Construction	230	Tractors/Loaders/Backhoes	1	7	97	0.37	251	3,123
	230	Welders	3	8	46	0.45	497	6,176
	20	Pavers	2	8	130	0.42	874	944
Paving	20	Paving Equipment	2	8	132	0.36	760	822
	20	Rollers	2	8	80	0.38	486	526
Architectural Coating	20	Air Compressors	1	6	78	0.48	225	243
CONSTRUCTION	FUEL DEMA	AND (gallons of diesel fuel)						30,939

Notes:

8.1.3 Construction Worker Fuel Estimates

It is assumed that all construction worker trips are from light duty autos (LDA) along area roadways. With respect to estimated VMT, the construction worker trips would generate an estimated 394,695 VMT. Vehicle fuel efficiencies for construction workers were estimated in the air quality and greenhouse gas analysis using information generated using CARB's EMFAC model (see Appendix C for details). Table 18 shows that an estimated 12,753 gallons of fuel would be consumed for construction worker trips.

¹Using Carl Moyer Guidelines Table D-21 Fuel consumption rate factors (bhp-hr/gal) for engines less than 750 hp. (Source: https://www.arb.ca.gov/msprog/moyer/guidelines/2017gl/2017_gl_appendix_d.pdf)

²³ Aggregate fuel consumption rate for all equipment was estimated at 18.5 hp-hr/day (from CARB's 2017 Emissions Factors Tables and fuel consumption rate factors as shown in Table D-21 of the Moyer Guidelines: (https://www.arb.ca.gov/msprog/moyer/guidelines/2017gl/2017_gl_appendix_d.pdf).

Table 18: Construction Worker Fuel Consumption Estimates

Phase	Number of Days	Worker Trips/Day	Trip Length (miles)	Vehicle Miles Traveled	Average Vehicle Fuel Economy (mpg)	Estimated Fuel Consumption (gallons)
Site Preparation	10	5	14.7	735	30.95	24
Grading	20	15	14.7	4,410	30.95	142
Building Construction	230	112	14.7	378,672	30.95	12,235
Paving	20	15	14.7	4,410	30.95	142
Architectural Coating	20	22	14.7	6,468	30.95	209
Total Construction Worker Fuel Consumption						12,753

Notes:

8.1.4 Construction Vendor/Hauling Fuel Estimates

Tables 19 and 20 show the estimated fuel consumption for vendor and hauling during building construction and architectural coating. With respect to estimated VMT, the vendor and hauling trips would generate an estimated 134,109 VMT. For the architectural coatings it is assumed that the contractors would be responsible for bringing coatings and equipment with them in their light duty vehicles.²⁴ Tables 19 and 20 show that an estimated 16,921 gallons of fuel would be consumed for vendor and hauling trips.

Table 19: Construction Vendor Fuel Consumption Estimates (MHD Trucks)¹

Phase	Number of Days	Vendor Trips/Day	Trip Length (miles)	Vehicle Miles Traveled	Average Vehicle Fuel Economy (mpg)	Estimated Fuel Consumption (gallons)
Site Preparation	10	0	6.9	0	9.22	0
Grading	20	0	6.9	0	9.22	0
Building Construction	230	47	6.9	74,589	9.22	8,090
Paving	20	0	6.9	0	9.22	0
Architectural Coating	20	0	6.9	0	9.22	0
Total Vendor Fuel Consumption						8,090

Notes:

 $^{^{1}\!}Assumptions for the worker trip length and vehicle miles traveled are consistent with CalEEMod 2020.4.0 defaults.$

 $^{^{1}}$ Assumptions for the vendor trip length and vehicle miles traveled are consistent with CalEEMod 2020.4.0 defaults.

²⁴ Vendors delivering construction material or hauling debris from the site during grading would use medium to heavy duty vehicles with an average fuel consumption of 9.22 mpg for medium heavy-duty trucks and 6.74 mpg for heavy heavy-duty trucks (see Appendix C for details).

Table 20: Construction Hauling Fuel Consumption Estimates (HHD Trucks)¹

Phase	Number of Days	Hauling Trips/Day	Trip Length (miles)	Vehicle Miles Traveled	Average Vehicle Fuel Economy (mpg)	Estimated Fuel Consumption (gallons)
Site Preparation	10	0	20	0	6.74	0
Grading	20	148.8	20	59,520	6.74	8,831
Building Construction	230	0	20	0	6.74	0
Paving	20	0	20	0	6.74	0
Architectural Coating	20	0	20	0	6.74	0
Total Construction Hauling Fuel Consumption						8,831

Notes:

8.1.5 Construction Energy Efficiency/Conservation Measures

Construction equipment used over the approximately 14-month construction phase would conform to CARB regulations and California emissions standards and is evidence of related fuel efficiencies. In addition, the CARB Airborne Toxic Control Measure limits idling times of construction vehicles to no more than five minutes, thereby minimizing unnecessary and wasteful consumption of fuel due to unproductive idling of construction equipment. Furthermore, the Project has been designed in compliance with California's Energy Efficiency Standards and 2019 CALGreen Standards.

Construction of the proposed residential development would require the typical use of energy resources. There are no unusual Project characteristics or construction processes that would require the use of equipment that would be more energy intensive than is used for comparable activities; or equipment that would not conform to current emissions standards (and related fuel efficiencies). Equipment employed in construction of the Project would therefore not result in inefficient wasteful, or unnecessary consumption of fuel.

8.2 Operational Energy Demand

Energy consumption in support of or related to Project operations would include transportation energy demands (energy consumed by employee and patron vehicles accessing the Project site) and facilities energy demands (energy consumed by building operations and site maintenance activities).

8.2.1 Transportation Fuel Consumption

The largest source of operational energy use would be vehicle operation of employees. The site is located in an urban area. Using the CalEEMod output, it is assumed that an average trip for autos were assumed to be 16.6 miles, light trucks were assumed to travel an average of 6.9 miles, and 3- 4-axle trucks were

¹Assumptions for the hauling trip length and vehicle miles traveled are consistent with CalEEMod 2020.40 defaults.

assumed to travel an average of 8.4 miles²⁵. To show a worst-case analysis, as the proposed Project is an office project, it was assumed that vehicles would operate 365 days per year. Table 21 shows the worst-case estimated annual fuel consumption for all classes of vehicles from autos to heavy-heavy trucks.²⁶ Table 21 shows that an estimated 72,189 gallons of fuel would be consumed per year for the operation of the proposed Project.

Table 21: Estimated Vehicle Operations Fuel Consumption

Vehicle Type	Vehicle Mix	Number of Vehicles	Average Trip (miles) ¹	Daily VMT	Average Fuel Economy (mpg)	Total Gallons per Day	Total Annual Fuel Consumption (gallons)
Light Auto	Automobile	244	16.6	4,058	31.82	127.54	46,553
Light Truck	Automobile	25	6.69	170	27.16	6.25	2,282
Light Truck	Automobile	78	6.69	524	25.6	20.48	7,474
Medium Truck	Automobile	63	6.69	423	20.81	20.32	7,415
Light Heavy Truck	2-Axle Truck	12	8.4	103	13.81	7.47	2,726
Light Heavy Truck 10,000 lbs +	2-Axle Truck	3	8.4	27	14.18	1.94	707
Medium Heavy Truck	3-Axle Truck	5	8.4	44	9.58	4.54	1,657
Heavy Heavy Truck	4-Axle Truck	8	8.4	66	7.14	9.24	3,374
Total		440		5,415		197.78	
Total Annual Fuel Consumption							72,189

Notes:

Trip generation generated by the proposed Project are consistent with other office residential uses of similar scale and configuration as reflected in the trip generation analysis (Integrated Engineering Group). That is, the proposed Project does not propose uses or operations that would inherently result in excessive and wasteful vehicle trips, nor associated excess and wasteful vehicle energy consumption. Therefore, Project transportation energy consumption would not be considered inefficient, wasteful, or otherwise unnecessary.

8.2.2 Facility Energy Demands (Electricity and Natural Gas)

The annual natural gas and electricity demands were provided per the CalEEMod output and are provided in Table 22.

<Table 22, next page>

¹The trip generation assessment, the Project is to generate 832 total net new trips after reduction of existing uses. Default CalEEMod vehicle fleet mix utilized.
¹Based on the size of the site and relative location, trips were assumed to be local rather than regional.

²⁵ CalEEMod default distance for H-W (home-work) or C-W (commercial-work) is 16.6 miles; 6.9 miles for H-S (home-shop) or C-C (commercial-customer); and 8.4 miles for H-O (home-other) or C-O (commercial-other).

²⁶ Average fuel economy based on aggregate mileage calculated in EMFAC 2017 for opening year (2023). See Appendix C for EMFAC output.

Table 22: Project Unmitigated Annual Operational Energy Demand Summary¹

Natural Gas Demand	kBTU/year
General Office Building	257,463
Total	257,463
Electricity Demand	kWh/year
General Office Building	689,820
Parking Lot	35,000
Total	724,820

Notes:

As shown in Table 22, the estimated electricity demand for the proposed Project is approximately 724,820 kWh per year. It should be noted that the project would install photovoltaic systems in the project which will reduce the electricity demand. In 2020, the non-residential sector of the County of San Bernardino consumed approximately 9,866 million kWh of electricity.²⁷ In addition, the estimated natural gas consumption for the proposed Project is approximately 257,463 kBTU per year. In 2020, the non-residential sector of the County of San Bernardino consumed approximately 260 million therms of gas.²⁸ Therefore, the increase in both electricity and natural gas demand from the proposed Project is insignificant compared to the County's 2020 demand.

8.3 Renewable Energy and Energy Efficiency Plan Consistency

Regarding federal transportation regulations, the Project site is located in an already developed area. Access to/from the Project site is from existing roads. These roads are already in place so the Project would not interfere with, nor otherwise obstruct intermodal transportation plans or projects that may be proposed pursuant to the ISTEA because SCAG is not planning for intermodal facilities in the Project area.

Regarding the State's Energy Plan and compliance with Title 24 CCR energy efficiency standards, the applicant is required to comply with the California Green Building Standard Code requirements for energy efficient buildings and appliances as well as utility energy efficiency programs implemented by the SCE and Southern California Gas Company.

Regarding the State's Renewable Energy Portfolio Standards, the Project would be required to meet or exceed the energy standards established in the California Green Building Standards Code, Title 24, Part 11 (CALGreen). CalGreen Standards require that new buildings reduce water consumption, employ building commissioning to increase building system efficiencies, divert construction waste from landfills, and install low pollutant-emitting finish materials.

¹Taken from the CalEEMod 2020.4.0 annual output.

²⁷ California Energy Commission, Electricity Consumption by County. https://ecdms.energy.ca.gov/elecbycounty.aspx

²⁸ California Energy Commission, Gas Consumption by County. http://ecdms.energy.ca.gov/gasbycounty.aspx

References

The project would install a 700 KVA photovoltaic system as parking canopies over portions of the north and south parking area which would reduce the project's energy demand.

8.4 Cumulative Regional Energy Impacts

Cumulative projects include local development as well as general growth within the project area. However, as with most development, the greatest source of energy usage is from mobile sources, which travel well out of the local area. Therefore, from an energy standpoint, the cumulative analysis would extend beyond any local projects and when wind patterns are considered, would cover an even larger area. Accordingly, the cumulative analysis for the Project's energy must be generic by nature.

The greatest cumulative impact on the regional energy usage will be from increased traffic from residential, commercial, and industrial development and the use of heavy equipment and trucks associated with the construction of these projects. Energy usage will temporarily increase during construction activities that occur separately or simultaneously. However, as the Project's natural gas and electricity usage will both be under 0.01% of the County of San Bernardino's 2019 usage, the Project is considered less than significant.

9.0 References

The following references were used in the preparing this analysis.

California Air Pollution Control Officers Association

2009 Health Risk Assessments for Proposed Land Use Projects

California Air Resources Board

2008	Resolution 08-43
2008	Recommended Approaches for Setting Interim Significance Thresholds for Greenhouse Gases under the California Environmental Quality Act
2008	ARB Recommended Interim Risk Management Policy for Inhalation-Based Residential Cancer Risk – Frequently Asked Questions
2008	Climate Change Scoping Plan, a framework for change.
2011	Supplement to the AB 32 Scoping Plan Functional Equivalent Document
2013	Revised Emission Factors for Gasoline Marketing Operations at California Gasoline Dispensing Facilities
2014	First Update to the Climate Change Scoping Plan, Building on the Framework Pursuant to AB32, the California Global Warming Solutions Act of 2006. May.

County of San Bernardino

2018

- 2007 County of San Bernardino 2007 General Plan, March 13 (amended April 24, 2014).
- 2011 County of San Bernardino Greenhouse Gas Emissions Reduction Plan.

Governor's Office of Planning and Research

- 2008 CEQA and Climate: Addressing Climate Change Through California Environmental Quality Act (CEQA) Review
- 2009 CEQA Guideline Sections to be Added or Amended

Historical Air Quality, Top 4 Summary

Office of Environmental Health Hazard Assessment

2015 Air Toxics Hot Spots Program Risk Assessment Guidelines

References

Integrated Engineering Group

Trip Generation Memorandum - Valley Communications Center, County of San Bernardino. June 24.

South Coast Air Quality Management District

1993	CEQA Air Quality Handbook
2005	Rule 403 Fugitive Dust
2007	2007 Air Quality Management Plan
2008	Final Localized Significance Threshold Methodology, Revised
2011	Appendix A Calculation Details for CalEEMod
2012	Final 2012 Air Quality Management Plan
2016	Final 2016 Air Quality Management Plan

Appendix A:

CalEEMod Daily Emission Output

CalEEMod Version: CalEEMod.2020.4.0 Page 1 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Valley Communications Center

San Bernardino-South Coast County, Summer

1.0 Project Characteristics

1.1 Land Usage

Land Uses	Size	Metric	Lot Acreage	Floor Surface Area	Population
Other Non-Asphalt Surfaces	0.70	Acre	0.70	30,492.00	0
Parking Lot	250.00	Space	2.25	100,000.00	0
General Office Building	75.06	1000sqft	1.72	75,062.00	0
Other Asphalt Surfaces	1.82	Acre	1.82	79,279.20	0

1.2 Other Project Characteristics

Urbanization	Urban	Wind Speed (m/s)	2.2	Precipitation Freq (Days)	32
Climate Zone	10			Operational Year	2023

Utility Company Southern California Edison

 CO2 Intensity
 390.98
 CH4 Intensity
 0.033
 N2O Intensity
 0.004

 (lb/MWhr)
 (lb/MWhr)
 (lb/MWhr)
 (lb/MWhr)

1.3 User Entered Comments & Non-Default Data

Project Characteristics -

Land Use - 6.49 acre lot with 75,062 sqft of office building

Construction Phase -

Grading - 14,000 CY of cut, 2,100 of fill. Site is 6.49 acres.

Construction Off-road Equipment Mitigation -

Waste Mitigation - AB-341

Vehicle Trips - Per trip generation memo, 440 trips per day

Off-road Equipment - Site Preparation required for approx. 1/10 of site.

Valley Communications Center - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Table Name	Column Name	Default Value	New Value
tblGrading	MaterialExported	0.00	11,900.00
tblOffRoadEquipment	OffRoadEquipmentUnitAmount	3.00	1.00
tblOffRoadEquipment	OffRoadEquipmentUnitAmount	4.00	1.00
tblVehicleTrips	ST_TR	2.21	5.86
tblVehicleTrips	SU_TR	0.70	5.86
tblVehicleTrips	WD_TR	9.74	5.86

2.0 Emissions Summary

CalEEMod Version: CalEEMod.2020.4.0 Page 3 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

2.1 Overall Construction (Maximum Daily Emission)

Unmitigated Construction

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Year					lb/d	day							lb/d	day		
2022	2.2935	31.0355	21.7327	0.0750	8.6205	1.0482	9.6687	3.8367	0.9683	4.8050	0.0000	7,794.541 8	7,794.541 8	1.1370	0.7590	8,049.157 0
2023	37.9857	16.2977	21.1594	0.0465	1.5530	0.7183	2.2713	0.4187	0.6760	1.0947	0.0000	4,601.494 1	4,601.494 1	0.7176	0.1601	4,665.675 8
Maximum	37.9857	31.0355	21.7327	0.0750	8.6205	1.0482	9.6687	3.8367	0.9683	4.8050	0.0000	7,794.541 8	7,794.541 8	1.1370	0.7590	8,049.157 0

Mitigated Construction

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Year					lb/d	day							lb/d	day		
2022	2.2935	31.0355	21.7327	0.0750	4.2590	1.0482	5.3073	1.7414	0.9683	2.7097	0.0000	7,794.541 8	7,794.541 8	1.1370	0.7590	8,049.157 0
2023	37.9857	16.2977	21.1594	0.0465	1.5530	0.7183	2.2713	0.4187	0.6760	1.0947	0.0000	4,601.494 1	4,601.494 1	0.7176	0.1601	4,665.675 8
Maximum	37.9857	31.0355	21.7327	0.0750	4.2590	1.0482	5.3073	1.7414	0.9683	2.7097	0.0000	7,794.541 8	7,794.541 8	1.1370	0.7590	8,049.157 0

CalEEMod Version: CalEEMod.2020.4.0 Page 4 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio-CO2	Total CO2	CH4	N20	CO2e
Percent Reduction	0.00	0.00	0.00	0.00	42.87	0.00	36.53	49.24	0.00	35.52	0.00	0.00	0.00	0.00	0.00	0.00

CalEEMod Version: CalEEMod.2020.4.0 Page 5 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

2.2 Overall Operational

Unmitigated Operational

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
Area	1.7703	3.0000e- 004	0.0334	0.0000		1.2000e- 004	1.2000e- 004		1.2000e- 004	1.2000e- 004		0.0717	0.0717	1.9000e- 004		0.0764
Energy	7.6100e- 003	0.0692	0.0581	4.1000e- 004		5.2600e- 003	5.2600e- 003		5.2600e- 003	5.2600e- 003		82.9856	82.9856	1.5900e- 003	1.5200e- 003	83.4787
Mobile	1.4851	1.8904	14.2624	0.0307	2.9922	0.0235	3.0157	0.7981	0.0220	0.8200		3,161.757 5	3,161.757 5	0.1681	0.1458	3,209.419 4
Total	3.2629	1.9598	14.3540	0.0311	2.9922	0.0288	3.0211	0.7981	0.0273	0.8254		3,244.814 8	3,244.814 8	0.1699	0.1474	3,292.974 5

Mitigated Operational

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/	day							lb/d	lay		
Area	1.7703	3.0000e- 004	0.0334	0.0000		1.2000e- 004	1.2000e- 004		1.2000e- 004	1.2000e- 004		0.0717	0.0717	1.9000e- 004		0.0764
Energy	7.6100e- 003	0.0692	0.0581	4.1000e- 004		5.2600e- 003	5.2600e- 003		5.2600e- 003	5.2600e- 003		82.9856	82.9856	1.5900e- 003	1.5200e- 003	83.4787
Mobile	1.4851	1.8904	14.2624	0.0307	2.9922	0.0235	3.0157	0.7981	0.0220	0.8200		3,161.757 5	3,161.757 5	0.1681	0.1458	3,209.419 4
Total	3.2629	1.9598	14.3540	0.0311	2.9922	0.0288	3.0211	0.7981	0.0273	0.8254		3,244.814 8	3,244.814 8	0.1699	0.1474	3,292.974 5

Valley Communications Center - San Bernardino-South Coast County, Summer

Date: 7/5/2022 12:12 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio-CO2	Total CO2	CH4	N20	CO2e
Percent Reduction	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

3.0 Construction Detail

Construction Phase

Phase Number	Phase Name	Phase Type	Start Date	End Date	Num Days Week	Num Days	Phase Description
1	Site Preparation	Site Preparation	9/1/2022	9/14/2022	5	10	
2	Grading	Grading	9/15/2022	10/12/2022	5	20	
3	Building Construction	Building Construction	10/13/2022	8/30/2023	5	230	
4	Paving	Paving	8/31/2023	9/27/2023	5	20	
5	Architectural Coating	Architectural Coating	9/28/2023	10/25/2023	5	20	

Acres of Grading (Site Preparation Phase): 5

Acres of Grading (Grading Phase): 20

Acres of Paving: 4.77

Residential Indoor: 0; Residential Outdoor: 0; Non-Residential Indoor: 112,593; Non-Residential Outdoor: 37,531; Striped Parking Area: 12,586 (Architectural Coating – sqft)

OffRoad Equipment

Phase Name	Offroad Equipment Type	Amount	Usage Hours	Horse Power	Load Factor
Grading	Excavators	1	8.00	158	0.38
Site Preparation	Rubber Tired Dozers	1	8.00	247	0.40
Site Preparation	Tractors/Loaders/Backhoes	1	8.00	97	0.37
Grading	Graders	1	8.00	187	0.41
Grading	Rubber Tired Dozers	1	8.00	247	0.40
Grading	Tractors/Loaders/Backhoes	3	8.00	97	0.37

CalEEMod Version: CalEEMod.2020.4.0 Page 7 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Building Construction	Cranes	1	7.00	231	0.29
Building Construction	Forklifts	3	8.00	89	0.20
Building Construction	Generator Sets	1	8.00	84	0.74
Building Construction	Tractors/Loaders/Backhoes	3	7.00	97	0.37
Building Construction	Welders	1	8.00	46	0.45
Paving	Pavers	2	8.00	130	0.42
Paving	Paving Equipment	2	8.00	132	0.36
Paving	Rollers	2	8.00	80	0.38
Architectural Coating	Air Compressors	1	6.00	78	0.48

Trips and VMT

Phase Name	Offroad Equipment Count	Worker Trip Number	Vendor Trip Number	Hauling Trip Number	Worker Trip Length	Vendor Trip Length	Hauling Trip Length	Worker Vehicle Class	Vendor Vehicle Class	Hauling Vehicle Class
Site Preparation	2	5.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Grading	6	15.00	0.00	1,488.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Building Construction	9	112.00	47.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Paving	6	15.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Architectural Coating	1	22.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT

3.1 Mitigation Measures Construction

Water Exposed Area

CalEEMod Version: CalEEMod.2020.4.0 Page 8 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.2 Site Preparation - 2022

Unmitigated Construction On-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	day		
Fugitive Dust					6.5523	0.0000	6.5523	3.3675	0.0000	3.3675			0.0000			0.0000
Off-Road	1.0018	10.4693	5.8199	0.0116		0.5075	0.5075		0.4669	0.4669		1,128.274 3	1,128.274 3	0.3649		1,137.397 0
Total	1.0018	10.4693	5.8199	0.0116	6.5523	0.5075	7.0598	3.3675	0.4669	3.8344		1,128.274 3	1,128.274 3	0.3649		1,137.397 0

Unmitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	day		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Worker	0.0212	0.0134	0.2060	5.2000e- 004	0.0559	2.9000e- 004	0.0562	0.0148	2.7000e- 004	0.0151		52.4784	52.4784	1.3600e- 003	1.3100e- 003	52.9017
Total	0.0212	0.0134	0.2060	5.2000e- 004	0.0559	2.9000e- 004	0.0562	0.0148	2.7000e- 004	0.0151		52.4784	52.4784	1.3600e- 003	1.3100e- 003	52.9017

CalEEMod Version: CalEEMod.2020.4.0 Page 9 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.2 Site Preparation - 2022

Mitigated Construction On-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	day		
Fugitive Dust					2.5554	0.0000	2.5554	1.3133	0.0000	1.3133			0.0000			0.0000
Off-Road	1.0018	10.4693	5.8199	0.0116		0.5075	0.5075		0.4669	0.4669	0.0000	1,128.274 3	1,128.274 3	0.3649	 	1,137.397 0
Total	1.0018	10.4693	5.8199	0.0116	2.5554	0.5075	3.0629	1.3133	0.4669	1.7802	0.0000	1,128.274 3	1,128.274 3	0.3649		1,137.397 0

Mitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	lay		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Worker	0.0212	0.0134	0.2060	5.2000e- 004	0.0559	2.9000e- 004	0.0562	0.0148	2.7000e- 004	0.0151		52.4784	52.4784	1.3600e- 003	1.3100e- 003	52.9017
Total	0.0212	0.0134	0.2060	5.2000e- 004	0.0559	2.9000e- 004	0.0562	0.0148	2.7000e- 004	0.0151		52.4784	52.4784	1.3600e- 003	1.3100e- 003	52.9017

CalEEMod Version: CalEEMod.2020.4.0 Page 10 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.3 Grading - 2022
Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	day		
Fugitive Dust) 				7.1499	0.0000	7.1499	3.4349	0.0000	3.4349			0.0000			0.0000
Off-Road	1.9486	20.8551	15.2727	0.0297	 	0.9409	0.9409		0.8656	0.8656		2,872.046 4	2,872.046 4	0.9289	 	2,895.268 4
Total	1.9486	20.8551	15.2727	0.0297	7.1499	0.9409	8.0907	3.4349	0.8656	4.3005		2,872.046 4	2,872.046 4	0.9289		2,895.268 4

Unmitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/e	day							lb/d	day		
Hauling	0.2813	10.1401	2.6457	0.0438	1.3029	0.1065	1.4094	0.3573	0.1019	0.4592		4,765.060 2	4,765.060 2	0.2040	0.7551	4,995.183 6
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Worker	0.0635	0.0402	0.6179	1.5500e- 003	0.1677	8.8000e- 004	0.1685	0.0445	8.1000e- 004	0.0453		157.4352	157.4352	4.0900e- 003	3.9200e- 003	158.7050
Total	0.3449	10.1804	3.2637	0.0453	1.4706	0.1074	1.5780	0.4017	0.1027	0.5045		4,922.495 4	4,922.495 4	0.2081	0.7590	5,153.888 6

CalEEMod Version: CalEEMod.2020.4.0 Page 11 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.3 Grading - 2022

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
Fugitive Dust					2.7885	0.0000	2.7885	1.3396	0.0000	1.3396		i ! !	0.0000			0.0000
Off-Road	1.9486	20.8551	15.2727	0.0297		0.9409	0.9409		0.8656	0.8656	0.0000	2,872.046 4	2,872.046 4	0.9289		2,895.268 4
Total	1.9486	20.8551	15.2727	0.0297	2.7885	0.9409	3.7293	1.3396	0.8656	2.2052	0.0000	2,872.046 4	2,872.046 4	0.9289		2,895.268 4

Mitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/e	day							lb/d	day		
Hauling	0.2813	10.1401	2.6457	0.0438	1.3029	0.1065	1.4094	0.3573	0.1019	0.4592		4,765.060 2	4,765.060 2	0.2040	0.7551	4,995.183 6
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Worker	0.0635	0.0402	0.6179	1.5500e- 003	0.1677	8.8000e- 004	0.1685	0.0445	8.1000e- 004	0.0453		157.4352	157.4352	4.0900e- 003	3.9200e- 003	158.7050
Total	0.3449	10.1804	3.2637	0.0453	1.4706	0.1074	1.5780	0.4017	0.1027	0.5045		4,922.495 4	4,922.495 4	0.2081	0.7590	5,153.888 6

CalEEMod Version: CalEEMod.2020.4.0 Page 12 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.4 Building Construction - 2022 <u>Unmitigated Construction On-Site</u>

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
	1.7062	15.6156	16.3634	0.0269		0.8090	0.8090		0.7612	0.7612		2,554.333 6	2,554.333 6	0.6120		2,569.632 2
Total	1.7062	15.6156	16.3634	0.0269		0.8090	0.8090		0.7612	0.7612		2,554.333 6	2,554.333 6	0.6120		2,569.632

Unmitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0819	2.0581	0.7553	8.7700e- 003	0.3011	0.0245	0.3256	0.0867	0.0234	0.1101		940.3235	940.3235	0.0254	0.1392	982.4262
Worker	0.4743	0.3004	4.6140	0.0116	1.2519	6.5700e- 003	1.2585	0.3320	6.0500e- 003	0.3381		1,175.516 1	1,175.516 1	0.0306	0.0293	1,184.997 7
Total	0.5562	2.3586	5.3693	0.0203	1.5530	0.0311	1.5841	0.4187	0.0295	0.4482		2,115.839 6	2,115.839 6	0.0560	0.1684	2,167.423 9

CalEEMod Version: CalEEMod.2020.4.0 Page 13 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.4 Building Construction - 2022

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	lay		
Off-Road	1.7062	15.6156	16.3634	0.0269		0.8090	0.8090		0.7612	0.7612	0.0000	2,554.333 6	2,554.333 6	0.6120		2,569.632 2
Total	1.7062	15.6156	16.3634	0.0269		0.8090	0.8090		0.7612	0.7612	0.0000	2,554.333 6	2,554.333 6	0.6120		2,569.632 2

Mitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	lay		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0819	2.0581	0.7553	8.7700e- 003	0.3011	0.0245	0.3256	0.0867	0.0234	0.1101		940.3235	940.3235	0.0254	0.1392	982.4262
Worker	0.4743	0.3004	4.6140	0.0116	1.2519	6.5700e- 003	1.2585	0.3320	6.0500e- 003	0.3381		1,175.516 1	1,175.516 1	0.0306	0.0293	1,184.997 7
Total	0.5562	2.3586	5.3693	0.0203	1.5530	0.0311	1.5841	0.4187	0.0295	0.4482		2,115.839 6	2,115.839 6	0.0560	0.1684	2,167.423 9

CalEEMod Version: CalEEMod.2020.4.0 Page 14 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.4 Building Construction - 2023

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
Off-Road	1.5728	14.3849	16.2440	0.0269		0.6997	0.6997		0.6584	0.6584		2,555.209 9	2,555.209 9	0.6079		2,570.406 1
Total	1.5728	14.3849	16.2440	0.0269		0.6997	0.6997		0.6584	0.6584		2,555.209 9	2,555.209 9	0.6079		2,570.406 1

Unmitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	day		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0550	1.6486	0.6918	8.4100e- 003	0.3011	0.0124	0.3135	0.0867	0.0119	0.0986		902.0155	902.0155	0.0236	0.1332	942.2993
Worker	0.4379	0.2643	4.2236	0.0112	1.2519	6.1900e- 003	1.2581	0.3320	5.6900e- 003	0.3377		1,144.268 8	1,144.268 8	0.0273	0.0269	1,152.970 5
Total	0.4930	1.9128	4.9154	0.0196	1.5530	0.0186	1.5716	0.4187	0.0175	0.4363		2,046.284	2,046.284	0.0509	0.1601	2,095.269 8

CalEEMod Version: CalEEMod.2020.4.0 Page 15 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.4 Building Construction - 2023

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	lay		
Off-Road	1.5728	14.3849	16.2440	0.0269		0.6997	0.6997		0.6584	0.6584	0.0000	2,555.209 9	2,555.209 9	0.6079		2,570.406 1
Total	1.5728	14.3849	16.2440	0.0269		0.6997	0.6997		0.6584	0.6584	0.0000	2,555.209 9	2,555.209 9	0.6079		2,570.406 1

Mitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0550	1.6486	0.6918	8.4100e- 003	0.3011	0.0124	0.3135	0.0867	0.0119	0.0986		902.0155	902.0155	0.0236	0.1332	942.2993
Worker	0.4379	0.2643	4.2236	0.0112	1.2519	6.1900e- 003	1.2581	0.3320	5.6900e- 003	0.3377		1,144.268 8	1,144.268 8	0.0273	0.0269	1,152.970 5
Total	0.4930	1.9128	4.9154	0.0196	1.5530	0.0186	1.5716	0.4187	0.0175	0.4363		2,046.284	2,046.284 2	0.0509	0.1601	2,095.269 8

CalEEMod Version: CalEEMod.2020.4.0 Page 16 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.5 Paving - 2023
<u>Unmitigated Construction On-Site</u>

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	day		
Off-Road	1.0327	10.1917	14.5842	0.0228		0.5102	0.5102		0.4694	0.4694		2,207.584 1	2,207.584 1	0.7140		2,225.433 6
Paving	0.5332]			0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Total	1.5659	10.1917	14.5842	0.0228		0.5102	0.5102		0.4694	0.4694		2,207.584 1	2,207.584 1	0.7140		2,225.433 6

Unmitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Worker	0.0587	0.0354	0.5657	1.5000e- 003	0.1677	8.3000e- 004	0.1685	0.0445	7.6000e- 004	0.0452		153.2503	153.2503	3.6600e- 003	3.6000e- 003	154.4157
Total	0.0587	0.0354	0.5657	1.5000e- 003	0.1677	8.3000e- 004	0.1685	0.0445	7.6000e- 004	0.0452		153.2503	153.2503	3.6600e- 003	3.6000e- 003	154.4157

CalEEMod Version: CalEEMod.2020.4.0 Page 17 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.5 Paving - 2023

<u>Mitigated Construction On-Site</u>

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	day		
Off-Road	1.0327	10.1917	14.5842	0.0228		0.5102	0.5102		0.4694	0.4694	0.0000	2,207.584 1	2,207.584 1	0.7140		2,225.433 6
Paving	0.5332]			0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Total	1.5659	10.1917	14.5842	0.0228		0.5102	0.5102		0.4694	0.4694	0.0000	2,207.584 1	2,207.584 1	0.7140		2,225.433 6

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	lay		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Worker	0.0587	0.0354	0.5657	1.5000e- 003	0.1677	8.3000e- 004	0.1685	0.0445	7.6000e- 004	0.0452		153.2503	153.2503	3.6600e- 003	3.6000e- 003	154.4157
Total	0.0587	0.0354	0.5657	1.5000e- 003	0.1677	8.3000e- 004	0.1685	0.0445	7.6000e- 004	0.0452		153.2503	153.2503	3.6600e- 003	3.6000e- 003	154.4157

CalEEMod Version: CalEEMod.2020.4.0 Page 18 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.6 Architectural Coating - 2023 <u>Unmitigated Construction On-Site</u>

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
Archit. Coating	37.7080					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Off-Road	0.1917	1.3030	1.8111	2.9700e- 003		0.0708	0.0708		0.0708	0.0708		281.4481	281.4481	0.0168		281.8690
Total	37.8997	1.3030	1.8111	2.9700e- 003		0.0708	0.0708		0.0708	0.0708		281.4481	281.4481	0.0168		281.8690

Unmitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	lay		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Worker	0.0860	0.0519	0.8296	2.2000e- 003	0.2459	1.2100e- 003	0.2471	0.0652	1.1200e- 003	0.0663		224.7671	224.7671	5.3700e- 003	5.2900e- 003	226.4763
Total	0.0860	0.0519	0.8296	2.2000e- 003	0.2459	1.2100e- 003	0.2471	0.0652	1.1200e- 003	0.0663		224.7671	224.7671	5.3700e- 003	5.2900e- 003	226.4763

CalEEMod Version: CalEEMod.2020.4.0 Page 19 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.6 Architectural Coating - 2023 Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	day		
Archit. Coating	37.7080					0.0000	0.0000	i i i	0.0000	0.0000			0.0000			0.0000
Off-Road	0.1917	1.3030	1.8111	2.9700e- 003		0.0708	0.0708	1 1 1 1	0.0708	0.0708	0.0000	281.4481	281.4481	0.0168	, , ,	281.8690
Total	37.8997	1.3030	1.8111	2.9700e- 003		0.0708	0.0708		0.0708	0.0708	0.0000	281.4481	281.4481	0.0168		281.8690

Mitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	day		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Worker	0.0860	0.0519	0.8296	2.2000e- 003	0.2459	1.2100e- 003	0.2471	0.0652	1.1200e- 003	0.0663		224.7671	224.7671	5.3700e- 003	5.2900e- 003	226.4763
Total	0.0860	0.0519	0.8296	2.2000e- 003	0.2459	1.2100e- 003	0.2471	0.0652	1.1200e- 003	0.0663		224.7671	224.7671	5.3700e- 003	5.2900e- 003	226.4763

CalEEMod Version: CalEEMod.2020.4.0 Page 20 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

4.0 Operational Detail - Mobile

4.1 Mitigation Measures Mobile

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
Mitigated	1.4851	1.8904	14.2624	0.0307	2.9922	0.0235	3.0157	0.7981	0.0220	0.8200		3,161.757 5	3,161.757 5	0.1681	0.1458	3,209.419 4
Unmitigated	1.4851	1.8904	14.2624	0.0307	2.9922	0.0235	3.0157	0.7981	0.0220	0.8200		3,161.757 5	3,161.757 5	0.1681	0.1458	3,209.419 4

4.2 Trip Summary Information

	Avei	age Daily Trip Ra	ate	Unmitigated	Mitigated
Land Use	Weekday	Saturday	Sunday	Annual VMT	Annual VMT
General Office Building	439.86	439.86	439.86	1,417,003	1,417,003
Other Asphalt Surfaces	0.00	0.00	0.00		
Other Non-Asphalt Surfaces	0.00	0.00	0.00		
Parking Lot	0.00	0.00	0.00		
Total	439.86	439.86	439.86	1,417,003	1,417,003

4.3 Trip Type Information

		Miles			Trip %			Trip Purpos	e %
Land Use	H-W or C-W	H-S or C-C	H-O or C-NW	H-W or C-W	H-S or C-C	H-O or C-NW	Primary	Diverted	Pass-by
General Office Building	16.60	8.40	6.90	33.00	48.00	19.00	77	19	4
Other Asphalt Surfaces	16.60	8.40	6.90	0.00	0.00	0.00	0	0	0
Other Non-Asphalt Surfaces	16.60	8.40	6.90	0.00	0.00	0.00	0	0	0

Valley Communications Center - San Bernardino-South Coast County, Summer

Date: 7/5/2022 12:12 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

		Miles			Trip %			Trip Purpos	e %
Land Use	H-W or C-W	H-S or C-C	H-O or C-NW	H-W or C-W	H-S or C-C	H-O or C-NW	Primary	Diverted	Pass-by
Parking Lot	16.60	8.40	6.90	0.00	0.00	0.00	0	0	0

4.4 Fleet Mix

Land Use	LDA	LDT1	LDT2	MDV	LHD1	LHD2	MHD	HHD	OBUS	UBUS	MCY	SBUS	MH
General Office Building	0.537785	0.055838	0.172353	0.139003	0.027005	0.007196	0.011392	0.017285	0.000559	0.000254	0.025303	0.000954	0.005071
Other Asphalt Surfaces	0.537785	0.055838	0.172353	0.139003	0.027005	0.007196	0.011392	0.017285	0.000559	0.000254	0.025303	0.000954	0.005071
Other Non-Asphalt Surfaces	0.537785	0.055838	0.172353	0.139003	0.027005	0.007196	0.011392	0.017285	0.000559	0.000254	0.025303	0.000954	0.005071
Parking Lot	0.537785	0.055838	0.172353	0.139003	0.027005	0.007196	0.011392	0.017285	0.000559	0.000254	0.025303	0.000954	0.005071

5.0 Energy Detail

Historical Energy Use: N

5.1 Mitigation Measures Energy

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	lay		
Natural Cao	7.6100e- 003	0.0692	0.0581	4.1000e- 004		5.2600e- 003	5.2600e- 003		5.2600e- 003	5.2600e- 003		82.9856	82.9856	1.5900e- 003	1.5200e- 003	83.4787
Unmitigated	7.6100e- 003	0.0692	0.0581	4.1000e- 004		5.2600e- 003	5.2600e- 003		5.2600e- 003	5.2600e- 003		82.9856	82.9856	1.5900e- 003	1.5200e- 003	83.4787

Valley Communications Center - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

5.2 Energy by Land Use - NaturalGas

Unmitigated

	NaturalGa s Use	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU/yr					lb/d	day							lb/d	lay		
General Office Building	705.377	7.6100e- 003	0.0692	0.0581	4.1000e- 004		5.2600e- 003	5.2600e- 003		5.2600e- 003	5.2600e- 003		82.9856	82.9856	1.5900e- 003	1.5200e- 003	83.4787
Other Asphalt Surfaces	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Other Non- Asphalt Surfaces	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Parking Lot	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Total		7.6100e- 003	0.0692	0.0581	4.1000e- 004		5.2600e- 003	5.2600e- 003		5.2600e- 003	5.2600e- 003		82.9856	82.9856	1.5900e- 003	1.5200e- 003	83.4787

CalEEMod Version: CalEEMod.2020.4.0 Page 23 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

5.2 Energy by Land Use - NaturalGas

Mitigated

	NaturalGa s Use	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU/yr					lb/d	day							lb/d	day		
General Office Building	0.705377	7.6100e- 003	0.0692	0.0581	4.1000e- 004		5.2600e- 003	5.2600e- 003		5.2600e- 003	5.2600e- 003		82.9856	82.9856	1.5900e- 003	1.5200e- 003	83.4787
Other Asphalt Surfaces	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Other Non- Asphalt Surfaces	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Parking Lot	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Total		7.6100e- 003	0.0692	0.0581	4.1000e- 004		5.2600e- 003	5.2600e- 003		5.2600e- 003	5.2600e- 003		82.9856	82.9856	1.5900e- 003	1.5200e- 003	83.4787

6.0 Area Detail

6.1 Mitigation Measures Area

CalEEMod Version: CalEEMod.2020.4.0 Page 24 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	lay		
Mitigated	1.7703	3.0000e- 004	0.0334	0.0000		1.2000e- 004	1.2000e- 004		1.2000e- 004	1.2000e- 004		0.0717	0.0717	1.9000e- 004		0.0764
Unmitigated	1.7703	3.0000e- 004	0.0334	0.0000		1.2000e- 004	1.2000e- 004		1.2000e- 004	1.2000e- 004		0.0717	0.0717	1.9000e- 004		0.0764

6.2 Area by SubCategory

Unmitigated

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e	
SubCategory		lb/day										lb/day					
Architectural Coating	0.2066					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000	
Products	1.5605				 	0.0000	0.0000	 	0.0000	0.0000			0.0000			0.0000	
· · · •	3.1000e- 003	3.0000e- 004	0.0334	0.0000	 	1.2000e- 004	1.2000e- 004	 	1.2000e- 004	1.2000e- 004		0.0717	0.0717	1.9000e- 004		0.0764	
Total	1.7703	3.0000e- 004	0.0334	0.0000		1.2000e- 004	1.2000e- 004		1.2000e- 004	1.2000e- 004		0.0717	0.0717	1.9000e- 004		0.0764	

CalEEMod Version: CalEEMod.2020.4.0 Page 25 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

6.2 Area by SubCategory

Mitigated

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e	
SubCategory		lb/day										lb/day					
Architectural Coating	0.2066					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000	
Consumer Products	1.5605					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000	
Landscaping	3.1000e- 003	3.0000e- 004	0.0334	0.0000		1.2000e- 004	1.2000e- 004		1.2000e- 004	1.2000e- 004		0.0717	0.0717	1.9000e- 004		0.0764	
Total	1.7703	3.0000e- 004	0.0334	0.0000		1.2000e- 004	1.2000e- 004		1.2000e- 004	1.2000e- 004		0.0717	0.0717	1.9000e- 004		0.0764	

7.0 Water Detail

7.1 Mitigation Measures Water

CalEEMod Version: CalEEMod.2020.4.0 Page 26 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Summer

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

8.0 Waste Detail

8.1 Mitigation Measures Waste

Institute Recycling and Composting Services

9.0 Operational Offroad

Equipment Type	Number	Hours/Day	Days/Year	Horse Power	Load Factor	Fuel Type

10.0 Stationary Equipment

Fire Pumps and Emergency Generators

Equipment Type	Number	Hours/Day	Hours/Year	Horse Power	Load Factor	Fuel Type

Boilers

Equipment Type	Number	Heat Input/Day	Heat Input/Year	Boiler Rating	Fuel Type

User Defined Equipment

Equipment Type	Number
' ' ''	

11.0 Vegetation

CalEEMod Version: CalEEMod.2020.4.0 Page 1 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Valley Communications Center

San Bernardino-South Coast County, Winter

1.0 Project Characteristics

1.1 Land Usage

Land Uses	Size	Metric	Lot Acreage	Floor Surface Area	Population
Other Non-Asphalt Surfaces	0.70	Acre	0.70	30,492.00	0
Parking Lot	250.00	Space	2.25	100,000.00	0
General Office Building	75.06	1000sqft	1.72	75,062.00	0
Other Asphalt Surfaces	1.82	Acre	1.82	79,279.20	0

1.2 Other Project Characteristics

Urbanization	Urban	Wind Speed (m/s)	2.2	Precipitation Freq (Days)	32
Climate Zone	10			Operational Year	2023

Utility Company Southern California Edison

 CO2 Intensity
 390.98
 CH4 Intensity
 0.033
 N2O Intensity
 0.004

 (lb/MWhr)
 (lb/MWhr)
 (lb/MWhr)
 (lb/MWhr)

1.3 User Entered Comments & Non-Default Data

Project Characteristics -

Land Use - 6.49 acre lot with 75,062 sqft of office building

Construction Phase -

Grading - 14,000 CY of cut, 2,100 of fill. Site is 6.49 acres.

Construction Off-road Equipment Mitigation -

Waste Mitigation - AB-341

Vehicle Trips - Per trip generation memo, 440 trips per day

Off-road Equipment - Site Preparation required for approx. 1/10 of site.

Valley Communications Center - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Table Name	Column Name	Default Value	New Value
tblGrading	MaterialExported	0.00	11,900.00
tblOffRoadEquipment	OffRoadEquipmentUnitAmount	3.00	1.00
tblOffRoadEquipment	OffRoadEquipmentUnitAmount	4.00	1.00
tblVehicleTrips	ST_TR	2.21	5.86
tblVehicleTrips	SU_TR	0.70	5.86
tblVehicleTrips	WD_TR	9.74	5.86

2.0 Emissions Summary

CalEEMod Version: CalEEMod.2020.4.0 Page 3 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

2.1 Overall Construction (Maximum Daily Emission)

Unmitigated Construction

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Year	lb/day												lb/d	lay		
2022	2.2794	31.5441	20.9354	0.0748	8.6205	1.0484	9.6689	3.8367	0.9685	4.8051	0.0000	7,783.252 7	7,783.252 7	1.1364	0.7597	8,038.059 5
2023	37.9826	16.4040	20.4334	0.0455	1.5530	0.7184	2.2714	0.4187	0.6760	1.0947	0.0000	4,496.091 3	4,496.091 3	0.7176	0.1614	4,560.650 2
Maximum	37.9826	31.5441	20.9354	0.0748	8.6205	1.0484	9.6689	3.8367	0.9685	4.8051	0.0000	7,783.252 7	7,783.252 7	1.1364	0.7597	8,038.059 5

Mitigated Construction

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Year	lb/day												lb/c	lay		
2022	2.2794	31.5441	20.9354	0.0748	4.2590	1.0484	5.3074	1.7414	0.9685	2.7098	0.0000	7,783.252 7	7,783.252 7	1.1364	0.7597	8,038.059 5
2023	37.9826	16.4040	20.4334	0.0455	1.5530	0.7184	2.2714	0.4187	0.6760	1.0947	0.0000	4,496.091 3	4,496.091 3	0.7176	0.1614	4,560.650 2
Maximum	37.9826	31.5441	20.9354	0.0748	4.2590	1.0484	5.3074	1.7414	0.9685	2.7098	0.0000	7,783.252 7	7,783.252 7	1.1364	0.7597	8,038.059 5

CalEEMod Version: CalEEMod.2020.4.0 Page 4 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio-CO2	Total CO2	CH4	N20	CO2e
Percent Reduction	0.00	0.00	0.00	0.00	42.87	0.00	36.53	49.24	0.00	35.51	0.00	0.00	0.00	0.00	0.00	0.00

CalEEMod Version: CalEEMod.2020.4.0 Page 5 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

2.2 Overall Operational

Unmitigated Operational

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day							lb/day								
Area	1.7703	3.0000e- 004	0.0334	0.0000		1.2000e- 004	1.2000e- 004		1.2000e- 004	1.2000e- 004		0.0717	0.0717	1.9000e- 004		0.0764
Energy	7.6100e- 003	0.0692	0.0581	4.1000e- 004		5.2600e- 003	5.2600e- 003		5.2600e- 003	5.2600e- 003		82.9856	82.9856	1.5900e- 003	1.5200e- 003	83.4787
Mobile	1.2912	2.0073	12.7381	0.0285	2.9922	0.0235	3.0157	0.7981	0.0220	0.8200		2,933.378 9	2,933.378 9	0.1724	0.1496	2,982.255 7
Total	3.0691	2.0767	12.8297	0.0289	2.9922	0.0289	3.0211	0.7981	0.0274	0.8254		3,016.436 2	3,016.436 2	0.1742	0.1511	3,065.810 8

Mitigated Operational

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day									lb/d	lay					
Area	1.7703	3.0000e- 004	0.0334	0.0000		1.2000e- 004	1.2000e- 004		1.2000e- 004	1.2000e- 004		0.0717	0.0717	1.9000e- 004		0.0764
Energy	7.6100e- 003	0.0692	0.0581	4.1000e- 004		5.2600e- 003	5.2600e- 003		5.2600e- 003	5.2600e- 003		82.9856	82.9856	1.5900e- 003	1.5200e- 003	83.4787
Mobile	1.2912	2.0073	12.7381	0.0285	2.9922	0.0235	3.0157	0.7981	0.0220	0.8200		2,933.378 9	2,933.378 9	0.1724	0.1496	2,982.255 7
Total	3.0691	2.0767	12.8297	0.0289	2.9922	0.0289	3.0211	0.7981	0.0274	0.8254		3,016.436 2	3,016.436 2	0.1742	0.1511	3,065.810 8

Valley Communications Center - San Bernardino-South Coast County, Winter

Date: 7/5/2022 12:12 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio-CO2	Total CO2	CH4	N20	CO2e
Percent Reduction	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

3.0 Construction Detail

Construction Phase

Phase Number	Phase Name	Phase Type	Start Date	End Date	Num Days Week	Num Days	Phase Description
1	Site Preparation	Site Preparation	9/1/2022	9/14/2022	5	10	
2	Grading	Grading	9/15/2022	10/12/2022	5	20	
3	Building Construction	Building Construction	10/13/2022	8/30/2023	5	230	
4	Paving	Paving	8/31/2023	9/27/2023	5	20	
5	Architectural Coating	Architectural Coating	9/28/2023	10/25/2023	5	20	

Acres of Grading (Site Preparation Phase): 5

Acres of Grading (Grading Phase): 20

Acres of Paving: 4.77

Residential Indoor: 0; Residential Outdoor: 0; Non-Residential Indoor: 112,593; Non-Residential Outdoor: 37,531; Striped Parking Area: 12,586 (Architectural Coating – sqft)

OffRoad Equipment

Phase Name	Offroad Equipment Type	Amount	Usage Hours	Horse Power	Load Factor
Grading	Excavators	1	8.00	158	0.38
Site Preparation	Rubber Tired Dozers	1	8.00	247	0.40
Site Preparation	Tractors/Loaders/Backhoes	1	8.00	97	0.37
Grading	Graders	1	8.00	187	0.41
Grading	Rubber Tired Dozers	1	8.00	247	0.40
Grading	Tractors/Loaders/Backhoes	3	8.00	97	0.37

CalEEMod Version: CalEEMod.2020.4.0 Page 7 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Building Construction	Cranes	1	7.00	231	0.29
Building Construction	Forklifts	3	8.00	89	0.20
Building Construction	Generator Sets	1	8.00	84	0.74
Building Construction	Tractors/Loaders/Backhoes	3	7.00	97	0.37
Building Construction	Welders	1	8.00	46	0.45
Paving	Pavers	2	8.00	130	0.42
Paving	Paving Equipment	2	8.00	132	0.36
Paving	Rollers	2	8.00	80	0.38
Architectural Coating	Air Compressors	1	6.00	78	0.48

Trips and VMT

Phase Name	Offroad Equipment Count	Worker Trip Number	Vendor Trip Number	Hauling Trip Number	Worker Trip Length	Vendor Trip Length	Hauling Trip Length	Worker Vehicle Class	Vendor Vehicle Class	Hauling Vehicle Class
Site Preparation	2	5.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Grading	6	15.00	0.00	1,488.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Building Construction	9	112.00	47.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Paving	6	15.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Architectural Coating	1	22.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT

3.1 Mitigation Measures Construction

Water Exposed Area

CalEEMod Version: CalEEMod.2020.4.0 Page 8 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.2 Site Preparation - 2022

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	day		
Fugitive Dust					6.5523	0.0000	6.5523	3.3675	0.0000	3.3675			0.0000			0.0000
Off-Road	1.0018	10.4693	5.8199	0.0116		0.5075	0.5075		0.4669	0.4669		1,128.274 3	1,128.274 3	0.3649		1,137.397 0
Total	1.0018	10.4693	5.8199	0.0116	6.5523	0.5075	7.0598	3.3675	0.4669	3.8344		1,128.274 3	1,128.274 3	0.3649		1,137.397 0

Unmitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	lay		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Worker	0.0203	0.0141	0.1692	4.7000e- 004	0.0559	2.9000e- 004	0.0562	0.0148	2.7000e- 004	0.0151		47.5295	47.5295	1.3600e- 003	1.3500e- 003	47.9653
Total	0.0203	0.0141	0.1692	4.7000e- 004	0.0559	2.9000e- 004	0.0562	0.0148	2.7000e- 004	0.0151		47.5295	47.5295	1.3600e- 003	1.3500e- 003	47.9653

CalEEMod Version: CalEEMod.2020.4.0 Page 9 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.2 Site Preparation - 2022

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	lay		
Fugitive Dust					2.5554	0.0000	2.5554	1.3133	0.0000	1.3133			0.0000			0.0000
Off-Road	1.0018	10.4693	5.8199	0.0116		0.5075	0.5075		0.4669	0.4669	0.0000	1,128.274 3	1,128.274 3	0.3649		1,137.397 0
Total	1.0018	10.4693	5.8199	0.0116	2.5554	0.5075	3.0629	1.3133	0.4669	1.7802	0.0000	1,128.274 3	1,128.274 3	0.3649		1,137.397 0

Mitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	lay		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Worker	0.0203	0.0141	0.1692	4.7000e- 004	0.0559	2.9000e- 004	0.0562	0.0148	2.7000e- 004	0.0151		47.5295	47.5295	1.3600e- 003	1.3500e- 003	47.9653
Total	0.0203	0.0141	0.1692	4.7000e- 004	0.0559	2.9000e- 004	0.0562	0.0148	2.7000e- 004	0.0151		47.5295	47.5295	1.3600e- 003	1.3500e- 003	47.9653

CalEEMod Version: CalEEMod.2020.4.0 Page 10 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.3 Grading - 2022

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	day		
Fugitive Dust					7.1499	0.0000	7.1499	3.4349	0.0000	3.4349			0.0000			0.0000
Off-Road	1.9486	20.8551	15.2727	0.0297		0.9409	0.9409		0.8656	0.8656		2,872.046 4	2,872.046 4	0.9289		2,895.268 4
Total	1.9486	20.8551	15.2727	0.0297	7.1499	0.9409	8.0907	3.4349	0.8656	4.3005		2,872.046 4	2,872.046 4	0.9289		2,895.268 4

Unmitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	day		
Hauling	0.2698	10.6466	2.7055	0.0438	1.3029	0.1067	1.4096	0.3573	0.1021	0.4593		4,768.617 9	4,768.617 9	0.2035	0.7557	4,998.895 3
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Worker	0.0610	0.0423	0.5076	1.4000e- 003	0.1677	8.8000e- 004	0.1685	0.0445	8.1000e- 004	0.0453		142.5884	142.5884	4.0800e- 003	4.0400e- 003	143.8959
Total	0.3308	10.6890	3.2131	0.0452	1.4706	0.1076	1.5781	0.4017	0.1029	0.5046		4,911.206 3	4,911.206 3	0.2075	0.7597	5,142.791 2

CalEEMod Version: CalEEMod.2020.4.0 Page 11 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.3 Grading - 2022

Mitigated Construction On-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	lay		
Fugitive Dust					2.7885	0.0000	2.7885	1.3396	0.0000	1.3396			0.0000			0.0000
Off-Road	1.9486	20.8551	15.2727	0.0297		0.9409	0.9409		0.8656	0.8656	0.0000	2,872.046 4	2,872.046 4	0.9289		2,895.268 4
Total	1.9486	20.8551	15.2727	0.0297	2.7885	0.9409	3.7293	1.3396	0.8656	2.2052	0.0000	2,872.046 4	2,872.046 4	0.9289		2,895.268 4

Mitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/	day							lb/d	day		
Hauling	0.2698	10.6466	2.7055	0.0438	1.3029	0.1067	1.4096	0.3573	0.1021	0.4593		4,768.617 9	4,768.617 9	0.2035	0.7557	4,998.895 3
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Worker	0.0610	0.0423	0.5076	1.4000e- 003	0.1677	8.8000e- 004	0.1685	0.0445	8.1000e- 004	0.0453		142.5884	142.5884	4.0800e- 003	4.0400e- 003	143.8959
Total	0.3308	10.6890	3.2131	0.0452	1.4706	0.1076	1.5781	0.4017	0.1029	0.5046		4,911.206 3	4,911.206 3	0.2075	0.7597	5,142.791 2

CalEEMod Version: CalEEMod.2020.4.0 Page 12 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.4 Building Construction - 2022 <u>Unmitigated Construction On-Site</u>

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
Off-Road	1.7062	15.6156	16.3634	0.0269		0.8090	0.8090		0.7612	0.7612		2,554.333 6	2,554.333 6	0.6120		2,569.632 2
Total	1.7062	15.6156	16.3634	0.0269		0.8090	0.8090		0.7612	0.7612		2,554.333 6	2,554.333 6	0.6120		2,569.632 2

Unmitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0787	2.1606	0.7819	8.7800e- 003	0.3011	0.0246	0.3257	0.0867	0.0235	0.1102		941.3607	941.3607	0.0253	0.1394	983.5314
Worker	0.4557	0.3160	3.7901	0.0105	1.2519	6.5700e- 003	1.2585	0.3320	6.0500e- 003	0.3381		1,064.659 7	1,064.659 7	0.0305	0.0302	1,074.422 3
Total	0.5344	2.4766	4.5720	0.0193	1.5530	0.0311	1.5842	0.4187	0.0296	0.4483		2,006.020 4	2,006.020 4	0.0557	0.1696	2,057.953 7

CalEEMod Version: CalEEMod.2020.4.0 Page 13 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.4 Building Construction - 2022

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	lay		
Off-Road	1.7062	15.6156	16.3634	0.0269		0.8090	0.8090		0.7612	0.7612	0.0000	2,554.333 6	2,554.333 6	0.6120		2,569.632 2
Total	1.7062	15.6156	16.3634	0.0269		0.8090	0.8090		0.7612	0.7612	0.0000	2,554.333 6	2,554.333 6	0.6120		2,569.632 2

Mitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/e	day							lb/d	day		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0787	2.1606	0.7819	8.7800e- 003	0.3011	0.0246	0.3257	0.0867	0.0235	0.1102		941.3607	941.3607	0.0253	0.1394	983.5314
Worker	0.4557	0.3160	3.7901	0.0105	1.2519	6.5700e- 003	1.2585	0.3320	6.0500e- 003	0.3381		1,064.659 7	1,064.659 7	0.0305	0.0302	1,074.422 3
Total	0.5344	2.4766	4.5720	0.0193	1.5530	0.0311	1.5842	0.4187	0.0296	0.4483		2,006.020 4	2,006.020 4	0.0557	0.1696	2,057.953 7

CalEEMod Version: CalEEMod.2020.4.0 Page 14 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.4 Building Construction - 2023

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
Off-Road	1.5728	14.3849	16.2440	0.0269		0.6997	0.6997		0.6584	0.6584		2,555.209 9	2,555.209 9	0.6079		2,570.406 1
Total	1.5728	14.3849	16.2440	0.0269		0.6997	0.6997		0.6584	0.6584		2,555.209 9	2,555.209 9	0.6079		2,570.406 1

Unmitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	lay		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0512	1.7413	0.7131	8.4300e- 003	0.3011	0.0124	0.3136	0.0867	0.0119	0.0986		904.2029	904.2029	0.0234	0.1336	944.6054
Worker	0.4219	0.2779	3.4763	0.0101	1.2519	6.1900e- 003	1.2581	0.3320	5.6900e- 003	0.3377		1,036.678 4	1,036.678 4	0.0274	0.0278	1,045.638 7
Total	0.4730	2.0191	4.1894	0.0186	1.5530	0.0186	1.5716	0.4187	0.0176	0.4363		1,940.881 4	1,940.881 4	0.0508	0.1614	1,990.244 1

CalEEMod Version: CalEEMod.2020.4.0 Page 15 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.4 Building Construction - 2023

Mitigated Construction On-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
Off-Road	1.5728	14.3849	16.2440	0.0269		0.6997	0.6997	1 1 1	0.6584	0.6584	0.0000	2,555.209 9	2,555.209 9	0.6079		2,570.406 1
Total	1.5728	14.3849	16.2440	0.0269		0.6997	0.6997		0.6584	0.6584	0.0000	2,555.209 9	2,555.209 9	0.6079		2,570.406 1

Mitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	day		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0512	1.7413	0.7131	8.4300e- 003	0.3011	0.0124	0.3136	0.0867	0.0119	0.0986		904.2029	904.2029	0.0234	0.1336	944.6054
Worker	0.4219	0.2779	3.4763	0.0101	1.2519	6.1900e- 003	1.2581	0.3320	5.6900e- 003	0.3377		1,036.678 4	1,036.678 4	0.0274	0.0278	1,045.638 7
Total	0.4730	2.0191	4.1894	0.0186	1.5530	0.0186	1.5716	0.4187	0.0176	0.4363		1,940.881 4	1,940.881 4	0.0508	0.1614	1,990.244 1

CalEEMod Version: CalEEMod.2020.4.0 Page 16 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.5 Paving - 2023
<u>Unmitigated Construction On-Site</u>

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
Off-Road	1.0327	10.1917	14.5842	0.0228		0.5102	0.5102		0.4694	0.4694		2,207.584 1	2,207.584 1	0.7140		2,225.433 6
Paving	0.5332					0.0000	0.0000	1 1 1 1	0.0000	0.0000			0.0000			0.0000
Total	1.5659	10.1917	14.5842	0.0228		0.5102	0.5102		0.4694	0.4694		2,207.584 1	2,207.584 1	0.7140		2,225.433 6

Unmitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	lay		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Worker	0.0565	0.0372	0.4656	1.3600e- 003	0.1677	8.3000e- 004	0.1685	0.0445	7.6000e- 004	0.0452		138.8409	138.8409	3.6600e- 003	3.7200e- 003	140.0409
Total	0.0565	0.0372	0.4656	1.3600e- 003	0.1677	8.3000e- 004	0.1685	0.0445	7.6000e- 004	0.0452		138.8409	138.8409	3.6600e- 003	3.7200e- 003	140.0409

CalEEMod Version: CalEEMod.2020.4.0 Page 17 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.5 Paving - 2023

<u>Mitigated Construction On-Site</u>

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	day		
Off-Road	1.0327	10.1917	14.5842	0.0228		0.5102	0.5102		0.4694	0.4694	0.0000	2,207.584 1	2,207.584 1	0.7140		2,225.433 6
Paving	0.5332]			0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Total	1.5659	10.1917	14.5842	0.0228		0.5102	0.5102		0.4694	0.4694	0.0000	2,207.584 1	2,207.584 1	0.7140		2,225.433 6

Mitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day				lb/d	day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Worker	0.0565	0.0372	0.4656	1.3600e- 003	0.1677	8.3000e- 004	0.1685	0.0445	7.6000e- 004	0.0452		138.8409	138.8409	3.6600e- 003	3.7200e- 003	140.0409
Total	0.0565	0.0372	0.4656	1.3600e- 003	0.1677	8.3000e- 004	0.1685	0.0445	7.6000e- 004	0.0452		138.8409	138.8409	3.6600e- 003	3.7200e- 003	140.0409

CalEEMod Version: CalEEMod.2020.4.0 Page 18 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.6 Architectural Coating - 2023 <u>Unmitigated Construction On-Site</u>

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
Archit. Coating	37.7080					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Off-Road	0.1917	1.3030	1.8111	2.9700e- 003		0.0708	0.0708		0.0708	0.0708		281.4481	281.4481	0.0168	 	281.8690
Total	37.8997	1.3030	1.8111	2.9700e- 003		0.0708	0.0708		0.0708	0.0708		281.4481	281.4481	0.0168		281.8690

Unmitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d			lb/d	day							
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Worker	0.0829	0.0546	0.6828	1.9900e- 003	0.2459	1.2100e- 003	0.2471	0.0652	1.1200e- 003	0.0663		203.6333	203.6333	5.3800e- 003	5.4600e- 003	205.3933
Total	0.0829	0.0546	0.6828	1.9900e- 003	0.2459	1.2100e- 003	0.2471	0.0652	1.1200e- 003	0.0663		203.6333	203.6333	5.3800e- 003	5.4600e- 003	205.3933

CalEEMod Version: CalEEMod.2020.4.0 Page 19 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.6 Architectural Coating - 2023 Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	day		
Archit. Coating	37.7080					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Off-Road	0.1917	1.3030	1.8111	2.9700e- 003		0.0708	0.0708		0.0708	0.0708	0.0000	281.4481	281.4481	0.0168		281.8690
Total	37.8997	1.3030	1.8111	2.9700e- 003		0.0708	0.0708		0.0708	0.0708	0.0000	281.4481	281.4481	0.0168		281.8690

Mitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	day		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Worker	0.0829	0.0546	0.6828	1.9900e- 003	0.2459	1.2100e- 003	0.2471	0.0652	1.1200e- 003	0.0663		203.6333	203.6333	5.3800e- 003	5.4600e- 003	205.3933
Total	0.0829	0.0546	0.6828	1.9900e- 003	0.2459	1.2100e- 003	0.2471	0.0652	1.1200e- 003	0.0663		203.6333	203.6333	5.3800e- 003	5.4600e- 003	205.3933

CalEEMod Version: CalEEMod.2020.4.0 Page 20 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

4.0 Operational Detail - Mobile

4.1 Mitigation Measures Mobile

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
Mitigated	1.2912	2.0073	12.7381	0.0285	2.9922	0.0235	3.0157	0.7981	0.0220	0.8200		2,933.378 9	2,933.378 9	0.1724	0.1496	2,982.255 7
Unmitigated	1.2912	2.0073	12.7381	0.0285	2.9922	0.0235	3.0157	0.7981	0.0220	0.8200		2,933.378 9	2,933.378 9	0.1724	0.1496	2,982.255 7

4.2 Trip Summary Information

	Avei	age Daily Trip Ra	ate	Unmitigated	Mitigated
Land Use	Weekday	Saturday	Sunday	Annual VMT	Annual VMT
General Office Building	439.86	439.86	439.86	1,417,003	1,417,003
Other Asphalt Surfaces	0.00	0.00	0.00		
Other Non-Asphalt Surfaces	0.00	0.00	0.00		
Parking Lot	0.00	0.00	0.00		
Total	439.86	439.86	439.86	1,417,003	1,417,003

4.3 Trip Type Information

		Miles			Trip %			Trip Purpos	e %
Land Use	H-W or C-W	H-S or C-C	H-O or C-NW	H-W or C-W	H-S or C-C	H-O or C-NW	Primary	Diverted	Pass-by
General Office Building	16.60	8.40	6.90	33.00	48.00	19.00	77	19	4
Other Asphalt Surfaces	16.60	8.40	6.90	0.00	0.00	0.00	0	0	0
Other Non-Asphalt Surfaces	16.60	8.40	6.90	0.00	0.00	0.00	0	0	0

Valley Communications Center - San Bernardino-South Coast County, Winter

Date: 7/5/2022 12:12 PM

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

		Miles			Trip %			Trip Purpos	e %
Land Use	H-W or C-W	H-S or C-C	H-O or C-NW	H-W or C-W	H-S or C-C	H-O or C-NW	Primary	Diverted	Pass-by
Parking Lot	16.60	8.40	6.90	0.00	0.00	0.00	0	0	0

4.4 Fleet Mix

Land Use	LDA	LDT1	LDT2	MDV	LHD1	LHD2	MHD	HHD	OBUS	UBUS	MCY	SBUS	MH
General Office Building	0.537785	0.055838	0.172353	0.139003	0.027005	0.007196	0.011392	0.017285	0.000559	0.000254	0.025303	0.000954	0.005071
Other Asphalt Surfaces	0.537785	0.055838	0.172353	0.139003	0.027005	0.007196	0.011392	0.017285	0.000559	0.000254	0.025303	0.000954	0.005071
Other Non-Asphalt Surfaces	0.537785	0.055838	0.172353	0.139003	0.027005	0.007196	0.011392	0.017285	0.000559	0.000254	0.025303	0.000954	0.005071
Parking Lot	0.537785	0.055838	0.172353	0.139003	0.027005	0.007196	0.011392	0.017285	0.000559	0.000254	0.025303	0.000954	0.005071

5.0 Energy Detail

Historical Energy Use: N

5.1 Mitigation Measures Energy

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	lay		
Natural Cao	7.6100e- 003	0.0692	0.0581	4.1000e- 004		5.2600e- 003	5.2600e- 003		5.2600e- 003	5.2600e- 003		82.9856	82.9856	1.5900e- 003	1.5200e- 003	83.4787
Unmitigated	7.6100e- 003	0.0692	0.0581	4.1000e- 004		5.2600e- 003	5.2600e- 003		5.2600e- 003	5.2600e- 003		82.9856	82.9856	1.5900e- 003	1.5200e- 003	83.4787

Valley Communications Center - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

5.2 Energy by Land Use - NaturalGas

Unmitigated

	NaturalGa s Use	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU/yr					lb/d	day							lb/d	lay		
General Office Building	705.377	7.6100e- 003	0.0692	0.0581	4.1000e- 004		5.2600e- 003	5.2600e- 003		5.2600e- 003	5.2600e- 003		82.9856	82.9856	1.5900e- 003	1.5200e- 003	83.4787
Other Asphalt Surfaces	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Other Non- Asphalt Surfaces	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Parking Lot	0	0.0000	0.0000	0.0000	0.0000	 	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Total		7.6100e- 003	0.0692	0.0581	4.1000e- 004		5.2600e- 003	5.2600e- 003		5.2600e- 003	5.2600e- 003		82.9856	82.9856	1.5900e- 003	1.5200e- 003	83.4787

CalEEMod Version: CalEEMod.2020.4.0 Page 23 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

5.2 Energy by Land Use - NaturalGas

Mitigated

	NaturalGa s Use	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU/yr					lb/d	day							lb/d	day		
General Office Building	0.705377	7.6100e- 003	0.0692	0.0581	4.1000e- 004		5.2600e- 003	5.2600e- 003		5.2600e- 003	5.2600e- 003		82.9856	82.9856	1.5900e- 003	1.5200e- 003	83.4787
Other Asphalt Surfaces	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Other Non- Asphalt Surfaces	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Parking Lot	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Total		7.6100e- 003	0.0692	0.0581	4.1000e- 004		5.2600e- 003	5.2600e- 003		5.2600e- 003	5.2600e- 003		82.9856	82.9856	1.5900e- 003	1.5200e- 003	83.4787

6.0 Area Detail

6.1 Mitigation Measures Area

CalEEMod Version: CalEEMod.2020.4.0 Page 24 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/d	day		
Mitigated	1.7703	3.0000e- 004	0.0334	0.0000		1.2000e- 004	1.2000e- 004		1.2000e- 004	1.2000e- 004		0.0717	0.0717	1.9000e- 004		0.0764
Unmitigated	1.7703	3.0000e- 004	0.0334	0.0000		1.2000e- 004	1.2000e- 004		1.2000e- 004	1.2000e- 004		0.0717	0.0717	1.9000e- 004		0.0764

6.2 Area by SubCategory

Unmitigated

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
SubCategory					lb/d	day							lb/d	day		
Architectural Coating	0.2066					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Products	1.5605				 	0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
· · · •	3.1000e- 003	3.0000e- 004	0.0334	0.0000	 	1.2000e- 004	1.2000e- 004	 	1.2000e- 004	1.2000e- 004		0.0717	0.0717	1.9000e- 004		0.0764
Total	1.7703	3.0000e- 004	0.0334	0.0000		1.2000e- 004	1.2000e- 004		1.2000e- 004	1.2000e- 004		0.0717	0.0717	1.9000e- 004		0.0764

CalEEMod Version: CalEEMod.2020.4.0 Page 25 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

6.2 Area by SubCategory

Mitigated

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
SubCategory					lb/d	day							lb/d	day		
Architectural Coating	0.2066					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Consumer Products	1.5605					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Landscaping	3.1000e- 003	3.0000e- 004	0.0334	0.0000		1.2000e- 004	1.2000e- 004		1.2000e- 004	1.2000e- 004		0.0717	0.0717	1.9000e- 004		0.0764
Total	1.7703	3.0000e- 004	0.0334	0.0000		1.2000e- 004	1.2000e- 004		1.2000e- 004	1.2000e- 004		0.0717	0.0717	1.9000e- 004		0.0764

7.0 Water Detail

7.1 Mitigation Measures Water

CalEEMod Version: CalEEMod.2020.4.0 Page 26 of 26 Date: 7/5/2022 12:12 PM

Valley Communications Center - San Bernardino-South Coast County, Winter

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

8.0 Waste Detail

8.1 Mitigation Measures Waste

Institute Recycling and Composting Services

9.0 Operational Offroad

Equipment Type	Number	Hours/Day	Days/Year	Horse Power	Load Factor	Fuel Type

10.0 Stationary Equipment

Fire Pumps and Emergency Generators

Equipment Type	Number	Hours/Day	Hours/Year	Horse Power	Load Factor	Fuel Type

Boilers

Equipment Type	Number	Heat Input/Day	Heat Input/Year	Boiler Rating	Fuel Type

User Defined Equipment

Equipment Type	Number
----------------	--------

11.0 Vegetation

Appendix B:

CalEEMod Annual Emission Output

CalEEMod Version: CalEEMod.2020.4.0 Page 1 of 32 Date: 7/5/2022 12:03 PM

Valley Communications Center - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Valley Communications Center

San Bernardino-South Coast County, Annual

1.0 Project Characteristics

1.1 Land Usage

Land Uses	Size	Metric	Lot Acreage	Floor Surface Area	Population
Other Non-Asphalt Surfaces	0.70	Acre	0.70	30,492.00	0
Parking Lot	250.00	Space	2.25	100,000.00	0
General Office Building	75.06	1000sqft	1.72	75,062.00	0
Other Asphalt Surfaces	1.82	Acre	1.82	79,279.20	0

1.2 Other Project Characteristics

Urbanization	Urban	Wind Speed (m/s)	2.2	Precipitation Freq (Days)	32
Climate Zone	10			Operational Year	2023

Utility Company Southern California Edison

 CO2 Intensity
 390.98
 CH4 Intensity
 0.033
 N2O Intensity
 0.004

 (lb/MWhr)
 (lb/MWhr)
 (lb/MWhr)
 (lb/MWhr)

1.3 User Entered Comments & Non-Default Data

Project Characteristics -

Land Use - 6.49 acre lot with 75,062 sqft of office building

Construction Phase -

Grading - 14,000 CY of cut, 2,100 of fill. Site is 6.49 acres.

Construction Off-road Equipment Mitigation -

Waste Mitigation - AB-341

Vehicle Trips - Per trip generation memo, 440 trips per day

Off-road Equipment - Site Preparation required for approx. 1/10 of site.

Valley Communications Center - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Table Name	Column Name	Default Value	New Value
tblGrading	MaterialExported	0.00	11,900.00
tblOffRoadEquipment	OffRoadEquipmentUnitAmount	3.00	1.00
tblOffRoadEquipment	OffRoadEquipmentUnitAmount	4.00	1.00
tblVehicleTrips	ST_TR	2.21	5.86
tblVehicleTrips	SU_TR	0.70	5.86
tblVehicleTrips	WD_TR	9.74	5.86

2.0 Emissions Summary

CalEEMod Version: CalEEMod.2020.4.0 Page 3 of 32 Date: 7/5/2022 12:03 PM

Valley Communications Center - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

2.1 Overall Construction

Unmitigated Construction

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Year					ton	s/yr							MT	/yr		
2022	0.0909	0.8848	0.8162	2.1300e- 003	0.1624	0.0370	0.1994	0.0670	0.0346	0.1015	0.0000	194.3926	194.3926	0.0293	0.0113	198.4929
2023	0.5703	1.5354	1.9571	4.2400e- 003	0.1359	0.0680	0.2039	0.0367	0.0639	0.1006	0.0000	380.0785	380.0785	0.0584	0.0128	385.3562
Maximum	0.5703	1.5354	1.9571	4.2400e- 003	0.1624	0.0680	0.2039	0.0670	0.0639	0.1015	0.0000	380.0785	380.0785	0.0584	0.0128	385.3562

Mitigated Construction

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e	
Year	ar tons/yr										MT/yr						
2022	0.0909	0.8848	0.8162	2.1300e- 003	0.0988	0.0370	0.1358	0.0357	0.0346	0.0703	0.0000	194.3925	194.3925	0.0293	0.0113	198.4928	
2023	0.5703	1.5354	1.9571	4.2400e- 003	0.1359	0.0680	0.2039	0.0367	0.0639	0.1006	0.0000	380.0783	380.0783	0.0584	0.0128	385.3559	
Maximum	0.5703	1.5354	1.9571	4.2400e- 003	0.1359	0.0680	0.2039	0.0367	0.0639	0.1006	0.0000	380.0783	380.0783	0.0584	0.0128	385.3559	

Valley Communications Center - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio-CO2	Total CO2	CH4	N20	CO2e
Percent Reduction	0.00	0.00	0.00	0.00	21.32	0.00	15.77	30.12	0.00	15.45	0.00	0.00	0.00	0.00	0.00	0.00

Quarter	Start Date	End Date	Maximum Unmitigated ROG + NOX (tons/quarter)	Maximum Mitigated ROG + NOX (tons/quarter)
1	9-1-2022	11-30-2022	0.7488	0.7488
2	12-1-2022	2-28-2023	0.6139	0.6139
3	3-1-2023	5-31-2023	0.6043	0.6043
4	6-1-2023	8-31-2023	0.6010	0.6010
5	9-1-2023	9-30-2023	0.1564	0.1564
		Highest	0.7488	0.7488

2.2 Overall Operational

Unmitigated Operational

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e	
Category					ton	s/yr					MT/yr						
Area	0.3229	4.0000e- 005	4.1800e- 003	0.0000		1.0000e- 005	1.0000e- 005		1.0000e- 005	1.0000e- 005	0.0000	8.1300e- 003	8.1300e- 003	2.0000e- 005	0.0000	8.6600e- 003	
Energy	1.3900e- 003	0.0126	0.0106	8.0000e- 005		9.6000e- 004	9.6000e- 004		9.6000e- 004	9.6000e- 004	0.0000	142.2828	142.2828	0.0111	1.5700e- 003	143.0275	
Mobile	0.2331	0.3729	2.4153	5.2500e- 003	0.5343	4.2600e- 003	0.5386	0.1427	3.9900e- 003	0.1467	0.0000	490.9606	490.9606	0.0288	0.0250	499.1407	
Waste	r,					0.0000	0.0000		0.0000	0.0000	14.1708	0.0000	14.1708	0.8375	0.0000	35.1076	
Water	#,	,]			0.0000	0.0000	,	0.0000	0.0000	4.2324	46.9169	51.1493	0.4387	0.0107	65.3178	
Total	0.5573	0.3855	2.4301	5.3300e- 003	0.5343	5.2300e- 003	0.5396	0.1427	4.9600e- 003	0.1477	18.4032	680.1683	698.5715	1.3160	0.0374	742.6023	

CalEEMod Version: CalEEMod.2020.4.0 Page 5 of 32 Date: 7/5/2022 12:03 PM

Valley Communications Center - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

2.2 Overall Operational

Mitigated Operational

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	MT/yr										
Area	0.3229	4.0000e- 005	4.1800e- 003	0.0000		1.0000e- 005	1.0000e- 005		1.0000e- 005	1.0000e- 005	0.0000	8.1300e- 003	8.1300e- 003	2.0000e- 005	0.0000	8.6600e- 003
Energy	1.3900e- 003	0.0126	0.0106	8.0000e- 005		9.6000e- 004	9.6000e- 004		9.6000e- 004	9.6000e- 004	0.0000	142.2828	142.2828	0.0111	1.5700e- 003	143.0275
Mobile	0.2331	0.3729	2.4153	5.2500e- 003	0.5343	4.2600e- 003	0.5386	0.1427	3.9900e- 003	0.1467	0.0000	490.9606	490.9606	0.0288	0.0250	499.1407
Waste	,,					0.0000	0.0000		0.0000	0.0000	3.5427	0.0000	3.5427	0.2094	0.0000	8.7769
Water	,,]			0.0000	0.0000	 	0.0000	0.0000	4.2324	46.9169	51.1493	0.4387	0.0107	65.3178
Total	0.5573	0.3855	2.4301	5.3300e- 003	0.5343	5.2300e- 003	0.5396	0.1427	4.9600e- 003	0.1477	7.7751	680.1683	687.9434	0.6879	0.0374	716.2716

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio-CO2	Total CO2	CH4	N20	CO2e
Percent Reduction	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	57.75	0.00	1.52	47.73	0.00	3.55

3.0 Construction Detail

Construction Phase

Phase Number	Phase Name	Phase Type	Start Date	End Date	Num Days Week	Num Days	Phase Description
1	Site Preparation	Site Preparation	9/1/2022	9/14/2022	5	10	
2	Grading	Grading	9/15/2022	10/12/2022	5	20	
3	Building Construction	Building Construction	10/13/2022	8/30/2023	5	230	

Valley Communications Center - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

4	Paving	Paving	8/31/2023	9/27/2023	5	20	
5	Architectural Coating	-	T	10/25/2023	5	20	

Acres of Grading (Site Preparation Phase): 5

Acres of Grading (Grading Phase): 20

Acres of Paving: 4.77

Residential Indoor: 0; Residential Outdoor: 0; Non-Residential Indoor: 112,593; Non-Residential Outdoor: 37,531; Striped Parking Area: 12,586 (Architectural Coating – sqft)

OffRoad Equipment

Phase Name	Offroad Equipment Type	Amount	Usage Hours	Horse Power	Load Factor
Grading	Excavators	1	8.00	158	0.38
Site Preparation	Rubber Tired Dozers	1	8.00	247	0.40
Site Preparation	Tractors/Loaders/Backhoes	1	8.00	97	0.37
Grading	Graders	1	8.00	187	0.41
Grading	Rubber Tired Dozers	1	8.00	247	0.40
Grading	Tractors/Loaders/Backhoes	3	8.00	97	0.37
Building Construction	Cranes	1	7.00	231	0.29
Building Construction	Forklifts	3	8.00	89	0.20
Building Construction	Generator Sets	1	8.00	84	0.74
Building Construction	Tractors/Loaders/Backhoes	3	7.00	97	0.37
Building Construction	Welders	1	8.00	46	0.45
Paving	Pavers	2	8.00	130	0.42
Paving	Paving Equipment	2	8.00	132	0.36
Paving	Rollers	2	8.00	80	0.38
Architectural Coating	Air Compressors	1	6.00	78	0.48

Trips and VMT

Valley Communications Center - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Phase Name	Offroad Equipment Count	Worker Trip Number	Vendor Trip Number	Hauling Trip Number	Worker Trip Length	Vendor Trip Length	Hauling Trip Length	Worker Vehicle Class	Vendor Vehicle Class	Hauling Vehicle Class
Site Preparation	2	5.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Grading	6	15.00	0.00	1,488.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Building Construction	9	112.00	47.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Paving	6	15.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Architectural Coating	1	22.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT

3.1 Mitigation Measures Construction

Water Exposed Area

3.2 Site Preparation - 2022

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Fugitive Dust	ii ii ii				0.0328	0.0000	0.0328	0.0168	0.0000	0.0168	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	5.0100e- 003	0.0524	0.0291	6.0000e- 005		2.5400e- 003	2.5400e- 003		2.3300e- 003	2.3300e- 003	0.0000	5.1178	5.1178	1.6600e- 003	0.0000	5.1592
Total	5.0100e- 003	0.0524	0.0291	6.0000e- 005	0.0328	2.5400e- 003	0.0353	0.0168	2.3300e- 003	0.0192	0.0000	5.1178	5.1178	1.6600e- 003	0.0000	5.1592

CalEEMod Version: CalEEMod.2020.4.0 Page 8 of 32 Date: 7/5/2022 12:03 PM

Valley Communications Center - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.2 Site Preparation - 2022

Unmitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Worker	9.0000e- 005	7.0000e- 005	8.9000e- 004	0.0000	2.7000e- 004	0.0000	2.8000e- 004	7.0000e- 005	0.0000	7.0000e- 005	0.0000	0.2199	0.2199	1.0000e- 005	1.0000e- 005	0.2219
Total	9.0000e- 005	7.0000e- 005	8.9000e- 004	0.0000	2.7000e- 004	0.0000	2.8000e- 004	7.0000e- 005	0.0000	7.0000e- 005	0.0000	0.2199	0.2199	1.0000e- 005	1.0000e- 005	0.2219

Mitigated Construction On-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Fugitive Dust	ii ii				0.0128	0.0000	0.0128	6.5700e- 003	0.0000	6.5700e- 003	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
- [5.0100e- 003	0.0524	0.0291	6.0000e- 005		2.5400e- 003	2.5400e- 003		2.3300e- 003	2.3300e- 003	0.0000	5.1178	5.1178	1.6600e- 003	0.0000	5.1591
Total	5.0100e- 003	0.0524	0.0291	6.0000e- 005	0.0128	2.5400e- 003	0.0153	6.5700e- 003	2.3300e- 003	8.9000e- 003	0.0000	5.1178	5.1178	1.6600e- 003	0.0000	5.1591

CalEEMod Version: CalEEMod.2020.4.0 Page 9 of 32 Date: 7/5/2022 12:03 PM

Valley Communications Center - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.2 Site Preparation - 2022

Mitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Worker	9.0000e- 005	7.0000e- 005	8.9000e- 004	0.0000	2.7000e- 004	0.0000	2.8000e- 004	7.0000e- 005	0.0000	7.0000e- 005	0.0000	0.2199	0.2199	1.0000e- 005	1.0000e- 005	0.2219
Total	9.0000e- 005	7.0000e- 005	8.9000e- 004	0.0000	2.7000e- 004	0.0000	2.8000e- 004	7.0000e- 005	0.0000	7.0000e- 005	0.0000	0.2199	0.2199	1.0000e- 005	1.0000e- 005	0.2219

3.3 Grading - 2022

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Fugitive Dust					0.0715	0.0000	0.0715	0.0344	0.0000	0.0344	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Off-Road	0.0195	0.2086	0.1527	3.0000e- 004		9.4100e- 003	9.4100e- 003		8.6600e- 003	8.6600e- 003	0.0000	26.0548	26.0548	8.4300e- 003	0.0000	26.2654
Total	0.0195	0.2086	0.1527	3.0000e- 004	0.0715	9.4100e- 003	0.0809	0.0344	8.6600e- 003	0.0430	0.0000	26.0548	26.0548	8.4300e- 003	0.0000	26.2654

CalEEMod Version: CalEEMod.2020.4.0 Page 10 of 32 Date: 7/5/2022 12:03 PM

Valley Communications Center - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.3 Grading - 2022

Unmitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	2.7600e- 003	0.1072	0.0267	4.4000e- 004	0.0128	1.0700e- 003	0.0139	3.5200e- 003	1.0200e- 003	4.5400e- 003	0.0000	43.2414	43.2414	1.8500e- 003	6.8500e- 003	45.3297
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Worker	5.7000e- 004	4.4000e- 004	5.3200e- 003	1.0000e- 005	1.6400e- 003	1.0000e- 005	1.6500e- 003	4.4000e- 004	1.0000e- 005	4.4000e- 004	0.0000	1.3193	1.3193	4.0000e- 005	4.0000e- 005	1.3315
Total	3.3300e- 003	0.1076	0.0320	4.5000e- 004	0.0145	1.0800e- 003	0.0155	3.9600e- 003	1.0300e- 003	4.9800e- 003	0.0000	44.5607	44.5607	1.8900e- 003	6.8900e- 003	46.6612

Mitigated Construction On-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Fugitive Dust					0.0279	0.0000	0.0279	0.0134	0.0000	0.0134	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Off-Road	0.0195	0.2086	0.1527	3.0000e- 004		9.4100e- 003	9.4100e- 003		8.6600e- 003	8.6600e- 003	0.0000	26.0547	26.0547	8.4300e- 003	0.0000	26.2654
Total	0.0195	0.2086	0.1527	3.0000e- 004	0.0279	9.4100e- 003	0.0373	0.0134	8.6600e- 003	0.0221	0.0000	26.0547	26.0547	8.4300e- 003	0.0000	26.2654

CalEEMod Version: CalEEMod.2020.4.0 Page 11 of 32 Date: 7/5/2022 12:03 PM

Valley Communications Center - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.3 Grading - 2022

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
I riadining	2.7600e- 003	0.1072	0.0267	4.4000e- 004	0.0128	1.0700e- 003	0.0139	3.5200e- 003	1.0200e- 003	4.5400e- 003	0.0000	43.2414	43.2414	1.8500e- 003	6.8500e- 003	45.3297
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
' '	5.7000e- 004	4.4000e- 004	5.3200e- 003	1.0000e- 005	1.6400e- 003	1.0000e- 005	1.6500e- 003	4.4000e- 004	1.0000e- 005	4.4000e- 004	0.0000	1.3193	1.3193	4.0000e- 005	4.0000e- 005	1.3315
Total	3.3300e- 003	0.1076	0.0320	4.5000e- 004	0.0145	1.0800e- 003	0.0155	3.9600e- 003	1.0300e- 003	4.9800e- 003	0.0000	44.5607	44.5607	1.8900e- 003	6.8900e- 003	46.6612

3.4 Building Construction - 2022

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
	0.0486	0.4451	0.4664	7.7000e- 004		0.0231	0.0231		0.0217	0.0217	0.0000	66.0417	66.0417	0.0158	0.0000	66.4372
Total	0.0486	0.4451	0.4664	7.7000e- 004		0.0231	0.0231		0.0217	0.0217	0.0000	66.0417	66.0417	0.0158	0.0000	66.4372

CalEEMod Version: CalEEMod.2020.4.0 Page 12 of 32 Date: 7/5/2022 12:03 PM

Valley Communications Center - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.4 Building Construction - 2022 <u>Unmitigated Construction Off-Site</u>

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	2.2800e- 003	0.0617	0.0219	2.5000e- 004	8.4500e- 003	7.0000e- 004	9.1500e- 003	2.4400e- 003	6.7000e- 004	3.1100e- 003	0.0000	24.3232	24.3232	6.6000e- 004	3.6000e- 003	25.4130
Worker	0.0120	9.4400e- 003	0.1133	3.0000e- 004	0.0350	1.9000e- 004	0.0352	9.3000e- 003	1.7000e- 004	9.4700e- 003	0.0000	28.0746	28.0746	8.0000e- 004	8.1000e- 004	28.3350
Total	0.0143	0.0711	0.1352	5.5000e- 004	0.0435	8.9000e- 004	0.0443	0.0117	8.4000e- 004	0.0126	0.0000	52.3977	52.3977	1.4600e- 003	4.4100e- 003	53.7480

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Off-Road	0.0486	0.4451	0.4664	7.7000e- 004		0.0231	0.0231		0.0217	0.0217	0.0000	66.0416	66.0416	0.0158	0.0000	66.4372
Total	0.0486	0.4451	0.4664	7.7000e- 004		0.0231	0.0231		0.0217	0.0217	0.0000	66.0416	66.0416	0.0158	0.0000	66.4372

CalEEMod Version: CalEEMod.2020.4.0 Page 13 of 32 Date: 7/5/2022 12:03 PM

Valley Communications Center - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.4 Building Construction - 2022

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr				MT	/yr					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	2.2800e- 003	0.0617	0.0219	2.5000e- 004	8.4500e- 003	7.0000e- 004	9.1500e- 003	2.4400e- 003	6.7000e- 004	3.1100e- 003	0.0000	24.3232	24.3232	6.6000e- 004	3.6000e- 003	25.4130
Worker	0.0120	9.4400e- 003	0.1133	3.0000e- 004	0.0350	1.9000e- 004	0.0352	9.3000e- 003	1.7000e- 004	9.4700e- 003	0.0000	28.0746	28.0746	8.0000e- 004	8.1000e- 004	28.3350
Total	0.0143	0.0711	0.1352	5.5000e- 004	0.0435	8.9000e- 004	0.0443	0.0117	8.4000e- 004	0.0126	0.0000	52.3977	52.3977	1.4600e- 003	4.4100e- 003	53.7480

3.4 Building Construction - 2023

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
	0.1360	1.2443	1.4051	2.3300e- 003		0.0605	0.0605	 	0.0570	0.0570	0.0000	200.5111	200.5111	0.0477	0.0000	201.7036
Total	0.1360	1.2443	1.4051	2.3300e- 003		0.0605	0.0605		0.0570	0.0570	0.0000	200.5111	200.5111	0.0477	0.0000	201.7036

CalEEMod Version: CalEEMod.2020.4.0 Page 14 of 32 Date: 7/5/2022 12:03 PM

Valley Communications Center - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.4 Building Construction - 2023 <u>Unmitigated Construction Off-Site</u>

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	4.5800e- 003	0.1500	0.0607	7.3000e- 004	0.0256	1.0700e- 003	0.0267	7.4000e- 003	1.0300e- 003	8.4300e- 003	0.0000	70.8548	70.8548	1.8400e- 003	0.0105	74.0212
Worker	0.0338	0.0252	0.3152	8.9000e- 004	0.1062	5.4000e- 004	0.1068	0.0282	4.9000e- 004	0.0287	0.0000	82.9640	82.9640	2.1800e- 003	2.2500e- 003	83.6893
Total	0.0383	0.1752	0.3760	1.6200e- 003	0.1319	1.6100e- 003	0.1335	0.0356	1.5200e- 003	0.0371	0.0000	153.8188	153.8188	4.0200e- 003	0.0127	157.7105

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Off-Road	0.1360	1.2443	1.4051	2.3300e- 003		0.0605	0.0605		0.0570	0.0570	0.0000	200.5109	200.5109	0.0477	0.0000	201.7033
Total	0.1360	1.2443	1.4051	2.3300e- 003		0.0605	0.0605		0.0570	0.0570	0.0000	200.5109	200.5109	0.0477	0.0000	201.7033

CalEEMod Version: CalEEMod.2020.4.0 Page 15 of 32 Date: 7/5/2022 12:03 PM

Valley Communications Center - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.4 Building Construction - 2023

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							МТ	/уг		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	4.5800e- 003	0.1500	0.0607	7.3000e- 004	0.0256	1.0700e- 003	0.0267	7.4000e- 003	1.0300e- 003	8.4300e- 003	0.0000	70.8548	70.8548	1.8400e- 003	0.0105	74.0212
Worker	0.0338	0.0252	0.3152	8.9000e- 004	0.1062	5.4000e- 004	0.1068	0.0282	4.9000e- 004	0.0287	0.0000	82.9640	82.9640	2.1800e- 003	2.2500e- 003	83.6893
Total	0.0383	0.1752	0.3760	1.6200e- 003	0.1319	1.6100e- 003	0.1335	0.0356	1.5200e- 003	0.0371	0.0000	153.8188	153.8188	4.0200e- 003	0.0127	157.7105

3.5 Paving - 2023

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Off-Road	0.0103	0.1019	0.1458	2.3000e- 004		5.1000e- 003	5.1000e- 003		4.6900e- 003	4.6900e- 003	0.0000	20.0269	20.0269	6.4800e- 003	0.0000	20.1888
Paving	5.3300e- 003					0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Total	0.0157	0.1019	0.1458	2.3000e- 004		5.1000e- 003	5.1000e- 003		4.6900e- 003	4.6900e- 003	0.0000	20.0269	20.0269	6.4800e- 003	0.0000	20.1888

CalEEMod Version: CalEEMod.2020.4.0 Page 16 of 32 Date: 7/5/2022 12:03 PM

Valley Communications Center - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.5 Paving - 2023
<u>Unmitigated Construction Off-Site</u>

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Worker	5.2000e- 004	3.9000e- 004	4.8800e- 003	1.0000e- 005	1.6400e- 003	1.0000e- 005	1.6500e- 003	4.4000e- 004	1.0000e- 005	4.4000e- 004	0.0000	1.2845	1.2845	3.0000e- 005	3.0000e- 005	1.2958
Total	5.2000e- 004	3.9000e- 004	4.8800e- 003	1.0000e- 005	1.6400e- 003	1.0000e- 005	1.6500e- 003	4.4000e- 004	1.0000e- 005	4.4000e- 004	0.0000	1.2845	1.2845	3.0000e- 005	3.0000e- 005	1.2958

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Off-Road	0.0103	0.1019	0.1458	2.3000e- 004		5.1000e- 003	5.1000e- 003		4.6900e- 003	4.6900e- 003	0.0000	20.0268	20.0268	6.4800e- 003	0.0000	20.1888
Paving	5.3300e- 003					0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Total	0.0157	0.1019	0.1458	2.3000e- 004		5.1000e- 003	5.1000e- 003		4.6900e- 003	4.6900e- 003	0.0000	20.0268	20.0268	6.4800e- 003	0.0000	20.1888

CalEEMod Version: CalEEMod.2020.4.0 Page 17 of 32 Date: 7/5/2022 12:03 PM

Valley Communications Center - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.5 Paving - 2023

<u>Mitigated Construction Off-Site</u>

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Worker	5.2000e- 004	3.9000e- 004	4.8800e- 003	1.0000e- 005	1.6400e- 003	1.0000e- 005	1.6500e- 003	4.4000e- 004	1.0000e- 005	4.4000e- 004	0.0000	1.2845	1.2845	3.0000e- 005	3.0000e- 005	1.2958
Total	5.2000e- 004	3.9000e- 004	4.8800e- 003	1.0000e- 005	1.6400e- 003	1.0000e- 005	1.6500e- 003	4.4000e- 004	1.0000e- 005	4.4000e- 004	0.0000	1.2845	1.2845	3.0000e- 005	3.0000e- 005	1.2958

3.6 Architectural Coating - 2023 <u>Unmitigated Construction On-Site</u>

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Archit. Coating	0.3771					0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Off-Road	1.9200e- 003	0.0130	0.0181	3.0000e- 005		7.1000e- 004	7.1000e- 004	 	7.1000e- 004	7.1000e- 004	0.0000	2.5533	2.5533	1.5000e- 004	0.0000	2.5571
Total	0.3790	0.0130	0.0181	3.0000e- 005		7.1000e- 004	7.1000e- 004		7.1000e- 004	7.1000e- 004	0.0000	2.5533	2.5533	1.5000e- 004	0.0000	2.5571

CalEEMod Version: CalEEMod.2020.4.0 Page 18 of 32 Date: 7/5/2022 12:03 PM

Valley Communications Center - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.6 Architectural Coating - 2023 <u>Unmitigated Construction Off-Site</u>

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							МТ	/yr		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Worker	7.7000e- 004	5.7000e- 004	7.1600e- 003	2.0000e- 005	2.4100e- 003	1.0000e- 005	2.4200e- 003	6.4000e- 004	1.0000e- 005	6.5000e- 004	0.0000	1.8840	1.8840	5.0000e- 005	5.0000e- 005	1.9005
Total	7.7000e- 004	5.7000e- 004	7.1600e- 003	2.0000e- 005	2.4100e- 003	1.0000e- 005	2.4200e- 003	6.4000e- 004	1.0000e- 005	6.5000e- 004	0.0000	1.8840	1.8840	5.0000e- 005	5.0000e- 005	1.9005

Mitigated Construction On-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							МТ	/yr		
Archit. Coating	0.3771					0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Off-Road	1.9200e- 003	0.0130	0.0181	3.0000e- 005		7.1000e- 004	7.1000e- 004		7.1000e- 004	7.1000e- 004	0.0000	2.5533	2.5533	1.5000e- 004	0.0000	2.5571
Total	0.3790	0.0130	0.0181	3.0000e- 005		7.1000e- 004	7.1000e- 004		7.1000e- 004	7.1000e- 004	0.0000	2.5533	2.5533	1.5000e- 004	0.0000	2.5571

CalEEMod Version: CalEEMod.2020.4.0 Page 19 of 32 Date: 7/5/2022 12:03 PM

Valley Communications Center - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

3.6 Architectural Coating - 2023

Mitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Worker	7.7000e- 004	5.7000e- 004	7.1600e- 003	2.0000e- 005	2.4100e- 003	1.0000e- 005	2.4200e- 003	6.4000e- 004	1.0000e- 005	6.5000e- 004	0.0000	1.8840	1.8840	5.0000e- 005	5.0000e- 005	1.9005
Total	7.7000e- 004	5.7000e- 004	7.1600e- 003	2.0000e- 005	2.4100e- 003	1.0000e- 005	2.4200e- 003	6.4000e- 004	1.0000e- 005	6.5000e- 004	0.0000	1.8840	1.8840	5.0000e- 005	5.0000e- 005	1.9005

4.0 Operational Detail - Mobile

4.1 Mitigation Measures Mobile

CalEEMod Version: CalEEMod.2020.4.0 Page 20 of 32 Date: 7/5/2022 12:03 PM

Valley Communications Center - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Mitigated	0.2331	0.3729	2.4153	5.2500e- 003	0.5343	4.2600e- 003	0.5386	0.1427	3.9900e- 003	0.1467	0.0000	490.9606	490.9606	0.0288	0.0250	499.1407
Unmitigated	0.2331	0.3729	2.4153	5.2500e- 003	0.5343	4.2600e- 003	0.5386	0.1427	3.9900e- 003	0.1467	0.0000	490.9606	490.9606	0.0288	0.0250	499.1407

4.2 Trip Summary Information

	Avei	age Daily Trip Ra	ite	Unmitigated	Mitigated
Land Use	Weekday	Saturday	Sunday	Annual VMT	Annual VMT
General Office Building	439.86	439.86	439.86	1,417,003	1,417,003
Other Asphalt Surfaces	0.00	0.00	0.00		
Other Non-Asphalt Surfaces	0.00	0.00	0.00		
Parking Lot	0.00	0.00	0.00		
Total	439.86	439.86	439.86	1,417,003	1,417,003

4.3 Trip Type Information

		Miles			Trip %			Trip Purpos	e %
Land Use	H-W or C-W	H-S or C-C	H-O or C-NW	H-W or C-W	H-S or C-C	H-O or C-NW	Primary	Diverted	Pass-by
General Office Building	16.60	8.40	6.90	33.00	48.00	19.00	77	19	4
Other Asphalt Surfaces	16.60	8.40	6.90	0.00	0.00	0.00	0	0	0
Other Non-Asphalt Surfaces	16.60	8.40	6.90	0.00	0.00	0.00	0	0	0
Parking Lot	16.60	8.40	6.90	0.00	0.00	0.00	0	0	0

4.4 Fleet Mix

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Land Use	LDA	LDT1	LDT2	MDV	LHD1	LHD2	MHD	HHD	OBUS	UBUS	MCY	SBUS	MH
General Office Building	0.537785	0.055838	0.172353	0.139003	0.027005	0.007196	0.011392	0.017285	0.000559	0.000254	0.025303	0.000954	0.005071
Other Asphalt Surfaces	0.537785	0.055838	0.172353	0.139003	0.027005	0.007196	0.011392	0.017285	0.000559	0.000254	0.025303	0.000954	0.005071
Other Non-Asphalt Surfaces	0.537785	0.055838	0.172353	0.139003	0.027005	0.007196	0.011392	0.017285	0.000559	0.000254	0.025303	0.000954	0.005071
Parking Lot	0.537785	0.055838	0.172353	0.139003	0.027005	0.007196	0.011392	0.017285	0.000559	0.000254	0.025303	0.000954	0.005071

5.0 Energy Detail

Historical Energy Use: N

5.1 Mitigation Measures Energy

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Electricity Mitigated						0.0000	0.0000		0.0000	0.0000	0.0000	128.5436	128.5436	0.0109	1.3200e- 003	129.2067
Electricity Unmitigated						0.0000	0.0000		0.0000	0.0000	0.0000	128.5436	128.5436	0.0109	1.3200e- 003	129.2067
NaturalGas Mitigated	1.3900e- 003	0.0126	0.0106	8.0000e- 005		9.6000e- 004	9.6000e- 004		9.6000e- 004	9.6000e- 004	0.0000	13.7392	13.7392	2.6000e- 004	2.5000e- 004	13.8208
NaturalGas Unmitigated	1.3900e- 003	0.0126	0.0106	8.0000e- 005		9.6000e- 004	9.6000e- 004		9.6000e- 004	9.6000e- 004	0.0000	13.7392	13.7392	2.6000e- 004	2.5000e- 004	13.8208

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

5.2 Energy by Land Use - NaturalGas

Unmitigated

	NaturalGa s Use	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU/yr					ton	ıs/yr							МТ	-/yr		
General Office Building	257463	1.3900e- 003	0.0126	0.0106	8.0000e- 005		9.6000e- 004	9.6000e- 004		9.6000e- 004	9.6000e- 004	0.0000	13.7392	13.7392	2.6000e- 004	2.5000e- 004	13.8208
Other Asphalt Surfaces	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Other Non- Asphalt Surfaces	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Parking Lot	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Total		1.3900e- 003	0.0126	0.0106	8.0000e- 005		9.6000e- 004	9.6000e- 004		9.6000e- 004	9.6000e- 004	0.0000	13.7392	13.7392	2.6000e- 004	2.5000e- 004	13.8208

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

5.2 Energy by Land Use - NaturalGas

Mitigated

	NaturalGa s Use	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU/yr					ton	s/yr							MT	-/yr		
General Office Building	257463	1.3900e- 003	0.0126	0.0106	8.0000e- 005		9.6000e- 004	9.6000e- 004		9.6000e- 004	9.6000e- 004	0.0000	13.7392	13.7392	2.6000e- 004	2.5000e- 004	13.8208
Other Asphalt Surfaces	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Other Non- Asphalt Surfaces	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Parking Lot	0	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Total		1.3900e- 003	0.0126	0.0106	8.0000e- 005		9.6000e- 004	9.6000e- 004		9.6000e- 004	9.6000e- 004	0.0000	13.7392	13.7392	2.6000e- 004	2.5000e- 004	13.8208

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

5.3 Energy by Land Use - Electricity <u>Unmitigated</u>

	Electricity Use	Total CO2	CH4	N2O	CO2e
Land Use	kWh/yr		MT	√yr	
General Office Building	689820	122.3365	0.0103	1.2500e- 003	122.9676
Other Asphalt Surfaces	0	0.0000	0.0000	0.0000	0.0000
Other Non- Asphalt Surfaces	0	0.0000	0.0000	0.0000	0.0000
Parking Lot	35000	6.2071	5.2000e- 004	6.0000e- 005	6.2391
Total		128.5436	0.0109	1.3100e- 003	129.2067

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

5.3 Energy by Land Use - Electricity

<u>Mitigated</u>

	Electricity Use	Total CO2	CH4	N2O	CO2e
Land Use	kWh/yr		MT	/yr	
General Office Building	689820	122.3365	0.0103	1.2500e- 003	122.9676
Other Asphalt Surfaces	0	0.0000	0.0000	0.0000	0.0000
Other Non- Asphalt Surfaces	0	0.0000	0.0000	0.0000	0.0000
Parking Lot	35000	6.2071	5.2000e- 004	6.0000e- 005	6.2391
Total		128.5436	0.0109	1.3100e- 003	129.2067

6.0 Area Detail

6.1 Mitigation Measures Area

CalEEMod Version: CalEEMod.2020.4.0 Page 26 of 32 Date: 7/5/2022 12:03 PM

Valley Communications Center - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Mitigated	0.3229	4.0000e- 005	4.1800e- 003	0.0000		1.0000e- 005	1.0000e- 005		1.0000e- 005	1.0000e- 005	0.0000	8.1300e- 003	8.1300e- 003	2.0000e- 005	0.0000	8.6600e- 003
Unmitigated	0.3229	4.0000e- 005	4.1800e- 003	0.0000		1.0000e- 005	1.0000e- 005		1.0000e- 005	1.0000e- 005	0.0000	8.1300e- 003	8.1300e- 003	2.0000e- 005	0.0000	8.6600e- 003

6.2 Area by SubCategory

Unmitigated

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
SubCategory	tons/yr					MT/yr										
Architectural Coating	0.0377					0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	0.2848				 	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
' "	3.9000e- 004	4.0000e- 005	4.1800e- 003	0.0000	 	1.0000e- 005	1.0000e- 005	1 1 1 1	1.0000e- 005	1.0000e- 005	0.0000	8.1300e- 003	8.1300e- 003	2.0000e- 005	0.0000	8.6600e- 003
Total	0.3229	4.0000e- 005	4.1800e- 003	0.0000		1.0000e- 005	1.0000e- 005		1.0000e- 005	1.0000e- 005	0.0000	8.1300e- 003	8.1300e- 003	2.0000e- 005	0.0000	8.6600e- 003

CalEEMod Version: CalEEMod.2020.4.0 Page 27 of 32 Date: 7/5/2022 12:03 PM

Valley Communications Center - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

6.2 Area by SubCategory

Mitigated

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
SubCategory	tons/yr					MT/yr										
Coating	0.0377					0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	0.2848					0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
· · ·	3.9000e- 004	4.0000e- 005	4.1800e- 003	0.0000		1.0000e- 005	1.0000e- 005		1.0000e- 005	1.0000e- 005	0.0000	8.1300e- 003	8.1300e- 003	2.0000e- 005	0.0000	8.6600e- 003
Total	0.3229	4.0000e- 005	4.1800e- 003	0.0000		1.0000e- 005	1.0000e- 005		1.0000e- 005	1.0000e- 005	0.0000	8.1300e- 003	8.1300e- 003	2.0000e- 005	0.0000	8.6600e- 003

7.0 Water Detail

7.1 Mitigation Measures Water

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

	Total CO2	CH4	N2O	CO2e
Category		МТ	-/yr	
Willigatou	51.1493	0.4387	0.0107	65.3178
Unmitigated	51.1493	0.4387	0.0107	65.3178

7.2 Water by Land Use <u>Unmitigated</u>

	Indoor/Out door Use	Total CO2	CH4	N2O	CO2e
Land Use	Mgal		MT	/yr	
General Office Building	13.3407 / 8.17656	51.1493	0.4387	0.0107	65.3178
Other Asphalt Surfaces	0/0	0.0000	0.0000	0.0000	0.0000
Other Non- Asphalt Surfaces	0/0	0.0000	0.0000	0.0000	0.0000
Parking Lot	0/0	0.0000	0.0000	0.0000	0.0000
Total		51.1493	0.4387	0.0107	65.3178

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

7.2 Water by Land Use

Mitigated

	Indoor/Out door Use	Total CO2	CH4	N2O	CO2e
Land Use	Mgal		MT	/yr	
General Office Building	13.3407 / 8.17656	51.1493	0.4387	0.0107	65.3178
Other Asphalt Surfaces	0/0	0.0000	0.0000	0.0000	0.0000
Other Non- Asphalt Surfaces	0/0	0.0000	0.0000	0.0000	0.0000
Parking Lot	0/0	0.0000	0.0000	0.0000	0.0000
Total		51.1493	0.4387	0.0107	65.3178

8.0 Waste Detail

8.1 Mitigation Measures Waste

Institute Recycling and Composting Services

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Category/Year

	Total CO2	CH4	N2O	CO2e
		MT	-/yr	
Mitigated	. 0.0127	0.2094	0.0000	8.7769
•ga.ca	14.1708	0.8375	0.0000	35.1076

8.2 Waste by Land Use <u>Unmitigated</u>

	Waste Disposed	Total CO2	CH4	N2O	CO2e
Land Use	tons		МТ	-/yr	
General Office Building	69.81	14.1708	0.8375	0.0000	35.1076
Other Asphalt Surfaces	0	0.0000	0.0000	0.0000	0.0000
Other Non- Asphalt Surfaces	0	0.0000	0.0000	0.0000	0.0000
Parking Lot	0	0.0000	0.0000	0.0000	0.0000
Total		14.1708	0.8375	0.0000	35.1076

Date: 7/5/2022 12:03 PM

Valley Communications Center - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

8.2 Waste by Land Use

Mitigated

	Waste Disposed	Total CO2	CH4	N2O	CO2e
Land Use	tons		MT	-/yr	
General Office Building	17.4525	3.5427	0.2094	0.0000	8.7769
Other Asphalt Surfaces	0	0.0000	0.0000	0.0000	0.0000
Other Non- Asphalt Surfaces	0	0.0000	0.0000	0.0000	0.0000
Parking Lot	0	0.0000	0.0000	0.0000	0.0000
Total		3.5427	0.2094	0.0000	8.7769

9.0 Operational Offroad

Equipment Type Number	Hours/Day	Days/Year	Horse Power	Load Factor	Fuel Type
-----------------------	-----------	-----------	-------------	-------------	-----------

10.0 Stationary Equipment

Fire Pumps and Emergency Generators

Equipment Type	Number	Hours/Day	Hours/Year	Horse Power	Load Factor	Fuel Type

Boilers

Equipment Type	Number	Heat Input/Day	Heat Input/Year	Boiler Rating	Fuel Type

User Defined Equipment

CalEEMod Version: CalEEMod.2020.4.0 Page 32 of 32 Date: 7/5/2022 12:03 PM

Valley Communications Center - San Bernardino-South Coast County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Applied

Equipment Type Number

11.0 Vegetation

Appendix C:

EMFAC2017 Output

Calendar Year: 2022 Season: Annual

Vehicle Classification: EMFAC2007 Categories

Units: miles/day for VMT, trips/day for Trips, tons/day for Emissions, 1000 gallons/day for Fuel Consumption

Region	Calendar Year Vehicle Ca	Model Year	Speed	Fuel	Population	Trips	Fuel Consumption	Fuel Consumption	Total Fuel Consumption	VMT	Total VMT	Miles Per Gallon	Vehicle Class
South Coast AQMD	2022 HHDT	Aggregate	Aggregate	Gasoline	77.82251	1557.073	1.914672095	1914.672095	1984478.157	7970.981	13381402.09		6.74 HHD
South Coast AQMD	2022 HHDT	Aggregate	Aggregate	Diesel	108362	1118617	1982.563485	1982563.485		13373431			
South Coast AQMD	2022 LDA	Aggregate	Aggregate	Gasoline	6542832	30915701	8178.144259	8178144.259	8226568.36	2.52E+08	254602375.4		30.95 LDA
South Coast AQMD	2022 LDA	Aggregate	Aggregate	Diesel	58937.5	279973.4	48.42410045	48424.10045		2358230	1		
South Coast AQMD	2022 LDA	Aggregate	Aggregate	Electricity	127532.6	637025.4	0	0		5177709			
South Coast AQMD	2022 LDT1	Aggregate	Aggregate	Gasoline	736905.6	3399512	1031.447408	1031447.408	1031847.287	27300896	27309932.68		26.47 LDT1
South Coast AQMD	2022 LDT1	Aggregate	Aggregate	Diesel	387.1571	1348.408	0.39987912	399.8791198		9037.122			
South Coast AQMD	2022 LDT1	Aggregate	Aggregate	Electricity	5339.042	26794.47	0	0		221507.4			
South Coast AQMD	2022 LDT2	Aggregate	Aggregate	Gasoline	2246303	10535910	3436.155557	3436155.557	3453207.618	84740129	85348125.78		24.72 LDT2
South Coast AQMD	2022 LDT2	Aggregate	Aggregate	Diesel	14234.59	70193.22	17.05206088	17052.06088		607996.5			
South Coast AQMD	2022 LDT2	Aggregate	Aggregate	Electricity	22589.96	114302.6	0	0		734756.1			
South Coast AQMD	2022 LHDT1	Aggregate	Aggregate	Gasoline	175903.1	2620694	598.0685493	598068.5493	821513.5103	6298251	11115258.37		13.53 LHDT1
South Coast AQMD	2022 LHDT1	Aggregate	Aggregate	Diesel	119380.7	1501659	223.444961	223444.961		4817007			
South Coast AQMD	2022 LHDT2	Aggregate	Aggregate	Gasoline	30009.92	447103.1	113.5150695	113515.0695	209067.0531	1040649	2902289.397		13.88 LHDT2
South Coast AQMD	2022 LHDT2	Aggregate	Aggregate	Diesel	47335.63	595422.7	95.55198358	95551.98358		1861640	1		
South Coast AQMD	2022 MCY	Aggregate	Aggregate	Gasoline	295960.1	591920.2	56.92214589	56922.14589	56922.14589	2072370	2072370.126		36.41 MCY
South Coast AQMD	2022 MDV	Aggregate	Aggregate	Gasoline	1579640	7302407	2793.799561	2793799.561	2842944.316	55888916	57233722.8		20.13 MDV
South Coast AQMD	2022 MDV	Aggregate	Aggregate	Diesel	33348.92	163526.3	49.14475473	49144.75473		1344806			
South Coast AQMD	2022 MDV	Aggregate	Aggregate	Electricity	11658.48	59625.3	0	0		391944.3			
South Coast AQMD	2022 MH	Aggregate	Aggregate	Gasoline	35097.75	3511.179	64.70410395	64704.10395	76270.38211	333282.4	455641.5746		5.97 MH
South Coast AQMD	2022 MH	Aggregate	Aggregate	Diesel	12758.81	1275.881	11.56627815	11566.27815		122359.2			
South Coast AQMD	2022 MHDT	Aggregate	Aggregate	Gasoline	25445.41	509111.8	269.2842176			1367743	9307083.084		9.22 MHDT
South Coast AQMD	2022 MHDT	Aggregate	Aggregate	Diesel	123310	1231988	740.28427	740284.27		7939340	1		
South Coast AQMD		Aggregate	Aggregate	Gasoline	5959.443		49.67589796	49675.89796					6.54 OBUS
South Coast AQMD		Aggregate	Aggregate	Diesel	4274.499		38.46214418	38462.14418		325950.1			
South Coast AQMD		Aggregate	Aggregate	Gasoline	2630.829		11.7605267	11760.5267					8.06 SBUS
South Coast AQMD		Aggregate	Aggregate	Diesel	6631.313		27.5676618	27567.6618		209546.1			
South Coast AQMD		Aggregate	Aggregate	Gasoline		3808.584	18.40085629	18400.85629					4.87 UBUS
South Coast AQMD		Aggregate	Aggregate	Diesel	14.14142		0.246796198	246.7961984		1478.086			
South Coast AQMD	2022 UBUS	Aggregate	Aggregate	Electricity	17.11694	68.46776	0			1343.185			

Source: EMFAC2017 (v1.0.3) Emissions Inventory

Region Type: Air District Region: South Coast AQMD Calendar Year: 2023 Season: Annual

Vehicle Classification: EMFAC2007 Categories

Units: miles/day for VMT, trips/day for Trips, tons/day for Emissions, 1000 gallons/day for Fuel Consumption

Region Ca	alendar Yı Vehicle (Cat (Model Year	Speed	Fuel	Population	VMT	Trips	Fuel Consumption	Fuel Consumption	Total Fuel Consumption	VMT	Total VMT	Miles Per Gallon Vehicle Class
South Coas	2023 HHDT	Aggregate	Aggregate	Gasoline	75.10442936	8265.097	1502.689	1.936286145	1936.286145	1913466.474	8265.097	13656273.03	7.14 HHD
South Coas	2023 HHDT	Aggregate	Aggregate	Diesel	109818.6753	13648008	1133618	1911.530188	1911530.188		13648008		
South Coas	2023 LDA	Aggregate	Aggregate	Gasoline	6635002.295	2.53E+08	31352477	7971.24403	7971244.03	8020635.698	2.53E+08	255180358.3	31.82 LDA
South Coas	2023 LDA	Aggregate	Aggregate	Diesel	62492.97958	2469816	297086.6	49.3916685	49391.6685		2469816		
South Coas	2023 LDA	Aggregate	Aggregate	Electricity	150700.3971	6237106	751566	0	0		6237106		
South Coas	2023 LDT1	Aggregate	Aggregate	Gasoline	758467.6481	27812996	3504563	1023.913006	1023913.006	1024279.466	27812996	27821405.09	27.16 LDT1
South Coas	2023 LDT1	Aggregate	Aggregate	Diesel	360.7799144	8408.618	1256.88	0.366459477	366.4594769		8408.618		
South Coas	2023 LDT1	Aggregate	Aggregate	Electricity	7122.93373	303507.5	35798.19	0	0		303507.5		
South Coas	2023 LDT2	Aggregate	Aggregate	Gasoline	2285150.139	85272416	10723315	3338.798312	3338798.312	3356536.438	85272416	85922778.34	25.60 LDT2
South Coas	2023 LDT2	Aggregate	Aggregate	Diesel	15594.68309	650362.8	76635.83	17.73812611	17738.12611		650362.8		
South Coas	2023 LDT2	Aggregate	Aggregate	Electricity	28809.63735	917592.8	145405.4	0	0		917592.8		
South Coas	2023 LHDT1	Aggregate	Aggregate	Gasoline	174910.3847	6216643	2605904	583.3851736	583385.1736	811563.1022	6216643	11211395.79	13.81 LHDT1
South Coas	2023 LHDT1	Aggregate	Aggregate	Diesel	125545.0822	4994753	1579199	228.1779285	228177.9285		4994753		
South Coas	2023 LHDT2	Aggregate	Aggregate	Gasoline	30102.75324	1034569	448486.2	111.5753864	111575.3864	209423.5025	1034569	2969599.008	14.18 LHDT2
South Coas	2023 LHDT2	Aggregate	Aggregate	Diesel	50003.13116	1935030	628976.5	97.84811618	97848.11618		1935030		
South Coas	2023 MCY	Aggregate	Aggregate	Gasoline	305044.5141	2104624	610089	57.849018	57849.018	57849.018	2104624	2104623.657	36.38 MCY
South Coas	2023 MDV	Aggregate	Aggregate	Gasoline	1589862.703	55684188	7354860	2693.883526	2693883.526	2744536.341	55684188	57109879.73	20.81 MDV
South Coas	2023 MDV	Aggregate	Aggregate	Diesel	36128.1019	1425691	176566.9	50.65281491	50652.81491		1425691		
South Coas	2023 MDV	Aggregate	Aggregate	Electricity	16376.67653			0			537591.7		
South Coas	2023 MH	Aggregate	Aggregate	Gasoline	34679.50542	330042.9	3469.338	63.26295123	63262.95123	74893.26955	330042.9	454344.9436	6.07 MH
South Coas	2023 MH	Aggregate	Aggregate	Diesel	13122.69387	124302	1312.269	11.63031832	11630.31832		124302		
South Coas	2023 MHDT	Aggregate	Aggregate	Gasoline	25624.3151			265.2060557	265206.0557	989975.6425		9484317.768	9.58 MHDT
South Coas	2023 MHDT	Aggregate	Aggregate	Diesel	122124.488			724.7695868	724769.5868		8120623		
South Coas	2023 OBUS	Aggregate	Aggregate	Gasoline	5955.291639		119153.5	48.07750689	48077.50689	86265.88761		579743.8353	6.72 OBUS
South Coas	2023 OBUS	Aggregate	Aggregate	Diesel	4286.940093			38.18838072	38188.38072		333969.8		
South Coas	2023 SBUS	Aggregate	Aggregate	Gasoline	2783.643068		11134.57	12.19474692	12194.74692	39638.85935			8.15 SBUS
South Coas	2023 SBUS	Aggregate	Aggregate	Diesel	6671.825716	210853.9		27.44411242	27444.11242		210853.9		
South Coas	2023 UBUS	Aggregate	Aggregate	Gasoline	957.7686184			17.62416327	17624.16327	17863.66378		91199.2533	5.11 UBUS
South Coas	2023 UBUS	Aggregate	Aggregate	Diesel	13.00046095			0.239500509	239.5005093		1416.622		
South Coas	2023 UBUS	Aggregate	Aggregate	Electricity	16.11693886	1320.163	64.46776	0			1320.163		